

DUP11

OFF LINE SDLC TRANSMITTER
CZDPBC0

AH-8577C-MC
COPYRIGHT © 75-78
FICHE 1 OF 1

DEC 1978
digital
MADE IN USA

This microfiche card contains a grid of frames. The frames are arranged in approximately 15 rows and 10 columns. Each frame contains a small, high-contrast image of a document page, likely containing technical specifications or data for the 'OFF LINE SDLC TRANSMITTER CZDPBC0'. The text within the frames is too small to be legible. The card is otherwise blank.

IDENTIFICATION

PRODUCT CODE: AC-8576C-MC
PRODUCT NAME: CZDPBCO OFLNE SDLC YMTR
DATE: APRIL 1978
MAINTAINER: DIAGNOSTICS

THE INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION. DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR ANY ERRORS THAT MAY APPEAR IN THIS DOCUMENT.

NO RESPONSIBILITY IS ASSUMED FOR THE USE OR RELIABILITY OF SOFTWARE ON EQUIPMENT THAT IS NOT SUPPLIED BY DIGITAL OR ITS AFFILIATED COMPANIES.

COPYRIGHT (C) 1975, 1978 BY DIGITAL EQUIPMENT CORPORATION

THE FOLLOWING ARE TRADEMARKS OF DIGITAL EQUIPMENT CORPORATION:

DIGITAL	PDP	UNIBUS	MASSBUS
DEC	DECUS	DECTAPE	

1.0 ABSTRACT

THE FUNCTION OF THE DUP11 DIAGNOSTICS IS TO VERIFY THAT THE OPTION OPERATES ACCORDING TO SPECIFICATIONS. THE DIAGNOSTICS VERIFY THAT THERE ARE NO MALFUNCTIONS AND THAT ALL OPERATIONS OF THE DUP11 ARE CORRECT IN ITS ENVIRONMENT. PARAMETERS MAY BE SET TO ALERT DIAGNOSTICS AS TO THE DUP11 CONFIGURATION BY ANSWERING THE PARAMETER DIALOG (LOAD ADDRESS=200, START ADDRESS=1). ALL QUESTIONS SHOULD BE ANSWERED AND THEN EACH DIAGNOSTIC WILL 'OVERLAY' THESE PARAMETERS WHICH ARE STORED IN THE 'STATUS TABLE' (SEE SECTION 8.4). THE ALTERNATIVE TO THE PARAMETER DIALOG IS DEFAULT PARAMETERS (SEE SECTION 8.5).

THE DIAGNOSTICS WILL RUN UP TO EIGHT CONSECUTIVELY ADDRESSED AND CONSECUTIVELY VECTORED DUP11'S IN A CHAIN MODE, I.E., RUNNING THE DIAGNOSTIC COMPLETELY FOR ONE DEVICE BEFORE STARTING THE NEXT.

CZDPB DOES READ/WRITE CHECKING, BUS ADDRESS CHECKING, DEVICE AND BUS RESET TESTS ON THE CONTROL AND STATUS REGISTERS. TESTS ARE MADE TO PROVE THERE IS NO INTERACTION WITHIN AND BETWEEN REGISTERS. THE REGISTERS ARE CHECKED BOTH A BIT AT A TIME AND ALL AT ONCE.

IN ADDITION, THE TRANSMITTER SDLC FUNCTIONS ARE CHECKED IN MAINTENANCE INTERNAL MODE, I.E., CLOCKING OF THE DEVICE IS DONE BY THE PROGRAM. THE DEVICE IS SET UP, A SPECIFIC NUMBER OF HALF-CLOCKS ARE DONE, AND A TEST IS MADE FOR A SIGNIFICANT EVENT.

IN CHECKING DATA, THE SOFTWARE EMULATES THE HARDWARE AND USES THE PROCESSOR CARRY BIT AFTER A ROTATE TO DETERMINE WHAT THE OUTPUT SHOULD BE AT THE TRANSMITTER BIT WINDOW A BIT AT A TIME. THE PROGRAM THEN COMPARES THE EMULATED SOFTWARE BIT TO THE HARDWARE BIT OUTPUT. THE PROCESS IS REPEATED UNTIL ALL DATA IS CHECKED.

THE TRANSMITTER BCC IS CHECKED USING THE CRC.CCITT POLYNOMIAL IN THE SAME WAY AS DATA, WITH ONE EXCEPTION--THE BCC IS CALCULATED FIRST BY THE PROGRAM AND THEN COMPARED TO THE OUTPUT OF THE TRANSMITER.

CURRENTLY THERE ARE THREE OFF-LINE DIAGNOSTICS THAT ARE TO BE RUN IN SEQUENCE TO ENSURE THAT IF AN ERROR SHOULD OCCUR IT WILL BE DETECTED AT AN EARLY STAGE AND ESTABLISH THAT DIAGNOSIS OF THE ERROR WILL BE IMMEDIATE TO DISCOVERING THE

PROBLEM.

NOTE: ADDITIONAL DIAGNOSTICS MAY BE ADDED IN THE FUTURE.

THE THREE DIAGNOSTICS ARE:

1. CZDPB [REV] BASIC AND OFFLINE TRANSMITTER TESTS
2. CZDPC [REV] OFFLINE RECEIVER AND MODEM CONTROL AND
INTERRUPT TESTS
3. CZDPD [REV] OFFLINE SDLC AND DECMODE DATA AND FUNCTION
TESTS

NOTE: THERE IS A FOURTH PROGRAM, TAPE CZDPE [REV] WHICH IS A
QUICK-VERIFY TAPE THAT REQUIRES ANSWERING A DIALOG.
ITS FUNCTION IS TO ENABLE THE OPERATOR TO QUICKLY
DETERMINE IF THERE IS A PROBLEM WITH THE DEVICE. SEE
THE DOCUMENTATION IN THAT LISTING FOR MORE INFORMATION.

2.0 REQUIREMENTS

2.1 EQUIPMENT

ANY PDP11 FAMILY CPU (WITH MINIMUM 8K MEMORY)
ASR 33 (OR EQUIVALENT)
DUP11

2.2 STORAGE

PROGRAM WILL USE ALL 8K OF MEMORY EXCEPT WHERE ABS AND
BOOTSTRAP LOADER RESIDE. LOCATION 1500 THRU 1560 ARE
ESPECIALLY TO BE NOTED AND LEFT UNTOUCHED BY THE OPERATOR
AFTER THE DUP11 PARAMETER DIALOG HAS BEEN EXECUTED OR AFTER
THE DEFAULT SETUP HAS BEEN DONE.

3.0 LOADING PROCEDURE

3.1 METHOD

ALL PROGRAMS ARE IN ABSOLUTE FORMAT AND ARE LOADED USING THE
ABSOLUTE LOADER. NOTE: IF THE DIAGNOSTICS ARE ON A MEDIA
SUCH AS DISK, MAGTAPE, DECTAPE, OR CASSETTE FOLLOW
INSTRUCTIONS FOR THE MONITOR WHICH HAS BEEN PROVIDED ON THAT
SPECIFIC MEDIA.

ABSOLUTE LOADER STARTING ADDRESS = **500

MEMORY	SIZE
	(*)=
8K	37
12K	57
16K	77
20K	117
24K	137
28K	157

3.1.1 PLACE ADDRESS OF ABS LOADER INTO SWITCH REGISTER. (ALSO PLACE
'HALT' SW UP)

3.1.2 DEPRESS 'LOAD ADDRESS' KEY ON CONSOLE AND RELEASE.

3.1.3 DEPRESS 'START KEY' ON CONSOLE AND RELEASE (PROGRAM SHOULD NOW
BE LOADING INTO CPU)

4.0 STARTING PROCEEDURE

- A. SET SWITCH REGISTER TO 000200
- B. DEPRESS 'LOAD ADDRESS' KEY AND RELEASE
- C. SET SWR TO ZERO FOR DEFAULT PARAMETERS ESTABLISHED IN THE TAPE (SEE SECTION 8.5.3 FOR FULL EXPLANATION OF DEFAULT PARAMETERS) OR LEAVE SWR BIT 7=1 TO USE EXISTING PARAMETERS PREVIOUSLY SET UP BY THE DUP11 PARAMETER DIALOG OR A PREVIOUSLY RUN DUP11 DIAGNOSTIC. SET SWR=1 TO GO THROUGH THE PARAMETER DIALOG. (IT IS NOT NECESSARY TO INPUT NEW PARAMETERS FOR EACH TAPE.) (SECTION 7.2, 8.4 AND 8.5 MAY BE HELPFUL)
- D. DEPRESS 'START KEY' AND RELEASE. THE PROGRAM WILL TYPE MAINDEC NAME AND PROGRAM NAME (IF THIS WAS THE FIRST START UP OF THE PROGRAM) AND ALSO THE FOLLOWING:

'EXAMPLE'

'MAP OF DUP11 STATUS'

1500	160050	CSR OF FIRST DUP11
1502	000300	VECTOR OF FIRST DUP11
1504	140026	STATUS AND SYNC FOR FIRST DUP11
1506	160060	CSR OF SECOND DUP11
1510	000310	VECTOR OF SECOND DUP11
1512	140026	STATUS AND SYNC FOR SECOND DUP11

THE ABOVE IS ONLY AN EXAMPLE! THIS WOULD INDICATE THE STATUS TABLE STARTING AT ADDRESS 1500 IN THE PROGRAM. THE STATUS TABLE MUST BE VERIFIED BY THE USER. FOR INFORMATION ON THE STATUS TABLE SEE SECTION 8.4 FOR HELP.

IT IS POSSIBLE FOR THE OPERATOR TO MANUALLY CHANGE (TOGGLE IN) THE INFORMATION IN THE MAP TO SUIT A SPECIFIC CONFIGURATION OF DEVICES, BUT THE RESPONSIBILITY FOR VERIFYING THAT INFORMATION RESTS WITH THE OPERATOR.

THE PROGRAM WILL TYPE 'R' AND PROCEED TO RUN THE DIAGNOSTIC

4.1 CONTROL SWITCH SETTINGS

SW 15	SET:	HALT ON ERROR
SW 14	SET:	LOOP ON CURRENT TEST
SW 13	SET:	INHIBIT ERROR PRINT OUT
SW 12	SET:	INHIBIT TYPE OUT/BELL ON ERROR.
SW 11	SET:	INHIBIT ITERATIONS. (QUICK PASS)
SW 10	SET:	ESCAPE TO NEXT TEST ON ERROR
SW 09	SET:	LOOP WITH CURRENT DATA
SW 08	SET:	CATCH ERROR AND LOOP ON IT
SW 07	SET:	USE PREVIOUS STATUS TABLE.
SW 06	SET:	RESERVED
SW 05	SET:	RESERVED
SW 04	SET:	RESERVED

SW 03 SET: SELECT DUP11'S DESIRED ACTIVE
SW 02 SET: LOCK ON SELECTED TEST
SW 01 SET: RESTART PROGRAM AT SELECTED TEST
SW 00 SET: ENTER PARAMETERS USING MANUAL DIALOG

SWITCHES 8 THROUGH 15 ARE DYNAMIC AND SHOULD BE USED AS NEEDED IN THE DIAGNOSTIC. SWITCHES 0 THROUGH 3 ARE STATIC (ONLY ARE OPERABLE WHEN THE MONITOR PORTION OF THE TAPE IS RUNNING) AND SHOULD BE SET UP PRIOR TO STARTING OR RESTARTING THE DIAGNOSTIC.

4.1.2 SWITCH REGISTER RESTRICTIONS

SW 03 RESELECT DUP11'S DESIRED ACTIVE. PLEASE NOTE THAT A MESSAGE IS TYPED OUT FOR SETTING THE SWITCH REGISTER EQUAL TO DUP11'S ACTIVE. THIS MEANS IF THE SYSTEM HAS THREE DUP11S BITS 00, 01, 02 WILL BE SET IN LOC 'DUPACTV' FROM THE SWITCH REGISTER. USING THIS SWITCH(SW03) ALTERS THAT LOCATION. THEREFORE, IF THREE DUP11S ARE IN THE SYSTEM ***DO NOT*** SET SWITCHES GREATER THAN SW 02 IN THE UP POSITION. THIS WOULD BE A FATAL ERROR. DO NOT SELECT MORE ACTIVE DUP11S THAN HAS BEEN GIVEN INFORMATION ABOUT IN THE PARAMETER PROGRAM.

AS EXPLAINED IN SECTION 1.0, DEVICES SHOULD BE CONSECUTIVELY ADDRESSED, AND CAN BE SELECTED OR DESELECTED USING THIS SWITCH.

METHOD: A. LOAD ADDRESS 200
B. START WITH SW 03=1
C. PROGRAM WILL TYPE MESSAGE
D. SET THE BINARY NUMBER OF DUP11S DESIRED ACTIVE. EXAMPLE: 1=1 DUP11; 3=2 DUP11; 7=3 DUP11; 17=4 DUP11 37=5 DUP11 ETC. PRESS CONTINUE.
E. NUMBER (IF VALID) WILL BE IN DATA LIGHTS (EXCLUDING 11/05)
F. SET WITH ANY OTHER SWITCH SETTINGS DESIRED. PRESS CONTINUE.

SW 01 RESTART PROGRAM AT SELECTED TEST. IT IS STRONGLY SUGGESTED THAT AT LEAST ONE PASS HAS BEEN MADE BEFORE TRYING TO SELECT A TEST THAT IS NOT IN THE ORDER OF SEQUENCE. THE REASON FOR THIS IS THAT THE PROGRAM HAS TO CLEAR AREAS AND SET UP PARAMETERS IN THE MONITOR PORTION OF THE PROGRAM. IT IS POSSIBLE TO LD200, AND RAISE SW01, THEN START, PROVIDED PARAMETERS HAVE BEEN PREVIOUSLY SET UP AS DESCRIBED IN SECTION 4.0. ALSO, WHEN A TEST IS SELECTED, ALWAYS START AT THE VERY BEGINNING OF THAT TEST.

SW 09 LOOP ON CURRENT DATA. THIS SWITCH WILL ONLY WORK IF CALL 'SCOPI' IS IN THAT TEST. THE REASON IS THAT MOST TESTS DEAL WITH BLOCKS OF DIFFERENT DATA TO BE SENT OR RECEIVED ALL AT ONCE, THUS KNOWN AS BLOCK DATA--ONE

PATTERN CAN'T BE SINGLED OUT. (SEE SECTION 4.1.3.B.1)
4.1.3 SWITCH REGISTER PRIORITIES

A) ERROR SWITCHES

1. SW 12 DELETE PRINT OUT/BELL ON ERROR.
2. SW 13 DELETE ERROR PRINTOUT.
3. SW 15 HALT ON THE ERROR.
4. SW 08 GOTO BEGINNING OF THE TEST(ON ERROR).
5. SW 10 GOTO NEXT TEST(ON ERROR).

B) SCOPE SWITCHES

1. SW 09 - (IF ENABLED BY 'SCOPI') ON AN ERROR. IF AN ASTERISK '*' IS PRINTED IN FRONT OF THE TEST NUMBER (EX. *TEST NO. 10), SW09 IS INCORPORATED IN THAT TEST AND THEREFORE SW09 IS USUALLY THE BEST SWITCH FOR THE SCOPE LOOP (SW14=0, SW10=0, SW09=1, SW08=0).

IF SW09 IS NOT ENABELED AND THERE IS A *HARD* ERROR (CONSTANT ERROR) SW08 IS BEST. (SW14=0, SW10=0, SW09=0, SW08=1).

FOR INTERMITTENT ERRORS, SW14=1 WILL LOOP ON TEST REGARDLESS OF ERROR OR NO ERROR. (SW14=1, SW10=0, SW09=0, SW08=1,0)

2. SW 14 - LOOP ON TEST. WILL LOOP ON TEST UNTIL SWITCH IS LOWERED.
3. SW 11 - INHIBIT ITERATIONS (QUICK PASS). ALLOWS ONLY ONE PASS THROUGH A TEST.

4.2 STARTING ADDRESS

STARTING ADDRESS IS AT 000200. THERE ARE NO OTHER STARTING ADDRESSES FOR THE DUP11 DIAGNOSTICS.

NOTE: IF ADDRESS 000042 IS NON-ZERO THE PROGRAM ASSUMES IT IS UNDER ACT11 OR XXDP CONTROL AND WILL ACT ACCORDINGLY. AFTER *ALL* AVAILABLE DUP11'S ARE TESTED THE PROGRAM WILL RETURN TO 'XXDP' OR 'ACT-11'.

5.0 OPERATING PROCEDURE

WHEN THE PROGRAM IS INITIALLY STARTED MESSAGES AS DESCRIBED IN SECTION FOUR WILL BE PRINTED AND PROGRAM WILL BEGIN RUNNING THE DIAGNOSTIC.

5.1 PROGRAM AND/OR OPERATOR ACTION

THE TYPICAL APPROACH SHOULD BE

1. HALT ON ERROR (VIA SW 15-1) WHENEVER AN ERROR OCCURS.
2. CLEAR SW 15.
3. SET SW 14: (LOOP ON THIS TEST)
4. SET SW 13: (INHIBIT ERROR PRINT OUT)

THE TEST NUMBER AND PC WILL BE TYPED OUT AND POSSIBLY AN ERROR MESSAGE (THIS DEPENDS ON THE TEST), TO GIVE THE OPERATOR AN IDEA AS TO THE SOURCE OF THE PROBLEM. IF IT IS NECESSARY TO KNOW MORE INFORMATION CONCERNING THE ERROR REPORT, LOOK IN THE LISTING FOR THAT TEST NUMBER WHICH WAS TYPED OUT AND THEN NOTE THE PC OF THE ERROR REPORT. IN THIS WAY THE EXACT FUNCTIONING OF THE TEST CAN BE INTERPRETED SINCE THE ERROR PC IS THE HLT+2 LOCATION.

IN SOME TESTS, THERE IS A SUBROUTINE CALL THROUGH A REGISTER (E.G., JSR R1,FLAG). THE SUBROUTINE DOES THE DATA CHECKING FOR THE TEST AND WILL REPORT AN ERROR IF ONE OCCURS. THIS MEANS THAT THE FAILING TEST COULD BE IN ONE PART OF THE LISTING WHILE THE SUBROUTINE THAT FOUND THE ERROR IS IN ANOTHER PART. TO DETERMINE THE PC OF THE FAILING TEST, CHECK THE REGISTER USED BY THE SUBROUTINE. IT WILL CONTAIN THE RETURN ADDRESS OF THE FAILING TEST.

6.0 ERRORS

AS DESCRIBED PREVIOUSLY THERE WILL ALWAYS BE A TEST NUMBER AND PC TYPED OUT AT THE TIME OF AN ERROR (PROVIDING SW 13=0 AND SW 12=0). IN MOST CASES ADDITIONAL INFORMATION WILL BE SUPPLIED TO THE ERROR MESSAGE WHICH IS TO GIVE THE OPERATOR AN INDICATION OF THE ERROR.

6.1 ERROR RECOVERY

IF FOR SOME REASON THE DUP11 SHOULD 'HANG THE BUS' (GAIN CONTROL OF BUS SO THAT CONSOLE MANUAL FUNCTIONS ARE INHIBITED) AN INIT OR POWER DOWN/UP IS NECESSARY FOR OPERATOR TO REGAIN CONTROL OF CPU. IF THIS SHOULD HAPPEN LOOK IN LOCATION 'TSTNO' FOR THE NUMBER OF THE TEST THAT WAS RUNNING AT THE TIME OF THE CATASTROPHIC ERROR. THIS GIVES THE OPERATOR SOME IDEA AS TO WHAT THE DUP11 WAS DOING AT THE TIME OF THE ERROR.

7.0 RESTRICTIONS

7.1 STARTING RESTRICTIONS

SEE SECTION 4 (PLEASE). STATUS TABLE SHOULD BE VERIFIED REGARDLESS OF HOW THE PROGRAM WAS STARTED. ALSO, IT IS IMPORTANT TO USE THE LISTING ALONG WITH THE INFORMATION PRINTED ON THE TTY TO COMPLETELY ISCLATE PROBLEMS.

7.2 OPERATING RESTRICTIONS

DUP11 'PARAMETER DIALOG' MUST BE RUN ONLY ONCE PRIOR TO THE FIRST RUNNING OF ANY DUP11 DIAGNOSTIC IF 'DEFAULT PARAMETERS' ARE NOT USED. IF ONLY DUP11 DIAGNOSTICS WERE LOADED AFTER DUP11 PARAMETER SETUP, AND IF CORE MEMORY HAS NOT BEEN CHANGED, I.E., USE OF DIAGNOSTICS OTHER THAN DUP11 DIAGNOSTICS, AND IF THERE WERE NO DUP11 CONFIGURATION CHANGES, THE DUP11 PARAMETER SETUP NEED NEVER BE RUN AGAIN. HOWEVER, IF ANY OF THE ABOVE HAVE BEEN VIOLATED THE DUP11 PARAMETER SETUP MUST BE RUN AGAIN BEFORE RUNNING THE DIAGNOSTICS. UNDER NORMAL OPERATING CONDITIONS IT SHOULD NOT BE NECESSARY TO INPUT NEW PARAMETERS TO SUBSEQUENT DIAGNOSTICS, UNLESS A CHANGE IS REQUIRED.

NOTE: AN ALTERNATIVE TO THE ABOVE IS ATTEMPTING THE DEFAULT PARAMETERS WHEN THE PROGRAM IS INITIALLY STARTED WITH SWR 0.

7.3 HARDWARE CONFIGURATION RESTRICTIONS FOR THE PURPOSE OF RUNNING MULTIPLE DUP11'S IN CHAIN MODE.

1. CSR ADDRESSES MUST BE CONSECUTIVE.
2. VECTORS ARE CONSECUTIVE IF PARAMETER PROGRAM IS USED.
3. ALL JUMPERS ARE ASSUMED TO BE AS SETUP IN PARAMETER DIALOG.
4. PRIORITY LEVEL MUST BE THE SAME FOR ALL DEVICES.

8.0 MISCELLANEOUS

8.1 EXECUTION TIME

ALL DUP11 DEVICE DIAGNOSTICS WILL GIVE AN 'END PASS' MESSAGE (PROVIDING NO ERRORS AND SW12=0) WITHIN 4 MINS. THIS IS ASSUMING SW11=1 (DELETE ITERATIONS) IS SET TO GIVE THE FASTEST POSSIBLE EXECUTION. THE ACTUAL EXECUTION TIME DEPENDS GREATLY ON THE PDP11 CPU CONFIGURATION.

8.2 PASS COMPLETE

NOTE: *EVERY* TIME THE PROGRAM IS STARTED, THE TESTS WILL RUN AS IF SW11 (DELETE ITERATIONS) WAS UP (=1). THIS IS TO VERIFY NO *HARD* ERRORS AS SOON AS POSSIBLE. THEREFORE THE FIRST PASS--EACH TIME PROGRAM IS STARTED--WILL BE A 'QUICK PASS' UNTIL ALL DUP11'S IN SYSTEM ARE TESTED. WHEN THE DIAGNOSTIC HAS COMPLETED A PASS WITH THE NORMAL ITERATION COUNT (ICOUNT=50), THE FOLLOWING IS AN EXAMPLE OF THE PRINT OUT TO BE EXPECTED.

END PASS CZDPBC CSR:160050 VEC:300 PASSES:000001 ERRORS:000000

NOTE: THE NUMBERS FOR CSR AND VEC ARE NOT NECESSARILY THE VALUES FOR THE DEVICE. THEY ARE ONLY FOR THIS EXAMPLE.

8.3 KEY LOCATIONS

RETURN CONTAINS THE ADDRESS WHERE PROGRAM WILL RETURN WHEN ITERATION COUNT IS REACHED OR IF LOOP ON TEST IS ASSERTED.

NEXT CONTAINS THE ADDRESS OF THE NEXT TEST TO BE PERFORMED.

TSTNO CONTAINS THE NUMBER OF THE TEST NOW BEING PERFORMED.

RUN THE BIT IN 'RUN' ALWAYS POINTS ONE PAST THE DUP11 CURRENTLY BEING TESTED. EXAMPLE: (RUN) /000000001000000 MEANS THAT DUP11 NO.05 IS THE DUP11 NOW RUNNING.

DUPCRO0-DUPCRO7 (1500)-(1560) THESE LOCATIONS CONTAIN THE INFORMATION NEEDED TO TEST UP TO 8 (DECIMAL) DUP11S SEQUENTIALY. THEY CONTAIN THE CSR, VECTOR AND STATUS CONCERNING THE CONFIGURATION OF EACH DUP11.

DUPACTV EACH BIT SET IN THIS LOCATION INDICATES THAT THE ASSOCIATED DUP11 WILL BE TESTED IN TURN. EXAMPLE: (DUPACTV) /000000000011111 MEANS THAT DUP11 NO. 00,01,02,03,04 WILL BE TESTED. EXAMPLE: (DUPACTV) /000000000010001 MEANS THAT DUP11 NO. 00,04 WILL BE TESTED.

RXCSR CONTAINS THE RECEIVER CSR OF THE CURRENT DUP11 UNDER TEST.

8.4 MORE ON THAT 'STATUS TABLE' (1500-1560)

'MAP OF DUP11 STATUS'

1500	160050
1502	000300
1504	140000

THE ABOVE INFORMATION WILL BE REPEATED FOR EACH OF UP TO 8 DUP11'S IN THE SYSTEM (THESE WILL FOLLOW UNDER THIS TABLE).
EXPLANATION:

1500	160050	THIS IS THE SYSTEM CONTROL REGISTER FOR THE 1ST DUP11 IN THE SYSTEM.
1502	000300	THIS IS VECTOR 'A' FOR THE FIRST DUP11 IN THE SYSTEM.
1504	140026	THIS REPRESENTS SYNC AND SOFTWARE STATUS FOR THE FIRST DUP.

THE BITS ARE AS FOLLOWS:

BIT 15	SET:	OPTIONAL CLEAR JUMPER IN
BIT 14	SET:	TURNAROUND CONNECTOR ON
BIT 13	SET:	
BIT 12	SET:	
BIT 11	SET:	
BIT 10	SET:	
BIT 09	SET:	
BIT 08	SET:	
BIT 07-00		SYNC CHARACTER FOR DECMODE TESTS.

THE ABOVE IS REPEATED FOR EACH DUP11 IN THE SYSTEM. THE TABLE IS FILLED BY DEFAULT PARAMETERS OR BY THE MANUAL PARAMETER INPUT AS DESCRIBED PREVIOUSLY. ALSO, IF DESIRED BY THE USER - THE LOCATIONS MAY BE ALTERED BY HAND (TOGGLED IN) TO SUIT THE SPECIFIC CONFIGURATION, THUS MAKING EACH DEVICE MAP DIFFERENT. IT IS THE RESPONSIBILITY OF THE OPERATOR TO VERIFY THE DATA IN THE MAP.

8.5 METHOD OF DEVELOPING DEFAULT PARAMETERS

8.5.1 DEFAULT PARAMETER ASSUMPTIONS

TOO MUCH HARDWARE WOULD HAVE TO BE ANALYZED TO SIZE THE THE PARAMETERS. THE PROGRAM MUST ASSUME THE VARIATIONS. THE RESULT, IF NOT TO YOUR SPECIFIC CONFIGURATION, MAY BE ALTERED BY HAND (TOGGLE IN) AS DESIRED. IN THIS WAY 95% OF THE PARAMETER SETUP WAS DONE BY THE PROGRAM AND 5% BY YOU. THEREFORE:

- 1) ALL JUMPERS ARE ASSUMED TO BE IN THE FOLLOWING CONFIGURATION.

	IN	OUT
W1=SECONDARY REC ENABLE	X	
W2=SEC REC DISABLE		X
W3=CLEAR OPTION	X	
W4=SEC TX ENABLE	X	
W5=DSC A CONTROL		X
W6-A+B DS CONTROL	X	
W7=BUS GRANT CONTROL	X	

- 2) THE H325 TURN AROUND CONNECTOR IS ASSUMED TO BE ON.
- 3) THE MANUFACTURING OPTION CSR OF 160050 AND VECTOR OF 770 ARE USED.
- 4) THE BR LEVEL IS ASSUMED TO BE 5.

IN ALL ADJUSTMENTS PLEASE REFER TO SECTION 8.4 FOR GREATER DETAIL.

INTRODUCTION TO DUP11 DIAGNOSTIC

```
558      :*CZDPBC0 /<377>/DUP11 OFLNE SDLC XMTR
559      :*COPYRIGHT(C) 1975,1978, DIGITAL EQUIPMENT CORP., MAYNARD, MASS. 01754
560      :-----
561
562      :STARTING PROCEDURE
563      :LOAD PROGRAM
564      :LOAD ADDRESS 000200
565      :PRESS START
566      :PROGRAM WILL TYPE 'CZDPBC0 /<377>/DUP11 OFLNE SDLC XMTR '
567      :PROGRAM WILL TYPE 'R' TO INDICATE THAT TESTING HAS STARTED
568      :AT THE END OF A PASS, PROGRAM WILL TYPE PASS COMPLETE MESSAGE
569      :AND THEN RESUME TESTING
570
571
572      :SWITCH REGISTER OPTIONS
573      :-----
574
575      100000      SW15=100000      :=1,HALT ON ERROR
576      040000      SW14=40000      :=1,LOOP ON CURRENT TEST
577      020000      SW13=20000      :=1,INHIBIT ERROR TYPEOUT
578      010000      SW12=10000      :=1,DELETE TYPEOUT/BELL ON ERROR.
579      004000      SW11=4000       :=1,INHIBIT ITERATIONS
580      002000      SW10=2000       :=1,ESCAPE TO NEXT TEST ON ERROR
581      001000      SW09=1000       :=1,LOOP WITH CURRENT DATA
582      000400      SW08=400        :=1,LOOP ON ERROR
583      000200      SW07=200
584      000100      SW06=100
585      000040      SW05=40
586      000020      SW04=20
587      000010      SW03=10
588
589      000004      SW02=4
590      000002      SW01=2
591      000001      SW00=1
                    :SELECT DUP'S DESIRED ACTIVE
                    :NOTE:THIS MUST NOT EXCEED ORIGINAL COUNT
                    :LOCK ON TEST SELECT
                    :RESTART PROGRAM AT SELECTED TEST
                    :ENTER PARAMETERS
```


GENERAL DEFINITIONS AND EQUIVALENCIES

```
592
593
594           ;REGISTER DEFINITIONS
595           ;-----
596
597           000000      R0=%0           ;GENERAL REGISTER
598           000001      R1=%1           ;GENERAL REGISTER
599           000002      R2=%2           ;GENERAL REGISTER
600           000003      R3=%3           ;GENERAL REGISTER
601           000004      R4=%4           ;GENERAL REGISTER
602           000005      R5=%5           ;GENERAL REGISTER
603           000006      SP=%6          ;PROCESSOR STACK POINTER
604           000007      PC=%7          ;PROGRAM COUNTER
605
606           ;LOCATION EQUIVALENCIES
607           ;-----
608
609           177776      PS=177776       ;PROCESSOR STATUS WORD
610           001150      STACK=1150     ;START OF PROCESSOR STACK
611
612           ;INSTRUCTION DEFINITIONS
613           ;-----
614
615           005746      PUSH1SP=5746    ;DECREMENT PROCESSOR STACK 1 WORD
616           005726      POP1SP=5726    ;INCREMENT PROCESSOR STACK 1 WORD
617           010046      PUSHRO=10046    ;SAVE R0 ON STACK
618           012600      POPRO=12600    ;RESTORE R0 FROM STACK
619           024646      PUSH2SP=24646  ;DECREMENT STACK TWICE
620           022626      POP2SP=22626  ;INCREMENT STACK TWICE
621           .EQUIV EMT,HLT ;BASIC DEFINITION OF ERROR CALL
622
623
624           100000      BIT15=100000
625           040000      BIT14=40000
626           020000      BIT13=20000
627           010000      BIT12=10000
628           004000      BIT11=4000
629           002000      BIT10=2000
630           001000      BIT9=1000
631           000400      BIT8=400
632           000200      BIT7=200
633           000100      BIT6=100
634           000040      BIT5=40
635           000020      BIT4=20
636           000010      BIT3=10
637           000004      BIT2=4
638           000002      BIT1=2
639           000001      BIT0=1
640
641
```

TRAPCATCHER FOR UNEXPECTED INTERRUPTS

```
642 :*****
643 :-----
644 :TRAPCATCHER FOR ILLEGAL INTERRUPTS
645 :THE STANDARD 'TRAP CATCHER' IS PLACED
646 :BETWEEN ADDRESS 0 TO ADDRESS 776.
647 :IT LOOKS LIKE 'PC+2 HALT'.
648 :-----
649 :*****
650
651 000000 .-0
652 :STANDARD INTERRUPT VECTORS
653 :-----
654
655 .=24
656 000024 005050 .PFAIL ;POWER FAIL HANDLER
657 000026 000340 340 ;SERVICE AT LEVEL 7
658 000030 004350 .HALT ;ERROR HANDLER
659 000032 000340 340 ;SERVICE AT LEVEL 7
660 000034 004316 .TRPSRV ;GENERAL HANDLER DISPATCH SERVICE
661 000036 000340 340 ;SERVICE AT LEVEL 7
662
663 .=40
664 000040 000000 0 ;SAVE FOR ACT-11 OR DDP2
665 000042 000000 0 ;RETURN ADDRESS IF UNDER ACT-11 OR DDP2
666 000044 000000 0 ;SAVE FOR ACT-11 OR DDP2
667 000046 003104 $ENDAD ;FOR USE WITH ACT-11 OR DDP2
668 000052 000000 .=52
669 0 ;ACT-11 PROGRAM CHARACTERISTICS
670
671 000174 000174 .-174
672 000176 000000 DISPREG:0 ;SOFTWARE DISPLAY REGISTER
673 000200 000200 SWREG: 0 ;SOFTWARE SWITCH REGISTER
674 000200 000137 001562 .=200 JMP .START ;GO TO START OF PROGRAM
675
676
677 .=1000
678 001000 005377 055103 050104 MTITLE: .ASCIZ <377><12>/CZDPBC0 /<377>/DUP11 OFLNE SDLC XMTR /<377>
679 001200 .=1200
680 :SWR AND LIGHTS
681 :-----
682
683 001200 177570 DISPLAY: 177570 ;11/45 CONSOLE LIGHTS
684 001202 177570 SWR: 177570 ;INDIRECT POINTER TO SWITCH REGISTER
685
686 :INDIRECT POINTERS TO TELETYPE VECTORS AND REGISTERS
687 :-----
688
689 001204 177560 TKLSR: 177560 ;TELETYPE KEYBOARD CONTROL REGISTER
690 001206 177562 TKDBR: 177562 ;TELETYPE KEYBOARD DATA BUFFER
691 001210 177564 TPCSR: 177564 ;TELEPRINTER CONTROL REGISTER
692 001212 177566 TPDBR: 177566 ;TELEPRINTER DATA BUFFER
693
694 :PROGRAM CONTROL PARAMETERS
695 :-----
696
```

PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

697	001214	000000	RETURN: 0	:SCOPE ADDRESS FOR LOOP ON TEST
698	001216	000000	NEXT: 0	:ADDRESS OF NEXT TEST TO BE EXECUTED
699	001220	000000	LOCK: 0	:ADDRESS FOR LOCK ON CURRENT DATA
700	001222	000001	ICOUNT: 1	:NUMBER OF ITERATIONS THAT CURRENT TEST WILL BE EXECUTED
701	001224	000000	LPCNT: 0	:NUMBER OF ITERATIONS COMPLETED
702	001226	000000	TSTNO: 0	:NUMBER OF TEST IN PROGRESS
703	001230	000000	PASCNT: 0	:NUMBER OF PASSES COMPLETED
704	001232	000000	ERRCNT: 0	:TOTAL NUMBER OF ERRORS
705	001234	000000	LSTERR: 0	:PC OF LAST ERROR CALL
706				
707			:PROGRAM VARIABLES	
708			:-----	
709				
710	001236	000000	TEMP1: 0	:TEMPORARY STORAGE
711	001240	000000	TEMP2: 0	:TEMPORARY STORAGE
712	001242	000000	TEMP3: 0	:TEMPORARY STORAGE
713	001244	000000	TEMP4: 0	:TEMPORARY STORAGE
714	001246	000000	TEMP5: 0	:TEMPORARY STORAGE
715	001250	000000	SAVR0: 0	:R0 STORAGE
716	001252	000000	SAVR1: 0	:R1 STORAGE
717	001254	000000	SAVR2: 0	:R2 STORAGE
718	001256	000000	SAVR3: 0	:R3 STORAGE
719	001260	000000	SAVR4: 0	:R4 STORAGE
720	001262	000000	SAVR5: 0	:R5 STORAGE
721	001264	000000	SAVSP: 0	:STACK POINTER STORAGE
722	001266	000000	SAVPC: 0	:PROGRAM COUNTER STORAGE
723				
724	001270	000000	SAVR0A: 0	:R0 STORAGE
725	001272	000000	SAVR1A: 0	:R1 STORAGE
726	001274	000000	SAVR2A: 0	:R2 STORAGE
727	001276	000000	SAVR3A: 0	:R3 STORAGE
728	001300	000000	SAVR4A: 0	:R4 STORAGE
729	001302	000000	SAVR5A: 0	:R5 STORAGE
730	001304	000000	SAVSPA: 0	:STACK POINTER STORAGE
731	001306	000000	SAVPCA: 0	:PROGRAM COUNTER STORAGE
732				
733	001310	000001	DUPACTV: .BLKB 1	:DUP11'S SELECTED ACTIVE.
734	001311	000001	DUPNUM: .BLKB 1	:OCTAL NUMBER OF DUP11'S.
735	001312	000001	SAVACT: .BLKB 1	:ORIGINAL ACTV. DEVICES.
736	001313	000001	SAVNUM: .BLKB 1	:WORKABLE NUMBER.
737	001314	000001	RUN: .BLKB 1	:POINTER ONE PAST RUNNING DEVICE.
738		001316	.EVEN	
739	001316	001500	CREAM: DUP.MAP	:TABLE POINTER.


```
740
741                                     :CONTRCL REGISTER DEFINITIONS
742                                     :-----
743                                     :RXCSR BIT DEFINITIONS
744      100000      DSCA=BIT15      :DATA SET CHANGE A
745      040000      RING=BIT14      :RING
746      020000      CTS=BIT13       :CLR TO SEND
747      010000      CARDET=BIT12    :CARRIER DETECT
748      004000      RE ACT=BIT11    :REC ACTIVE
749      002000      SRD=BIT10       :SEC REC DATA
750      001000      DSR=BIT9        :DATA SET RDY
751      000400      STPSYN=BIT8     :STRIP SYNC
752      000200      RXDONE=BIT7     :REC DONE
753      000100      RINTEN=BIT6     :REC INTR ENABLE
754      000040      DSINTE=BIT5     :DSC INTR ENABLE
755      000020      RCVEN=BIT4      :REC ENABLE
756      000010      STD=BIT3        :SEC XMIT DATA
757      000004      RTS=BIT2        :REQ TO SEND
758      000002      DTR=BIT1        :DATA TERM RDY
759      000001      DSCB=BIT0       :DATA SET CHANGE B
760                                     :RXDBUF BIT DEFINITIONS
761      100000      RXDERR=BIT15     :REC DATA ERROR
762      040000      OVRUN=BIT14     :OVERRUN ERROR
763      010000      CRCERR=BIT12    :CRC ERROR
764      002000      RABORT=BIT10    :REC ABORT
765      001000      REOM=BIT9       :REC END OF MESSAGE
766      000400      RSOM=BIT8      :REC START OF MESSAGE
767                                     :PARCSR BIT DEFINITIONS
768      100000      DECMOD=BIT15     :DEC MODE (DDCMP)
769      001000      CRCEN=BIT9      :CRC ENABLE
770      010000      PRISEC=BIT12    :PRI/SEC SELECT
771                                     :TXCSR BIT DEFINITIONS
772      100000      TXDLAT=BIT15     :TX DATA LATE
773      040000      MTDATA=BIT14    :MAINT DATA OUT
774      020000      CLK=BIT13       :CLK
775      010000      MMODEB=BIT12    :MAINT MODE B
776      004000      MMODEA=BIT11    :MAINT MODE A
777      002000      BITW=BIT10     :BIT WINDOW INPUT
778      001000      TXACT=BIT9      :TX ACTIVE
779      000400      MRESET=BIT8     :MASTER RESET
780      000200      TXDONE=BIT7     :XMIT DONE
781      000100      TXINTE=BIT6     :XMIT DONE INTR ENABLE
782      000020      SEND=BIT4      :SEND
783      000010      HDXEN=BIT3     :HDX/FDX
784                                     :TXCSR WRD DEFINITIONS
785      000000      USER=0          :USER MODE
786      014000      MMODE=14000     :MAINT INT MODE
787      010000      MEXT=10000     :MAINT EXT MODE
788      004000      SYSTST=4000    :SYSTEM TEST MODE
789
790                                     :TXDBUF BIT DEFINITIONS
791                                     :-----
792      100000      RCRC7T=BIT15
793      040000      RCRCIN=BIT14
794      020000      TCRC7T=BIT13
795      010000      TCRCIN=BIT12
```

PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

796	004000	TIMER=BIT11	;MAINTENANCE TIMER
797	002000	TABORT=BIT10	;TRANSMIT ABORT
798	001000	TEOM=BIT9	;TRANSMIT END OF MESSAGE
799	000400	TSOM=BIT8	;TRANSMIT START OF MESSAGE

800
801 ;MISC. PROGRAM DEFINITIONS
802 ;-----

803	001320	000000	PRIRTY: .WORD 0
804	001322	000001	TCNFLG: .BLKB 1
805	001323	000001	OPCLRJ: .BLKB 1
806	001324	000000	DATA: .WORD 0
807	001326	000000	SHIFTS: .WORD 0
808	001330	000000	MIND: .WORD 0
809	001332	000000	FLAG: .WORD 0
810	001334	000001	STJMFL: .BLKW 1
811	001336	000001	SRJMFL: .BLKW 1

812
813

PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

```
814  
815  
816  
817  
818 001340 000 INIFLG: .BYTE 0 ;PROGRAM INITIALIZATION FLAG  
819 001341 000 ERRFLG: .BYTE 0 ;ERROR OCCURED FLAG  
820 001342 000 LOKFLG: .BYTE 0 ;LOCK ON CURRENT TEST FLAG  
821 001343 000 QV.FLG: .BYTE 0 ;QUICK VERIFY FLAG.  
822 ;ON FIRST PASS OF EACH DUP11 ITERATIONS  
823 ;WILL BE SUPPRESSED  
824  
825 .EVEN  
826 $Y=0  
827  
828 ;DEFINITIONS FOR TRAP SUBROUTINE CALLS  
829 ;POINTERS TO SUBROUTINES CAN BE FOUND  
830 ;IN THE TABLE IMMEDIATLY FOLLOWING THE DEFINITIONS  
831  
832 ;:*****  
833 ;-----  
834 .TRPTAB:  
835 SCOPE=TRAP+0 ;CALL TO SCOPE LOOP AND ITERATION HANDLER  
836 .SCOPE  
837 SCOP1=TRAP+1 ;CALL TO LOOP ON CURRENT DATA HANDLER  
838 .SCOP1  
839 TYPE=TRAP+2 ;CALL TO TELETYPE OUTPUT ROUTINE  
840 .TYPE  
841 INSTR=TRAP+3 ;CALL TO ASCII STRING INPUT ROUTINE  
842 .INSTR  
843 INSTER=TRAP+4 ;CALL TO INPUT ERROR HANDLER  
844 .INSTER  
845 PARAM=TRAP+5 ;CALL TO NUMERICAL DATA INPUT ROUTINE  
846 .PARAM  
847 SAV05=TRAP+6 ;CALL TO REGISTER SAVE ROUTINE  
848 .SAV05  
849 RES05=TRAP+7 ;CALL TO REGISTER RESTORE ROUTINE  
850 .RES05  
851 CONVRT=TRAP+10 ;CALL TO DATA OUTPUT ROUTINE  
852 .CONVRT  
853 CNVRT=TRAP+11 ;CALL TO DATA OUTPUT ROUTINE WITHOUT CR/LF.  
854 .CNVRT  
855 PKCLK=TRAP+12 ;CALL TO CLOCK ROUTINE  
856 .PKCLK  
857 SETFLG=TRAP+13 ;CALL TO TELETYPE INPUT ROUTINE  
858 .SETFLG  
859 ;-----  
860 ;:*****
```


PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

```
861 ;DUP11 VECTOR AND REGISTER INDIRECT POINTERS
862
863 001374 000000 DUPRVC: 0 ;POINTER TO DUP11 RECEIVER INTERRUPT VECTOR
864 001376 000000 DUPRPS: 0 ;POINTER TO DUP11 RECEIVER INTERRUPT SERVICE PS
865 001400 000000 DUPTVC: 0 ;POINTER TO DUP11 TRANSMITTER INTERRUPT VECTOR
866 001402 000000 DUPTPS: 0 ;POINTER TO DUP11 TRANSMITTER INTERRUPT SERVICE PS
867 001404 000000 RXCSR: 0 ;POINTER TO DUP11 RECEIVER STATUS REGISTER
868 001406 000000 RXDBUF: 0 ;POINTER TO DUP11 RECEIVER DATA BUFFER
869 001410 000000 PARCSR: 0 ;POINTER TO DUP11 PARAMETER STATUS REGISTER
870 001412 000000 TXCSR: 0 ;POINTER TO DUP11 TRANSMITTER STATUS REGISTER
871 001414 000000 TXDBUF: 0 ;POINTER TO DUP11 TRANSMITTER DATA BUFFER
872 001416 000000 DUPSEC: 0 ;POINTER TO DUP11 SECONDARY REGISTER SELECT REGISTER
873 001420 000000 HUPPSR: 0 ;POINTER TO PARAMETER STATUS HIGH BYTE
874 001422 000000 HUPRBF: 0 ;POINTER TO RECEIVER BUFFER HIGH BYTE
875 001424 000000 HUPRCR: 0 ;POINTER TO RECEIVER CONTROL REG HIGH BYTE
876 001426 000000 HUPTBF: 0 ;POINTER TO TRANSMITTER BUFFER HIGH BYTE
877 001430 000000 HUPTCR: 0 ;POINTER TO TRANSMITTER CONTROL REG HIGH BYTE
878
879
880 ;DUP11 CONTROL INDICATORS FOR CURRENT DUP11 UNDER TEST
881 :-----
882
883 001432 000 MASK.A: .BYTE 000 ;LAST CHAR TO TEST AND PARITY MASK
884
885 001433 010 CLK.A: .BYTE 8. ;NUMBER OF CLOCKS NEEDED FOR ONE CHAR
886
887 001434 000000 L00.00: 000000 ;PARAMETERS
888
```

PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

```
889                                     ;DUP11 STATUS TABLE AND ADDRESS ASSIGNMENTS
890                                     -----
891
892         001500         .=1500
893         001500         DUP.MAP:
894         001500         000001         DUPCR0: .BLKW 1         ;CONTROL STATUS REGISTER FOR DUP11 NUMBER 0
895         001502         000001         DUPTR0: .BLKW 1         ;VECTOR 'A' FOR DUP11 NUMBER 0
896         001504         000001         DUP0.A: .BLKW 1         ;PARAMETER FOR DUP11 NUMBER 0
897
898         001506         000001         DUPCR1: .BLKW 1         ;CONTROL STATUS REGISTER FOR DUP11 NUMBER 1
899         001510         000001         DUPTR1: .BLKW 1         ;VECTOR 'A' FOR DUP11 NUMBER 1
900         001512         000001         DUP1.A: .BLKW 1         ;PARAMETER FOR DUP11 NUMBER 1
901
902         001514         000001         DUPCR2: .BLKW 1         ;CONTROL STATUS REGISTER FOR DUP11 NUMBER 2
903         001516         000001         DUPTR2: .BLKW 1         ;VECTOR 'A' FOR DUP11 NUMBER 2
904         001520         000001         DUP2.A: .BLKW 1         ;PARAMETER FOR DUP11 NUMBER 2
905
906         001522         000001         DUPCR3: .BLKW 1         ;CONTROL STATUS REGISTER FOR DUP11 NUMBER 3
907         001524         000001         DUPTR3: .BLKW 1         ;VECTOR 'A' FOR DUP11 NUMBER 3
908         001526         000001         DUP3.A: .BLKW 1         ;PARAMETER FOR DUP11 NUMBER 3
909
910         001530         000001         DUPCR4: .BLKW 1         ;CONTROL STATUS REGISTER FOR DUP11 NUMBER 4
911         001532         000001         DUPTR4: .BLKW 1         ;VECTOR 'A' FOR DUP11 NUMBER 4
912         001534         000001         DUP4.A: .BLKW 1         ;PARAMETER FOR DUP11 NUMBER 4
913
914         001536         000001         DUPCR5: .BLKW 1         ;CONTROL STATUS REGISTER FOR DUP11 NUMBER 5
915         001540         000001         DUPTR5: .BLKW 1         ;VECTOR 'A' FOR DUP11 NUMBER 5
916         001542         000001         DUP5.A: .BLKW 1         ;PARAMETER FOR DUP11 NUMBER 5
917
918         001544         000001         DUPCR6: .BLKW 1         ;CONTROL STATUS REGISTER FOR DUP11 NUMBER 6
919         001546         000001         DUPTR6: .BLKW 1         ;VECTOR 'A' FOR DUP11 NUMBER 6
920         001550         000001         DUP6.A: .BLKW 1         ;PARAMETER FOR DUP11 NUMBER 6
921
922         001552         000001         DUPCR7: .BLKW 1         ;CONTROL STATUS REGISTER FOR DUP11 NUMBER 7
923         001554         000001         DUPTR7: .BLKW 1         ;VECTOR 'A' FOR DUP11 NUMBER 7
924         001556         000001         DUP7.A: .BLKW 1         ;PARAMETER FOR DUP11 NUMBER 7
925
926         001560         000000         DUP.END:         000000
927
928
929
930
931
```

PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

15	14	13	12	11	10	09	08	07	06	05	04	03	02	01	00
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I
I	C	O	N	T	R	O	L	R	E	G	I	S	T	E	R
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I
I	A	B	C	D	E	F	G	H	I	I	I	I	I	I	I
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I

DEFINITIONS

- A- OPTIONAL CLEAR JUMPER IN 1
- B- TURNAROUND CONNECTOR CN 1
- C-
- D-

```

951
952
953      :PROGRAM INITIALIZATION
954      :LOCK OUT INTERRUPTS
955      :SET UP PROCESSOR STACK
956      :SET UP POWER FAIL VECTOR
957      :CLEAR PROGRAM CONTROL FLAGS AND COUNTS
958      :TYPE TITLE MESSAGE
959 001562 012737 000340 177776 .START: MOV #340,PS      ;LOCK OUT INTERRUPTS
960 001570 012706 001150      MOV #STACK,SP    ;SET UP STACK
961 001574 012737 005050 000024      MOV #.PFAIL,@#24 ;SET UP POWER FAIL VECTOR
962 001602 113737 001311 001313      MOVB DUPNUM,SAVNUM ;SAVE NUMBER OF DEVICES IN SYSTEM
963 001610 005037 001230      CLR PASCNT      ;CLEAR PASS COUNT
964 001614 105037 001341      CLRB ERRFLG     ;CLEAR ERROR FLAG
965 001620 105037 001343      CLRB QV.FLG     ;ZERO QUICK VERIFY FLAG
966 001624 012737 001500 001316      MOV #DUP.MAP,CREAM ;GET MAP POINTER.
967 001632 112737 000001 001314      MOVB #1,RUN     ;POINT POINTER TO FIRST DEVICE.
968 001640 005037 001232      CLR ERRCNT     ;CLEAR ERROR COUNT
969 001644 005037 001234      CLR LSTERR     ;CLEAR LAST ERROR POINTER
970 001650 012737 000001 001226      MOV #1,TSTNO   ;SET UP FOR TEST 1
971 001656 012737 001562 001214      MOV #.START,RETURN ;SET UP FOR POWER FAIL BEFORE
972                                     ;TESTING STARTS
973 001664 013746 000006      MOV @#6,-(SP)   ;SAVE CURRENT VECTORS
974 001670 013746 000004      MOV @#4,-(SP)   ;
975 001674 012737 001710 000004      MOV #12$,@#4   ;SETUP FOR TIMEOUT
976 001702 005777 177274      TST @SWR       ;REFERENCE HARDWARE SWITCH REG
977 001706 000407      BR 13$        ;BR IF IT EXISTS
978 001710 012737 000176 001202 12$: MOV #SWREG,SWR   ;POINT TO SOFT SWR
979 001716 012737 000174 001200      MOV #DISPREG,DISPLAY ;POINT TO SOFT DISPLAY REG
980 001724 022626      CMP (SP)+,(SP)+ ;ADJUST STACK
981 001726 012637 000004 13$: MOV (SP)+,@#4   ;RESTORE VECTORS
982 001732 012637 000006      MOV (SP)+,@#6   ;
983 001736 105737 001340      TSTB INIFLG    ;HAS INITIALIZATION BEEN PERFORMED
984 001742 001401      BEQ 11$
985 001744 000410      BR 6$
986 001746 022737 003104 000042 11$: CMP #SENDAD,@#42 ;IF ACT-11 AUTO MODE,
987 001754 001404      BEQ 6$        ;DON'T TYPE ID
988 001756 104402 001000      TYPE ,MTITLE   ;TYPE TITLE MESSAGE
989 001762 105137 001340      COMB INIFLG    ;IF NOT SET FLAG AND DO
990 001766 105777 177210 6$: TSTB @SWR      ;BIT7=1??
991 001772 100002      BPL 10$
992 001774 000137 002520      JMP 1$
993 002000      10$:
994 002000 032777 000001 177174      BIT #SW00,@SWR  ;ENTER PARAMETERS
995 002006 001002      BNE .+6        ;YES
996 002010 000137 002360      JMP 21$       ;NO
997 002014 105137 001332      COMB FLAG
998 002020 112737 000001 001340      MOVB #1,INIFLG ;SET TO MANUAL ENTRY
999 002026 012700 001500      MOV #DUP.MAP,RO ;CLR MAP
1000 002032 005020 68$: CLR (RO)+
1001 002034 020027 001560      CMP RO,#DUP.END ;DONE WITH MAP?
1002 002040 001374      BNE 68$      ;BR IF NO
1003 002042 104403      INSTR ;OUTPUT MESSAGE & GET INPUT STRING
1004 002044 005474      MCSR ;MESSAGE
1005 002046 104405      PARAM ;CONVERT STRING
1006 002050 160000      160000 ;LOW LIMIT

```

1007	002052	175500			175500	:HIGH LIMIT
1008	002054	001500			DUPCRO	:STORE AT THIS LOCATION
1009	002056	001			.BYTE 1	:MASK
1010	002057	001			.BYTE 1	:HOW MANY TIMES + 2
1011	002060	104403			INSTR	:OUTPUT MESSAGE & GET INPUT STRING
1012	002062	005513			MVEC	:MESSAGE
1013	002064	104405			PARAM	:CONVERT STRING
1014	002066	000300			300	:LOW LIMIT
1015	002070	000770			770	:HIGH LIMIT
1016	002072	001502			DUPTR0	:STORE AT THIS LOCATION
1017	002074	001			.BYTE 1	:MASK
1018	002075	001			.BYTE 1	:HOW MANY TIMES + 2
1019	002076	104403			INSTR	:OUTPUT MESSAGE & GET INPUT STRING
1020	002100	005703			MPAR	:MESSAGE
1021	002102	104405			PARAM	:CONVERT STRING
1022	002104	000004			4	:LOW LIMIT
1023	002106	000007			7	:HIGH LIMIT
1024	002110	001240			TEMP2	:STORE AT THIS LOCATION
1025	002112	000			.BYTE 0	:MASK
1026	002113	001			.BYTE 1	:HOW MANY TIMES + 2
1027	002114	013737	001240	001320	MOV	TEMP2,PRIITY ;SAVE PRIORITY
1028	002122	104403			INSTR	:OUTPUT MESSAGE & GET INPUT STRING
1029	002124	005650			MTOTAL	:MESSAGE
1030	002126	104405			PARAM	:CONVERT STRING
1031	002130	000001			1	:LOW LIMIT
1032	002132	000010			8.	:HIGH LIMIT
1033	002134	001236			TEMP1	:STORE AT THIS LOCATION
1034	002136	000			.BYTE 0	:MASK
1035	002137	001			.BYTE 1	:HOW MANY TIMES + 2
1036	002140	104403			INSTR	:OUTPUT MESSAGE & GET INPUT STRING
1037	002142	005526			MJMPR	:MESSAGE
1038	002144	104413			SETFLG	:SET FLAG BASED UPON INPUT STRING
1039	002146	001323			OPCLRJ	:THIS FLAG
1040	002150	104403			INSTR	:OUTPUT MESSAGE & GET INPUT STRING
1041	002152	005601			MTCN	:MESSAGE
1042	002154	104413			SETFLG	:SET FLAG BASED UPON INPUT STRING
1043	002156	001322			TCNFLG	:THIS FLAG
1044	002160	105737	001322		TSTB	TCNFLG
1045	002164	001410			BEQ	71\$
1046	002166	104403			INSTR	:OUTPUT MESSAGE & GET INPUT STRING
1047	002170	005727			MSTJM	:MESSAGE
1048	002172	104413			SETFLG	:SET FLAG BASED UPON INPUT STRING
1049	002174	001334			STJMFL	:THIS FLAG
1050	002176	104403			INSTR	:OUTPUT MESSAGE & GET INPUT STRING
1051	002200	005762			MSRJM	:MESSAGE
1052	002202	104413			SETFLG	:SET FLAG BASED UPON INPUT STRING
1053	002204	001336			SRJMFL	:THIS FLAG
1054	002206	105737	001323		TSTB	OPCLRJ
1055	002212	001403			BEQ	69\$
1056	002214	052737	100000	001504	BIS	#BIT15,DUPO.A
1057	002222	105737	001322		TSTB	TCNFLG
1058	002226	001403			BEQ	70\$
1059	002230	052737	040000	001504	BIS	#BIT14,DUPO.A
1060	002236	112737	000001	001312	MOVB	#1,SAVACT
1061	002244	113737	001236	001311	MOVB	TEMP1,DUPNUM
1062	002252	113737	001236	001313	MOVB	TEMP1,SAVNUM

```

1063 002260 005337 001236      65$: DEC    TEMP1
1064 002264 001404              BEQ    64$
1065 002266 000261              SEC
1066 002270 106137 001312      ROLB   SAVACT
1067 002274 000771              BR     65$
1068 002276 113737 001312 001240 64$: MOVB   SAVACT,TEMP2  ;# OF TIMES
1069 002304 113737 001312 001310  MOVB   SAVACT,DUPACTV
1070 002312 000241              CLC
1071 002314 106037 001240      RORB   TEMP2
1072 002320 012700 001500      MOV    #DUPCRO,R0
1073 002324 012701 001506      MOV    #DUPCR1,R1
1074 002330 000241              67$: CLC
1075 002332 106037 001240      RORB   TEMP2
1076 002336 103051              BCC    66$
1077 002340 012011              MOV    (R0)+,(R1)
1078 002342 062721 000010      ADD    #10,(R1)+      ;CSR
1079 002346 012011              MOV    (R0)+,(R1)
1080 002350 062721 000010      ADD    #10,(R1)+      ;VECTOR
1081 002354 012021              MOV    (R0)+,(R1)+    ;PARAMETERS
1082 002356 000764              BR     67$
1083 002360 012700 001500      21$: MOV    #DUP.MAP,R0      ;SETUP TO CLEAR MAP
1084 002364 005020              20$: CLR    (R0)+          ;CLEAR
1085 002366 020027 001560      CMP    R0,#DUP.END    ;CHECK FOR FINISH
1086 002372 001374              BNE    20$            ;BR IF MORE TO GO
1087 002374 012700 001500      MOV    #DUP.MAP,R0    ;SETUP TO DEFAULT
1088 002400 012710 160050      MOV    #160050,(R0)   ;LOAD CSR
1089 002404 012760 000770 000002  MOV    #770,2(R0)     ;LOAD VECTOR
1090 002412 012760 140026 000004  MOV    #140026,4(R0)  ;LOAD PARAMETERS AND SYNC
1091 002420 112737 000005 001320  MOVB   #5,PRIORITY   ;LOAD PRIORITY
1092 002426 012700 000001      MOV    #1,R0          ;SAVE CORE THIS WAY
1093 002432 110037 001310      MOVB   R0,DUPACTV     ;PRESET PROGRAM CONTROLS
1094 002436 110037 001311      MOVB   R0,DUPNUM      ;DITTO
1095 002442 110037 001312      MOVB   R0,SAVACT      ;DITTO
1096 002446 110037 001313      MOVB   R0,SAVNUM      ;DITTO
1097 002452 110037 001322      MOVB   R0,TCNFLG     ;DITTO
1098 002456 110037 001323      MOVB   R0,OF^LRJ     ;DITTO
1099 002462              66$:
1100 002462 104402 006015      16$: TYPE   ,XHEAD      ;TYPE HEADER
1101 002466 012737 001500 001276  MOV    #DUP.MAP,TEMP1 ;SET POINTER
1102 002474 017737 176536 001240  5$: MOV    @TEMP1,TEMP2  ;SET DATA
1103 002502 001406              BEQ    1$            ;ALL DONE WITH DATA
1104 002504 104410              CONVRT
1105 002506 006044              XSTATQ
1106 002510 062737 000002 001236  ADD    #2,TEMP1      ;UPDATE POINTER
1107 002516 000766              BR     5$
1108 002520 032777 000001 176454  1$: BIT    #SW00,@SWR
1109 002526 001405              BEQ    7$
1110 002530 005737 001332      TST    FLAG
1111 002534 001002              BNE    7$
1112 002536 000137 002000      JMP    10$
1113 002542 005037 001332      7$: CLR    FLAG
1114 002546 005737 000042      TST    @#42          ;IS PROGRAM RUNNING UNDER MONITOR
1115 002552 001030              BNE    3$            ;BR IF YES
1116 002554 032777 000010 176420  BIT    #SW03,@SWR    ;SELECT SPECIFIC DEVICES??
1117 002562 001424              BEQ    3$            ;BR IF NO.
1118 002564 104402 005414      TYPE   ,MNEW        ;TYPE THE MESSAGE.

```


1119	002570	005000				CLR	R0		:ZERO DATA LIGHTS
1120	002572	000000				HALT			:WAIT FOR USER TO TELL WHAT DEVICES TO RUN
1121	002574	127737	176402	001312		CMPB	@SWR,SAVACT		:IS THE NUMBER VALID?
1122	002602	101404				BLOS	2\$:BR IF NUMBER IS OK.
1123	002604	104402	005255			TYPE	,MERR3		:TELL USER OF INVALID NUMBER.
1124	002610	000000				HALT			:STOP EVERY THING.
1125	002612	000776				BR	.-2		:RESTART THE PROGRAM AGAIN.
1126	002614	117737	176362	001310	2\$:	MOVB	@SWR,DUPACTV		:GET NEW DEVICE PATTERN
1127	002622	113700	001310			MOVB	DUPACTV,R0		:SHOW THE USER WHAT HE SELECTED.
1128	002626	042700	177400			BIC	#*C<377>,R0		:USE ONLY LOW BYTE.
1129	002632	000000				HALT			:CONTINUE DYNAMIC SWITCHES.
1130	002634	012700	000300		3\$:	MOV	#300,R0		:PREPARE TO CLEAR THE FLOATING
1131	002640	012701	000302			MOV	#302,R1		:VECTOR AREA. 300-776
1132	002644	010120			4\$:	MOV	R1,(R0)+		:START PUTTING 'PC+2' - HALT''
1133	002646	005021				CLR	(R1)+		:IN VECTOR AREA.
1134	002650	022021				CMP	(R0)+,(R1)+		:POP POINTERS
1135	002652	022700	001000			CMP	#1000,R0		:ALL DONE??
1136	002656	001372				BNE	4\$:BR IF NO.
1137									
1138									
1139									
1140									
1141	002660	012737	000340	177776	.BEGIN:	MOV	#340,PS		:LOCK OUT INTERRUPTS
1142	002666	012706	001150			MOV	#STACK,SP		:SET UP STACK
1143	002672	005737	000042			TST	@#42		:IS PROGRAM UNDER MONITOR CONTROL
1144	002676	001023				BNE	2\$:BR IF YES
1145	002700	032777	000004	176274		BIT	#BIT2,@SWR		:CHECK FOR LOCK ON TEST
1146	002706	001411				BEQ	1\$:BR IF NO LOCK DESIRED.
1147	002710	104402	005313			TYPE	,MLOCK		:TYPE LOCK SELECTED.
1148	002714	012737	000240	003174		MOV	#NOP,TTST		:ADJUST SCOPE ROUTINE.
1149	002722	012737	000240	003176		MOV	#NOP,TTST+2		:SET UP TO LOCK
1150	002730	000406				BR	2\$:CONTINUE ALONG.
1151	002732	013737	003306	003174	1\$:	MOV	BRW,TTST		:PREPARE NORMAL SCOPE ROUTINE
1152	002740	013737	003310	003176		MOV	BRX,TTST+2		:LOCK NOT SELECTED, SET UP FOR NORMAL SCOPE LOOP
1153	002746	012737	006226	001214	2\$:	MOV	#CYCLE,RETURN		:START AT "CYCLE" FIND WHICH DEVICE TO TEST
1154	002754	104402	005203			TYPE	,MR		:TYPE R
1155	002760	000177	176230			JMP	@RETURN		:START TESTING

:TEST START AND RESTART

:-----

```

1156                                     ;END OF PASS
1157                                     ;TYPE NAME OF TEST
1158                                     ;UPDATE PASS COUNT
1159                                     ;CHECK FOR EXIT TO ACT-11
1160                                     ;RESTART TEST
1161
1162 002764 005037 001234                .EOP: CLR      LSTERR      ;CLEAR LAST ERROR PC
1163 002770 105037 001341                CLR      ERRFLG      ;CLEAR ERROR FLAG
1164 002774 005237 001230                INC      PASCNT      ;UPDATE PASS COUNT
1165 003000 013777 001230 176172        MOV      PASCNT,@DISPLAY ;DISPLAY PASS COUNT
1166 003006 104402 005157                TYPE    ,MEPASS      ;TYPE END PASS
1167 003012 104402 005342                TYPE    ,MCSR        ;TYPE CSR
1168 003016 104411 003130                CNVRT   ,XCSR        ;SHOW IT
1169 003022 104402 005350                TYPE    ,MVECX       ;TYPE VECTOR
1170 003026 104411 003136                CNVRT   ,XVEC        ;SHOW IT
1171 003032 104402 005356                TYPE    ,MPASSX      ;TYPE PASSES
1172 003036 104411 003144                CNVRT   ,XPASS       ;SHOW IT
1173 003042 104402 005367                TYPE    ,MERRX       ;TYPE ERRORS
1174 003046 104411 003152                CNVRT   ,XERR        ;SHOW IT
1175 003052 105337 001313                DECB    SAVNUM       ;ARE ALL DEVICES TESTED?
1176 003056 001017                        BNE     RESTR        ;BR IF NO.
1177 003060 112737 000377 001343        MOV     #377,QV.FLG  ;SET THE QUICK VERIFY FLAG.
1178 003066 113737 001311 001313        MOV     DUPNUM,SAVNUM ;RESTORE THE COUNT
1179 003074 013701 000042                MOV     @#42,R1      ;CHECK FOR ACT-11 OR DDP
1180 003100 001406                        BEQ     RESTR        ;IF NOT, CONTINUE TESTING
1181 003102 000005                        RESET                    ;STOP THE SHOW--CLEAR THE WORLD
1182 003104                                $ENDAD:
1183 003104 004711                        JSR     PC,(R1)
1184 003106 000240                        NOP
1185 003110 000240                        NOP
1186 003112 000240                        NOP
1187 003114 000240                        NOP
1188 003116 012737 006226 001214        RESTR: MOV     #CYCLE,RETURN
1189 003124 000137 006226                JMP     CYCLE
1190 003130 000001                        XCSR:  1
1191 003132 006 002                        .BYTE  6,2
1192 003134 001404                        RXCSR
1193 003136 000001                        XVEC:  1
1194 003140 003 002                        .BYTE  3,2
1195 003142 001374                        DUPRVC
1196 003144 000001                        XPASS: 1
1197 003146 006 002                        .BYTE  6,2
1198 003150 001230                        PASCNT
1199 003152 000001                        XERR:  1
1200 003154 006 002                        .BYTE  6,2
1201 003156 001232                        ERRCNT
1202
1203                                     ;SCOPE LOOP AND INTERATION HANDLER
1204
1205 003160 005037 001234                .SCOPE: CLR     LSTERR      ;CLEAR LAST ERROR PC
1206 003164 010016                        MOV     R0,(SP)      ;SAVE R0 ON STACK
1207 003166 032777 040000 176006        BIT     #BIT14,@SWR  ;LOOP ON TEST?
1208 003174 001407                        TTST:  BEQ     1$      ;BR IF NO (IF LOCK SW01 = 1;THIS LOCATION = 240)
1209 003176 000437                        BR      3$           ;GO TO 3$ (DITTO)
1210 003200 105777 176000                TSTB   @TK.CSR      ;KYBD DONE?
1211 003204 100034                        BPL     3$           ;BR IF NO (LOCK: HIT A KEY ON TTY TO GO TO NEXT TEST)

```

```

1212 003206 017700 175774      MOV      @TKDBR,R0      ;CLR DONE BIT
1213 003212 000415      BR       2$           ;CONTINUE
1214 003214 032777 004000 175760 1$:  BIT      #SW11,@SWR    ;DELETE ITERATION (QUICK PASS)?
1215 003222 001011      BNE     2$           ;BR IF YES
1216 003224 105737 001343      TSTB   QV.FLG        ;HAS FIRST PASS BEEN COMPLETED?
1217 003230 001406      BEQ    2$           ;BR IF QUICK VERIFY
1218 003232 005237 001224      INC    LPCNT         ;UPDATE ITERATION COUNTER
1219 003236 023737 001224 001222  CMP     LPCNT,ICOUNT  ;ALL ITERATIONS DONE?
1220 003244 001014      BNE     3$           ;BR IF NOT YET
1221 003246 105037 001341      CLRB   ERRFLG       ;PREPARE FOR NEW TEST
1222 003252 005037 001224      CLR    LPCNT        ;START ICOUNT AT ZERO
1223 003256 005037 001220      CLR    LOCK
1224 003262 012737 000050 001222  MOV     #50,ICOUNT    ;RESET ITERATIONS
1225 003270 013737 001216 001214  MOV     NEXT,RETURN   ;GET NEXT TEST
1226 003276 011600      MOV     (SP),R0      ;POP R0 OFF STACK
1227 003300 022626      POP2SP              ;FAKE AN RTI
1228 003302 000177 175706      JMP    @RETURN      ;GO DO THE TEST
1229 003306 001407      BRW:   1407
1230 003310 000437      BRX:   437
1231
1232      ;CHECK FOR FREEZE ON CURRENT DATA
1233      -----
1234
1235 003312 032777 001000 175662 .SCOPI: BIT      #SW09,@SWR    ;IS SW09=1(SET)?
1236 003320 001405      BEQ    1$           ;BR IF NOT SET.
1237 003322 005737 001220      TST    LOCK
1238 003326 001402      BEQ    1$
1239 003330 013716 001220      MOV     LOCK,(SP)    ;GOTO THE ADDRESS IN LOCK.
1240 003334 000002      1$:   RTI           ;GO BACK.
1241
1242      ;TELETYPE OUTPUT ROUTINE
1243      -----
1244
1245 003336 010546      .TYPE: MOV     R5,-(SP)    ;SAVE R5 ON THE STACK.
1246 003340 017605 000002      MOV     @2(SP),R5    ;GET ADDRESS OF MESSAGE.
1247 003344 062766 000002 000002  ADD     #2,2(SP)     ;POP OVER ADDRESS.
1248 003352 032777 010000 175622 1$:   BIT      #SW12,@SWR    ;INHIBIT ALL PRINT OUT??
1249 003360 001012      BNE     3$           ;BR IF NO PRINT OUT WANTED (SW12=1)
1250 003362 105715      TSTB   (R5)         ;IS NUMBER MINUS? (MSB=1(BIT7))
1251 003364 100002      BPL     2$           ;BR IF NUMBER IS PLUS
1252 003366 104402 005136      TYPE   ,MCRLF       ;TYPE A CR/LF!
1253 003372 105777 175612 2$:   TSTB   @TPCSR      ;TTY READY?
1254 003376 100375      BPL     2$           ;BR IF NO.
1255 003400 112577 175606      MOVB   (R5)+,@TPDBR ;PRINT CURRENT CHAR.
1256 003404 001362      BNE     1$           ;IF NOT ZERO KEEP PRINTING!
1257 003406 012605      3$:   MOV     (SP)+,R5   ;END OF OUTPUT. RESTORE R5
1258 003410 000002      RTI           ;GO HOME
1259
1260
1261 003412 010346      .INSTR: MOV     R3,-(SP) ;SAVE R3 ON STACK
1262 003414 010446      MOV     R4,-(SP)    ;SAVE R4 ON STACK
1263 003416 017637 000004 003434  MOV     @4(SP),.MSG
1264 003424 062766 000002 000004  ADD     #2,4(SP)
1265 003432 104402      .INST1: TYPE
1266 003434 000000      .MSG:  0
1267 003436 012704 006162      MOV     #INBUF,R4
  
```

```
1268 003442 012703 000007      MOV      #7,R3
1269 003446 105777 175532      1$:     TSTB   @TKCSR
1270 003452 100375      BPL      1$
1271 003454 117714 175526      MOVB    @TKDBR,(R4)
1272 003460 142714 000200      BILB   #200,(R4)
1273 003464 122427 000015      CMPB   (R4)+,#15
1274 003470 001417      BEQ     INSTR2
1275 003472 105777 175512      2$:     TSTB   @TPCSR
1276 003476 100375      BPL     2$
1277 003500 017777 175502 175504      MOV     @TKDBR,@TPDBR
1278 003506 005303      DEC     R3
1279 003510 001356      BNE     1$
1280 003512 012604      MOV     (SP)+,R4
1281 003514 012603      MOV     (SP)+,R3
1282 003516 010346      .INSTE: MOV     R3,-(SP)
1283 003520 010446      MOV     R4,-(SP)
1284 003522 104402 005132      TYPE   ,MQM
1285 003526 000741      BR      .INST1
1286 003530 012604      INSTR2: MOV    (SP)+,R4      ;RESTORE R4
1287 003532 012603      MOV    (SP)+,R3      ;RESTORE R3
1288 003534 000002      RTI
1289
1290      ;CONVERT ASCII STRING TO OCTAL
1291      ;-----
1292
1293 003536 010546      .PARAM: MOV    R5,-(SP)
1294 003540 010446      MOV    R4,-(SP)
1295 003542 016605 000004      MOV    4(SP),R5
1296 003546 012537 003726      MOV    (R5)+,LOLIM
1297 003552 012537 003730      MOV    (R5)+,HILIM
1298 003556 012537 003732      MOV    (R5)+,DEVADR
1299 003562 112537 003734      MOVB   (R5)+,LOBITS
1300 003566 112537 003735      MOVB   (R5)+,ADRCNT
1301 003572 010566 000004      MOV    R5,4(SP)
1302 003576 005005      PARAM1: CLR    R5
1303 003600 012704 006162      MOV    #INBUF,R4
1304 003604 122714 000015      CMPB   #15,(R4)
1305 003610 001420      BEQ    PARERR
1306 003612 121427 000060      1$:     CMPB   (R4),#60
1307 003616 002415      BLT    PARERR
1308 003620 121427 000067      CMPB   (R4),#67
1309 003624 003012      BGT    PARERR
1310 003626 142714 000060      BICB   #60,(R4)
1311 003632 152405      BISB   (R4)+,R5
1312 003634 122714 000015      CMPB   #15,(R4)
1313 003640 001406      BEQ    LIMITS
1314 003642 006305      ASL    R5
1315 003644 006305      ASL    R5
1316 003646 006305      ASL    R5
1317 003650 000760      BR     1$
1318 003652 104404      PARERR: INSTER
1319 003654 000750      BR     PARAM1
1320
1321      ;TEST TO SEE IF NUMBER IS WITHIN LIMITS
1322      ;-----
1323
```

```
1324 003656 020537 003730      LIMITS: CMP      R5,HILIM
1325 003662 101373              BHI      PARERR
1326 003664 020537 003726      CMP      R5,LOLIM
1327 003670 103770              BLO      PARERR
1328 003672 133705 003734      BITB     LOBITS,R5
1329 003676 001365              BNE      PARERR
1330
1331                          ;STORE NUMBER AT SPECIFIED ADDRESS
1332
1333 003700 013704 003732      1$:     MOV      DEVADR,R4
1334 003704 010524              MOV      R5,(R4)+
1335 003706 062705 000002      ADD      #2,R5
1336 003712 105337 003735      DECB     ADRCNT
1337 003716 001372              BNE      1$
1338 003720 012604              MOV      (SP)+,R4
1339 003722 012605              MOV      (SP)+,R5
1340 003724 000002              RTI
1341 003726 000000      LOLIM:  0
1342 003730 000000      HILIM:  0
1343 003732 000000      DEVADR: 0
1344 003734 000000      LOBITS: 0
1345                          ADRCNT=LOBITS+1
1346
1347                          ;SAVE PC OF TEST THAT FAILED AND R0-R5
1348                          ;-----
1349
1350 003736 016637 000004 001266 .SAV05: MOV      4(SP),SAVPC      ;SAVE R7 (PC)
1351
1352                          ;SAVE R0-R5
1353
1354 003744 010537 001262      SV05:   MOV      R5,SAVR5      ;SAVE R5
1355 003750 010437 001260      MOV      R4,SAVR4      ;SAVE R4
1356 003754 010337 001256      MOV      R3,SAVR3      ;SAVE R3
1357 003760 010237 001254      MOV      R2,SAVR2      ;SAVE R2
1358 003764 010137 001252      MOV      R1,SAVR1      ;SAVE R1
1359 003770 010037 001250      MOV      R0,SAVR0      ;SAVE R0
1360 003774 000002              RTI                      ;LEAVE.
1361
1362                          ;RESTORE R0-R5
1363
1364 003776 013700 001250      .RES05: MOV      SAVR0,R0      ;RESTORE R0
1365 004002 013701 001252      MOV      SAVR1,R1      ;RESTORE R1
1366 004006 013702 001254      MOV      SAVR2,R2      ;RESTORE R2
1367 004012 013703 001256      MOV      SAVR3,R3      ;RESTORE R3
1368 004016 013704 001260      MOV      SAVR4,R4      ;RESTORE R4
1369 004022 013705 001262      MOV      SAVR5,R5      ;RESTORE R5
1370 004026 000002              RTI                      ;LEAVE
1371
1372
1373                          ;CONVERT OCTAL NUMBER TO ASCII AND OUTPUT TO TELEPRINTER
1374                          ;-----
1375
1376 004030 104402 005136      .CONVR: TYPE     ,MCRLF
1377 004034 010046      .CNVRT: MOV      R0,-(SF)
1378 004036 010146      MOV      R1,-(SP)
1379 004040 010346      MOV      R3,-(SP)
```

1380	004042	010446			MOV	R4,-(SP)	
1381	004044	010546			MOV	R5,-(SF)	
1382	004046	017601	000012		MOV	@12(SP),R1	
1383	004052	062766	000002	000012	ADD	#2,12(SP)	
1384	004060	012137	004234		MOV	(R1)+,WRDCNT	
1385	004064	112137	004236		1\$:	MOVB	(R1)+,CHRCNT
1386	004070	112137	004237		MOVB	(R1)+,SPACNT	
1387	004074	013137	004240		MOV	@(R1)+,BINWRD	
1388	004100	013704	004240		2\$:	MOV	BINWRD,R4
1389	004104	113705	004236		MOVB	CHRCNT,R5	
1390	004110	012700	006056		MOV	#TEMP,R0	
1391	004114	010403			3\$:	MOV	R4,R3
1392	004116	042703	177770		BIC	#177770,R3	
1393	004122	062703	000060		ADD	#060,R3	
1394	004126	110320			MOVB	R3,(R0)+	
1395	004130	000241			CLC		
1396	004132	006004			RJR	R4	
1397	004134	000241			CLC		
1398	004136	006004			ROR	R4	
1399	004140	000241			CLC		
1400	004142	006004			ROR	R4	
1401	004144	005305			DEC	R5	
1402	004146	001362			BNE	3\$	
1403	004150	012703	006120		MOV	#MDATA,R3	
1404	004154	114023			4\$:	MOVB	-(R0),(R3)+
1405	004156	105337	004236		DECB	CHRCNT	
1406	004162	001374			BNE	4\$	
1407	004164	105737	004237		TSTB	SPACNT	
1408	004170	001405			BEQ	6\$	
1409	004172	112723	000040		5\$:	MOVB	#040,(R3)+
1410	004176	105337	004237		DECB	SPACNT	
1411	004202	001373			BNE	5\$	
1412	004204	105013			6\$:	CLRB	(R3)
1413	004206	104402	006120		TYPE	,MDATA	
1414	004212	005337	004234		DEC	WRDCNT	
1415	004216	001322			BNE	1\$	
1416	004220	012605			MOV	(SP)+,R5	
1417	004222	012604			MOV	(SP)+,R4	
1418	004224	012603			MOV	(SP)+,R3	
1419	004226	012601			MOV	(SP)+,R1	
1420	004230	012600			MOV	(SP)+,R0	
1421	004232	000002			RTI		
1422	004234	000000			WRDCNT:	0	
1423	004236	000000			CHRCNT:	0	
1424		004237			SPACNT-CHRCNT+1		
1425	004240	000000			BINWRD:	0	
1426							
1427							
1428							
1429							
1430							
1431							
1432							
1433	004242	017605	000000		.SETFLG:MOV	@(SP),R5	
1434	004246	042737	000040	006162	BIC	#40,INBUF	
1435	004254	122737	000116	006162	CMPB	#'N',INBUF	;IS IT 'N' ?


```

1436 004262 001002      BNE      1$
1437 004264 105015      CLR      (R5)      ;000
1438 004266 000406      BR       2$
1439 004270 122737 000'31 006162 1$:  CMP      #'Y',INBUF      ;IS IT 'Y' ?
1440 004276 001005      BNE      3$
1441 004300 112715 177777      MOV      #-1,(R5)      ;377
1442 004304 062716 000002      ADD      #2,(SP)
1443 004310 000002      RTI
1444 004312 104404      3$:  INSTER  ;RETRY
1445 004314 000752      BR       .SETFLG
1446
1447
1448      ;TRAP DISPATCH SERVICE
1449      ;ARGUMENT OF TRAP IS EXTRACTED
1450      ;AND USED AS OFFSET TO OBTAIN POINTER
1451      ;TO SELECTED SUBROUTINE
1452
1453 004316 011646      .TRPSR: MOV      (SP),-(SP)      ;GET PC OF RETURN
1454 004320 162716 000002      SUB      #2,(SP)      ;=PC OF TRAP
1455 004324 017616 000000      MOV      @ (SP), (SP)      ;GET TRP
1456 004330 006316      TRPOK: ASL      (SP)      ;MULTIPLY TRAP ARG BY 2
1457 004332 042716 177001      BIC      #177001,(SP)      ;CLEAR UNWANTED BITS
1458 004336 062716 001344      ADD      #.TRPTAB,(SP)      ;POINTER TO SUBROUTINE ADDRESS
1459 004342 017616 000000      MOV      @ (SP), (SP)      ;SUBROUTINE ADDRESS
1460 004346 000136      JMP      @ (SP)+      ;GO TO SUBROUTINE
1461
1462      ;ERROR HANDLER
1463      ;-----
1464
1465 004350 032777 010000 174624 .HLT:  BIT      #SW12,@SWR      ;BELL ON ERROR?
1466 004356 001406      BEQ      XBX      ;BR IF NO BELL
1467 004360 105777 174624      TSTB     @TPCSR      ;TTY READY.
1468 004364 100003      BPL      XBX      ;DON'T WAIT IF TTY NOT READY.
1469 004366 112777 000207 174616      MOV      #207,@TPDBR      ;PUSH A BELL AT THE TTY.
1470 004374 032777 020000 174600 XBX:  BIT      #SW13,@SWR      ;DELETE ERROR PRINT OUT?
1471 004402 001105      BNE      HALTS      ;BR IF NO PRINT OUT WANTED.
1472 004404 021637 001234      CMP      (SP),LSTERR      ;WAS THIS ERROR FOUND LAST TIME?
1473 004410 001404      BEQ      1$      ;BR IF YES
1474 004412 011637 001234      MOV      (SP),LSTERR      ;RECORD BEING HERE
1475 004416 105037 001341      CLR      ERRFLG      ;PREPARE HEADER
1476 004422 104406      1$:  SAVO5      ;SAVE ALL PROC REGISTERS
1477 004424 011605      MOV      (SP),R5      ;GET THE PC OF ERROR
1478 004426 162705 000002      SUB      #2,R5      ;GET ADDRESS OF TRAP CALL
1479 004432 011504      MOV      (R5),R4      ;GET HLT INSTRUCTION
1480 004434 006304      ASL      R4      ;MULT BY TWO
1481 004436 061504      ADD      (R5),R4      ;DOUBLE IT
1482 004440 006304      ASL      R4      ;MULT AGAIN
1483 004442 042704 177001      BIC      #177001,R4      ;CLEAR JUNK
1484 004446 062704 030026      ADD      #.ERRTAB,R4      ;GET POINTER
1485 004452 012437 004566      MOV      (R4)+,ERRMSG      ;GET ERROR MESSAGE
1486 004456 012437 004600      MOV      (R4)+,DATAHD      ;GET DATA HEADRER
1487 004462 011437 004612      MOV      (R4),DATABP      ;GET DATA TABLE
1488 004466 105737 001341      TSTB     ERRFLG      ;TYPE HEADREER
1489 004472 001403      BEQ      TYPMSG      ;BR IF YES
1490 004474 005737 004612      TST      DATABP      ;DOES DATA TABLE EXIST?
1491 004500 001040      BNE      TYPDAT      ;BR IF YES.

```

1492	004502	104402	005136		TYPMSG: TYPE	,MCRLF	
1493	004506	104402	005136		TYPE	,MCRLF	
1494	004512	005737	001220		TST	LOCK	
1495	004516	001402			BEQ	1\$	
1496	004520	104402	005412		TYPE	,MASTEK	
1497	004524	104402	005400		1\$: TYPE	,MTSTN	
1498	004530	104411	005000		CONVRT	,XTSTN	:SHOW IT
1499	004534	104402	005467		TYPE	,MERRPC	:TYPE PC.
1500	004540	104411	004772		CONVRT	,ERTABO	:SHOW IT
1501	004544	104402	005136		TYPE	,MCRLF	:GIVE A CR/LF
1502	004550	112737	177777	001341	MOV#	#-1,ERRFLG	:NO MORE HEADER UNLESS NO DATA TABLE.
1503	004556	005737	004566		TST	ERRMSG	:IS THERE AN ERROR MESSAGE?
1504	004562	001402			BEQ	WRKO.FM	:BR IF NO.
1505	004564	104402			TYPE		:TYPE
1506	004566	000000			ERRMSG: 0		: ERROR MESSAGE
1507	004570				WRKO.FM		
1508	004570	005737	004600		TST	DATAHD	:DATA HEADER?
1509	004574	001402			BEQ	TYPDAT	:BR IF NO
1510	004576	104402			TYPE		:TYPE
1511	004600	000000			DATAHD: 0		: DATA HEADER
1512	004602	005737	004612		TYPDAT: TST	DATABP	:DATA TABLE?
1513	004606	001402			BEQ	RESREG	:BR IF NO.
1514	004610	104410			CONVRT		:SHOW
1515	004612	000000			DATABP: 0		: DATA TABLE
1516	004614	104407			RESREG: RES05		:RESTORE PROC REGISTERS
1517	004616	022737	003104	000042	HALTS: CMP	#SENDAD,@#42	:IF ACT-11 AUTO MODE--HALT.!
1518	004624	001403			BEQ	1\$	
1519	004626	005777	174350		TST	@SWR	:HALT ON ERROR?
1520	004632	100035			BPL	EXITER	:BR IF NO HALT ON ERROR
1521	004634	010046			1\$: PUSHRO		:SAVE RO
1522	004636	016600	000002		MOV	2(SP),RO	:SHOW ERROR PC IN DATA LIGHTS
1523	004642	013746	000004		MOV	4,-(SP)	:SAVE OLD TRAP
1524	004646	013746	000006		MOV	6,-(SP)	
1525	004652	012737	004710	000004	MOV	#22\$,4	:FORCE HALT IF TIME-OUT
1526	004660	012737	000340	000006	MOV	#340,6	:WHEN REFERENCING TXCSR
1527	004666	042777	014000	174516	BIC	#SYSTST!MEXT,@TXCSR	
1528	004674	000000			HALT		:HALT
1529	004676	012637	000006		MOV	(SP)+,6	:RESTORE TRAP
1530	004702	012637	000004		MOV	(SP)+,4	
1531	004706	000406			BR	33\$	
1532	004710	000000			22\$: HALT		:HALT
1533	004712	022626			CMP	(SP)+,(SP)+	:POP STACK
1534	004714	012637	000006		MOV	(SP)+,6	:RESTORE TRAP
1535	004720	012637	000004		MOV	(SP)+,4	
1536	004724	012600			33\$: POPRO		:GET RO
1537	004726	005237	001232		EXITER: INC	ERRCNT	:UPDATE ERROR COUNT
1538	004732	032777	000400	174242	BIT	#SW08,@SWR	:GOTO TOP OF TEST?
1539	004740	001007			BNE	1\$:BR IF YES
1540	004742	032777	002000	174232	BIT	#SW10,@SWR	:GOTO NEXT TEST?
1541	004750	001407			BEQ	2\$:BR IF NO
1542	004752	013737	001216	001214	MOV	NEXT,RETURN	:SET FOR NEXT TEST
1543	004760	012706	001150		1\$: MOV	#STACK,SP	:RESET SP
1544	004764	000177	174224		JMP	@RETURN	:GOTO SPECIFIED TEST
1545	004770	000002			2\$: RTI		:RETURN
1546	004772	000001			ERTABO: 1		
1547	004774	006	002		.BYTE	6,2	

```

1548 004776 001266          SAVPC
1549 005000 C00001          XTSTN: 1
1550 005002 003          002          .BYTE 3,2
1551 005004 001226          TSTNO
1552 005006 017600 000000  .PKCLK: MOV @ (SP),R0          :GET THE # OF TICKS TO POKE
1553 005012 062716 000002  ADD #2,(SP)          :POP OVER THE #
1554 005016
1555 005016 052777 020000 174366 1$: BIS #CLK,@TXCSR          :POKE CLOCK UP
1556 005024 005300          DEC R0          :ARE WE DONE?
1557 005026 001405          BEQ 2$          :YES-GO TO 2$
1558 005030 042777 020000 174354  BIC #CLK,@TXCSR          :POKE CLOCK DOWN
1559 005036 005300          DEC R0          :ARE WE DONE?
1560 005040 001366          BNE 1$          :NO-REPEAT
1561 005042 000002 2$: RTI          :RETURN
1562
1563
1564          ;WAIT ROUTINE
1565 005044 000240  SMALL: NOP          :STALL
1566 005046 000207          RTS PC          :RETURN
1567
1568          ;POWER FAIL ROUTINE
1569
1570 005050 012737 005060 000024  .PFAIL: MOV #PWRUP,24          :LOAD PFAIL VECTOR FOR POWER UP
1571 005056 000000          HALT
1572 005060 000005  PWRUP: RESET          :WAIT TTY TO COME UP
1573 005062 012706 001150          MOV #STACK,SP          :REINIT STACK POINTER
1574 005066 012737 005050 000024  MOV #.PFAIL,24          :LOAD PFAIL VECTOR FOR POWER DOWN
1575 005074 104402          TYPE
1576 005076 005141          MPOWER
1577 005100 000177 174110  JMP @RETURN
1578          ;CLRVEC ROUTINE TO FILL COMMUNICATION VECTOR AREA WITH .+2,HALT
1579
1580 005104 012702 000300  CLRVEC: MOV #300,R2          ;R2 COMM VECTOR AREA ADRS
1581 005110 012701 000302  MOV #302,R1          ;INIT R1 WITH ADRS OF HALT
1582 005114 010122 1$: MOV R1,(R2)+          ;MOV .+2 TO PC
1583 005116 005022  CLR (R2)+          ;MOV HALT TO PC
1584 005120 022121  CMP (R1)+,(R1)+          ;INC TO NEXT VECTOR AREA
1585 005122 022701 000776  CMP #776,R1          ;END OF VECTOR AREA
1586 005126 001372  BNE 1$          ;NO
1587 005130 000207  RTS PC          ;RETURN
1588
1589
1590
1591 005132 020040 000077  MQM: .ASCIZ / ?/
(2) 005136 005015 000  MCRLF: .ASCIZ <15><12>
(2) 005141 377 053520 020122  MPOWER: .ASCIZ <377>/PWR FAILED. /
(2) 005157 015 042777 042116  MEPASS: .ASCIZ <15><377>/END PASS CZDPBC /
(2) 005203 377 000122  MR: .ASCIZ <377>/R/
(2) 005206 050377 047522 051107  MERR2: .ASCIZ <377>/PROGRAM INDICATES NO DEVICES PRESENT./
(2) 005255 377 047111 052523  MERR3: .ASCIZ <377>/INSUFFICIENT DATA!/
(2) 005301 377 042524 052123  MTSTPC: .ASCIZ <377>/TEST PC-/
(2) 005313 377 047514 045503  MLOCK: .ASCIZ <377>/LOCK ON SELECTED TEST/
(2) 005342 051503 035122 000040  MCSRX: .ASCIZ /CSR: /
(2) 005350 042526 035103 000040  MVECX: .ASCIZ /VEC: /
(2) 005356 040520 051523 051505  MPASSX: .ASCIZ /PASSES: /
(2) 005367 105 051122 051117  MERRX: .ASCIZ /ERRORS: /

```

```

(2) 005400 042524 052123 047040 MTSTN: .ASCIZ /TEST NO: /
(2) 005412 000052 MASTEK: .ASCIZ /*/
(2) 005414 051777 052105 051440 MNEW: .ASCIZ <377>/SET SWITCH REG TO DUP11'S DESIRED ACTIVE./
(2) 005467 120 035103 000040 MERRPC: .ASCIZ /PC: /
(2) 005474 051377 041505 041440 MCSR: .ASCIZ <377>/REC CSR ADRS /
(2) 005513 377 042526 020103 MVEC: .ASCIZ <377>/VEC ADRS /
(2) 005526 044777 020123 044124 MJMPR: .ASCIZ <377>/IS THE OPTIONAL CLR JMPR IN? (Y OR N) /
(2) 005601 377 051511 052040 MTCN: .ASCIZ <377>/IS THE H325 CONNECTOR ON? (Y OR N) /
(2) 005650 021777 047440 020106 MTOTAL: .ASCIZ <377>/# OF DUP'S (IN OCTAL) /
(2) 005703 377 051120 047511 MPAR: .ASCIZ <377>/PRIORITY (4 TO 7) /
(2) 005727 377 042523 020103 MSTJM: .ASCIZ <377>/SEC TX JMPR IN? (Y OR N) /
(2) 005762 051777 041505 051040 MSRJM: .ASCIZ <377>/SEC RX JMPR IN? (Y OR N) /
(2) 006015 377 040515 020120 XHEAD: .ASCIZ <377>/MAP OF DUP11 STATUS/<377>
(2) 006044 .EVEN
(2) 00604' 000002 XSTATQ: 2
1592 006046 006 003 .BYTE 6,3
1593 006050 001236 TEMP1
1594 006052 006 002 .BYTE 6,2
1595 006054 001240 TEMP2
1596 .EVEN
1597
1598 006056 000000 TEMP: 0
1599 006120 .=. +40
1600 006120 000000 MDATA: 0
1601 006162 .=. +40
1602 006162 000000 INBUF: 0
1603 006224 .-. +40
1604 006224 000001 TRP.PC: .BLKW 1
1605

```

```

1606
1607
1608
1609
1610
1611
1612
1613
1614
1615 006226 105737 001310      CYCLE:  TSTB      DUPACTV      ;ARE ANY DUP11'S TO BE TESTED?
1616 006232 001004                BNE          1$          ;BR IF OK.
1617 006234 104402 005206      TYPE        ,MERR2      ;NO DUP11'S SELECTED.!
1618 006240 000000                HALT                ;STOP THE SHOW.
1619 006242 000776                BR              .-2      ;DISQUALIFY CONT. SW.
1620 006244 133737 001314 001310 1$:  BITB      RUN,DUPACTV    ;IS THIS ONE 'ACTIVE'
1621 006252 001020                BNE          2$          ;BR IF GOOD ONE FOUND.
1622 006254 000241                CLC                ;CLEAR PROC. CARRY BIT.
1623 006256 106137 001314      ROLB       RUN          ;UPDATE POINTER
1624 006262 105537 001314      ADCB       RUN          ;CATCH CARRY FROM RUN
1625 006266 062737 000006 001316  ADD        #6,CREAM      ;UPDATE ADDRESS POINTER.
1626 006274 022737 001560 001316  CMP        #DUP.END,CREAM
1627 006302 001360                BNE          1$          ;KEEP GOING; NOT ALL TESTED FOR.
1628 006304 012737 001500 001316  MOV        #DUP.MAP,CREAM ;RESET ADDRESS POINTER.
1629 006312 000754                BR          1$          ;KEEP LOOKING FOR ACTIVE DUP11
1630 006314 000241                2$:  CLC                ;CLEAR PROC. CARRY.
1631 006316 106137 001314      ROLB       RUN          ;UPDATE POINTER.
1632 006322 105537 001314      ADCB       RUN          ;CATCH CARRY.
1633 006326 013700 001316      MOV        CREAM,RO     ;GET ADDRESS POINTER.
1634 006332 062737 000006 001316  ADD        #6,CREAM      ;UPDATE.
1635 006340 022737 001560 001316  CMP        #DUP.END,CREAM
1636
1637 006346 001003                BNE          3$          ;ALL DONE?
1638 006350 012737 001500 001316  MOV        #DUP.MAP,CREAM ;BR IF NO.
1639 006356 012037 001404                3$:  MOV        (RO)+,RXCSR    ;RESTORE POINTER.
1640 006362 012037 001374                MOV        (RO)+,DUPRVC  ;LOAD SYSTEM CTRL. REG
1641 006366 012037 001434                MOV        (RO)+,LOO.00  ;LOAD VECTOR
1642 006372 012700 000002                MOV        #2,RO        ;GET PARAMETERS
1643 006376 013737 001404 001424  MOV        RXCSR,HUPRCR  ;SAVE CORE THIS WAY!
1644 006404 005237 001424                INC        HUPRCR       ;GET CONTROL REG HIGH BYTE
1645 006410 013737 001424 001406  MOV        HUPRCR,RXDBUF ;GOT IT
1646 006416 005237 001406                INC        RXDBUF       ;GET RX CONTROL REG BUFFER
1647 006422 013737 001406 001416  MOV        RXDBUF,DUPSEC ;GOT IT
1648 006430 013737 001406 001410  MOV        RXDBUF,PARCSR ;GOT SECONDARY REG SELECT REG
1649 006436 013737 001406 001422  MOV        RXDBUF,HUPRBF ;GOT PARAMETER STATUS REGISTER
1650 006444 005237 001422                INC        HUPRBF       ;GET RX BUFFER HIGH BYTE
1651 006450 013737 001422 001420  MOV        HUPRBF,HUPPSR ;GOT IT
1652 006456 013737 001420 001412  MOV        HUPPSR,TXCSR  ;GOT PAR STATUS REG HIGH BYTE
1653 006464 005237 001412                INC        TXCSR        ;GET TX CONTROL REGISTER
1654 006470 013737 001412 001430  MOV        TXCSR,HUPTCR  ;GOT IT
1655 006476 005237 001430                INC        HUPTCR       ;GET TX CONTROL REG HIGH BYTE
1656 006502 013737 001430 001414  MOV        HUPTCR,TXDBUF ;GOT IT
1657 006510 005237 001414                INC        TXDBUF       ;BET TX BUFFER
1658 006514 013737 001414 001426  MOV        TXDBUF,HUPTBF ;GOT IT
1659 006522 005237 001426                INC        HUPTBF       ;GET TX BUFFER HIGH BYTE
1660
1661 006526 013737 001374 001376  MOV        DUPRVC,DUPRPS ;GOT IT
;RX VECTOR

```

1662	006534	060037	001376			ADD	RO,DUPRPS	:RX PRIORITY LEVEL
1663	006540	013737	001376	001400		MOV	DUPRPS,DUPTVC	
1664	006546	060037	001400			ADD	RO,DUPTVC	:TX VECTOR
1665	006552	013737	001400	001402		MOV	DUPTVC,DUPTPS	
1666	006560	060037	001402			ADD	RO,DUPTPS	:TX PRIORITY LEVEL
1667								
1668								
1669	006564	012700	001434			MOV	#L00.00,RO	:LOAD STAUS 00-00
1670	006570	012701	001432			MOV	#MASK,A,R1	:PREPARE MASK.
1671	006574	012702	001433			MOV	#CLK.A,R2	:PREPARE CLOCKS
1672	006600	004737	006744			JSR	PC,FIX.00	:GO AND CALCULATE CONFIGURATION.
1673	006604	005737	000042			TST	@#42	
1674	006610	001050				BNE	4\$	
1675	006612	032777	000002	172362		BIT	#SW01,@SWR	:IF SW01-1,GET STARTING TEST #
1676	006620	001444				BEQ	4\$	
1677	006622	104402	005136		7\$:	TYPE	,MCRLF	
1678	006626	104403				INSTR	:OUTPUT MESSAGE & GET INPUT STRING	
1679	006630	005400				MTSTN	:MESSAGE	
1680	006632	104405				PARAM	:CONVERT STRING	
1681	006634	000001				1	:LOW LIMIT	
1682	006636	001000				1000	:HIGH LIMIT	
1683	006640	001226				TSTNO	:STORE AT THIS LOCATION	
1684	006642	000			.BYTE	0	:MASK	
1685	006643	001			.BYTE	1	:HOW MANY TIMES + 2	
1686	006644	012700	007160			MOV	#TST1,RO	
1687	006650	022710	012737		5\$:	CMP	#12737,(RO)	
1688	006654	001017				BNE	6\$	
1689	006656	023760	001226	000002		CMP	TSTNO,2(RO)	
1690	006664	001013				BNE	6\$	
1691	006666	022760	001226	000004		CMP	#TSTNO,4(RO)	
1692	006674	001007				BNE	6\$	
1693	006676	010037	001214			MOV	RO,RETURN	:SAVE PC
1694	006702	104402	005136			TYPE	,MCRLF	
1695	006706	104402	005203			TYPE	,MR	
1696	006712	000412				BR	8\$	
1697	006714	005720			6\$:	TST	(RO)+	
1698	006716	020027	026412			CMP	RO,#TLAST+10	
1699	006722	001352				BNE	5\$	
1700	006724	104402	005132			TYPE	,MQM	
1701	006730	000734				BR	7\$	
1702								
1703	006732	012737	007160	001214	4\$:	MOV	#TST1,RETURN	:PREPARE RETURN ADDRESS
1704	006740	000177	172250		8\$:	JMP	@RETURN	:GO START TESTING.
1705								
1706	006744	011003			FIX.00:	MOV	(RO),R3	:GET PARAMETERS.
1707	006746	000207			5\$:	RTS	PC	:


```

1708
1709
1710
1711 006750 012104 ACC: MOV (R1)+,R4 ;GET THE FLAG FOR # OF CLOCK TICKS
1712 006752 104412 000002 1$: PKCLK .2
1713 006756 000241 CLC ;PUT CARRY IN A KNOWN STATE
1714 006760 032777 040000 172424 BIT #MTDATA,@TXCSR ;FIND OUT IF BIT IS A 1 OR 0
1715 006766 001401 BEQ .+4 ;BR IF 0
1716 006770 000261 SEC ;SET THE BIT
1717 006772 006004 ROR R4 ;PICK UP CARRY AND PUSH INTO R4
1718 006774 103366 BCC 1$ ;BRANCH IF MORE TO GO
1719 006776 000201 RTS R1
1720 007000 005037 001246 ABRT: CLR TEMP5
1721 007004 012137 001244 MOV (R1)+,TEMP4 ;GET THE # OF ABORTS TO DO
1722 007010 104412 000002 1$: PKCLK .2 ;POKE OUT A BIT
1723 007014 032777 040000 172370 BIT #MTDATA,@TXCSR ;CHECK MAINT DATA OUT
1724 007022 001001 BNE 2$ ;BRANCH IF IT IS A ONE
1725 007024 104013 HLT 13 ;OUTPUT WAS A ZERO--NG
1726 007026 005237 001246 2$: INC TEMP5 ;INC THE # OF BITS OUTPUT
1727 007032 022737 000010 001246 CMP #8.,TEMP5 ;IS THE CHARACTER DONE?
1728 007040 001363 BNE 1$ ;BRANCH IF NOT DONE
1729 007042 005337 001244 DEC TEMP4 ;LOWER THE #TO DO
1730 007046 001360 BNE 1$ ;BRANCH IF NOT DONE
1731 007050 000201 RTS R1
1732
1733 007052 012137 001244 FLG: MOV (R1)+,TEMP4 ;GET THE # OF FLAGS
1734 007056 104412 000002 64$: PKCLK .2 ;POKE OUT THE FIRST BIT OF THE FLAG
1735 007062 032777 040000 172322 BIT #MTDATA,@TXCSR ;CHECK MAINT DATA OUT
1736 007070 001401 BEQ 65$ ;BRANCH IF 0
1737 007072 104012 HLT 12 ;DUP FAILED TO CLOCK OUT FIRST BIT
1738 007074 005037 001246 65$: CLR TEMP5 ;SETUP FOR 1'S OUTPUT
1739 007100 104412 000002 1$: PKCLK .2 ;CONTINUE TO POKE OUT BITS
1740 007104 032777 040000 172300 BIT #MTDATA,@TXCSR ;TEST MAINT DATA OUT
1741 007112 001001 BNE 2$ ;BRANCH IF A 1
1742 007114 104013 HLT 13 ;DUP FAILED TO CLOCK A ONE
1743 007116 005237 001246 2$: INC TEMP5 ;KEEP UP WITH THE # OF 1'S OUTPUT
1744 007122 022737 000006 001246 CMP #6.,TEMP5 ;ARE WE DONE WITH SIX ONES?
1745 007130 001363 BNE 1$ ;NO BRANCH BACK
1746 007132 104412 000002 PKCLK .2 ;YES,OUTPUT THE LAST 0
1747 007136 032777 040000 172246 BIT #MTDATA,@TXCSR ;CHECK IT
1748 007144 001401 BEQ 3$ ;BRANCH IF A 0
1749 007146 104012 HLT 12 ;LAST BIT OF FLAG WAS NOT CORECT
1750 007150 005337 001244 3$: DEC TEMP4 ;ARE WE DONE WITH FLAGS?
1751 007154 001340 BNE 64$ ;BR IF NO
1752 007156 000201 RTS R1
1753

```

CONTROL REGISTERS ADDRESS TIMEOUT TEST

1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785

007160	012737	000001	001226
007166	012737	007272	001216
007174	012737	007226	001220
007202	012700	000004	
007206	013701	001404	
007212	012737	007264	000004
007220	012737	000340	000006
007226	005711		
007230	105711		
007232	105761	000001	
007236	104401		
007240	062701	000002	
007244	005300		
007246	001367		
007250	012737	000006	000004
007256	005037	000006	
007262	104400		
007264	011602		
007266	104001		
007270	000002		

```
***** TEST 1 *****  
*VERIFY THAT ADDRESSING DEVICE DOES *NOT* CAUSE  
*A TIME-OUT TRAP.  
*****  
*  
TEST 1  
*  
*****  
TST1:  MOV #1,@TSTNO  
        MOV #TST2,NEXT  
        MOV #1$,LOCK  
        MOV #4,R0           ;SET FOR MAX. 4 PRI. REGISTERS  
        MOV RXCSR,R1       ;GET FIRST PRI. ADDRESS  
        MOV #2$,4         ;SET FOR TIME-OUT TRAP.  
        MOV #340,6        ;SAFE GUARD.  
1$:     TST (R1)           ;REFERENCE THE ADDRESS.  
        TSTB (R1)         ;REFERENCE BYTE ADDRESS.  
        TSTB 1(R1)  
        SCOP1             ;IF SW09=1; GOTO 1$  
        ADD #2,R1         ;UPDATE TO NEXT ADDRESS.  
        DEC R0            ;ARE ALL ADDRESS CHECKED?  
        BNE 1$           ;BR IF NO.  
        MOV #6,4         ;RESET TRAP ZONE.  
        CLR @#6  
        SCOPE             ;SCOPE THIS TEST  
2$:     MOV (SP),R2       ;SAVE THE TRAP PC  
        HLT 1            ;REPORT TIME-OUT TRAP  
        RTI              ;RETURN TO MAIN PROGRAM
```

::++C
::++C

1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809

007272	012737	000002	001226
007300	012737	007536	001216
007306	012737	007332	001220
007314	012700	007440	
007320	013703	001404	
007324	005013		
007326	012702	000004	
007332	011005		
007334	010513		
007336	011304		
007340	042704	000200	

```
***** TEST 2 *****  
*PRIMARY REGISTER ADDRESSING TEST  
*LOAD EACH PRIMARY REGISTER WITH A  
*DIFFERENT NUMBER AND VERIFY EACH  
*WAS INDIVIDUALLY ADDRESSED  
*****  
*  
TEST 2  
*  
*****  
TST2:  MOV #2,@TSTNO  
        MOV #TST3,NEXT  
        MOV #1$,LOCK  
        MOV #3$,R0           ;SET THE TABLE POINTER  
        MOV RXCSR,R3       ;SET THE DUP HARDWARE POINTER  
        CLR (R3)           ;CLR THE REGISTER BEFORE STARTING  
        MOV #4,R2         ;SET FOR 4 PRIMARY REGISTERS  
1$:     MOV (R0),R5       ;SET 'EXPECTED'  
        MOV R5,(R3)      ;WRITE 'EXPECTED' TO THE REGISTER  
        MOV (R3),R4      ;READ THE REGISTER BACK  
        BIC #BIT7,R4     ;CLR UNWANTED BIT
```

CONTROL REGISTERS DUAL ADDRESSING TEST

```
1810 007344 042704 000200      BIC    #BIT7,R4      ;CLR UNWANTED BITS
1811 007350 020504              CMP    R5,R4        ;DOES EXPECTED=RECEIVED?
1812 007352 001401              BEQ    2$           ;BR IF YES
1813 007354 104003              HLT    3            ;THIS IS A DATA ERROR. IT IS **NOT**
1814                                ;A DUAL ADDRESSING ERROR!!.....
1815 007356 104401      2$:   SCOP1          ;SW09=1?
1816 007360 022023              CMP    (R0)+,(R3)+ ;POP DATA AND HARDWARE POINTERS
1817 007362 005302              DEC    R2           ;UPDATE THE REGISTER COUNTER
1818 007364 001362              BNE    1$          ;BRANCH IF MORE TO GO
1819                                ;:NOW CHECK FOR DUAL ADDRESSING
1820 007366 012700 007440      MOV    #3$,R0       ;SET THE TABLE POINTER
1821 007372 013703 001404      MOV    RXCSR,R3    ;SET THE DUP HARDWARE POINTER
1822 007376 012737 007410 001220  MOV    #4$,LOCK    ;SET FOR SW09=1
1823 007404 012702 000004      MOV    #4,R2       ;SET FOR 4 PRIMARY REGISTERS
1824 007410 011005      4$:   MOV    (R0),R5   ;SET 'EXPECTED'
1825 007412 011304      MOV    (R3),R4    ;READ THE REGISTER BACK
1826 007414 042704 000200      BIC    #BIT7,R4    ;CLR UNWANTED BITS
1827 007420 020504              CMP    R5,R4
1828 007422 001401              BEQ    5$          ;BRANCH IF OK
1829 007424 104003              HLT    3            ;THIS IS A DUAL ADDRESSING ERROR
1830 007426 104401      5$:   SCOP1          ;SW09=1?
1831 007430 022023              CMP    (R0)+,(R3)+ ;POP POINTERS
1832 007432 005302              DEC    R2           ;UPDATE THE REGISTER COUNTER
1833 007434 001365              BNE    4$          ;BRANCH IF MORE TO GO
1834 007436 000404              BR     6$
1835 007440 000020      3$:   .WORD 00020    ;RXCSR
1836 007442 000000      .WORD 00000    ;RXDBUF AND PARCSR
1837 007444 000010      .WORD 00010    ;TXCSR
1838 007446 000100      .WORD 00100    ;TXDBUF
1839                                ;////////////////////////////////////
1840                                ;:NOW CHECK FOR BYTE ADDRESSING ;:++C
1841 007450 012737 007474 001220  6$:   MOV    #11$,LOCK
1842 007456 012700 007526      MOV    #12$,R0    ;SET TABLE POINTER
1843 007462 013703 001404      MOV    RXCSR,R3  ;SET DUP HARDWARE POINTER
1844 007466 005013              CLR    (R3)       ;CLEAR REG
1845 007470 012702 000010      MOV    #10,R2    ;SET 8 BYTE ADDRESSES
1846 007474 111005      11$:  MOVB   (R0),R5   ;SET EXPECTED
1847 007476 110513      MOVB   R5,(R3)   ;WRITE EXPECTED TO REG
1848 007500 111304      MOVB   (R3),R4  ;READ REG BACK
1849 007502 142704 000200      BICB  #BIT7,R4  ;CLR UNWANTED BITS
1850 007506 120504              CMPB  R5,R4      ;DOES EXPECTED=RECEIVED?
1851 007510 001401              BEQ    10$        ;IF YES, BR
1852 007512 104003              HLT    3          ;DATA ERROR
1853 007514 104401      10$:  SCOP1
1854 007516 122023              CMPB  (R0)+,(R3)+ ;POP POINTERS
1855 007520 005302              DEC    R2         ;UPDATE REG CNTR
1856 007522 001364              BNE    11$       ;BR IF MORE TO GO
1857 007524 104400      SCOPE
1858 007526      020      12$:  .BYTE 020      ;LO BYTE RXCSR
1859 007527      001      .BYTE 001      ;HI BYTE RXCSR
1860 007530      000      .BYTE 000      ;LO BYTE RXDBUF AND PARCSR
1861 007531      000      .BYTE 000      ;HI BYTE RXDBUF AND PARCSR
1862 007532      010      .BYTE 010      ;LO BYTE TXCSR
1863 007533      000      .BYTE 000      ;HI BYTE TXCSR
1864 007534      100      .BYTE 100      ;LO BYTE TXDBUF
1865 007535      002      .BYTE 002      ;HI BYTE TXDBUF
```

CONTROL REGISTERS DUAL ADDRESSING TEST

////////////////////////////////////

1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921

007536 012737 000003 001226
007544 012737 007600 001216
007552 005005
007554 013703 001404
007560 012713 177777
007564 000005
007566 011304
007570 020504
007572 001401
007574 104002
007576 104400

007600 012737 000004 001226
007606 012737 007636 001216
007614 005005
007616 013703 001406
007622 000005
007624 011304
007626 020504
007630 001401
007632 104002
007634 104400

```
***** TEST 3 *****  
*RECEIVER CONTROL REGISTER RESET TEST. TEST THAT AFTER  
*RECEIVER CONTROL REGISTER IS WRITTEN AND A BUS RESET IS  
*DONE THAT RECEIVER CONTROL REGISTER IS CLEARED.  
*****  
:*****  
: TEST 3  
:*****  
:*****  
TST3: MOV #3,@TSTNO  
      MOV #TST4,NEXT  
      CLR R5 ;SET 'EXPECTED'  
      MOV RXCSR,R3 ;GET THE RECEIVER CONTROL REGISTER  
      MOV #-1,(R3) ;LOAD RECEIVER CONTROL REGISTER WITH ALL ONES  
      RESET  
      MOV (R3),R4 ;READ THE RECEIVER CONTROL REGISTER  
      CMP R5,R4 ;R5=GOOD,R4= ?  
      BEQ 1$ ;BR IF OK  
      HLT 2 ;COMPARISON ERROR  
1$: SCOPE ;SCOPE THIS TEST
```

```
***** TEST 4 *****  
*RECEIVER BUFFER REGISTER RESET TEST. TEST THAT AFTER A BUS  
*RESET IS DONE THAT RECEIVER BUFFER REGISTER IS CLEARED.  
*****  
:*****  
: TEST 4  
:*****  
:*****  
TST4: MOV #4,@TSTNO  
      MOV #TST5,NEXT  
      CLR R5 ;SET 'EXPECTED'  
      MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER  
      RESE:  
      MOV (R3),R4 ;READ THE RECEIVER BUFFER REGISTER  
      CMP R5,R4 ;R5=GOOD,R4= ?  
      BEQ 1$ ;BR IF OK  
      HLT 2 ;COMPARISON ERROR  
1$: SCOPE ;SCOPE THIS TEST
```

```
***** TEST 5 *****  
*PARAMETER STATUS REGISTER RESET TEST. TEST THAT AFTER  
*PARAMETER STATUS REGISTER IS WRITTEN AND A BUS RESET IS  
*DONE THAT PARAMETER STATUS REGISTER IS CLEARED.  
*****
```

PARAMETER STATUS REGISTER RESET TEST

1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977

007636 012737 000005 001226
007644 012737 007700 001216
007652 005005
007654 013703 001410
007660 012713 177777
007664 000005
007666 011304
007670 020504
007672 001401
007674 104002
007676 104400

007700 012737 000006 001226
007706 012737 007746 001216
007714 005005
007716 013703 001412
007722 012713 177777
007726 000005
007730 011304
007732 042704 000200
007736 020504
007740 001401
007742 104002
007744 104400

```
*****  
*  
: TEST 5  
*  
*****  
*****  
TST5: MOV #5,@TSTNO  
MOV #TST6,NEXT  
CLR R5 ;SET 'EXPECTED'  
MOV PARCSR,R3 ;GET THE PARAMETER STATUS REGISTER  
MOV #-1,(R3) ;LOAD PARAMETER STATUS REGISTER WITH ALL ONES  
RESET  
MOV (R3),R4 ;READ THE PARAMETER STATUS REGISTER  
CMP R5,R4 ;R5=GOOD,R4= ?  
BEQ 1$ ;BR IF OK  
HLT ;COMPARISON ERROR  
1$: SCOPE ;SCOPE THIS TEST
```

***** TEST 6 *****
*TRANSMITTER CONTROL REGISTER RESET TEST. TEST THAT AFTER
*TRANSMITTER CONTROL REGISTER IS WRITTEN AND A BUS RESET IS
*DONE THAT TRANSMITTER CONTROL REGISTER IS CLEARED.

```
*****  
*  
: TEST 6  
*  
*****  
*****  
TST6: MOV #6,@TSTNO  
MOV #TST7,NEXT  
CLR R5 ;SET 'EXPECTED'  
MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER  
MOV #-1,(R3) ;LOAD TRANSMITTER CONTROL REGISTER WITH ALL ONES  
RESET  
MOV (R3),R4 ;READ THE TRANSMITTER CONTROL REGISTER  
BIC #BIT7,R4 ;CLR UNWANTED BITS  
CMP R5,R4 ;R5=GOOD,R4= ?  
BEQ 1$ ;BR IF OK  
HLT 2 ;COMPARISON ERROR  
1$: SCOPE ;SCOPE THIS TEST
```

***** TEST 7 *****
*TRANSMITTER BUFFER REGISTER RESET TEST. TEST THAT AFTER
*TRANSMITTER BUFFER REGISTER IS WRITTEN AND A BUS RESET IS
*DONE THAT TRANSMITTER BUFFER REGISTER IS CLEARED.

```
*****  
*  
: TEST 7  
*  
*****
```

TRANSMITTER BUFFER REGISTER RESET TEST

1978
1979
1980 007746 012737 000007 001226
1981 007754 012737 010010 001216
1982 007762 005005
1983 007764 013703 001414
1984 007770 012713 177777
1985 007774 000005
1986 007776 011304
1987 010000 020504
1988 010002 001401
1989 010004 104002
1990 010006 104400

```
*****  
*****  
TST7:  MOV    #7,@TSTNO  
        MOV    #TST10,NEXT  
        CLR    R5                ;SET 'EXPECTED'  
        MOV    TXDBUF,R3        ;GET THE TRANSMITTER BUFFER REGISTER  
        MOV    #-1,(R3)        ;LOAD TRANSMITTER BUFFER REGISTER WITH ALL ONES  
        RESET  
        MOV    (R3),R4          ;READ THE TRANSMITTER BUFFER REGISTER  
        CMP    R5,R4            ;R5=GOOD,R4=?  
        BEQ    1$              ;BR IF OK  
        HLT    2                ;COMPARISON ERROR  
1$:     SCOPE                    ;SCOPE THIS TEST
```

1991
1992
1993
1994
1995
1996
1997

```
***** TEST 10 *****  
*TRANSMITTER CONTROL REGISTER READ/WRITE BIT TEST.  
*SET BIT3, VERIFY BIT3 WAS SET.  
*CLEAR BIT3, VERIFY BIT3 WAS CLEARED.  
*****
```

1998
1999
2000
2001
2002
2003
2004

```
*****  
*  
: TEST 10  
*  
*****
```

2005 010010 012737 000010 001226
2006 010016 012737 010074 001216
2007 010024 013703 001412
2008 010030 012705 000010
2009 010034 010513
2010 010036 011304
2011 010040 042704 000200
2012 010044 020504
2013 010046 001401
2014 010050 104003
2015 010052 040513
2016 010054 011304
2017 010056 042704 000200
2018 010062 005005
2019 010064 020504
2020 010066 001401
2021 010070 104003
2022 010072 104400

```
*****  
*****  
TST10: MOV    #10,@TSTNO  
        MOV    #TST11,NEXT  
        MOV    TXCSR,R3        ;SET REGISTER TO BE TESTED.  
        MOV    #BIT3,R5        ;SET 'EXPECTED'  
        MOV    R5,(R3)        ;WRITE THE REGISTER.  
        MOV    (R3),R4        ;READ THE REGISTER.  
        BIC    #BIT7,R4        ;CLEAR UNWANTED BITS  
        CMP    R5,R4            ;R5=GOOD; R4=UNKNOWN.  
        BEQ    1$              ;ARE THEY THE SAME?  
        HLT    3                ;COMPARISON ERROR.  
1$:     BIC    R5,(R3)          ;CLEAR BIT3  
        MOV    (R3),R4        ;READ THE REGISTER.  
        BIC    #BIT7,R4        ;CLEAR UNWANTED BITS  
        CLR    R5                ;SET 'EXPECTED'  
        CMP    R5,R4            ;R5=GOOD; R4=?  
        BEQ    2$              ;BR IF OK  
        HLT    3                ;COMPARISON ERROR  
2$:     SCOPE                    ;SCOPE THIS TEST
```

2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033

```
***** TEST 11 *****  
*TRANSMITTER CONTROL REGISTER READ/WRITE BIT TEST.  
*SET BIT4, VERIFY BIT4 WAS SET.  
*CLEAR BIT4, VERIFY BIT4 WAS CLEARED.  
*****
```

```
*****  
*  
: TEST 11  
*  
*****
```

TRANSMITTER CONTROL REGISTER READ/WRITE TEST BIT 4

```
2034  
2035  
2036  
2037 010074 012737 000011 001226 TST11: MOV #11, @#TSTNO  
2038 010102 012737 010160 001216 MOV #TST12, NEXT  
2039 010110 013703 001412 MOV TXCSR, R3 ;SET REGISTER TO BE TESTED.  
2040 010114 012705 000020 MOV #BIT4, R5 ;SET 'EXPECTED'.  
2041 010120 010513 MOV R5, (R3) ;WRITE THE REGISTER.  
2042 010122 011304 MOV (R3), R4 ;READ THE REGISTER.  
2043 010124 042704 000200 BIC #BIT7, R4 ;CLEAR UNWANTED BITS  
2044 010130 020504 CMP R5, R4 ;R5=GOOD; R4=UNKNOWN.  
2045 010132 001401 BEQ 1$ ;ARE THEY THE SAME?  
2046 010134 104003 HLT 3 ;COMPARISON ERROR.  
2047 010136 040513 1$: BIC R5, (R3) ;CLEAR BIT4  
2048 010140 011304 MOV (R3), R4 ;READ THE REGISTER.  
2049 010142 042704 000200 BIC #BIT7, R4 ;CLEAR UNWANTED BITS  
2050 010146 005005 CLR R5 ;SET 'EXPECTED'  
2051 010150 020504 CMP R5, R4 ;R5=GOOD; R4=?  
2052 010152 001401 BEQ 2$ ;BR IF OK  
2053 010154 104003 HLT 3 ;COMPARISON ERROR  
2054 010156 104400 2$: SCOPE ;SCOPE THIS TEST  
2055  
2056  
2057 ;***** TEST 12 *****  
2058 ;*TRANSMITTER CONTROL REGISTER READ/WRITE BIT TEST.  
2059 ;*SET BIT10, VERIFY BIT10 WAS SET.  
2060 ;*CLEAR BIT10, VERIFY BIT10 WAS CLEARED.  
2061 ;*****  
2062  
2063 ;*****  
2064 ; TEST 12  
2065 ;*****  
2066  
2067 ;*****  
2068 ;*****  
2069 010160 012737 000012 001226 TST12: MOV #12, @#TSTNO  
2070 010166 012737 010244 001216 MOV #TST13, NEXT  
2071 010174 013703 001412 MOV TXCSR, R3 ;SET REGISTER TO BE TESTED.  
2072 010200 012705 002000 MOV #BIT10, R5 ;SET 'EXPECTED'.  
2073 010204 010513 MOV R5, (R3) ;WRITE THE REGISTER.  
2074 010206 011304 MOV (R3), R4 ;READ THE REGISTER.  
2075 010210 042704 000200 BIC #BIT7, R4 ;CLEAR UNWANTED BITS  
2076 010214 020504 CMP R5, R4 ;R5=GOOD; R4=UNKNOWN.  
2077 010216 001401 BEQ 1$ ;ARE THEY THE SAME?  
2078 010220 104003 HLT 3 ;COMPARISON ERROR.  
2079 010222 040513 1$: BIC R5, (R3) ;CLEAR BIT10  
2080 010224 011304 MOV (R3), R4 ;READ THE REGISTER.  
2081 010226 042704 000200 BIC #BIT7, R4 ;CLEAR UNWANTED BITS  
2082 010232 005005 CLR R5 ;SET 'EXPECTED'  
2083 010234 020504 CMP R5, R4 ;R5=GOOD; R4=?  
2084 010236 001401 BEQ 2$ ;BR IF OK  
2085 010240 104003 HLT 3 ;COMPARISON ERROR  
2086 010242 104400 2$: SCOPE ;SCOPE THIS TEST  
2087  
2088  
2089 ;***** TEST 13 *****
```


TRANSMITTER CONTROL REGISTER READ/WRITE TEST BIT 11

2090 ;*TRANSMITTER CONTROL REGISTER READ/WRITE BIT TEST.
2091 ;*SET BIT11, VERIFY BIT11 WAS SET.
2092 ;*CLEAR BIT11, VERIFY BIT11 WAS CLEARED.
2093 ;*****

2094
2095 ;*****
2096 ;*
2097 ; TEST 13
2098 ;*
2099 ;*****

```
2100 ;*****
2101 010244 012737 000013 001226 TST13: MOV #13,@TSTNO
2102 010252 012737 010330 001216 MOV #TST14,NEXT
2103 010260 013703 001412 MOV TXCSR,R3 ;SET REGISTER TO BE TESTED.
2104 010264 012705 004000 MOV #BIT11,R5 ;SET 'EXPECTED'
2105 010270 010513 MOV R5,(R3) ;WRITE THE REGISTER.
2106 010272 011304 MOV (R3),R4 ;READ THE REGISTER.
2107 010274 042704 000200 BIC #BIT7,R4 ;CLEAR UNWANTED BITS
2108 010300 020504 CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.
2109 010302 001401 BEQ 1$ ;ARE THEY THE SAME?
2110 010304 104003 HLT 3 ;COMPARISON ERROR.
2111 010306 040513 1$: BIC R5,(R3) ;CLEAR BIT11
2112 010310 011304 MOV (R3),R4 ;READ THE REGISTER.
2113 010312 042704 000200 BIC #BIT7,R4 ;CLEAR UNWANTED BITS
2114 010316 005005 CLR R5 ;SET 'EXPECTED'
2115 010320 020504 CMP R5,R4 ;R5=GOOD; R4=?
2116 010322 001401 BEQ 2$ ;BR IF OK
2117 010324 104003 HLT 3 ;COMPARISON ERROR
2118 010326 104400 2$: SCOPE ;SCOPE THIS TEST
2119
2120
```

2121 ;***** TEST 14 *****
2122 ;*TRANSMITTER CONTROL REGISTER READ/WRITE BIT TEST.
2123 ;*SET BIT12, VERIFY BIT12 WAS SET.
2124 ;*CLEAR BIT12, VERIFY BIT12 WAS CLEARED.
2125 ;*****

2126
2127 ;*****
2128 ;*
2129 ; TEST 14
2130 ;*
2131 ;*****

```
2132 ;*****
2133 010330 012737 000014 001226 TST14: MOV #14,@TSTNO
2134 010336 012737 010414 001216 MOV #TST15,NEXT
2135 010344 013703 001412 MOV TXCSR,R3 ;SET REGISTER TO BE TESTED.
2136 010350 012705 010000 MOV #BIT12,R5 ;SET 'EXPECTED'
2137 010354 010513 MOV R5,(R3) ;WRITE THE REGISTER.
2138 010356 011304 MOV (R3),R4 ;READ THE REGISTER.
2139 010360 042704 000200 BIC #BIT7,R4 ;CLEAR UNWANTED BITS
2140 010364 020504 CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.
2141 010366 001401 BEQ 1$ ;ARE THEY THE SAME?
2142 010370 104003 HLT 3 ;COMPARISON ERROR.
2143 010372 040513 1$: BIC R5,(R3) ;CLEAR BIT12
2144 010374 011304 MOV (R3),R4 ;READ THE REGISTER.
2145 010376 042704 000200 BIC #BIT7,R4 ;CLEAR UNWANTED BITS
```

TRANSMITTER CONTROL REGISTER READ/WRITE TEST BIT 12

```
2146 010402 005005 CLR R5 ;SET 'EXPECTED'  
2147 010404 020504 CMP R5,R4 ;R5=GOOD; R4=?  
2148 010406 001401 BEQ 2$ ;BR IF OK  
2149 010410 104003 HLT 3 ;COMPARISON ERROR  
2150 010412 104400 2$: SCOPE ;SCOPE THIS TEST
```

```
***** TEST 15 *****  
*TRANSMITTER CONTROL REGISTER READ/WRITE BIT TEST.  
*SET BIT13, VERIFY BIT13 WAS SET.  
*CLEAR BIT13, VERIFY BIT13 WAS CLEARED.  
*****
```

```
*****  
*  
: TEST 15  
*  
*****
```

```
*****  
TST15: MOV #15, @TSTNO  
MOV #TST16, NEXT  
MOV TXCSR, R3 ;SET REGISTER TO BE TESTED.  
MOV #BIT13, R5 ;SET 'EXPECTED'  
MOV R5, (R3) ;WRITE THE REGISTER.  
MOV (R3), R4 ;READ THE REGISTER.  
BIC #BIT7, R4 ;CLEAR UNWANTED BITS  
CMP R5, R4 ;R5=GOOD; R4=UNKNOWN.  
BEQ 1$ ;ARE THEY THE SAME?  
HLT 3 ;COMPARISON ERROR.  
2175 010456 040513 1$: BIC R5, (R3) ;CLEAR BIT13  
2176 010460 011304 MOV (R3), R4 ;READ THE REGISTER.  
2177 010462 042704 000200 BIC #BIT7, R4 ;CLEAR UNWANTED BITS  
2178 010466 005005 CLR R5 ;SET 'EXPECTED'  
2179 010470 020504 CMP R5, R4 ;R5=GOOD; R4=?  
2180 010472 001401 BEQ 2$ ;BR IF OK  
2181 010474 104003 HLT 3 ;COMPARISON ERROR  
2182 010476 104400 2$: SCOPE ;SCOPE THIS TEST
```

```
***** TEST 16 *****  
*TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.  
*SET BIT0, VERIFY BIT0 WAS SET.  
*CLEAR BIT0, VERIFY BIT0 WAS CLEARED.  
*****
```

```
*****  
*  
: TEST 16  
*  
*****
```

```
*****  
TST16: MOV #16, @TSTNO  
MOV #TST17, NEXT  
MOV TXDBUF, R3 ;SET REGISTER TO BE TESTED.  
MOV #BIT0, R5 ;SET 'EXPECTED'  
MOV R5, (R3) ;WRITE THE REGISTER.
```

TRANSMITTER BUFFER REGISTER READ/WRITE TEST BIT 0

```
2202 010526 011304      MOV      (R3),R4      ;READ THE REGISTER.
2203 010530 020504      CMP      R5,R4       ;R5=GOOD; R4=UNKNOWN.
2204 010532 001401      BEQ      1$          ;ARE THEY THE SAME?
2205 010534 104003      HLT      3           ;COMPARISON ERROR.
2206 010536 040513      1$: BIC      R5,(R3)    ;CLEAR BIT0
2207 010540 011304      MOV      (R3),R4     ;READ THE REGISTER.
2208 010542 005005      CLR      R5          ;SET 'EXPECTED'
2209 010544 020504      CMP      R5,R4       ;R5=GOOD; R4=?
2210 010546 001401      BEQ      2$          ;BR IF OK
2211 010550 104003      HLT      3           ;COMPARISON ERROR
2212 010552 104400      2$: SCOPE           ;SCOPE THIS TEST
```

```
:***** TEST 17 *****
:*TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.
:*SET BIT1, VERIFY BIT1 WAS SET.
:*CLEAR BIT1, VERIFY BIT1 WAS CLEARED.
:*****
```

```
:*****
:
: TEST 17
:
:*****
```

```
2226 *****
2227 010554 012737 000017 001226 TST17: MOV      #17,@TSTNO
2228 010562 012737 010630 001216      MOV      #TST20,NEXT
2229 010570 013703 001414      MOV      TXDBUF,R3    ;SET REGISTER TO BE TESTED.
2230 010574 012705 000002      MOV      #BIT1,R5     ;SET 'EXPECTED'
2231 010600 010513      MOV      R5,(R3)      ;WRITE THE REGISTER.
2232 010602 011304      MOV      (R3),R4     ;READ THE REGISTER.
2233 010604 020504      CMP      R5,R4       ;R5=GOOD; R4=UNKNOWN.
2234 010606 001401      BEQ      1$          ;ARE THEY THE SAME?
2235 010610 104003      HLT      3           ;COMPARISON ERROR.
2236 010612 040513      1$: BIC      R5,(R3)    ;CLEAR BIT1
2237 010614 011304      MOV      (R3),R4     ;READ THE REGISTER.
2238 010616 005005      CLR      R5          ;SET 'EXPECTED'
2239 010620 020504      CMP      R5,R4       ;R5=GOOD; R4=?
2240 010622 001401      BEQ      2$          ;BR IF OK
2241 010624 104003      HLT      3           ;COMPARISON ERROR
2242 010626 104400      2$: SCOPE           ;SCOPE THIS TEST
```

```
:***** TEST 20 *****
:*TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.
:*SET BIT2, VERIFY BIT2 WAS SET.
:*CLEAR BIT2, VERIFY BIT2 WAS CLEARED.
:*****
```

```
:*****
:
: TEST 20
:
:*****
```

```
2256 *****
2257 010630 012737 000020 001226 TST20: MOV      #20,@TSTNO
```

TRANSMITTER BUFFER REGISTER READ/WRITE TEST BIT 2

```
2258 010636 012737 010704 001216      MOV      #TST21,NEXT
2259 010644 013703 001414              MOV      TXDBUF,R3          ;SET REGISTER TO BE TESTED.
2260 010650 012705 000004              MOV      #BIT2,R5          ;SET 'EXPECTED '
2261 010654 010513                      MOV      R5,(R3)           ;WRITE THE REGISTER.
2262 010656 011304                      MOV      (R3),R4           ;READ THE REGISTER.
2263 010660 020504                      CMP      R5,R4             ;R5=GOOD; R4=UNKNOWN.
2264 010662 001401                      BEQ      1$                ;ARE THEY THE SAME?
2265 010664 104003                      HLT      3                  ;COMPARISON ERROR.
2266 010666 040513      1$:      BIC      R5,(R3)       ;CLEAR BIT2
2267 010670 011304                      MOV      (R3),R4           ;READ THE REGISTER.
2268 010672 005005                      CLR      R5                 ;SET 'EXPECTED'
2269 010674 020504                      CMP      R5,R4             ;R5=GOOD; R4=?
2270 010676 001401                      BEQ      2$                ;BR IF OK
2271 010700 104003                      HLT      3                  ;COMPARISON ERROR
2272 010702 104400      2$:      SCOPE          ;SCOPE THIS TEST
```

```
:***** TEST 21 *****
;*TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.
;*SET BIT3, VERIFY BIT3 WAS SET.
;*CLEAR BIT3, VERIFY BIT3 WAS CLEARED.
:*****
```

```
:*****
:
: TEST 21
:
:*****
```

```
2286
2287 010704 012737 000021 001226 TST21: MOV      #21,@TSTNO
2288 010712 012737 010760 001216      MOV      #TST22,NEXT
2289 010720 013703 001414              MOV      TXDBUF,R3          ;SET REGISTER TO BE TESTED.
2290 010724 012705 000010              MOV      #BIT3,R5          ;SET 'EXPECTED '
2291 010730 010513                      MOV      R5,(R3)           ;WRITE THE REGISTER.
2292 010732 011304                      MOV      (R3),R4           ;READ THE REGISTER.
2293 010734 020504                      CMP      R5,R4             ;R5=GOOD; R4=UNKNOWN.
2294 010736 001401                      BEQ      1$                ;ARE THEY THE SAME?
2295 010740 104003                      HLT      3                  ;COMPARISON ERROR.
2296 010742 040513      1$:      BIC      R5,(R3)       ;CLEAR BIT3
2297 010744 011304                      MOV      (R3),R4           ;READ THE REGISTER.
2298 010746 005005                      CLR      R5                 ;SET 'EXPECTED'
2299 010750 020504                      CMP      R5,R4             ;R5=GOOD; R4=?
2300 010752 001401                      BEQ      2$                ;BR IF OK
2301 010754 104003                      HLT      3                  ;COMPARISON ERROR
2302 010756 104400      2$:      SCOPE          ;SCOPE THIS TEST
```

```
:***** TEST 22 *****
;*TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.
;*SET BIT4, VERIFY BIT4 WAS SET.
;*CLEAR BIT4, VERIFY BIT4 WAS CLEARED.
:*****
```

```
:*****
:
: TEST 22
```

2313

TRANSMITTER BUFFER REGISTER READ/WRITE TEST BIT 4

2314
2315
2316
2317 010760 012737 000022 001226
2318 010766 012737 011034 001216
2319 010774 013703 001414
2320 011000 012705 000020
2321 011004 010513
2322 011006 011304
2323 011010 020504
2324 011012 001401
2325 011014 104003
2326 011016 040513
2327 011020 011304
2328 011022 005005
2329 011024 020504
2330 011026 001401
2331 011030 104003
2332 011032 104400

```

:*****
:*****
:*****
TST22: MOV #22,@TSTNO
MOV #TST23,NEXT
MOV TXDBUF,R3 ;SET REGISTER TO BE TESTED.
MOV #BIT4,R5 ;SET 'EXPECTED'
MOV R5,(R3) ;WRITE THE REGISTER.
MOV (R3),R4 ;READ THE REGISTER.
CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.
BEQ 1$ ;ARE THEY THE SAME?
HLT 3 ;COMPARISON ERROR.
1$: BIC R5,(R3) ;CLEAR BIT4
MOV (R3),R4 ;READ THE REGISTER.
CLR R5 ;SET 'EXPECTED'
CMP R5,R4 ;R5=GOOD; R4=?
BEQ 2$ ;BR IF OK
HLT 3 ;COMPARISON ERROR
2$: SCOPE ;SCOPE THIS TEST

```

2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346

```

:***** TEST 23 *****
:*TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.
:*SET BITS, VERIFY BITS WAS SET.
:*CLEAR BITS, VERIFY BITS WAS CLEARED.
:*****

```

2347 011034 012737 000023 001226
2348 011042 012737 011110 001216
2349 011050 013703 001414
2350 011054 012705 000040
2351 011060 010513
2352 011062 011304
2353 011064 020504
2354 011066 001401
2355 011070 104003
2356 011072 040513
2357 011074 011304
2358 011076 005005
2359 011100 020504
2360 011102 001401
2361 011104 104003
2362 011106 104400

```

:*****
:*****
:*****
TEST 23
:*****
:*****
TST23: MOV #23,@TSTNO
MOV #TST24,NEXT
MOV TXDBUF,R3 ;SET REGISTER TO BE TESTED.
MOV #BIT5,R5 ;SET 'EXPECTED'
MOV R5,(R3) ;WRITE THE REGISTER.
MOV (R3),R4 ;READ THE REGISTER.
CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.
BEQ 1$ ;ARE THEY THE SAME?
HLT 3 ;COMPARISON ERROR.
1$: BIC R5,(R3) ;CLEAR BITS
MOV (R3),R4 ;READ THE REGISTER.
CLR R5 ;SET 'EXPECTED'
CMP R5,R4 ;R5=GOOD; R4=?
BEQ 2$ ;BR IF OK
HLT 3 ;COMPARISON ERROR
2$: SCOPE ;SCOPE THIS TEST

```

2363
2364
2365
2366
2367
2368
2369

```

:***** TEST 24 *****
:*TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.
:*SET BIT6, VERIFY BIT6 WAS SET.
:*CLEAR BIT6, VERIFY BIT6 WAS CLEARED.
:*****

```

TRANSMITTER BUFFER REGISTER READ/WRITE TEST BIT 6

2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425

011110 012737 000024 001226
011116 012737 011164 001216
011124 013703 001414
011130 012705 000100
011134 010513
011136 011304
011140 020504
011142 001401
011144 104003
011146 040513
011150 011304
011152 005005
011154 020504
011156 001401
011160 104003
011162 104400

```
*****  
: TEST 24  
: *****  
: *****  
TST24: MOV #24,@TSTNO  
MOV #TST25,NEXT  
MOV TXDBUF,R3 ;SET REGISTER TO BE TESTED.  
MOV #BIT6,R5 ;SET 'EXPECTED'  
MOV R5,(R3) ;WRITE THE REGISTER.  
MOV (R3),R4 ;READ THE REGISTER.  
CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.  
BEQ 1$ ;ARE THEY THE SAME?  
HLT 3 ;COMPARISON ERROR.  
1$: BIC R5,(R3) ;CLEAR BIT6  
MOV (R3),R4 ;READ THE REGISTER.  
CLR R5 ;SET 'EXPECTED'  
CMP R5,R4 ;R5=GOOD; R4=?  
BEQ 2$ ;BR IF OK  
HLT 3 ;COMPARISON ERROR  
2$: SCOPE ;SCOPE THIS TEST
```

***** TEST 25 *****
*TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.
*SET BIT7, VERIFY BIT7 WAS SET.
*CLEAR BIT7, VERIFY BIT7 WAS CLEARED.

```
*****  
: TEST 25  
: *****  
: *****  
TST25: MOV #25,@TSTNO  
MOV #TST26,NEXT  
MOV TXDBUF,R3 ;SET REGISTER TO BE TESTED.  
MOV #BIT7,R5 ;SET 'EXPECTED'  
MOV R5,(R3) ;WRITE THE REGISTER.  
MOV (R3),R4 ;READ THE REGISTER.  
CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.  
BEQ 1$ ;ARE THEY THE SAME?  
HLT 3 ;COMPARISON ERROR.  
1$: BIC R5,(R3) ;CLEAR BIT7  
MOV (R3),R4 ;READ THE REGISTER.  
CLR R5 ;SET 'EXPECTED'  
CMP R5,R4 ;R5=GOOD; R4=?  
BEQ 2$ ;BR IF OK  
HLT 3 ;COMPARISON ERROR  
2$: SCOPE ;SCOPE THIS TEST
```

***** TEST 26 *****

TRANSMITTER BUFFER REGISTER READ/WRITE TEST BIT 8

2426 ;*TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.
2427 ;*SET BIT8, VERIFY BIT8 WAS SET.
2428 ;*CLEAR BIT8, VERIFY BIT8 WAS CLEARED.
2429 ;:*****

2430
2431 :*****
2432 *
2433 : TEST 26
2434 *
2435 :*****

```
2436  
2437 011240 012737 000026 001226 TST26: MOV #26,@TSTNO  
2438 011246 012737 011314 001216 MOV #TST27,NEXT  
2439 011254 013703 001414 MOV TXDBUF,R3 ;SET REGISTER TO BE TESTED.  
2440 011260 012705 000400 MOV #BIT8,R5 ;SET 'EXPECTED'  
2441 011264 010513 MOV R5,(R3) ;WRITE THE REGISTER.  
2442 011266 011304 MOV (R3),R4 ;READ THE REGISTER.  
2443 011270 020504 CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.  
2444 011272 001401 BEQ 1$ ;ARE THEY THE SAME?  
2445 011274 104003 HLT 3 ;COMPARISON ERROR.  
2446 011276 040513 1$: BIC R5,(R3) ;CLEAR BIT8  
2447 011300 011304 MOV (R3),R4 ;READ THE REGISTER.  
2448 011302 005005 CLR R5 ;SET 'EXPECTED'  
2449 011304 020504 CMP R5,R4 ;R5=GOOD; R4=?  
2450 011306 001401 BEQ 2$ ;BR IF OK  
2451 011310 104003 HLT 3 ;COMPARISON ERROR  
2452 011312 104400 2$: SCOPE ;SCOPE THIS TEST  
2453  
2454  
2455
```

2456 ;:***** TEST 27 *****
2457 ;*TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.
2458 ;*SET BIT9, VERIFY BIT9 WAS SET.
2459 ;*CLEAR BIT9, VERIFY BIT9 WAS CLEARED.
2460 ;:*****

2461 :*****
2462 *
2463 : TEST 27
2464 *
2465 :*****

```
2466  
2467 011314 012737 000027 001226 TST27: MOV #27,@TSTNO  
2468 011322 012737 011370 001216 MOV #TST30,NEXT  
2469 011330 013703 001414 MOV TXDBUF,R3 ;SET REGISTER TO BE TESTED.  
2470 011334 012705 001000 MOV #BIT9,R5 ;SET 'EXPECTED'  
2471 011340 010513 MOV R5,(R3) ;WRITE THE REGISTER.  
2472 011342 011304 MOV (R3),R4 ;READ THE REGISTER.  
2473 011344 020504 CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.  
2474 011346 001401 BEQ 1$ ;ARE THEY THE SAME?  
2475 011350 104003 HLT 3 ;COMPARISON ERROR.  
2476 011352 040513 1$: BIC R5,(R3) ;CLEAR BIT9  
2477 011354 011304 MOV (R3),R4 ;READ THE REGISTER.  
2478 011356 005005 CLR R5 ;SET 'EXPECTED'  
2479 011360 020504 CMP R5,R4 ;R5=GOOD; R4=?  
2480 011362 001401 BEQ 2$ ;BR IF OK  
2481 011364 104003 HLT 3 ;COMPARISON ERROR
```

TRANSMITTER BUFFER REGISTER READ/WRITE TEST BIT 9

2482 011366 104400

2\$: SCOPE ;SCOPE THIS TEST

2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537

011370 012737 000030 001226
011376 012737 011444 001216
011404 013703 001414
011410 012705 002000
011414 010513
011416 011304
011420 020504
011422 001401
011424 104003
011426 040513
011430 011304
011432 005005
011434 020504
011436 001401
011440 104003
011442 104400

***** TEST 30 *****
:TRANSMITTER DATA BUFFER REGISTER READ/WRITE BIT TEST.
:SET BIT10, VERIFY BIT10 WAS SET.
:CLEAR BIT10, VERIFY BIT10 WAS CLEARED.

: TEST 30

TST30: MOV #30,@TSTNO
MOV #TST31,NEXT
MOV TXDBUF,R3 ;SET REGISTER TO BE TESTED.
MOV #BIT10,R5 ;SET 'EXPECTED'
MOV R5,(R3) ;WRITE THE REGISTER.
MOV (R3),R4 ;READ THE REGISTER.
CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.
BEQ 1\$;ARE THEY THE SAME?
HLT 3 ;COMPARISON ERROR.
1\$: BIC R5,(R3) ;CLEAR BIT10
MOV (R3),R4 ;READ THE REGISTER.
CLR R5 ;SET 'EXPECTED'
CMP R5,R4 ;R5=GOOD; R4=?
BEQ 2\$;BR IF OK
HLT 3 ;COMPARISON ERROR
2\$: SCOPE ;SCOPE THIS TEST

***** TEST 31 *****
:RECEIVER CONTROL REGISTER READ/WRITE BIT 1 RESET AND CLEAR TEST
:WRITE BIT 1,AND TEST THAT IT WILL BE CLEARED AFTER A
:DEVICE RESET AND RECEIVER CONTROL REGISTER CLR INSTRUCTION

: TEST 31

TST31: MOV #31,@TSTNO
MOV #TST32,NEXT
MOV RXCSR,R3 ;GET THE RECEIVER CONTROL REGISTER
BIS #BIT1,(R3) ;SET BIT 1 AT RECEIVER CONTROL REGISTER
CLR R5 ;SET 'EXPECTED'
BIS #MRESET,@TXCSR ;RESET THE DEVICE
JSR PC,SMALL ;WAIT FOR RESET TO FINISH
BIT #BIT1,(R3) ;TEST BIT 1
BEQ 1\$;BIT 1 IS CLEARED
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 1 IS SET AND SHOULDN'T BE

RECEIVER CONTROL REGISTER RESET AND CLEAR TEST BIT 1

```

2538 011516 052713 000002 1$: BIS #BIT1,(R3) ;SET BIT 1 AGAIN
2539 011522 005013 CLR (R3) ;CLEAR THE RECEIVER CONTROL REGISTER
2540 011524 032713 000002 BIT #BIT1,(R3) ;TEST TO SEE IF BIT 1 CLEARED
2541 011530 001402 BEQ 2$ ;BIT 1 IS OK
2542 011532 011304 MOV (R3),R4 ;LOAD 'FOUND'
2543 011534 104003 HLT 3 ;BIT 1 FAILED TO CLEAR
2544 011536 104400 2$: SCOPE ;SCOPE THIS TEST

```

```

2545
2546
2547 ;***** TEST 32 *****
2548 ;*RECEIVER CONTROL REGISTER READ/WRITE BIT 2 RESET AND CLEAR TEST
2549 ;*WRITE BIT 2,AND TEST THAT IT WILL BE CLEARED AFTER A
2550 ;*DEVICE RESET AND RECEIVER CONTROL REGISTER CLR INSTRUCTION
2551 ;*****
2552
2553

```

```

2554 ;*****
2555 ; TEST 32
2556 ;*****
2557
2558 ;*****

```

```

2559 011540 012737 000032 001226 TST32: MOV #32,@TSTNO
2560 011546 012737 011634 001216 MOV #TST33,NEXT
2561 011554 013703 001404 MOV RXCSR,R3 ;GET THE RECEIVER CONTROL REGISTER
2562 011560 052713 000004 BIS #BIT2,(R3) ;SET BIT 2 AT RECEIVER CONTROL REGISTER
2563 011564 005005 CLR R5 ;SET 'EXPECTED'
2564 011566 052777 000400 167616 BIS #MRESET,@TXCSR ;RESET THE DEVICE
2565 011574 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
2566 011600 032713 000004 BIT #BIT2,(R3) ;TEST BIT 2
2567 011604 001402 BEQ 1$ ;BIT 2 IS CLEARED
2568 011606 011304 MOV (R3),R4 ;LOAD 'FOUND'
2569 011610 104003 HLT 3 ;BIT 2 IS SET AND SHOULDN'T BE
2570 011612 052713 000004 1$: BIS #BIT2,(R3) ;SET BIT 2 AGAIN
2571 011616 005013 CLR (R3) ;CLEAR THE RECEIVER CONTROL REGISTER
2572 011620 032713 000004 BIT #BIT2,(R3) ;TEST TO SEE IF BIT 2 CLEARED
2573 011624 001402 BEQ 2$ ;BIT 2 IS OK
2574 011626 011304 MOV (R3),R4 ;LOAD 'FOUND'
2575 011630 104003 HLT 3 ;BIT 2 FAILED TO CLEAR
2576 011632 104400 2$: SCOPE ;SCOPE THIS TEST
2577
2578

```

```

2579 ;***** TEST 33 *****
2580 ;*RECEIVER CONTROL REGISTER READ/WRITE BIT 3 RESET AND CLEAR TEST
2581 ;*WRITE BIT 3,AND TEST THAT IT WILL BE CLEARED AFTER A
2582 ;*DEVICE RESET AND RECEIVER CONTROL REGISTER CLR INSTRUCTION
2583 ;*****
2584

```

```

2585 ;*****
2586 ; TEST 33
2587 ;*****
2588
2589 ;*****

```

```

2590
2591 011634 012737 000033 001226 TST33: MOV #33,@TSTNO
2592 011642 012737 011730 001216 MOV #TST34,NEXT
2593 011650 013703 001404 MOV RXCSR,R3 ;GET THE RECEIVER CONTROL REGISTER

```

RECEIVER CONTROL REGISTER RESET AND CLEAR TEST BIT 3

```
2594 011654 052713 000010      BIS    #BIT3,(R3)    ;SET BIT 3 AT RECEIVER CONTROL REGISTER
2595 011660 005005              CLR    R5           ;SET 'EXPECTED'
2596 011662 052777 000400 167522  BIS    #MRESET,@TXCSR ;RESET THE DEVICE
2597 011670 004737 005044      JSR    PC,SMALL    ;WAIT FOR RESET TO FINISH
2598 011674 032713 000010      BIT    #BIT3,(R3)  ;TEST BIT 3
2599 011700 001402              BEQ    1$          ;BIT 3 IS CLEARED
2600 011702 011304              MOV    (R3),R4    ;LOAD 'FOUND'
2601 011704 104003              HLT    3           ;BIT 3 IS SET AND SHOULDN'T BE
2602 011706 052713 000010 1$:  BIS    #BIT3,(R3)  ;SET BIT 3 AGAIN
2603 011712 005013              CLR    (R3)       ;CLEAR THE RECEIVER CONTROL REGISTER
2604 011714 032713 000010      BIT    #BIT3,(R3)  ;TEST TO SEE IF BIT 3 CLEARED
2605 011720 001402              BEQ    2$          ;BIT 3 IS OK
2606 011722 011304              MOV    (R3),R4    ;LOAD 'FOUND'
2607 011724 104003              HLT    3           ;BIT 3 FAILED TO CLEAR
2608 011726 104400 2$:  SCOPE          ;SCOPE THIS TEST
```

2609
2610
2611
2612
2613
2614
2615
2616
2617
2618
2619
2620
2621
2622

```
***** TEST 34 *****  
*RECEIVER CONTROL REGISTER READ/WRITE BIT 4 RESET AND CLEAR TEST  
*WRITE BIT 4,AND TEST THAT IT WILL BE CLEARED AFTER A  
*DEVICE RESET AND RECEIVER CONTROL REGISTER CLR INSTRUCTION  
*****
```

```
*****  
*  
: TEST 34  
*  
*****
```

```
2623 011730 012737 000034 001226 TST34: MOV    #34,@TSTNO
2624 011736 012737 012024 001216  MOV    #TST35,NEXT
2625 011744 013703 001404      MOV    RXCSR,R3   ;GET THE RECEIVER CONTROL REGISTER
2626 011750 052713 000020      BIS    #BIT4,(R3) ;SET BIT 4 AT RECEIVER CONTROL REGISTER
2627 011754 005005              CLR    R5         ;SET 'EXPECTED'
2628 011756 052777 000400 167426  BIS    #MRESET,@TXCSR ;RESET THE DEVICE
2629 011764 004737 005044      JSR    PC,SMALL   ;WAIT FOR RESET TO FINISH
2630 011770 032713 000020      BIT    #BIT4,(R3) ;TEST BIT 4
2631 011774 001402              BEQ    1$         ;BIT 4 IS CLEARED
2632 011776 011304              MOV    (R3),R4   ;LOAD 'FOUND'
2633 012000 104003              HLT    3         ;BIT 4 IS SET AND SHOULDN'T BE
2634 012002 052713 000020 1$:  BIS    #BIT4,(R3) ;SET BIT 4 AGAIN
2635 012006 005013              CLR    (R3)      ;CLEAR THE RECEIVER CONTROL REGISTER
2636 012010 032713 000020      BIT    #BIT4,(R3) ;TEST TO SEE IF BIT 4 CLEARED
2637 012014 001402              BEQ    2$         ;BIT 4 IS OK
2638 012016 011304              MOV    (R3),R4   ;LOAD 'FOUND'
2639 012020 104003              HLT    3         ;BIT 4 FAILED TO CLEAR
2640 012022 104400 2$:  SCOPE          ;SCOPE THIS TEST
```

2641
2642
2643
2644
2645
2646
2647
2648
2649

```
***** TEST 35 *****  
*RECEIVER CONTROL REGISTER READ/WRITE BIT 8 RESET AND CLEAR TEST  
*WRITE BIT 8,AND TEST THAT IT WILL BE CLEARED AFTER A  
*DEVICE RESET AND RECEIVER CONTROL REGISTER CLR INSTRUCTION  
*****
```

```
*****
```

RECEIVER CONTROL REGISTER RESET AND CLEAR TEST BIT 8

2650
2651
2652
2653
2654
2655 012024 012737 000035 001226
2656 012032 012737 012120 001216
2657 012040 013703 001404
2658 012044 052713 000400
2659 012050 005005
2660 012052 052777 000400 167332
2661 012060 004737 005044
2662 012064 032713 000400
2663 012070 001402
2664 012072 011304
2665 012074 104003
2666 012076 052713 000400
2667 012102 005013
2668 012104 032713 000400
2669 012110 001402
2670 012112 011304
2671 012114 104003
2672 012116 104400

```

:
: TEST 35
:
: *****
: *****
TST35: MOV #35,@TSTNO
MOV #TST36,NEXT
MOV RXCSR,R3 ;GET THE RECEIVER CONTROL REGISTER
BIS #BIT8,(R3) ;SET BIT 8 AT RECEIVER CONTROL REGISTER
CLR R5 ;SET 'EXPECTED'
BIS #MRESET,@TXCSR ;RESET THE DEVICE
JSR PC,SMALL ;WAIT FOR RESET TO FINISH
BIT #BIT8,(R3) ;TEST BIT 8
BEQ 1$ ;BIT 8 IS CLEARED
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 8 IS SET AND SHOULDN'T BE
1$: BIS #BIT8,(R3) ;SET BIT 8 AGAIN
CLR (R3) ;CLEAR THE RECEIVER CONTROL REGISTER
BIT #BIT8,(R3) ;TEST TO SEE IF BIT 8 CLEARED
BEQ 2$ ;BIT 8 IS OK
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 8 FAILED TO CLEAR
2$: SCOPE ;SCOPE THIS TEST

```

***** TEST 36 *****
*TRANSMITTER CONTROL REGISTER READ/WRITE BIT 3 RESET AND CLEAR TEST
*WRITE BIT 3,AND TEST THAT IT WILL BE CLEARED AFTER A
*DEVICE RESET AND TRANSMITTER CONTROL REGISTER CLR INSTRUCTION

2673
2674
2675
2676
2677
2678
2679
2680
2681
2682
2683
2684
2685
2686
2687 012120 012737 000036 001226
2688 012126 012737 012214 001216
2689 012134 013703 001412
2690 012140 052713 000010
2691 012144 005005
2692 012146 052777 000400 167236
2693 012154 004737 005044
2694 012160 032713 000010
2695 012164 001402
2696 012166 011304
2697 012170 104003
2698 012172 052713 000010
2699 012176 005013
2700 012200 032713 000010
2701 012204 001402
2702 012206 011304
2703 012210 104003
2704 012212 104400
2705

```

: *****
:
: TEST 36
:
: *****
: *****
TST36: MOV #36,@TSTNO
MOV #TST37,NEXT
MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER
BIS #BIT3,(R3) ;SET BIT 3 AT TRANSMITTER CONTROL REGISTER
CLR R5 ;SET 'EXPECIL ..'
BIS #MRESET,@TXCSR ;RESET THE DEVICE
JSR PC,SMALL ;WAIT FOR RESET TO FINISH
BIT #BIT3,(R3) ;TEST BIT 3
BEQ 1$ ;BIT 3 IS CLEARED
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 3 IS SET AND SHOULDN'T BE
1$: BIS #BIT3,(R3) ;SET BIT 3 AGAIN
CLR (R3) ;CLEAR THE TRANSMITTER CONTROL REGISTER
BIT #BIT3,(R3) ;TEST TO SEE IF BIT 3 CLEARED
BEQ 2$ ;BIT 3 IS OK
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 3 FAILED TO CLEAR
2$: SCOPE ;SCOPE THIS TEST

```

TRANSMITTER CONTROL REGISTER RESET AND CLEAR TEST BIT 4

2706
2707
2708
2709
2710
2711
2712
2713
2714
2715
2716
2717
2718
2719
2720
2721
2722
2723
2724
2725
2726
2727
2728
2729
2730
2731
2732
2733
2734
2735
2736
2737
2738
2739
2740
2741
2742
2743
2744
2745
2746
2747
2748
2749
2750
2751
2752
2753
2754
2755
2756
2757
2758
2759
2760
2761

012214 012737 000037 001226
012222 012737 012310 001216
012230 013703 001412
012234 052713 000020
012240 005005
012242 052777 000400 167142
012250 004737 005044
012254 032713 000020
012260 001402
012262 011304
012264 104003
012266 052713 000020
012272 005013
012274 032713 000020
012300 001402
012302 011304
012304 104003
012306 104400

```
***** TEST 37 *****  
*TRANSMITTER CONTROL REGISTER READ/WRITE BIT 4 RESET AND CLEAR TEST  
*WRITE BIT 4, AND TEST THAT IT WILL BE CLEARED AFTER A  
*DEVICE RESET AND TRANSMITTER CONTROL REGISTER CLR INSTRUCTION  
*****  
:*****  
: *  
: TEST 37  
: *  
:*****  
:*****  
TST37: MOV #37,@TSTNO  
MOV #TST40,NEXT  
MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER  
BIS #BIT4,(R3) ;SET BIT 4 AT TRANSMITTER CONTROL REGISTER  
CLR R5 ;SET 'EXPECTED'  
BIS #MRESET,@TXCSR ;RESET THE DEVICE  
JSR PC,SMALL ;WAIT FOR RESET TO FINISH  
BIT #BIT4,(R3) ;TEST BIT 4  
BEQ 1$ ;BIT 4 IS CLEARED  
MOV (R3),R4 ;LOAD 'FOUND'  
HLT 3 ;BIT 4 IS SET AND SHOULDN'T BE  
1$: BIS #BIT4,(R3) ;SET BIT 4 AGAIN  
CLR (R3) ;CLEAR THE TRANSMITTER CONTROL REGISTER  
BIT #BIT4,(R3) ;TEST TO SEE IF BIT 4 CLEARED  
BEQ 2$ ;BIT 4 IS OK  
MOV (R3),R4 ;LOAD 'FOUND'  
HLT 3 ;BIT 4 FAILED TO CLEAR  
2$: SCOPE ;SCOPE THIS TEST
```

***** TEST 40 *****
*TRANSMITTER CONTROL REGISTER READ/WRITE BIT 10 RESET AND CLEAR TEST
*WRITE BIT 10, AND TEST THAT IT WILL BE CLEARED AFTER A
*DEVICE RESET AND TRANSMITTER CONTROL REGISTER CLR INSTRUCTION

```
*****  
:*****  
: *  
: TEST 40  
: *  
:*****  
:*****  
TST40: MOV #40,@TSTNO  
MOV #TST41,NEXT  
MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER  
BIS #BIT10,(R3) ;SET BIT 10 AT TRANSMITTER CONTROL REGISTER  
CLR R5 ;SET 'EXPECTED'  
BIS #MRESET,@TXCSR ;RESET THE DEVICE  
JSR PC,SMALL ;WAIT FOR RESET TO FINISH  
BIT #BIT10,(R3) ;TEST BIT 10  
BEQ 1$ ;BIT 10 IS CLEARED  
MOV (R3),R4 ;LOAD 'FOUND'  
HLT 3 ;BIT 10 IS SET AND SHOULDN'T BE
```

TRANSMITTER CONTROL REGISTER RESET AND CLEAR TEST BIT 10

```

2762 012362 052713 002000 1$: BIS #BIT10,(R3) ;SET BIT 10 AGAIN
2763 012366 005013 CLR (R3) ;CLEAR THE TRANSMITTER CONTROL REGISTER
2764 012370 032713 002000 BIT #BIT10,(R3) ;TEST TO SEE IF BIT 10 CLEARED
2765 012374 001402 BEQ 2$ ;BIT 10 IS OK
2766 012376 011304 MOV (R3),R4 ;LOAD 'FOUND'
2767 012400 104003 HLT 3 ;BIT 10 FAILED TO CLEAR
2768 012402 104400 2$: SCOPE ;SCOPE THIS TEST

```

```

2769
2770
2771 ;***** TEST 41 *****
2772 ;*TRANSMITTER CONTROL REGISTER READ/WRITE BIT 11 RESET AND CLEAR TEST
2773 ;*WRITE BIT 11,AND TEST THAT IT WILL BE CLEARED AFTER A
2774 ;*DEVICE RESET AND TRANSMITTER CONTROL REGISTER CLR INSTRUCTION
2775 ;*****
2776

```

```

2777 ;*****
2778 ;*
2779 ;* TEST 41
2780 ;*
2781 ;*****
2782 ;*****

```

```

2783 012404 012737 000041 001226 TST41: MOV #41,@TSTNO
2784 012412 012737 012500 001216 MOV #TST42,NEXT
2785 012420 013703 001412 MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER
2786 012424 052713 004000 BIS #BIT11,(R3) ;SET BIT 11 AT TRANSMITTER CONTROL REGISTER
2787 012430 005005 CLR R5 ;SET 'EXPECTED'
2788 012432 052777 000400 166752 BIS #MRESET,@TXCSR ;RESET THE DEVICE
2789 012440 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
2790 012444 032713 004000 BIT #BIT11,(R3) ;TEST BIT 11
2791 012450 001402 BEQ 1$ ;BIT 11 IS CLEARED
2792 012452 011304 MOV (R3),R4 ;LOAD 'FOUND'
2793 012454 104003 HLT 3 ;BIT 11 IS SET AND SHOULDN'T BE
2794 012456 052713 004000 1$: BIS #BIT11,(R3) ;SET BIT 11 AGAIN
2795 012462 005013 CLR (R3) ;CLEAR THE TRANSMITTER CONTROL REGISTER
2796 012464 032713 004000 BIT #BIT11,(R3) ;TEST TO SEE IF BIT 11 CLEARED
2797 012470 001402 BEQ 2$ ;BIT 11 IS OK
2798 012472 011304 MOV (R3),R4 ;LOAD 'FOUND'
2799 012474 104003 HLT 3 ;BIT 11 FAILED TO CLEAR
2800 012476 104400 2$: SCOPE ;SCOPE THIS TEST

```

```

2801
2802
2803 ;***** TEST 42 *****
2804 ;*TRANSMITTER CONTROL REGISTER READ/WRITE BIT 12 RESET AND CLEAR TEST
2805 ;*WRITE BIT 12,AND TEST THAT IT WILL BE CLEARED AFTER A
2806 ;*DEVICE RESET AND TRANSMITTER CONTROL REGISTER CLR INSTRUCTION
2807 ;*****
2808

```

```

2809 ;*****
2810 ;*
2811 ;* TEST 42
2812 ;*
2813 ;*****
2814 ;*****

```

```

2815 012500 012737 000042 001226 TST42: MOV #42,@TSTNO
2816 012506 012737 012574 001216 MOV #TST43,NEXT
2817 012514 013703 001412 MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER

```

TRANSMITTER CONTROL REGISTER RESET AND CLEAR TEST BIT 12

```
2818 012520 052713 010000      BIS    #BIT12,(R3)    ;SET BIT 12 AT TRANSMITTER CONTROL REGISTER
2819 012524 005005                CLR    R5            ;SET 'EXPECTED'
2820 012526 052777 000400 166656  BIS    #MRESET,@TXCSR ;RESET THE DEVICE
2821 012534 004737 005044                JSR    PC,SMALL      ;WAIT FOR RESET TO FINISH
2822 012540 032713 010000      BIT    #BIT12,(R3)    ;TEST BIT 12
2823 012544 001402                BEQ    1$           ;BIT 12 IS CLEARED
2824 012546 011304                MOV    (R3),R4       ;LOAD 'FOUND'
2825 012550 104003                HLT    3            ;BIT 12 IS SET AND SHOULDN'T BE
2826 012552 052713 010000 1$:  BIS    #BIT12,(R3)    ;SET BIT 12 AGAIN
2827 012556 005013                CLR    (R3)         ;CLEAR THE TRANSMITTER CONTROL REGISTER
2828 012560 032713 010000      BIT    #BIT12,(R3)    ;TEST TO SEE IF BIT 12 CLEARED
2829 012564 001402                BEQ    2$           ;BIT 12 IS OK
2830 012566 011304                MOV    (R3),R4       ;LOAD 'FOUND'
2831 012570 104003                HLT    3            ;BIT 12 FAILED TO CLEAR
2832 012572 104400 2$:  SCOPE           ;SCOPE THIS TEST
```

```
2833
2834
2835      ;***** TEST 43 *****
2836      ;*TRANSMITTER CONTROL REGISTER READ/WRITE BIT 13 RESET AND CLEAR TEST
2837      ;*WRITE BIT 13,AND TEST THAT IT WILL BE CLEARED AFTER A
2838      ;*DEVICE RESET AND TRANSMITTER CONTROL REGISTER CLR INSTRUCTION
2839      ;*****
```

```
2840
2841      ;*****
2842      ;*
2843      ;* TEST 43
2844      ;*
2845      ;*****
2846      ;*****
```

```
2847 012574 012737 000043 001226  TST43: MOV    #43,@TSTNO
2848 012602 012737 012670 001216  MOV    #TST44,NEXT
2849 012610 013703 001412                MOV    TXCSR,R3     ;GET THE TRANSMITTER CONTROL REGISTER
2850 012614 052713 020000      BIS    #BIT13,(R3)    ;SET BIT 13 AT TRANSMITTER CONTROL REGISTER
2851 012620 005005                CLR    R5            ;SET 'EXPECTED'
2852 012622 052777 000400 166562  BIS    #MRESET,@TXCSR ;RESET THE DEVICE
2853 012630 004737 005044                JSR    PC,SMALL      ;WAIT FOR RESET TO FINISH
2854 012634 032713 020000      BIT    #BIT13,(R3)    ;TEST BIT 13
2855 012640 001402                BEQ    1$           ;BIT 13 IS CLEARED
2856 012642 011304                MOV    (R3),R4       ;LOAD 'FOUND'
2857 012644 104003                HLT    3            ;BIT 13 IS SET AND SHOULDN'T BE
2858 012646 052713 020000 1$:  BIS    #BIT13,(R3)    ;SET BIT 13 AGAIN
2859 012652 005013                CLR    (R3)         ;CLEAR THE TRANSMITTER CONTROL REGISTER
2860 012654 032713 020000      BIT    #BIT13,(R3)    ;TEST TO SEE IF BIT 13 CLEARED
2861 012660 001402                BEQ    2$           ;BIT 13 IS OK
2862 012662 011304                MOV    (R3),R4       ;LOAD 'FOUND'
2863 012664 104003                HLT    3            ;BIT 13 FAILED TO CLEAR
2864 012666 104400 2$:  SCOPE           ;SCOPE THIS TEST
```

```
2865
2866
2867      ;***** TEST 44 *****
2868      ;*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 0 RESET AND CLEAR TEST
2869      ;*WRITE BIT 0,AND TEST THAT IT WILL BE CLEARED AFTER A
2870      ;*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION
2871      ;*****
```

```
2872
2873      ;*****
```

TRANSMITTER BUFFER REGISTER RESET AND CLEAR TEST BIT 0

```
2874  
2875  
2876  
2877  
2878  
2879 012670 012737 000044 001226  
2880 012676 012737 012764 001216  
2881 012704 013703 001414  
2882 012710 052713 000001  
2883 012714 005005  
2884 012716 052777 000400 166466  
2885 012724 004737 005044  
2886 012730 032713 000001  
2887 012734 001402  
2888 012736 011304  
2889 012740 104003  
2890 012742 052713 000001 1$:  
2891 012746 005013  
2892 012750 032713 000001  
2893 012754 001402  
2894 012756 011304  
2895 012760 104003  
2896 012762 104400 2$:  
2897  
2898  
2899  
2900  
2901  
2902  
2903  
2904  
2905  
2906  
2907  
2908  
2909  
2910  
2911 012764 012737 000045 001226  
2912 012772 012737 013060 001216  
2913 013000 013703 001414  
2914 013004 052713 000002  
2915 013010 005005  
2916 013012 052777 000400 166372  
2917 013020 004737 005044  
2918 013024 032713 000002  
2919 013030 001402  
2920 013032 011304  
2921 013034 104003  
2922 013036 052713 0000C2 1$:  
2923 013042 005013  
2924 013044 032713 000002  
2925 013050 001402  
2926 013052 011304  
2927 013054 104003  
2928 013056 104400 2$:  
2929
```

```
      *  
: TEST 44  
      *  
:*****  
:*****  
TST44: MOV #44,@TSTNO  
      MOV #TST45,NEXT  
      MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER  
      BIS #BIT0,(R3) ;SET BIT 0 AT TRANSMITTER BUFFER REGISTER  
      CLR R5 ;SET 'EXPECTED'  
      BIS #MRESET,@TXCSR ;RESET THE DEVICE  
      JSR PC,SMALL ;WAIT FOR RESET TO FINISH  
      BIT #BIT0,(R3) ;TEST BIT 0  
      BEQ 1$ ;BIT 0 IS CLEARED  
      MOV (R3),R4 ;LOAD 'FOUND'  
      HLT 3 ;BIT 0 IS SET AND SHOULDN'T BE  
1$: BIS #BIT0,(R3) ;SET BIT 0 AGAIN  
      CLR (R3) ;CLEAR THE TRANSMITTER BUFFER REGISTER  
      BIT #BIT0,(R3) ;TEST TO SEE IF BIT 0 CLEARED  
      BEQ 2$ ;BIT 0 IS OK  
      MOV (R3),R4 ;LOAD 'FOUND'  
      HLT 3 ;BIT 0 FAILED TO CLEAR  
2$: SCOPE ;SCOPE THIS TEST
```

```
:***** TEST 45 *****  
:*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 1 RESET AND CLEAR TEST  
:*WRITE BIT 1,AND TEST THAT IT WILL BE CLEARED AFTER A  
:*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION  
:*****
```

```
      *  
: TEST 45  
      *  
:*****  
:*****  
TST45: MOV #45,@TSTNO  
      MOV #TST46,NEXT  
      MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER  
      BIS #BIT1,(R3) ;SET BIT 1 AT TRANSMITTER BUFFER REGISTER  
      CLR R5 ;SET 'EXPECTED'  
      BIS #MRESET,@TXCSR ;RESET THE DEVICE  
      JSR PC,SMALL ;WAIT FOR RESET TO FINISH  
      BIT #BIT1,(R3) ;TEST BIT 1  
      BEQ 1$ ;BIT 1 IS CLEARED  
      MOV (R3),R4 ;LOAD 'FOUND'  
      HLT 3 ;BIT 1 IS SET AND SHOULDN'T BE  
1$: BIS #BIT1,(R3) ;SET BIT 1 AGAIN  
      CLR (R3) ;CLEAR THE TRANSMITTER BUFFER REGISTER  
      BIT #BIT1,(R3) ;TEST TO SEE IF BIT 1 CLEARED  
      BEQ 2$ ;BIT 1 IS OK  
      MOV (R3),R4 ;LOAD 'FOUND'  
      HLT 3 ;BIT 1 FAILED TO CLEAR  
2$: SCOPE ;SCOPE THIS TEST
```

TRANSMITTER BUFFER REGISTER RESET AND CLEAR TEST BIT 2

2930
2931
2932
2933
2934
2935
2936
2937
2938
2939
2940
2941
2942
2943
2944
2945
2946
2947
2948
2949
2950
2951
2952
2953
2954
2955
2956
2957
2958
2959
2960
2961
2962
2963
2964
2965
2966
2967
2968
2969
2970
2971
2972
2973
2974
2975
2976
2977
2978
2979
2980
2981
2982
2983
2984
2985

013060 012737 000046 001226
013066 012737 013154 001216
013074 013703 001414
013100 052713 000004
013104 005005
013106 052777 000400 166276
013114 004737 005044
013120 032713 000004
013124 001402
013126 011304
013130 104003
013132 052713 000004
013136 005013
013140 032713 000004
013144 001402
013146 011304
013150 104003
013152 104400

```

***** TEST 46 *****
*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 2 RESET AND CLEAR TEST
*WRITE BIT 2, AND TEST THAT IT WILL BE CLEARED AFTER A
*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION
*****

:*****
:
: TEST 46
:
:*****
:*****
TST46: MOV #46,@TSTNO
MOV #TST47,NEXT
MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
BIS #BIT2,(R3) ;SET BIT 2 AT TRANSMITTER BUFFER REGISTER
CLR R5 ;SET 'EXPECTED'
BIS #MRESET,@TXCSR ;RESET THE DEVICE
JSR PC,SMALL ;WAIT FOR RESET TO FINISH
BIT #BIT2,(R3) ;TEST BIT 2
BEQ 1$ ;BIT 2 IS CLEARED
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 2 IS SET AND SHOULDN'T BE
1$: BIS #BIT2,(R3) ;SET BIT 2 AGAIN
CLR (R3) ;CLEAR THE TRANSMITTER BUFFER REGISTER
BIT #BIT2,(R3) ;TEST TO SEE IF BIT 2 CLEARED
BEQ 2$ ;BIT 2 IS OK
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 2 FAILED TO CLEAR
2$: SCOPE ;SCOPE THIS TEST

```

```

***** TEST 47 *****
*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 3 RESET AND CLEAR TEST
*WRITE BIT 3, AND TEST THAT IT WILL BE CLEARED AFTER A
*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION
*****

:*****
:
: TEST 47
:
:*****
:*****
TST47: MOV #47,@TSTNO
MOV #TST50,NEXT
MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
BIS #BIT3,(R3) ;SET BIT 3 AT TRANSMITTER BUFFER REGISTER
CLR R5 ;SET 'EXPECTED'
BIS #MRESET,@TXCSR ;RESET THE DEVICE
JSR PC,SMALL ;WAIT FOR RESET TO FINISH
BIT #BIT3,(R3) ;TEST BIT 3
BEQ 1$ ;BIT 3 IS CLEARED
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 3 IS SET AND SHOULDN'T BE

```


TRANSMITTER BUFFER REGISTER RESET AND CLEAR TEST BIT 3

```
2986 013226 052713 000010 1$: BIS #BIT3,(R3) ;SET BIT 3 AGAIN
2987 013232 005013 CLR (R3) ;CLEAR THE TRANSMITTER BUFFER REGISTER
2988 013234 032713 000010 BIT #BIT3,(R3) ;TEST TO SEE IF BIT 3 CLEARED
2989 013240 001402 BEQ 2$ ;BIT 3 IS OK
2990 013242 011304 MOV (R3),R4 ;LOAD 'FOUND'
2991 013244 104003 HLT 3 ;BIT 3 FAILED TO CLEAR
2992 013246 104400 2$: SCOPE ;SCOPE THIS TEST
```

```
2993
2994
2995 ;***** TEST 50 *****
2996 ;*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 4 RESET AND CLEAR TEST
2997 ;*WRITE BIT 4,AND TEST THAT IT WILL BE CLEARED AFTER A
2998 ;*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION
2999 ;*****
```

```
3000
3001 :*****
3002 : *
3003 : TEST 50
3004 : *
3005 :*****
3006 :*****
```

```
3007 013250 012737 000050 001226 TST50: MOV #50,@TSTNO
3008 013256 012737 013344 001216 MOV #TST51,NEXT
3009 013264 013703 001414 MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
3010 013270 052713 000020 BIS #BIT4,(R3) ;SET BIT 4 AT TRANSMITTER BUFFER REGISTER
3011 013274 005005 CLR R5 ;SET 'EXPECTED'
3012 013276 052777 000400 166106 BIS #MRESET,@TXCSR ;RESET THE DEVICE
3013 013304 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
3014 013310 032713 000020 BIT #BIT4,(R3) ;TEST BIT 4
3015 013314 001402 BEQ 1$ ;BIT 4 IS CLEARED
3016 013316 011304 MOV (R3),R4 ;LOAD 'FOUND'
3017 013320 104003 HLT 3 ;BIT 4 IS SET AND SHOULDN'T BE
3018 013322 052713 000020 1$: BIS #BIT4,(R3) ;SET BIT 4 AGAIN
3019 013326 005013 CLR (R3) ;CLEAR THE TRANSMITTER BUFFER REGISTER
3020 013330 032713 000020 BIT #BIT4,(R3) ;TEST TO SEE IF BIT 4 CLEARED
3021 013334 001402 BEQ 2$ ;BIT 4 IS OK
3022 013336 011304 MOV (R3),R4 ;LOAD 'FOUND'
3023 013340 104003 HLT 3 ;BIT 4 FAILED TO CLEAR
3024 013342 104400 2$: SCOPE ;SCOPE THIS TEST
```

```
3025
3026
3027 ;***** TEST 51 *****
3028 ;*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 5 RESET AND CLEAR TEST
3029 ;*WRITE BIT 5,AND TEST THAT IT WILL BE CLEARED AFTER A
3030 ;*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION
3031 ;*****
```

```
3032 :*****
3033 : *
3034 : TEST 51
3035 : *
3036 :*****
3037 :*****
```

```
3038
3039 013344 012737 000051 001226 TST51: MOV #51,@TSTNO
3040 013352 012737 013440 001216 MOV #TST52,NEXT
3041 013360 013703 001414 MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
```

TRANSMITTER BUFFER REGISTER RESET AND CLEAR TEST BIT 5

```
3042 013364 052713 000040          BIS    #BIT5,(R3)    ;SET BIT 5 AT TRANSMITTER BUFFER REGISTER
3043 013370 005005                   CLR    R5            ;SET 'EXPECTED'
3044 013372 052777 000400 166012    BIS    #MRESET,@TXCSR ;RESET THE DEVICE
3045 013400 004737 005044                   JSR    PC,SMALL     ;WAIT FOR RESET TO FINISH
3046 013404 032713 000040          BIT    #BIT5,(R3)    ;TEST BIT 5
3047 013410 001402                   BEQ    1$           ;BIT 5 IS CLEARED
3048 013412 011304                   MOV    (R3),R4      ;LOAD 'FOUND'
3049 013414 104003                   HLT    3            ;BIT 5 IS SET AND SHOULDN'T BE
3050 013416 052713 000040 1$:    BIS    #BIT5,(R3)    ;SET BIT 5 AGAIN
3051 013422 005013                   CLR    (R3)         ;CLEAR THE TRANSMITTER BUFFER REGISTER
3052 013424 032713 000040          BIT    #BIT5,(R3)    ;TEST TO SEE IF BIT 5 CLEARED
3053 013430 001402                   BEQ    2$           ;BIT 5 IS OK
3054 013432 011304                   MOV    (R3),R4      ;LOAD 'FOUND'
3055 013434 104003                   HLT    3            ;BIT 5 FAILED TO CLEAR
3056 013436 104400 2$:    SCOPE    ;SCOPE THIS TEST
```

```
3057
3058
3059 ;***** TEST 52 *****
3060 ;*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 6 RESET AND CLEAR TEST
3061 ;*WRITE BIT 6,AND TEST THAT IT WILL BE CLEARED AFTER A
3062 ;*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION
3063 ;*****
```

```
3064
3065 ;:*****
3066 ;:
3067 ;: TEST 52
3068 ;:
3069 ;:*****
```

```
3070 ;*****
3071 013440 012737 000052 001226 TST52: MOV    #52,@TSTNO
3072 013446 012737 013534 001216    MOV    #TST53,NEXT
3073 013454 013703 001414          MOV    TXDBUF,R3    ;GET THE TRANSMITTER BUFFER REGISTER
3074 013460 052713 000100          BIS    #BIT6,(R3)    ;SET BIT 6 AT TRANSMITTER BUFFER REGISTER
3075 013464 005005                   CLR    R5            ;SET 'EXPECTED'
3076 013466 052777 000400 165716    BIS    #MRESET,@TXCSR ;RESET THE DEVICE
3077 013474 004737 005044                   JSR    PC,SMALL     ;WAIT FOR RESET TO FINISH
3078 013500 032713 000100          BIT    #BIT6,(R3)    ;TEST BIT 6
3079 013504 001402                   BEQ    1$           ;BIT 6 IS CLEARED
3080 013506 011304                   MOV    (R3),R4      ;LOAD 'FOUND'
3081 013510 104003                   HLT    3            ;BIT 6 IS SET AND SHOULDN'T BE
3082 013512 052713 000100 1$:    BIS    #BIT6,(R3)    ;SET BIT 6 AGAIN
3083 013516 005013                   CLR    (R3)         ;CLEAR THE TRANSMITTER BUFFER REGISTER
3084 013520 032713 000100          BIT    #BIT6,(R3)    ;TEST TO SEE IF BIT 6 CLEARED
3085 013524 001402                   BEQ    2$           ;BIT 6 IS OK
3086 013526 011304                   MOV    (R3),R4      ;LOAD 'FOUND'
3087 013530 104003                   HLT    3            ;BIT 6 FAILED TO CLEAR
3088 013532 104400 2$:    SCOPE    ;SCOPE THIS TEST
```

```
3089
3090
3091 ;***** TEST 53 *****
3092 ;*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 7 RESET AND CLEAR TEST
3093 ;*WRITE BIT 7,AND TEST THAT IT WILL BE CLEARED AFTER A
3094 ;*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION
3095 ;*****
```

```
3096 ;:*****
3097 ;:

```

TRANSMITTER BUFFER REGISTER RESET AND CLEAR TEST BIT 7

```
3098
3099
3100
3101
3102
3103 013534 012737 000053 001226 TST53: MOV #53,@TSTNO
3104 013542 012737 013630 001216 MOV #TST54,NEXT
3105 013550 013703 001414 MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
3106 013554 052713 000200 BIS #BIT7,(R3) ;SET BIT 7 AT TRANSMITTER BUFFER REGISTER
3107 013560 005005 CLR R5 ;SET 'EXPECTED'
3108 013562 052777 000400 165622 BIS #MRESET,@TXCSR ;RESET THE DEVICE
3109 013570 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
3110 013574 032713 000200 BIT #BIT7,(R3) ;TEST BIT 7
3111 013600 001402 BEQ 1$ ;BIT 7 IS CLEARED
3112 013602 011304 MOV (R3),R4 ;LOAD 'FOUND'
3113 013604 104003 HLT 3 ;BIT 7 IS SET AND SHOULDN'T BE
3114 013606 052713 000200 1$: BIS #BIT7,(R3) ;SET BIT 7 AGAIN
3115 013612 005013 CLR (R3) ;CLEAR THE TRANSMITTER BUFFER REGISTER
3116 013614 032713 000200 BIT #BIT7,(R3) ;TEST TO SEE IF BIT 7 CLEARED
3117 013620 001402 BEQ 2$ ;BIT 7 IS OK
3118 013622 011304 MOV (R3),R4 ;LOAD 'FOUND'
3119 013624 104003 HLT 3 ;BIT 7 FAILED TO CLEAR
3120 013626 104400 2$: SCOPE ;SCOPE THIS TEST
```

```
***** TEST 54 *****
*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 8 RESET AND CLEAR TEST
*WRITE BIT 8,AND TEST THAT IT WILL BE CLEARED AFTER A
*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION
*****
```

```
3121
3122
3123
3124
3125
3126
3127
3128
3129
3130
3131
3132
3133
3134
3135 013630 012737 000054 001226 TST54: MOV #54,@TSTNO
3136 013636 012737 013724 001216 MOV #TST55,NEXT
3137 013644 013703 001414 MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
3138 013650 052713 000400 BIS #BIT8,(R3) ;SET BIT 8 AT TRANSMITTER BUFFER REGISTER
3139 013654 005005 CLR R5 ;SET 'EXPECTED'
3140 013656 052777 000400 165526 BIS #MRESET,@TXCSR ;RESET THE DEVICE
3141 013664 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
3142 013670 032713 000400 BIT #BIT8,(R3) ;TEST BIT 8
3143 013674 001402 BEQ 1$ ;BIT 8 IS CLEARED
3144 013676 011304 MOV (R3),R4 ;LOAD 'FOUND'
3145 013700 104003 HLT 3 ;BIT 8 IS SET AND SHOULDN'T BE
3146 013702 052713 000400 1$: BIS #BIT8,(R3) ;SET BIT 8 AGAIN
3147 013706 005013 CLR (R3) ;CLEAR THE TRANSMITTER BUFFER REGISTER
3148 013710 032713 000400 BIT #BIT8,(R3) ;TEST TO SEE IF BIT 8 CLEARED
3149 013714 001402 BEQ 2$ ;BIT 8 IS OK
3150 013716 011304 MOV (R3),R4 ;LOAD 'FOUND'
3151 013720 104003 HLT 3 ;BIT 8 FAILED TO CLEAR
3152 013722 104400 2$: SCOPE ;SCOPE THIS TEST
3153
```

TRANSMITTER BUFFER REGISTER RESET AND CLEAR TEST BIT 9

3154
3155
3156
3157
3158
3159
3160
3161
3162
3163
3164
3165
3166
3167
3168
3169
3170
3171
3172
3173
3174
3175
3176
3177
3178
3179
3180
3181
3182
3183
3184
3185
3186
3187
3188
3189
3190
3191
3192
3193
3194
3195
3196
3197
3198
3199
3200
3201
3202
3203
3204
3205
3206
3207
3208
3209

013724 012737 000055 001226
013732 012737 014020 001216
013740 013703 001414
013744 052713 001000
013750 005005
013752 052777 000400 165432
013760 004737 005044
013764 032713 001000
013770 001402
013772 011304
013774 104003
013776 052713 001000
014002 005013
014004 032713 001000
014010 001402
014012 011304
014014 104003
014016 104400

***** TEST 55 *****
*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 9 RESET AND CLEAR TEST
*WRITE BIT 9, AND TEST THAT IT WILL BE CLEARED AFTER A
*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION

*
: TEST 55
*

```
TST55: MOV #55,@TSTNO
MOV #TST56,NEXT
MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
BIS #BIT9,(R3) ;SET BIT 9 AT TRANSMITTER BUFFER REGISTER
CLR R5 ;SET 'EXPECTED'
BIS #MRESET,@TXCSR ;RESET THE DEVICE
JSR PC,SMALL ;WAIT FOR RESET TO FINISH
BIT #BIT9,(R3) ;TEST BIT 9
BEQ 1$ ;BIT 9 IS CLEARED
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 9 IS SET AND SHOULDN'T BE
1$: BIS #BIT9,(R3) ;SET BIT 9 AGAIN
CLR (R3) ;CLEAR THE TRANSMITTER BUFFER REGISTER
BIT #BIT9,(R3) ;TEST TO SEE IF BIT 9 CLEARED
BEQ 2$ ;BIT 9 IS OK
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 9 FAILED TO CLEAR
2$: SCOPE ;SCOPE THIS TEST
```

***** TEST 56 *****
*TRANSMITTER BUFFER REGISTER READ/WRITE BIT 10 RESET AND CLEAR TEST
*WRITE BIT 10, AND TEST THAT IT WILL BE CLEARED AFTER A
*DEVICE RESET AND TRANSMITTER BUFFER REGISTER CLR INSTRUCTION

*
: TEST 56
*

```
TST56: MOV #56,@TSTNO
MOV #TST57,NEXT
MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
BIS #BIT10,(R3) ;SET BIT 10 AT TRANSMITTER BUFFER REGISTER
CLR R5 ;SET 'EXPECTED'
BIS #MRESET,@TXCSR ;RESET THE DEVICE
JSR PC,SMALL ;WAIT FOR RESET TO FINISH
BIT #BIT10,(R3) ;TEST BIT 10
BEQ 1$ ;BIT 10 IS CLEARED
MOV (R3),R4 ;LOAD 'FOUND'
HLT 3 ;BIT 10 IS SET AND SHOULDN'T BE
```

TRANSMITTER BUFFER REGISTER RESET AND CLEAR TEST BIT 10

```

3210 014072 052713 002000 1$: BIS #BIT10,(R3) ;SET BIT 10 AGAIN
3211 014076 005013 CLR (R3) ;CLEAR THE TRANSMITTER BUFFER REGISTER
3212 014100 032713 002000 BIT #BIT10,(R3) ;TEST TO SEE IF BIT 10 CLEARED
3213 014104 001402 BEQ 2$ ;BIT 10 IS OK
3214 014106 011304 MOV (R3),R4 ;LOAD 'FOUND'
3215 014110 104003 HLT 3 ;BIT 10 FAILED TO CLEAR
3216 014112 104400 2$: SCOPE ;SCOPE THIS TEST

```

```

3217
3218
3219 :***** TEST 57 *****
3220 :*RECEIVER BUFFER REGISTER TEST
3221 :*TEST THAT RECEIVER BUFFER REGISTER CANNOT BE WRITTEN.
3222 :*WRITE RECEIVER BUFFER REGISTER WITH ALL 1'S
3223 :*AND VERIFY THAT ALL 0'S ARE READ BACK.
3224 :*****

```

```

3225
3226 :*****
3227 :*
3228 : TEST 57
3229 :*
3230 :*****

```

```

3231 :*****
3232 014114 012737 000057 001226 TST57: MOV #57,@TSTNO
3233 014122 012737 014154 001216 MOV #TST60,NEXT
3234 014130 013703 001406 MOV RXDBUF,R3
3235 :GET THE REGISTER.
3236 014134 005005 CLR R5 ;SET EXPECTED (ZERO)
3237 014136 012713 177777 MOV #-1,(R3) ;WRITE REGISTER WITH ALL 1'S
3238 014142 011304 MOV (R3),R4 ;READ THE REGISTER.
3239 014144 020504 CMP R5,R4 ;IS THE REGISTER EQUAL TO ZERO.
3240 014146 001401 BEQ 1$ ;BR IF OK.
3241 014150 104003 HLT 3 ;REGISTER NOT ZERO.
3242 014152 104400 1$: SCOPE ;SCOPE THIS TEST.

```

```

3243
3244 :***** TEST 60 *****
3245 :*PARAMETER STATUS REGISTER TEST
3246 :*TEST THAT PARAMETER STATUS REGISTER CANNOT BE WRITTEN
3247 :*READ THE PARAMETER STATUS REGISTER AND STORE THE DATA;
3248 :*COMPLEMENT THE DATA AND WRITE THE PARAMETER STATUS REGISTER
3249 :*VERIFYING THAT THE PARAMETER STATUS REGISTER DID NOT CHANGE.
3250 :*****

```

```

3251 :*****
3252 :*
3253 : TEST 60
3254 :*
3255 :*****

```

```

3256 :*****
3257 :*
3258 :*****
3259 :*****
3260 014154 012737 000060 001226 TST60: MOV #60,@TSTNO
3261 014162 012737 014216 001216 MOV #TST61,NEXT
3262 014170 013703 001410 MOV PARCSR,R3
3263 :GET THE REGISTER.
3264 014174 011305 MOV (R3),R5 ;READ THE REGISTER INTO R5
3265 014176 010504 MOV R5,R4 ;SAVE REG INTO R4

```

```
3266 014200 005104          COM      R4          ;MAKE R4 OPPOSITE TO REGISTER
3267 014202 010413          MOV      R4,(R3)      ;WRITE THE REGISTER WITH THE COMPLIMENT
3268 014204 011304          MOV      (R3),R4      ;READ THE REGISTER.
3269 014206 020504          CMP      R5,R4        ;IS THE REGISTER EQUAL TO ZERO.
3270 014210 001401          BEQ     1$            ;BR IF OK.
3271 014212 104003          HLT     3              ;REGISTER NOT ZERO.
3272 014214 104400          1$:    SCOPE          ;SCOPE THIS TEST.
3273
3274
3275          ;***** TEST 61 *****
3276          ;*RECEIVER CONTROL REGISTER BIT 0 READ ONLY DEVICE RESET AND CLEAR TEST
3277          ;*WRITE BIT 0 A ONE AND VERIFY A ZERO IS READ BACK
3278          ;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
3279          ;*****
3280
3281          ;*****
3282          ;
3283          ; TEST 61
3284          ;
3285          ;*****
3286          ;*****
3287 014216 012737 000061 001226 TST61:  MOV      #61,@TSTNO
3288 014224 012737 014330 001216      MOV      #TST62,NEXT
3289 014232 013703 001404          MOV      RXCSR,R3      ;GET THE RECEIVER CONTROL REGISTER
3290 014236 012705 000001          MOV      #BIT0,R5      ;GET BIT 0
3291 014242 010513          MCV     R5,(R3)        ;WRITE BIT 0 TO RECEIVER CONTROL REGISTER
3292 014244 011304          MOV      (R3),R4        ;READ RECEIVER CONTROL REGISTER BACK
3293 014246 005005          CLR     R5              ;SET 'EXPECTED'
3294 014250 020504          CMP     R5,R4          ;R5=GOOD,R4= ?
3295 014252 001401          BEQ     5$            ;BIT 0 IS OK
3296 014254 104003          HLT     3              ;BIT FAILED TO CLR
3297 014256 012705 000001          5$:    MOV      #BIT0,R5      ;RELOAD THE BIT
3298 014262 010513          MOV      R5,(R3)        ;WRITE BIT 0 TO THE REG
3299 014264 052777 000400 165120      BIS     #MRESET,@TXCSR ;RESET THE DEVICE
3300 014272 004737 005044          JSR     PC,SMALL        ;WAIT FOR RESET TO FINISH
3301 014276 011304          MOV      (R3),R4        ;GET BIT 0
3302 014300 032704 000001          BIT     #BIT0,R4        ;TEST BIT 0 FOR RESET CLR
3303 014304 001401          BEQ     7$            ;BIT 0 IS OK
3304 014306 104003          HLT     3              ;BIT FAILED TO CLEAR
3305 014310 010513          7$:    MOV      R5,(R3)        ;SET BIT 0
3306 014312 005013          CLR     (R3)            ;CLR RECEIVER CONTROL REGISTER
3307 014314 011304          MOV      (R3),R4        ;READ THE RECEIVER CONTROL REGISTER
3308 014316 005005          CLR     R5              ;SET 'EXPECTED'
3309 014320 020504          CMP     R5,R4          ;R5=GOOD,R4= ?
3310 014322 001401          BEQ     10$           ;BIT 0 IS OK
3311 014324 104003          HLT     3              ;BIT FAILED TO CLEAR
3312 014326 104400          10$:   SCOPE          ;SCOPE THIS TEST
3313
3314
3315          ;***** TEST 62 *****
3316          ;*RECEIVER CONTROL REGISTER BIT 7 READ ONLY DEVICE RESET AND CLEAR TEST
3317          ;*WRITE BIT 7 A ONE AND VERIFY A ZERO IS READ BACK
3318          ;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
3319          ;*****
3320
3321          ;*****
```

RECEIVER CONTROL REGISTER READ ONLY BIT 7 TEST

```
3322      :
3323      : TEST 62
3324      :
3325      : *****
3326      : *****
3327 014330 012737 000062 001226 TST62: MOV #62,@TSTNO
3328 014336 012737 014442 001216 MOV #TST63,NEXT
3329 014344 013703 001404 MOV RXCSR,R3 ;GET THE RECEIVER CONTROL REGISTER
3330 014350 012705 000200 MOV #BIT7,R5 ;GET BIT 7
3331 014354 010513 MOV R5,(R3) ;WRITE BIT 7 TO RECEIVER CONTROL REGISTER
3332 014356 011304 MOV (R3),R4 ;READ RECEIVER CONTROL REGISTER BACK
3333 014360 005005 CLR R5 ;SET 'EXPECTED'
3334 014362 020504 CMP R5,R4 ;R5=GOOD,R4= ?
3335 014364 001401 BEQ 5$ ;BIT 7 IS OK
3336 014366 104003 HLT 3 ;BIT FAILED TO C R
3337 014370 012705 000200 5$: MOV #BIT7,R5 ;RELOAD THE BIT
3338 014374 010513 MOV R5,(R3) ;WRITE BIT 7 TO THE REG
3339 014376 052777 000400 165006 BIS #MRESET,@TXCSR ;RESET THE DEVICE
3340 014404 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
3341 014410 011304 MOV (R3),R4 ;GET BIT 7
3342 014412 032704 000200 BIT #BIT7,R4 ;TEST BIT 7 FOR RESET CLR
3343 014416 001401 BEQ 7$ ;BIT 7 IS OK
3344 014420 104003 HLT 3 ;BIT FAILED TO CLEAR
3345 014422 010513 7$: MOV R5,(R3) ;SET BIT 7
3346 014424 005013 CLR (R3) ;CLR RECEIVER CONTROL REGISTER
3347 014426 011304 MOV (R3),R4 ;READ THE RECEIVER CONTROL REGISTER
3348 014430 005005 CLR R5 ;SET 'EXPECTED'
3349 014432 020504 CMP R5,R4 ;R5=GOOD,R4= ?
3350 014434 001401 BEQ 10$ ;BIT 7 IS OK
3351 014436 104003 HLT 3 ;BIT FAILED TO CLEAR
3352 014440 104400 10$: SCOPE ;SCOPE THIS TEST
```

```
3353
3354
3355      : ***** TEST 63 *****
3356      : *RECEIVER CONTROL REGISTER BIT 9 READ ONLY DEVICE RESET AND CLEAR TEST
3357      : *WRITE BIT 9 A ONE AND VERIFY A ZERO IS READ BACK
3358      : *REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
3359      : *****
```

```
3360
3361      : *****
3362      :
3363      : TEST 63
3364      :
3365      : *****
3366      : *****
3367 014442 012737 000063 001226 TST63: MOV #63,@TSTNO
3368 014450 012737 014554 001216 MOV #TST64,NEXT
3369 014456 013703 001404 MOV RXCSR,R3 ;GET THE RECEIVER CONTROL REGISTER
3370 014462 012705 001000 MOV #BIT9,R5 ;GET BIT 9
3371 014466 010513 MOV R5,(R3) ;WRITE BIT 9 TO RECEIVER CONTROL REGISTER
3372 014470 011304 MOV (R3),R4 ;READ RECEIVER CONTROL REGISTER BACK
3373 014472 005005 CLR R5 ;SET 'EXPECTED'
3374 014474 020504 CMP R5,R4 ;R5=GOOD,R4= ?
3375 014476 001401 BEQ 5$ ;BIT 9 IS OK
3376 014500 104003 HLT 3 ;BIT FAILED TO CLR
3377 014502 012705 001000 5$: MOV #BIT9,R5 ;RELOAD THE BIT
```

RECEIVER CONTROL REGISTER READ ONLY BIT 9 TEST

```

3378 014506 010513          MOV    R5,(R3)          :WRITE BIT 9 TO THE REG
3379 014510 052777 000400 164674  BIS    #MRESET,@TXCSR  :RESET THE DEVICE
3380 014516 004737 005044          JSR    PC,SMALL        :WAIT FOR RESET TO FINISH
3381 014522 011304          MOV    (R3),R4         :GET BIT 9
3382 014524 032704 001000          BIT    #BIT9,R4       :TEST BIT 9 FOR RESET CLR
3383 014530 001401          BEQ    7$             :BIT 9 IS OK
3384 014532 104003          HLT    3              :BIT FAILED TO CLEAR
3385 014534 010513          7$:  MOV    R5,(R3)     :SET BIT 9
3386 014536 005013          CLR    (R3)           :CLR RECEIVER CONTROL REGISTER
3387 014540 011304          MOV    (R3),R4        :READ THE RECEIVER CONTROL REGISTER
3388 014542 005005          CLR    R5             :SET 'EXPECTED'
3389 014544 020504          CMP    R5,R4         :R5-GOOD,R4= ?
3390 014546 001401          BEQ    10$            :BIT 9 IS OK
3391 014550 104003          HLT    3              :BIT FAILED TO CLEAR
3392 014552 104400          10$: SCOPE           :SCOPE THIS TEST
3393
3394
3395

```

```

:***** TEST 64 *****
:*RECEIVER CONTROL REGISTER BIT 10 READ ONLY DEVICE RESET AND CLEAR TEST
:*WRITE BIT 10 A ONE AND VERIFY A ZERO IS READ BACK
:*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
:*****

```

```

3396
3397
3398
3399
3400
3401
3402
3403
3404
3405
3406

```

```

:*****
: *
: TEST 64
: *
:*****

```

```

3407 014554 012737 000064 001226 TST64: MOV    #64,@TSTNO
3408 014562 012737 014666 001216  MOV    #TST65,NEXT
3409 014570 013703 001404          MOV    RXCSR,R3       :GET THE RECEIVER CONTROL REGISTER
3410 014574 012705 002000          MOV    #BIT10,R5      :GET BIT 10
3411 014600 010513          MOV    R5,(R3)        :WRITE BIT 10 TO RECEIVER CONTROL REGISTER
3412 014602 011304          MOV    (R3),R4        :READ RECEIVER CONTROL REGISTER BACK
3413 014604 005005          CLR    R5             :SET 'EXPECTED'
3414 014606 020504          CMP    R5,R4         :R5=GOOD,R4= ?
3415 014610 001401          BEQ    5$             :BIT 10 IS OK
3416 014612 104003          HLT    3              :BIT FAILED TO CLR
3417 014614 012705 002000          5$:  MOV    #BIT10,R5   :RELOAD THE BIT
3418 014620 010513          MOV    R5,(R3)        :WRITE BIT 10 TO THE REG
3419 014622 052777 000400 164562  BIS    #MRESET,@TXCSR  :RESET THE DEVICE
3420 014630 004737 005044          JSR    PC,SMALL        :WAIT FOR RESET TO FINISH
3421 014634 011304          MOV    (R3),R4        :GET BIT 10
3422 014636 032704 002000          BIT    #BIT10,R4     :TEST BIT 10 FOR RESET CLR
3423 014642 001401          BEQ    7$             :BIT 10 IS OK
3424 014644 104003          HLT    3              :BIT FAILED TO CLEAR
3425 014646 010513          7$:  MOV    R5,(R3)     :SET BIT 10
3426 014650 005013          CLR    (R3)           :CLR RECEIVER CONTROL REGISTER
3427 014652 011304          MOV    (R3),R4        :READ THE RECEIVER CONTROL REGISTER
3428 014654 005005          CLR    R5             :SET 'EXPECTED'
3429 014656 020504          CMP    R5,R4         :R5=GOOD,R4= ?
3430 014660 001401          BEQ    10$            :BIT 10 IS OK
3431 014662 104003          HLT    3              :BIT FAILED TO CLEAR
3432 014664 104400          10$: SCOPE           :SCOPE THIS TEST
3433

```


RECEIVER CONTROL REGISTER READ ONLY BIT 11 TEST

3434
3435
3436
3437
3438
3439
3440
3441
3442
3443
3444
3445
3446
3447
3448
3449
3450
3451
3452
3453
3454
3455
3456
3457
3458
3459
3460
3461
3462
3463
3464
3465
3466
3467
3468
3469
3470
3471
3472
3473
3474
3475
3476
3477
3478
3479
3480
3481
3482
3483
3484
3485
3486
3487
3488
3489

014666 012737 000065 001226
014674 012737 015000 001216
014702 013703 001404
014706 012705 004000
014712 010513
014714 011304
014716 005005
014720 020504
014722 001401
014724 104003
014726 012705 004000
014732 010513
014734 052777 000400 164450
014742 004737 005044
014746 011304
014750 032704 004000
014754 001401
014756 104003
014760 010513
014762 005013
014764 011304
014766 005005
014770 020504
014772 001401
014774 104003
014776 104400

***** TEST 65 *****
*RECEIVER CONTROL REGISTER BIT 11 READ ONLY DEVICE RESET AND CLEAR TEST
*WRITE BIT 11 A ONE AND VERIFY A ZERO IS READ BACK
*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.

*
: TEST 65
*

```
TST65:  MOV #66,@TSTNO
        MOV #TST66,NEXT
        MOV RXCSR,R3      ;GET THE RECEIVER CONTROL REGISTER
        MOV #BIT11,R5     ;GET BIT 11
        MOV R5,(R3)       ;WRITE BIT 11 TO RECEIVER CONTROL REGISTER
        MOV (R3),R4       ;READ RECEIVER CONTROL REGISTER BACK
        CLR R5            ;SET 'EXPECTED'
        CMP R5,R4         ;R5=GOOD,R4= ?
        BEQ 5$           ;BIT 11 IS OK
        HLT 3            ;BIT FAILED TO CLR
5$:     MOV #BIT11,R5     ;RELOAD THE BIT
        MOV R5,(R3)       ;WRITE BIT 11 TO THE REG
        BIS #MRESET,@TXCSR ;RESET THE DEVICE
        JSR PC,SMALL      ;WAIT FOR RESET TO FINISH
        MOV (R3),R4       ;GET BIT 11
        BIT #BIT11,R4     ;TEST BIT 11 FOR RESET CLR
        BEQ 7$           ;BIT 11 IS OK
        HLT 3            ;BIT FAILED TO CLEAR
7$:     MOV R5,(R3)       ;SET BIT 11
        CLR (R3)          ;CLR RECEIVER CONTROL REGISTER
        MOV (R3),R4       ;READ THE RECEIVER CONTROL REGISTER
        CLR R5            ;SET 'EXPECTED'
        CMP R5,R4         ;R5=GOOD,R4= ?
        BEQ 10$          ;BIT 11 IS OK
        HLT 3            ;BIT FAILED TO CLEAR
10$:    SCOPE            ;SCOPE THIS TEST
```

***** TEST 66 *****
*RECEIVER CONTROL REGISTER BIT 12 READ ONLY DEVICE RESET AND CLEAR TEST
*WRITE BIT 12 A ONE AND VERIFY A ZERO IS READ BACK
*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.

*
: TEST 66
*

015000 012737 000066 001226
015006 012737 015112 001216
015014 013703 001404

```
TST66:  MOV #66,@TSTNO
        MOV #TST67,NEXT
        MOV RXCSR,R3      ;GET THE RECEIVER CONTROL REGISTER
```

RECEIVER CONTROL REGISTER READ ONLY BIT 12 TEST

```

3490 015020 012705 010000      MOV      #BIT12,R5      ;GET BIT 12
3491 015024 010513              MOV      R5,(R3)       ;WRITE BIT 12 TO RECEIVER CONTROL REGISTER
3492 015026 011304              MOV      (R3),R4       ;READ RECEIVER CONTROL REGISTER BACK
3493 015030 005005              CLR      R5            ;SET 'EXPECTED'
3494 015032 020504              CMP      R5,R4         ;R5=GOOD,R4= ?
3495 015034 0C1401              BEQ      5$           ;BIT 12 IS OK
3496 015036 104003              HLT      3            ;BIT FAILED TO CLR
3497 015040 012705 010000      5$:  MOV      #BIT12,R5      ;RELOAD THE BIT
3498 015044 010513              MOV      R5,(R3)       ;WRITE BIT 12 TO THE REG
3499 015046 052777 000400 164336  BIS      #MRESET,@TXCSR ;RESET THE DEVICE
3500 015054 004737 005044      JSR      PC,SMALL      ;WAIT FOR RESET TO FINISH
3501 015060 011304              MOV      (R3),R4       ;GET BIT 12
3502 015062 032704 010000      BIT      #BIT12,R4     ;TEST BIT 12 FOR RESET CLR
3503 015066 001401              BEQ      7$           ;BIT 12 IS OK
3504 015070 104003              HLT      3            ;BIT FAILED TO CLEAR
3505 015072 010513              7$:  MOV      R5,(R3)       ;SET BIT 12
3506 015074 005013              CLR      (R3)          ;CLR RECEIVER CONTROL REGISTER
3507 015076 011304              MOV      (R3),R4       ;READ THE RECEIVER CONTROL REGISTER
3508 015100 005005              CLR      R5            ;SET 'EXPECTED'
3509 015102 020504              CMP      R5,R4         ;R5=GOOD,R4= ?
3510 015104 001401              BEQ      10$          ;BIT 12 IS OK
3511 015106 104003              HLT      3            ;BIT FAILED TO CLEAR
3512 015110 104400              10$: SCOPE            ;SCOPE THIS TEST

```

```

:***** TEST 67 *****
:*RECEIVER CONTROL REGISTER BIT 13 READ ONLY DEVICE RESET AND CLEAR TEST
:*WRITE BIT 13 A ONE AND VERIFY A ZERO IS READ BACK
:*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
:*****

```

```

:*****
: *
: TEST 67
: *
:*****

```

```

3527 015112 012737 000067 001226  TST67: MOV      #67,@TSTNO
3528 015120 012737 015224 001216  MOV      #TST70,NEXT
3529 015126 013703 001404      MOV      RXCSR,R3      ;GET THE RECEIVER CONTROL REGISTER
3530 015132 012705 020000      MOV      #BIT13,R5     ;GET BIT 13
3531 015136 010513              MOV      R5,(R3)       ;WRITE BIT 13 TO RECEIVER CONTROL REGISTER
3532 015140 011304              MOV      (R3),R4       ;READ RECEIVER CONTROL REGISTER BACK
3533 015142 005005              CLR      R5            ;SET 'EXPECTED'
3534 015144 020504              CMP      R5,R4         ;R5=GOOD,R4= ?
3535 015146 001401              BEQ      5$           ;BIT 13 IS OK
3536 015150 104003              HLT      3            ;BIT FAILED TO CLR
3537 015152 012705 020000      5$:  MOV      #BIT13,R5     ;RELOAD THE BIT
3538 015156 010513              MOV      R5,(R3)       ;WRITE BIT 13 TO THE REG
3539 015160 052777 000400 164224  BIS      #MRESET,@TXCSR ;RESET THE DEVICE
3540 015166 004737 005044      JSR      PC,SMALL      ;WAIT FOR RESET TO FINISH
3541 015172 011304              MOV      (R3),R4       ;GET BIT 13
3542 015174 032704 020000      BIT      #BIT13,R4     ;TEST BIT 13 FOR RESET CLR
3543 015200 001401              BEQ      7$           ;BIT 13 IS OK
3544 015202 104003              HLT      3            ;BIT FAILED TO CLEAR
3545 015204 010513              7$:  MOV      R5,(R3)       ;SET BIT 13

```

RECEIVER CONTROL REGISTER READ ONLY BIT 13 TEST

```
3546 015206 005013 CLR (R3) ;CLR RECEIVER CONTROL REGISTER
3547 015210 011304 MOV (R3),R4 ;READ THE RECEIVER CONTROL REGISTER
3548 015212 005005 CLR R5 ;SET 'EXPECTED'
3549 015214 020504 CMP R5,R4 ;R5=GOOD,R4=?
3550 015216 001401 BEQ 10$ ;BIT 13 IS OK
3551 015220 104003 HLT 3 ;BIT FAILED TO CLEAR
3552 015222 104400 10$: SCOPE ;SCOPE THIS TEST
3553
3554
3555
```

```
:***** TEST 70 *****
;*RECEIVER CONTROL REGISTER BIT 14 READ ONLY DEVICE RESET AND CLEAR TEST
;*WRITE BIT 14 A ONE AND VERIFY A ZERO IS READ BACK
;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
:*****
```

```
:*****
:
: TEST 70
:
:*****
```

```
3566 *****
3567 015224 012737 000070 001226 TST70: MOV #70,@TSTNO
3568 015232 012737 015336 001216 MOV #TST71,NEXT
3569 015240 013703 001404 MOV RXCSR,R3 ;GET THE RECEIVER CONTROL REGISTER
3570 015244 012705 040000 MOV #BIT14,R5 ;GET BIT 14
3571 015250 010513 MOV R5,(R3) ;WRITE BIT 14 TO RECEIVER CONTROL REGISTER
3572 015252 011304 MOV (R3),R4 ;READ RECEIVER CONTROL REGISTER BACK
3573 015254 005005 CLR R5 ;SET 'EXPECTED'
3574 015256 020504 CMP R5,R4 ;R5=GOOD,R4=?
3575 015260 001401 BEQ 5$ ;BIT 14 IS OK
3576 015262 104003 HLT 3 ;BIT FAILED TO CLR
3577 015264 012705 040000 5$: MOV #BIT14,R5 ;RELOAD THE BIT
3578 015270 010513 MOV R5,(R3) ;WRITE BIT 14 TO THE REG
3579 015272 052777 000400 164112 BIS #MRESET,@TXCSR ;RESET THE DEVICE
3580 015300 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
3581 015304 011304 MOV (R3),R4 ;GET BIT 14
3582 015306 032704 040000 BIT #BIT14,R4 ;TEST BIT 14 FOR RESET CLR
3583 015312 001401 BEQ 7$ ;BIT 14 IS OK
3584 015314 104003 HLT 3 ;BIT FAILED TO CLEAR
3585 015316 010513 7$: MOV R5,(R3) ;SET BIT 14
3586 015320 005013 CLR (R3) ;CLR RECEIVER CONTROL REGISTER
3587 015322 011304 MOV (R3),R4 ;READ THE RECEIVER CONTROL REGISTER
3588 015324 005005 CLR R5 ;SET 'EXPECTED'
3589 015326 020504 CMP R5,R4 ;R5=GOOD,R4=?
3590 015330 001401 BEQ 10$ ;BIT 14 IS OK
3591 015332 104003 HLT 3 ;BIT FAILED TO CLEAR
3592 015334 104400 10$: SCOPE ;SCOPE THIS TEST
3593
3594
```

```
:***** TEST 71 *****
;*RECEIVER CONTROL REGISTER BIT 15 READ ONLY DEVICE RESET AND CLEAR TEST
;*WRITE BIT 15 A ONE AND VERIFY A ZERO IS READ BACK
;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
:*****
```

```
:*****
```

```
3600
3601
```

RECEIVER CONTROL REGISTER READ ONLY BIT 15 TEST

```
3602  
3603  
3604  
3605  
3606  
3607 015336 012737 000071 001226 TST71: MOV #71,@TSTNO  
3608 015344 012737 015450 001216 MOV #TST72,NEXT  
3609 015352 013703 001404 MOV RXCSR,R3 ;GET THE RECEIVER CONTROL REGISTER  
3610 015356 012705 100000 MOV #BIT15,R5 ;GET BIT 15  
3611 015362 010513 MOV R5,(R3) ;WRITE BIT 15 TO RECEIVER CONTROL REGISTER  
3612 015364 011304 MOV (R3),R4 ;READ RECEIVER CONTROL REGISTER BACK  
3613 015366 005005 CLR R5 ;SET 'EXPECTED'  
3614 015370 020504 CMP R5,R4 ;R5=GOOD,R4= ?  
3615 015372 001401 BEQ 5$ ;BIT 15 IS OK  
3616 015374 104003 HLT 3 ;BIT FAILED TO CLR  
3617 015376 012705 100000 5$: MOV #BIT15,R5 ;RELOAD THE BIT  
3618 015402 010513 MOV R5,(R3) ;WRITE BIT 15 TO THE REG  
3619 015404 052777 000400 164000 BIS #MRESET,@TXCSR ;RESET THE DEVICE  
3620 015412 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH  
3621 015416 011304 MOV (R3),R4 ;GET BIT 15  
3622 015420 032704 100000 BIT #BIT15,R4 ;TEST BIT 15 FOR RESET CLR  
3623 015424 001401 BEQ 7$ ;BIT 15 IS OK  
3624 015426 104003 HLT 3 ;BIT FAILED TO CLEAR  
3625 015430 010513 7$: MOV R5,(R3) ;SET BIT 15  
3626 015432 005013 CLR (R3) ;CLR RECEIVER CONTROL REGISTER  
3627 015434 011304 MOV (R3),R4 ;READ THE RECEIVER CONTROL REGISTER  
3628 015436 005005 CLR R5 ;SET 'EXPECTED'  
3629 015440 020504 CMP R5,R4 ;R5=GOOD,R4= ?  
3630 015442 001401 BEQ 10$ ;BIT 15 IS OK  
3631 015444 104003 HLT 3 ;BIT FAILED TO CLEAR  
3632 015446 104400 10$: SCOPE ;SCOPE THIS TEST
```

```
***** TEST 72 *****  
*RECEIVER BUFFER REGISTER BIT 0 READ ONLY DEVICE RESET AND CLEAR TEST  
*WRITE BIT 0 A ONE AND VERIFY A ZERO IS READ BACK  
*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.  
*****
```

```
3633  
3634  
3635  
3636  
3637  
3638  
3639  
3640  
3641  
3642  
3643  
3644  
3645  
3646  
3647 015450 012737 000072 001226 TST72: MOV #72,@TSTNO  
3648 015456 012737 015562 001216 MOV #TST73,NEXT  
3649 015464 013703 001406 MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER  
3650 015470 012705 0000C1 MOV #BIT0,R5 ;GET BIT 0  
3651 015474 010513 MOV R5,(R3) ;WRITE BIT 0 TO RECEIVER BUFFER REGISTER  
3652 015476 011304 MOV (R3),R4 ;READ RECEIVER BUFFER REGISTER BACK  
3653 015500 005005 CLR R5 ;SET 'EXPECTED'  
3654 015502 020504 CMP R5,R4 ;R5=GOOD,R4= ?  
3655 015504 001401 BEQ 5$ ;BIT 0 IS OK  
3656 015506 104003 HLT 3 ;BIT FAILED TO CLR  
3657 015510 012705 000001 5$: MOV #BIT0,R5 ;RELOAD THE BIT
```

RECEIVER BUFFER REGISTER READ ONLY BIT 0 TEST

```
3658 015514 010513          MOV    R5,(R3)      ;WRITE BIT 0 TO THE REG
3659 015516 052777 000400 163666  BIS    #MRESET,@TXCSR ;RESET THE DEVICE
3660 015524 004737 005044          JSR    PC,SMALL     ;WAIT FOR RESET TO FINISH
3661 015530 011304          MOV    (R3),R4     ;GET BIT 0
3662 015532 032704 000001          BIT    #BIT0,R4    ;TEST BIT 0 FOR RESET CLR
3663 015536 001401          BEQ    7$         ;BIT 0 IS OK
3664 015540 104003          HLT    3          ;BIT FAILED TO CLEAR
3665 015542 010513 7$:      MOV    R5,(R3)     ;SET BIT 0
3666 015544 005013          CLR    (R3)       ;CLR RECEIVER BUFFER REGISTER
3667 015546 011304          MOV    (R3),R4    ;READ THE RECEIVER BUFFER REGISTER
3668 015550 005005          CLR    R5        ;SET 'EXPECTED'
3669 015552 020504          CMP    R5,R4     ;R5=GOOD,R4= ?
3670 015554 001401          BEQ    10$       ;BIT 0 IS OK
3671 015556 104003          HLT    3          ;BIT FAILED TO CLEAR
3672 015560 104400 10$:   SCOPE      ;SCOPE THIS TEST
```

3673

3674

3675

3676

3677

3678

3679

3680

3681

3682

3683

3684

3685

3686

3687 015562 012737 000073 001226

3688 015570 012737 015674 001216

3689 015576 013703 001406

3690 015602 012705 000002

3691 015606 010513

3692 015610 011304

3693 015612 005005

3694 015614 020504

3695 015616 001401

3696 015620 104003

3697 015622 012705 000002 5\$:

3698 015626 010513

3699 015630 052777 000400 163554

3700 015636 004737 005044

3701 015642 011304

3702 015644 032704 000002

3703 015650 001401

3704 015652 104003

3705 015654 010513 7\$:

3706 015656 005013

3707 015660 011304

3708 015662 005005

3709 015664 020504

3710 015666 001401

3711 015670 104003

3712 015672 104400 10\$:

3713

```
***** TEST 73 *****
*RECEIVER BUFFER REGISTER BIT 1 READ ONLY DEVICE RESET AND CLEAR TEST
*WRITE BIT 1 A ONE AND VERIFY A ZERO IS READ BACK
*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
*****
```

TEST 73

TST73: MOV #73,@TSTNO

MOV #TST74,NEXT

MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER

MOV #BIT1,R5 ;GET BIT 1

MOV R5,(R3) ;WRITE BIT 1 TO RECEIVER BUFFER REGISTER

MOV (R3),R4 ;READ RECEIVER BUFFER REGISTER BACK

CLR R5 ;SET 'EXPECTED'

CMP R5,R4 ;R5=GOOD,R4= ?

BEQ 5\$;BIT 1 IS OK

HLT 3 ;BIT FAILED TO CLR

5\$: MOV #BIT1,R5 ;RELOAD THE BIT

MOV R5,(R3) ;WRITE BIT 1 TO THE REG

BIS #MRESET,@TXCSR ;RESET THE DEVICE

JSR PC,SMALL ;WAIT FOR RESET TO FINISH

MOV (R3),R4 ;GET BIT 1

BIT #BIT1,R4 ;TEST BIT 1 FOR RESET CLR

BEQ 7\$;BIT 1 IS OK

HLT 3 ;BIT FAILED TO CLEAR

7\$: MOV R5,(R3) ;SET BIT 1

CLR (R3) ;CLR RECEIVER BUFFER REGISTER

MOV (R3),R4 ;READ THE RECEIVER BUFFER REGISTER

CLR R5 ;SET 'EXPECTED'

CMP R5,R4 ;R5=GOOD,R4= ?

BEQ 10\$;BIT 1 IS OK

HLT 3 ;BIT FAILED TO CLEAR

10\$: SCOPE ;SCOPE THIS TEST

RECEIVER BUFFER REGISTER READ ONLY BIT 2 TEST

3714
3715
3716
3717
3718
3719
3720
3721
3722
3723
3724
3725
3726
3727
3728
3729
3730
3731
3732
3733
3734
3735
3736
3737
3738
3739
3740
3741
3742
3743
3744
3745
3746
3747
3748
3749
3750
3751
3752
3753
3754
3755
3756
3757
3758
3759
3760
3761
3762
3763
3764
3765
3766
3767
3768
3769

015674 012737 000074 001226
015702 012737 016006 001216
015710 013703 001406
015714 012705 000004
015720 010513
015722 011304
015724 005005
015726 020504
015730 001401
015732 104003
015734 012705 000004
015740 010513
015742 052777 000400 163442
015750 004737 005044
015754 011304
015756 032704 000004
015762 001401
015764 104003
015766 010513
015770 005013
015772 011304
015774 005005
015776 020504
016000 001401
016002 104003
016004 104400

```
***** TEST 74 *****  
*RECEIVER BUFFER REGISTER BIT 2 READ ONLY DEVICE RESET AND CLEAR TEST  
*WRITE BIT 2 A ONE AND VERIFY A ZERO IS READ BACK  
*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.  
*****  
*****  
*  
TEST 74  
*  
*****  
*****  
TST74: MOV #74,@TSTNO  
MOV #TST75,NEXT  
MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER  
MOV #BIT2,R5 ;GET BIT 2  
MOV R5,(R3) ;WRITE BIT 2 TO RECEIVER BUFFER REGISTER  
MOV (R3),R4 ;READ RECEIVER BUFFER REGISTER BACK  
CLR R5 ;SET 'EXPECTED'  
CMP R5,R4 ;R5=GOOD,R4= ?  
BEQ 5$ ;BIT 2 IS OK  
HLT 3 ;BIT FAILED TO CLR  
5$: MOV #BIT2,R5 ;RELOAD THE BIT  
MOV R5,(R3) ;WRITE BIT 2 TO THE REG  
BIS #MRESET,@TXCSR ;RESET THE DEVICE  
JSR PC,SMALL ;WAIT FOR RESET TO FINISH  
MOV (R3),R4 ;GET BIT 2  
BIT #BIT2,R4 ;TEST BIT 2 FOR RESET CLR  
BEQ 7$ ;BIT 2 IS OK  
HLT 3 ;BIT FAILED TO CLEAR  
7$: MOV R5,(R3) ;SET BIT 2  
CLR (R3) ;CLR RECEIVER BUFFER REGISTER  
MOV (R3),R4 ;READ THE RECEIVER BUFFER REGISTER  
CLR R5 ;SET 'EXPECTED'  
CMP R5,R4 ;R5=GOOD,R4= ?  
BEQ 10$ ;BIT 2 IS OK  
HLT 3 ;BIT FAILED TO CLEAR  
10$: SCOPE ;SCOPE THIS TEST
```

***** TEST 75 *****
*RECEIVER BUFFER REGISTER BIT 3 READ ONLY DEVICE RESET AND CLEAR TEST
*WRITE BIT 3 A ONE AND VERIFY A ZERO IS READ BACK
*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.

3761
3762
3763
3764
3765
3766
3767
3768
3769

016006 012737 000075 001226
016014 012737 016120 001216
016022 013703 001406

```
*****  
*  
TEST 75  
*  
*****  
*****  
TST75: MOV #75,@TSTNO  
MOV #TST76,NEXT  
MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER
```

RECEIVER BUFFER REGISTER READ ONLY BIT 3 TEST

```
3770 016026 012705 000010      MOV      #BIT3,R5      ;GET BIT 3
3771 016032 010513      MOV      R5,(R3)      ;WRITE BIT 3 TO RECEIVER BUFFER REGISTER
3772 016034 011304      MOV      (R3),R4      ;READ RECEIVER BUFFER REGISTER BACK
3773 016036 005005      CLR      R5           ;SET 'EXPECTED'
3774 016040 020504      CMP      R5,R4        ;R5=GOOD,R4= ?
3775 016042 001401      BEQ      5$           ;BIT 3 IS OK
3776 016044 104003      HLT      3            ;BIT FAILED TO CLR
3777 016046 012705 000010      5$:  MOV      #BIT3,R5      ;RELOAD THE BIT
3778 016052 010513      MOV      R5,(R3)      ;WRITE BIT 3 TO THE REG
3779 016054 052777 000400 163330  BIS      #MRESET,@TXCSR ;RESET THE DEVICE
3780 016062 004737 005044      JSR      PC,SMALL     ;WAIT FOR RESET TO FINISH
3781 016066 011304      MOV      (R3),R4      ;GET BIT 3
3782 016070 032704 000010  BIT      #BIT3,R4      ;TEST BIT 3 FOR RESET CLR
3783 016074 001401      BEQ      7$           ;BIT 3 IS OK
3784 016076 104003      HLT      3            ;BIT FAILED TO CLEAR
3785 016100 010513      7$:  MOV      R5,(R3)      ;SET BIT 3
3786 016102 005013      CLR      (R3)         ;CLR RECEIVER BUFFER REGISTER
3787 016104 011304      MOV      (R3),R4      ;READ THE RECEIVER BUFFER REGISTER
3788 016106 005005      CLR      R5           ;SET 'EXPECTED'
3789 016110 020504      CMP      R5,R4        ;R5=GOOD,R4= ?
3790 016112 001401      BEQ      10$          ;BIT 3 IS OK
3791 016114 104003      HLT      3            ;BIT FAILED TO CLEAR
3792 016116 104400      10$: SCOPE           ;SCOPE THIS TEST
```

```
:***** TEST 76 *****
:*RECEIVER BUFFER REGISTER BIT 4 READ ONLY DEVICE RESET AND CLEAR TEST
:*WRITE BIT 4 A ONE AND VERIFY A ZERO IS READ BACK
:*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
:*****
```

```
:*****
:
: TEST 76
:
:*****
```

```
3807 016120 012737 000076 001226  TST76: MOV      #76,@TSTNO
3808 016126 012737 016232 001216  MOV      #TST77,NEXT
3809 016134 013703 001406      MOV      RXDBUF,R3    ;GET THE RECEIVER BUFFER REGISTER
3810 016140 012705 000020      MOV      #BIT4,R5     ;GET BIT 4
3811 016144 010513      MOV      R5,(R3)      ;WRITE BIT 4 TO RECEIVER BUFFER REGISTER
3812 016146 011304      MOV      (R3),R4      ;READ RECEIVER BUFFER REGISTER BACK
3813 016150 005005      CLR      R5           ;SET 'EXPECTED'
3814 016152 020504      CMP      R5,R4        ;R5=GOOD,R4= ?
3815 016154 001401      BEQ      5$           ;BIT 4 IS OK
3816 016156 104003      HLT      3            ;BIT FAILED TO CLR
3817 016160 012705 000020      5$:  MOV      #BIT4,R5     ;RELOAD THE BIT
3818 016164 010513      MOV      R5,(R3)      ;WRITE BIT 4 TO THE REG
3819 016166 052777 000400 163216  BIS      #MRESET,@TXCSR ;RESET THE DEVICE
3820 016174 004737 005044      JSR      PC,SMALL     ;WAIT FOR RESET TO FINISH
3821 016200 011304      MOV      (R3),R4      ;GET BIT 4
3822 016202 032704 000020  BIT      #BIT4,R4      ;TEST BIT 4 FOR RESET CLR
3823 016206 001401      BEQ      7$           ;BIT 4 IS OK
3824 016210 104003      HLT      3            ;BIT FAILED TO CLEAR
3825 016212 010513      7$:  MOV      R5,(R3)      ;SET BIT 4
```

RECEIVER BUFFER REGISTER READ ONLY BIT 4 TEST

```
3826 016214 005013          CLR      (R3)          ;CLR RECEIVER BUFFER REGISTER
3827 016216 011304          MOV      (R3),R4       ;READ THE RECEIVER BUFFER REGISTER
3828 016220 005005          CLR      R5           ;SET 'EXPECTED'
3829 016222 020504          CMP      R5,R4        ;R5=GOOD,R4= ?
3830 016224 001401          BEQ      10$          ;BIT 4 IS OK
3831 016226 104003          HLT      3            ;BIT FAILED TO CLEAR
3832 016230 104400          10$:   SCOPE         ;SCOPE THIS TEST
3833
3834
3835          ;***** TEST 77 *****
3836          ;*RECEIVER BUFFER REGISTER BIT 5 READ ONLY DEVICE RESET AND CLEAR TEST
3837          ;*WRITE BIT 5 A ONE AND VERIFY A ZERO IS READ BACK
3838          ;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
3839          ;*****
3840
3841          ;*****
3842          ;*
3843          ;* TEST 77
3844          ;*
3845          ;*****
3846          ;*****
3847 016232 012737 000077 001226 TST77:  MOV      #77,@TSTNO
3848 016240 012737 016344 001216          MOV      #TST100,NEXT
3849 016246 013703 001406          MOV      RXDBUF,R3    ;GET THE RECEIVER BUFFER REGISTER
3850 016252 012705 000040          MOV      #BIT5,R5     ;GET BIT 5
3851 016256 010513          MOV      R5,(R3)      ;WRITE BIT 5 TO RECEIVER BUFFER REGISTER
3852 016260 011304          MOV      (R3),R4      ;READ RECEIVER BUFFER REGISTER BACK
3853 016262 005005          CLR      R5           ;SET 'EXPECTED'
3854 016264 020504          CMP      R5,R4        ;R5=GOOD,R4= ?
3855 016266 001401          BEQ      5$           ;BIT 5 IS OK
3856 016270 104003          HLT      3            ;BIT FAILED TO CLR
3857 016272 012705 000040          5$:   MOV      #BIT5,R5     ;RELOAD THE BIT
3858 016276 010513          MOV      R5,(R3)      ;WRITE BIT 5 TO THE REG
3859 016300 052777 000400 163104          BIS      #MRESET,@TXCSR ;RESET THE DEVICE
3860 016306 004737 005044          JSR      PC,SMALL     ;WAIT FOR RESET TO FINISH
3861 016312 011304          MOV      (R3),R4      ;GET BIT 5
3862 016314 032704 000040          BIT      #BIT5,R4     ;TEST BIT 5 FOR RESET CLR
3863 016320 001401          BEQ      7$           ;BIT 5 IS OK
3864 016322 104003          HLT      3            ;BIT FAILED TO CLEAR
3865 016324 010513          7$:   MOV      R5,(R3)      ;SET BIT 5
3866 016326 005013          CLR      (R3)         ;CLR RECEIVER BUFFER REGISTER
3867 016330 011304          MOV      (R3),R4      ;READ THE RECEIVER BUFFER REGISTER
3868 016332 005005          CLR      R5           ;SET 'EXPECTED'
3869 016334 020504          CMP      R5,R4        ;R5=GOOD,R4= ?
3870 016336 001401          BEQ      10$          ;BIT 5 IS OK
3871 016340 104003          HLT      3            ;BIT FAILED TO CLEAR
3872 016342 104400          10$:   SCOPE         ;SCOPE THIS TEST
3873
3874
3875          ;***** TEST 100 *****
3876          ;*RECEIVER BUFFER REGISTER BIT 6 READ ONLY DEVICE RESET AND CLEAR TEST
3877          ;*WRITE BIT 6 A ONE AND VERIFY A ZERO IS READ BACK
3878          ;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
3879          ;*****
3880
3881          ;*****
```


RECEIVER BUFFER REGISTER READ ONLY BIT 6 TEST

```
3882
3883      : TEST 100
3884      :
3885      :*****
3886      :*****
3887 016344 012737 000100 001226 TST100: MOV #100,@TSTNO
3888 016352 012737 016456 001216      MOV #TST101,NEXT
3889 016360 013703 001406      MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER
3890 016364 012705 000100      MOV #BIT6,R5 ;GET BIT 6
3891 016370 010513      MOV R5,(R3) ;WRITE BIT 6 TO RECEIVER BUFFER REGISTER
3892 016372 011304      MOV (R3),R4 ;READ RECEIVER BUFFER REGISTER BACK
3893 016374 005005      CLR R5 ;SET 'EXPECTED'
3894 016376 020504      CMP R5,R4 ;R5=GOOD,R4= ?
3895 016400 001401      BEQ 5$ ;BIT 6 IS OK
3896 016402 104003      HLT 3 ;BIT FAILED TO CLR
3897 016404 012705 000100 5$: MOV #BIT6,R5 ;RELOAD THE BIT
3898 016410 010513      MOV R5,(R3) ;WRITE BIT 6 TO THE REG
3899 016412 052777 000400 162772 BIS #MRESET,@TXCSR ;RESET THE DEVICE
3900 016420 004737 005044      JSR PC,SMALL ;WAIT FOR RESET TO FINISH
3901 016424 011304      MOV (R3),R4 ;GET BIT 6
3902 016426 032704 000100      BIT #BIT6,R4 ;TEST BIT 6 FOR RESET CLR
3903 016432 001401      BEQ 7$ ;BIT 6 IS OK
3904 016434 104003      HLT 3 ;BIT FAILED TO CLEAR
3905 016436 010513 7$: MOV R5,(R3) ;SET BIT 6
3906 016440 005013      CLR (R3) ;CLR RECEIVER BUFFER REGISTER
3907 016442 011304      MOV (R3),R4 ;READ THE RECEIVER BUFFER REGISTER
3908 016444 005005      CLR R5 ;SET 'EXPECTED'
3909 016446 020504      CMP R5,R4 ;R5=GOOD,R4= ?
3910 016450 001401      BEQ 10$ ;BIT 6 IS OK
3911 016452 104003      HLT 3 ;BIT FAILED TO CLEAR
3912 016454 104400 10$: SCOPE ;SCOPE THIS TEST
3913
3914
3915      :***** TEST 101 *****
3916      :*RECEIVER BUFFER REGISTER BIT 7 READ ONLY DEVICE RESET AND CLEAR TEST
3917      :*WRITE BIT 7 A ONE AND VERIFY A ZERO IS READ BACK
3918      :*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
3919      :*****
3920
3921      :*****
3922      :
3923      : TEST 101
3924      :
3925      :*****
3926      :*****
3927 016456 012737 000101 001226 TST101: MOV #101,@TSTNO
3928 016464 012737 016570 001216      MOV #TST102,NEXT
3929 016472 013703 001406      MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER
3930 016476 012705 000200      MOV #BIT7,R5 ;GET BIT 7
3931 016502 010513      MOV R5,(R3) ;WRITE BIT 7 TO RECEIVER BUFFER REGISTER
3932 016504 011304      MOV (R3),R4 ;READ RECEIVER BUFFER REGISTER BACK
3933 016506 005005      CLR R5 ;SET 'EXPECTED'
3934 016510 020504      CMP R5,R4 ;R5=GOOD,R4= ?
3935 016512 001401      BEQ 5$ ;BIT 7 IS OK
3936 016514 104003      HLT 3 ;BIT FAILED TO CLR
3937 016516 012705 000200 5$: MOV #BIT7,R5 ;RELOAD THE BIT
```

RECEIVER BUFFER REGISTER READ ONLY BIT 7 TEST

```
3938 016522 010513          MOV    R5,(R3)          ;WRITE BIT 7 TO THE REG
3939 016524 052777 000400 162660  BIS    #MRESET,@TXCSR  ;RESET THE DEVICE
3940 016532 004737 005044          JSR    PC,SMALL        ;WAIT FOR RESET TO FINISH
3941 016536 011304          MOV    (R3),R4         ;GET BIT 7
3942 016540 032704 000200          BIT    #BIT7,R4        ;TEST BIT 7 FOR RESET CLR
3943 016544 001401          BEQ    7$              ;BIT 7 IS OK
3944 016546 104003          HLT    3                ;BIT FAILED TO CLEAR
3945 016550 010513 7$:      MOV    R5,(R3)          ;SET BIT 7
3946 016552 005013          CLR    (R3)            ;CLR RECEIVER BUFFER REGISTER
3947 016554 011304          MOV    (R3),R4         ;READ THE RECEIVER BUFFER REGISTER
3948 016556 005005          CLR    R5              ;SET 'EXPECTED'
3949 016560 020504          CMP    R5,R4           ;R5=GOOD,R4= ?
3950 016562 001401          BEQ    10$             ;BIT 7 IS OK
3951 016564 104003          HLT    3                ;BIT FAILED TO CLEAR
3952 016566 104400 10$:    SCOPE           ;SCOPE THIS TEST
3953
3954
3955
```

```
:***** TEST 102 *****
:*RECEIVER BUFFER REGISTER BIT 8 READ ONLY DEVICE RESET AND CLEAR TEST
:*WRITE BIT 8 A ONE AND VERIFY A ZERO IS READ BACK
:*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
:*****
```

```
:*****
: *
: TEST 102
: *
:*****
```

```
3967 016570 012737 000102 001226 TST102: MOV    #102,@TSTNO
3968 016576 012737 016702 001216  MOV    #TST103,NEXT
3969 016604 013703 001406          MOV    RXDBUF,R3       ;GET THE RECEIVER BUFFER REGISTER
3970 016610 012705 000400          MOV    #BIT8,R5        ;GET BIT 8
3971 016614 010513          MOV    R5,(R3)         ;WRITE BIT 8 TO RECEIVER BUFFER REGISTER
3972 016616 011304          MOV    (R3),R4         ;READ RECEIVER BUFFER REGISTER BACK
3973 016620 005005          CLR    R5              ;SET 'EXPECTED'
3974 016622 020504          CMP    R5,R4           ;R5=GOOD,R4= ?
3975 016624 001401          BEQ    5$              ;BIT 8 IS OK
3976 016626 104003          HLT    3                ;BIT FAILED TO CLR
3977 016630 012705 000400 5$:      MOV    #BIT8,R5        ;RELOAD THE BIT
3978 016634 010513          MOV    R5,(R3)         ;WRITE BIT 8 TO THE REG
3979 016636 052777 000400 162546  BIS    #MRESET,@TXCSR  ;RESET THE DEVICE
3980 016644 004737 005044          JSR    PC,SMALL        ;WAIT FOR RESET TO FINISH
3981 016650 011304          MOV    (R3),R4         ;GET BIT 8
3982 016652 032704 000400          BIT    #BIT8,R4        ;TEST BIT 8 FOR RESET CLR
3983 016656 001401          BEQ    7$              ;BIT 8 IS OK
3984 016660 104003          HLT    3                ;BIT FAILED TO CLEAR
3985 016662 010513 7$:      MOV    R5,(R3)          ;SET BIT 8
3986 016664 005013          CLR    (R3)            ;CLR RECEIVER BUFFER REGISTER
3987 016666 011304          MOV    (R3),R4         ;READ THE RECEIVER BUFFER REGISTER
3988 016670 005005          CLR    R5              ;SET 'EXPECTED'
3989 016672 020504          CMP    R5,R4           ;R5=GOOD,R4= ?
3990 016674 001401          BEQ    10$             ;BIT 8 IS OK
3991 016676 104003          HLT    3                ;BIT FAILED TO CLEAR
3992 016700 104400 10$:    SCOPE           ;SCOPE THIS TEST
3993
```

RECEIVER BUFFER REGISTER READ ONLY BIT 9 TEST

3994
3995
3996
3997
3998
3999
4000
4001
4002
4003
4004
4005
4006
4007
4008
4009
4010
4011
4012
4013
4014
4015
4016
4017
4018
4019
4020
4021
4022
4023
4024
4025
4026
4027
4028
4029
4030
4031
4032
4033
4034
4035
4036
4037
4038
4039
4040
4041
4042
4043
4044
4045
4046
4047
4048
4049

016702 012737 000103 001226
016710 012737 017014 001216
016716 013703 001406
016722 012705 001000
016726 010513
016730 011304
016732 005005
016734 020504
016736 001401
016740 104003
016742 012705 001000
016746 010513
016750 052777 000400 162434
016756 004737 005044
016762 011304
016764 032704 001000
016770 001401
016772 104003
016774 010513
016776 005013
017000 011304
017002 005005
017004 020504
017006 001401
017010 104003
017012 104400

```
***** TEST 103 *****  
*RECEIVER BUFFER REGISTER BIT 9 READ ONLY DEVICE RESET AND CLEAR TEST  
*WRITE BIT 9 A ONE AND VERIFY A ZERO IS READ BACK  
*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.  
*****  
*****  
*  
TEST 103  
*  
*****  
*****  
TST103: MOV #103,@TSTNO  
MOV #TST104,NEXT  
MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER  
MOV #BIT9,R5 ;GET BIT 9  
MOV R5,(R3) ;WRITE BIT 9 TO RECEIVER BUFFER REGISTER  
MOV (R3),R4 ;READ RECEIVER BUFFER REGISTER BACK  
CLR R5 ;SET 'EXPECTED'  
CMP R5,R4 ;R5=GOOD,R4= ?  
BEQ 5$ ;BIT 9 IS OK  
HLT 3 ;BIT FAILED TO CLR  
5$: MOV #BIT9,R5 ;RELOAD THE BIT  
MOV R5,(R3) ;WRITE BIT 9 TO THE REG  
BIS #MRESET,@TXCSR ;RESET THE DEVICE  
JSR PC,SMALL ;WAIT FOR RESET TO FINISH  
MOV (R3),R4 ;GET BIT 9  
BIT #BIT9,R4 ;TEST BIT 9 FOR RESET CLR  
BEQ 7$ ;BIT 9 IS OK  
HLT 3 ;BIT FAILED TO CLEAR  
7$: MOV R5,(R3) ;SET BIT 9  
CLR (R3) ;CLR RECEIVER BUFFER REGISTER  
MOV (R3),R4 ;READ THE RECEIVER BUFFER REGISTER  
CLR R5 ;SET 'EXPECTED'  
CMP R5,R4 ;R5=GOOD,R4= ?  
BEQ 10$ ;BIT 9 IS OK  
HLT 3 ;BIT FAILED TO CLEAR  
10$: SCOPE ;SCOPE THIS TEST
```

***** TEST 104 *****
*RECEIVER BUFFER REGISTER BIT 10 READ ONLY DEVICE RESET AND CLEAR TEST
*WRITE BIT 10 A ONE AND VERIFY A ZERO IS READ BACK
*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.

4041
4042
4043
4044
4045
4046
4047
4048
4049

017014 012737 000104 001226
017022 012737 017126 001216
017030 013703 001406

```
*****  
*  
TEST 104  
*  
*****  
*****  
TST104: MOV #104,@TSTNO  
MOV #TST105,NEXT  
MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER
```

RECEIVER BUFFER REGISTER READ ONLY BIT 10 TEST

```
4050 017034 012705 002000      MOV      #BIT10,R5      ;GET BIT 10
4051 017040 010513      MOV      R5,(R3)       ;WRITE BIT 10 TO RECEIVER BUFFER REGISTER
4052 017042 011304      MOV      (R3),R4       ;READ RECEIVER BUFFER REGISTER BACK
4053 017044 005005      CLR      R5            ;SET 'EXPECTED'
4054 017046 020504      CMP      R5,R4         ;R5=GOOD,R4=?
4055 017050 001401      BEQ      5$           ;BIT 10 IS OK
4056 017052 104003      HLT      3            ;BIT FAILED TO CLR
4057 017054 012705 002000 5$:  MOV      #BIT10,R5     ;RELOAD THE BIT
4058 017060 010513      MOV      R5,(R3)       ;WRITE BIT 10 TO THE REG
4059 017062 052777 000400 162322  BIS      #MRESET,@TXCSR ;RESET THE DEVICE
4060 017070 004737 005044      JSR      PC,SMALL      ;WAIT FOR RESET TO FINISH
4061 017074 011304      MOV      (R3),R4       ;GET BIT 10
4062 017076 032704 002000      BIT      #BIT10,R4     ;TEST BIT 10 FOR RESET CLR
4063 017102 001401      BEQ      7$           ;BIT 10 IS OK
4064 017104 104003      HLT      3            ;BIT FAILED TO CLEAR
4065 017106 010513 7$:  MOV      R5,(R3)       ;SET BIT 10
4066 017110 005013      CLR      (R3)          ;CLR RECEIVER BUFFER REGISTER
4067 017112 011304      MOV      (R3),R4       ;READ THE RECEIVER BUFFER REGISTER
4068 017114 005005      CLR      R5            ;SET 'EXPECTED'
4069 017116 020504      CMP      R5,R4         ;R5=GOOD,R4=?
4070 017120 001401      BEQ      10$          ;BIT 10 IS OK
4071 017122 104003      HLT      3            ;BIT FAILED TO CLEAR
4072 017124 104400 10$: SCOPE              ;SCOPE THIS TEST
4073
4074
4075
```

```
***** TEST 105 *****
;*RECEIVER BUFFER REGISTER BIT 12 READ ONLY DEVICE RESET AND CLEAR TEST
;*WRITE BIT 12 A ONE AND VERIFY A ZERO IS READ BACK
;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
*****
```

```
*****
*
* TEST 105
*
*****
```

```
4086
4087 017126 012737 000105 001226 TST105: MOV      #105,@TSTNO
4088 017134 012737 017240 001216      MOV      #TST106,NEXT
4089 017142 013703 001406      MOV      RXDBUF,R3     ;GET THE RECEIVER BUFFER REGISTER
4090 017146 012705 010000      MOV      #BIT12,R5     ;GET BIT 12
4091 017152 010513      MOV      R5,(R3)       ;WRITE BIT 12 TO RECEIVER BUFFER REGISTER
4092 017154 011304      MOV      (R3),R4       ;READ RECEIVER BUFFER REGISTER BACK
4093 017156 005005      CLR      R5            ;SET 'EXPECTED'
4094 017160 020504      CMP      R5,R4         ;R5=GOOD,R4=?
4095 017162 001401      BEQ      5$           ;BIT 12 IS OK
4096 017164 104003      HLT      3            ;BIT FAILED TO CLR
4097 017166 012705 010000 5$:  MOV      #BIT12,R5     ;RELOAD THE BIT
4098 017172 010513      MOV      R5,(R3)       ;WRITE BIT 12 TO THE REG
4099 017174 052777 000400 162210  BIS      #MRESET,@TXCSR ;RESET THE DEVICE
4100 017202 004737 005044      JSR      PC,SMALL      ;WAIT FOR RESET TO FINISH
4101 017206 011304      MOV      (R3),R4       ;GET BIT 12
4102 017210 032704 010000      BIT      #BIT12,R4     ;TEST BIT 12 FOR RESET CLR
4103 017214 001401      BEQ      7$           ;BIT 12 IS OK
4104 017216 104003      HLT      3            ;BIT FAILED TO CLEAR
4105 017220 010513 7$:  MOV      R5,(R3)       ;SET BIT 12
```

```
4106 017222 005013 CLR (R3) ;CLR RECEIVER BUFFER REGISTER
4107 017224 011304 MOV (R3),R4 ;READ THE RECEIVER BUFFER REGISTER
4108 017226 005005 CLR R5 ;SET 'EXPECTED'
4109 017230 020504 CMP R5,R4 ;R5=GOOD,R4=?
4110 017232 001401 BEQ 10$ ;BIT 12 IS OK
4111 017234 104003 HLT 3 ;BIT FAILED TO CLEAR
4112 017236 104400 10$: SCOPE ;SCOPE THIS TEST
```

```
4113
4114
4115 ;***** TEST 106 *****
4116 ;*RECEIVER BUFFER REGISTER BIT 14 READ ONLY DEVICE RESET AND CLEAR TEST
4117 ;*WRITE BIT 14 A ONE AND VERIFY A ZERO IS READ BACK
4118 ;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
4119 ;*****
```

```
4120
4121 ;*****
4122 ;*
4123 ;* TEST 106
4124 ;*
4125 ;*****
4126 ;*****
```

```
4127 017240 012737 000106 001226 TST106: MOV #106,@TSTNO
4128 017246 012737 017352 001216 MOV #TST107,NEXT
4129 017254 013703 001406 MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER
4130 017260 012705 040000 MOV #BIT14,R5 ;GET BIT 14
4131 017264 010513 MOV R5,(R3) ;WRITE BIT 14 TO RECEIVER BUFFER REGISTER
4132 017266 011304 MOV (R3),R4 ;READ RECEIVER BUFFER REGISTER BACK
4133 017270 005005 CLR R5 ;SET 'EXPECTED'
4134 017272 020504 CMP R5,R4 ;R5=GOOD,R4=?
4135 017274 001401 BEQ 5$ ;BIT 14 IS OK
4136 017276 104003 HLT 3 ;BIT FAILED TO CLR
4137 017300 012705 040000 5$: MOV #BIT14,R5 ;RELOAD THE BIT
4138 017304 010513 MOV R5,(R3) ;WRITE BIT 14 TO THE REG
4139 017306 052777 000400 162076 BIS #MRESET,@TXCSR ;RESET THE DEVICE
4140 017314 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
4141 017320 011304 MOV (R3),R4 ;GET BIT 14
4142 017322 032704 040000 BIT #BIT14,R4 ;TEST BIT 14 FOR RESET CLR
4143 017326 001401 BEQ 7$ ;BIT 14 IS OK
4144 017330 104003 HLT 3 ;BIT FAILED TO CLEAR
4145 017332 010513 7$: MOV R5,(R3) ;SET BIT 14
4146 017334 005013 CLR (R3) ;CLR RECEIVER BUFFER REGISTER
4147 017336 011304 MOV (R3),R4 ;READ THE RECEIVER BUFFER REGISTER
4148 017340 005005 CLR R5 ;SET 'EXPECTED'
4149 017342 020504 CMP R5,R4 ;R5=GOOD,R4=?
4150 017344 001401 BEQ 10$ ;BIT 14 IS OK
4151 017346 104003 HLT 3 ;BIT FAILED TO CLEAR
4152 017350 104400 10$: SCOPE ;SCOPE THIS TEST
```

```
4153
4154
4155 ;***** TEST 107 *****
4156 ;*RECEIVER BUFFER REGISTER BIT 15 READ ONLY DEVICE RESET AND CLEAR TEST
4157 ;*WRITE BIT 15 A ONE AND VERIFY A ZERO IS READ BACK
4158 ;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
4159 ;*****
```

```
4160 ;*****
4161 ;*****
```

```

4162      :
4163      : TEST 107
4164      :
4165      : *****
4166      : *****
4167 017352 012737 000107 001226 TST107: MOV #107,@TSTNO
4168 017360 012737 017464 001216      MOV #TST110,NEXT
4169 017366 013703 001406      MOV RXDBUF,R3 ;GET THE RECEIVER BUFFER REGISTER
4170 017372 012705 100000      MOV #BIT15,R5 ;GET BIT 15
4171 017376 010513      MOV R5,(R3) ;WRITE BIT 15 TO RECEIVER BUFFER REGISTER
4172 017400 011304      MOV (R3),R4 ;READ RECEIVER BUFFER REGISTER BACK
4173 017402 005005      CLR R5 ;SET 'EXPECTED'
4174 017404 020504      CMP R5,R4 ;R5=GOOD,R4=?
4175 017406 001401      BEQ 5$ ;BIT 15 IS OK
4176 017410 104003      HLT 3 ;BIT FAILED TO CLR
4177 017412 012705 100000 5$: MOV #BIT15,R5 ;RELOAD THE BIT
4178 017416 010513      MOV R5,(R3) ;WRITE BIT 15 TO THE REG
4179 017420 052777 000400 161764 BIS #MRESET,@TXCSR ;RESET THE DEVICE
4180 017426 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
4181 017432 011304      MOV (R3),R4 ;GET BIT 15
4182 017434 032704 100000 BIT #BIT15,R4 ;TEST BIT 15 FOR RESET CLR
4183 017440 001401      BEQ 7$ ;BIT 15 IS OK
4184 017442 104003      HLT 3 ;BIT FAILED TO CLEAR
4185 017444 010513 7$: MOV R5,(R3) ;SET BIT 15
4186 017446 005013      CLR (R3) ;CLR RECEIVER BUFFER REGISTER
4187 017450 011304      MOV (R3),R4 ;READ THE RECEIVER BUFFER REGISTER
4188 017452 005005      CLR R5 ;SET 'EXPECTED'
4189 017454 020504      CMP R5,R4 ;R5=GOOD,R4=?
4190 017456 001401      BEQ 10$ ;BIT 15 IS OK
4191 017460 104003      HLT 3 ;BIT FAILED TO CLEAR
4192 017462 104400 10$: SCOPE ;SCOPE THIS TEST
4193
4194      : ***** TEST 110 *****
4195      : *THIS TEST VERIFIES BIT7 OF THE TRANSMITTER CONTROL REGISTER
4196      : *TEST THAT BIT 7 SETS AFTER A RESET AND MRESET
4197      : *VERIFY THAT WRITING THE LOW BYTE OF
4198      : *THE TRANSMITTER BUFFER REGISTER CLEARS BIT 7
4199      : *****
4200
4201      : *****
4202      :
4203      : TEST 110
4204      :
4205      : *****
4206      : *****
4207 017464 012737 000110 001226 TST110: MOV #110,@TSTNO
4208 017472 012737 017572 001216      MOV #TST111,NEXT
4209 017500 013702 001414      MOV TXDBUF,R2 ;LOAD SECOND REG
4210 017504 013703 001412      MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER
4211 017510 012705 000200      MOV #BIT7,R5 ;SET 'EXPECTED'
4212 017514 000005      RESET
4213 017516 011304      MOV (R3),R4 ;GET THE BIT
4214 017520 020504      CMP R5,R4 ;R5=GOOD,R4=?
4215 017522 001401      BEQ 1$ ;ARE THEY THE SAME?
4216 017524 104003      HLT 3 ;NO--REPORT THE ERROR
4217 017526 005005 1$: CLR R5 ;SET 'EXPECTED'
  
```

TRANSMITTER CONTROL REGISTER READ ONLY TEST BIT 7

```
4218 017530 005012 CLR (R2) ;WRITE THE LOW BYTE OF THE TXDBUF
4219 017532 011304 MOV (R3),R4 ;READ BACK BIT 7
4220 017534 020504 CMP R5,R4 ;R5-GOOD,R4=?
4221 017536 001401 BEQ 2$ ;ARE THEY THE SAME?
4222 017540 104003 HLT 3 ;NO-BIT 7 FAILED TO CLEAR
4223 017542 012705 000200 2$: MOV #BIT7,R5 ;SET 'EXPECTED'
4224 017546 052777 000400 161636 BIS #MRESET,@TXCSR ;RESET THE DEVICE
4225 017554 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
4226 017560 011304 MOV (R3),R4 ;READ BACK BIT 7
4227 017562 020504 CMP R5,R4 ;R5=GOOD,R4=?
4228 017564 001401 BEQ 3$ ;BRANCH IF BIT 7 OK
4229 017566 104003 HLT 3 ;BIT 7 FAILED TO SET AFTER A MRESET
4230 017570 104400 3$: SCOPE ;SCOPE THIS TEST
```

4231
4232
4233
4234
4235
4236
4237
4238
4239
4240
4241
4242
4243
4244
4245

```
:***** TEST 111 *****  
:*TRANSMITTER CONTROL REGISTER BIT 9 READ ONLY DEVICE RESET AND CLEAR TEST  
:*WRITE BIT 9 A ONE AND VERIFY A ZERO IS READ BACK  
:*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.  
:*****
```

```
:*****  
: *  
: TEST 111  
: *  
:*****
```

```
4246 017572 012737 000111 001226 TST111: MOV #111,@TSTNO
4247 017600 012737 017714 001216 MOV #TST112,NEXT
4248 017606 013703 001412 MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER
4249 017612 012705 001000 MOV #BIT9,R5 ;GET BIT 9
4250 017616 010513 MOV R5,(R3) ;WRITE BIT 9 TO TRANSMITTER CONTROL REGISTER
4251 017620 011304 MOV (R3),R4 ;READ TRANSMITTER CONTROL REGISTER BACK
4252 017622 005005 CLR R5 ;SET 'EXPECTED'
4253 017624 042704 000200 BIC #BIT7,R4 ;CLEAR UNWANTED BITS
4254 017630 020504 CMP R5,R4 ;R5=GOOD,R4=?
4255 017632 001401 BEQ 5$ ;BIT 9 IS OK
4256 017634 104003 HLT 3 ;BIT FAILED TO CLR
4257 017636 012705 001000 5$: MOV #BIT9,R5 ;RELOAD THE BIT
4258 017642 010513 MOV R5,(R3) ;WRITE BIT 9 TO THE REG
4259 017644 052777 000400 161540 BIS #MRESET,@TXCSR ;RESET THE DEVICE
4260 017652 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
4261 017656 011304 MOV (R3),R4 ;GET BIT 9
4262 017660 032704 001000 BIT #BIT9,R4 ;TEST BIT 9 FOR RESET CLR
4263 017664 001401 BEQ 7$ ;BIT 9 IS OK
4264 017666 104003 HLT 3 ;BIT FAILED TO CLEAR
4265 017670 010513 7$: MOV R5,(R3) ;SET BIT 9
4266 017672 005013 CLR (R3) ;CLR TRANSMITTER CONTROL REGISTER
4267 017674 011304 MOV (R3),R4 ;READ THE TRANSMITTER CONTROL REGISTER
4268 017676 005005 CLR R5 ;SET 'EXPECTED'
4269 017700 042704 000200 BIC #BIT7,R4 ;CLEAR UNWANTED BITS
4270 017704 020504 CMP R5,R4 ;R5=GOOD,R4=?
4271 017706 001401 BEQ 10$ ;BIT 9 IS OK
4272 017710 104003 HLT 3 ;BIT FAILED TO CLEAR
4273 017712 104400 10$: SCOPE ;SCOPE THIS TEST
```

TRANSMITTER CONTROL REGISTER READ ONLY TEST BIT 9

4274
4275
4276
4277
4278
4279
4280
4281
4282
4283
4284
4285
4286
4287
4288
4289
4290
4291
4292
4293
4294
4295
4296
4297
4298
4299
4300
4301
4302
4303
4304
4305
4306
4307
4308
4309
4310
4311
4312
4313
4314
4315
4316
4317
4318
4319
4320
4321
4322
4323
4324
4325
4326
4327
4328
4329

***** TEST 112 *****
TRANSMITTER CONTROL REGISTER BIT 14 READ ONLY DEVICE RESET AND CLEAR TEST
WRITE BIT 14 A ONE AND VERIFY A ZERO IS READ BACK
REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.

*
: TEST 112
*

017714 012737 000112 001226
017722 012737 020036 001216
017730 013703 001412
017734 012705 040000
017740 010513
017742 011304
017744 005005
017746 042704 000200
017752 020504
017754 001401
017756 104003
017760 012705 040000
017764 010513
017766 052777 000400 161416
017774 004737 005044
020000 011304
020002 032704 040000
020006 001401
020010 104003
020012 010513
020014 005013
020016 011304
020020 005005
020022 042704 000200
020026 020504
020030 001401
020032 104003
020034 104400

```
TST112: MOV #112,@TSTNO
MOV #TST113,NEXT
MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER
MOV #BIT14,R5 ;GET BIT 14
MOV R5,(R3) ;WRITE BIT 14 TO TRANSMITTER CONTROL REGISTER
MOV (R3),R4 ;READ TRANSMITTER CONTROL REGISTER BACK
CLR R5 ;SET 'EXPECTED'
BIC #BIT7,R4 ;CLEAR UNWANTED BITS
CMP R5,R4 ;R5=GOOD,R4=?
BEQ 5$ ;BIT 14 IS OK
HLT 3 ;BIT FAILED TO CLR
5$: MOV #BIT14,R5 ;RELOAD THE BIT
MOV R5,(R3) ;WRITE BIT 14 TO THE REG
BIS #MRESET,@TXCSR ;RESET THE DEVICE
JSR PC,SMALL ;WAIT FOR RESET TO FINISH
MOV (R3),R4 ;GET BIT 14
BIT #BIT14,R4 ;TEST BIT 14 FOR RESET CLR
BEQ 7$ ;BIT 14 IS OK
HLT 3 ;BIT FAILED TO CLEAR
7$: MOV R5,(R3) ;SET BIT 14
CLR (R3) ;CLR TRANSMITTER CONTROL REGISTER
MOV (R3),R4 ;READ THE TRANSMITTER CONTROL REGISTER
CLR R5 ;SET 'EXPECTED'
BIC #BIT7,R4 ;CLEAR UNWANTED BITS
CMP R5,R4 ;R5=GOOD,R4=?
BEQ 10$ ;BIT 14 IS OK
HLT 3 ;BIT FAILED TO CLEAR
10$: SCOPE ;SCOPE THIS TEST
```

***** TEST 113 *****
TRANSMITTER CONTROL REGISTER BIT 15 READ ONLY DEVICE RESET AND CLEAR TEST
WRITE BIT 15 A ONE AND VERIFY A ZERO IS READ BACK
REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.

*
: TEST 113
*

TRANSMITTER CONTROL REGISTER READ ONLY TEST BIT 15

```
4330 020036 012737 000113 001226 TST113: MOV #113,@TSTNO
4331 020044 012737 020160 001216 MOV #TST114,NEXT
4332 020052 013703 001412 MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER
4333 020056 012705 100000 MOV #BIT15,R5 ;GET BIT 15
4334 020062 010513 MOV R5,(R3) ;WRITE BIT 15 TO TRANSMITTER CONTROL REGISTER
4335 020064 011304 MOV (R3),R4 ;READ TRANSMITTER CONTROL REGISTER BACK
4336 020066 005005 CLR R5 ;SET 'EXPECTED'
4337 020070 042704 000200 BIC #BIT7,R4 ;CLEAR UNWANTED BITS
4338 020074 020504 CMP R5,R4 ;R5=GOOD,R4=?
4339 020076 001401 BEQ 5$ ;BIT 15 IS OK
4340 020100 104003 HLT 3 ;BIT FAILED TO CLR
4341 020102 012705 100000 5$: MOV #BIT15,R5 ;RELOAD THE BIT
4342 020106 010513 MOV R5,(R3) ;WRITE BIT 15 TO THE REG
4343 020110 052777 000400 161274 BIS #MRESET,@TXCSR ;RESET THE DEVICE
4344 020116 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
4345 020122 011304 MOV (R3),R4 ;GET BIT 15
4346 020124 032704 100000 BIT #BIT15,R4 ;TEST BIT 15 FOR RESET CLR
4347 020130 001401 BEQ 7$ ;BIT 15 IS OK
4348 020132 104003 HLT 3 ;BIT FAILED TO CLEAR
4349 020134 010513 7$: MOV R5,(R3) ;SET BIT 15
4350 020136 005013 CLR (R3) ;CLR TRANSMITTER CONTROL REGISTER
4351 020140 011304 MOV (R3),R4 ;READ THE TRANSMITTER CONTROL REGISTER
4352 020142 005005 CLR R5 ;SET 'EXPECTED'
4353 020144 042704 000200 BIC #BIT7,R4 ;CLEAR UNWANTED BITS
4354 020150 020504 CMP R5,R4 ;R5=GOOD,R4=?
4355 020152 001401 BEQ 10$ ;BIT 15 IS OK
4356 020154 104003 HLT 3 ;BIT FAILED TO CLEAR
4357 020156 104400 10$: SCOPE ;SCOPE THIS TEST
```

```
4358
4359
4360 ;***** TEST 114 *****
4361 ;*TRANSMITTER BUFFER REGISTER BIT 12 READ ONLY DEVICE RESET AND CLEAR TEST
4362 ;*WRITE BIT 12 A ONE AND VERIFY A ZERO IS READ BACK
4363 ;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
4364 ;:*****
```

```
4365
4366 ;:*****
4367 ;: *
4368 ;: TEST 114
4369 ;: *
4370 ;:*****
4371 ;:*****
```

```
4372 020160 012737 000114 001226 TST114: MOV #114,@TSTNO
4373 020166 012737 020272 001216 MOV #TST115,NEXT
4374 020174 013703 001414 MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
4375 020200 012705 010000 MOV #BIT12,R5 ;GET BIT 12
4376 020204 010513 MOV R5,(R3) ;WRITE BIT 12 TO TRANSMITTER BUFFER REGISTER
4377 020206 011304 MOV (R3),R4 ;READ TRANSMITTER BUFFER REGISTER BACK
4378 020210 005005 CLR R5 ;SET 'EXPECTED'
4379 020212 020504 CMP R5,R4 ;R5=GOOD,R4=?
4380 020214 001401 BEQ 5$ ;BIT 12 IS OK
4381 020216 104003 HLT 3 ;BIT FAILED TO CLR
4382 020220 012705 010000 5$: MOV #BIT12,R5 ;RELOAD THE BIT
4383 020224 010513 MOV R5,(R3) ;WRITE BIT 12 TO THE REG
4384 020226 052777 000400 161156 BIS #MRESET,@TXCSR ;RESET THE DEVICE
4385 020234 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
```

TRANSMITTER BUFFER REGISTER READ ONLY TEST BIT 12

```
4386 020240 011304          MOV      (R3),R4          ;GET BIT 12
4387 020242 032704 010000  BIT      #BIT12,R4       ;TEST BIT 12 FOR RESET CLR
4388 020246 001401          BEQ      7$              ;BIT 12 IS OK
4389 020250 104003          HLT      3               ;BIT FAILED TO CLEAR
4390 020252 010513          7$:  MOV      R5,(R3)      ;SET BIT 12
4391 020254 005013          CLR      (R3)           ;CLR TRANSMITTER BUFFER REGISTER
4392 020256 011304          MOV      (R3),R4       ;READ THE TRANSMITTER BUFFER REGISTER
4393 020260 005005          CLR      R5             ;SET 'EXPECTED'
4394 020262 020504          CMP      R5,R4         ;R5=GOOD,R4= ?
4395 020264 001401          BEQ      10$           ;BIT 12 IS OK
4396 020266 104003          HLT      3             ;BIT FAILED TO CLEAR
4397 020270 104400          10$:  SCOPE            ;SCOPE THIS TEST
4398
4399
```

```
:***** TEST 115 *****
;*TRANSMITTER BUFFER REGISTER BIT 13 READ ONLY DEVICE RESET AND CLEAR TEST
;*WRITE BIT 13 A ONE AND VERIFY A ZERO IS READ BACK
;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
:*****
```

```
:*****
: TEST 115
:*****
```

```
4412 020272 012737 000115 001226 TST115: MOV      #115,@TSTNO
4413 020270 012737 020404 001216  MOV      #TST116,NEXT
4414 020306 013703 001414          MOV      TXDBUF,R3      ;GET THE TRANSMITTER BUFFER REGISTER
4415 020312 012705 020000          MOV      #BIT13,R5     ;GET BIT 13
4416 020316 010513          MOV      R5,(R3)       ;WRITE BIT 13 TO TRANSMITTER BUFFER REGISTER
4417 020320 011304          MOV      (R3),R4       ;READ TRANSMITTER BUFFER REGISTER BACK
4418 020322 005005          CLR      R5             ;SET 'EXPECTED'
4419 020324 020504          CMP      R5,R4         ;R5=GOOD,R4= ?
4420 020326 001401          BEQ      5$            ;BIT 13 IS OK
4421 020330 104003          HLT      3             ;BIT FAILED TO CLR
4422 020332 012705 020000          5$:  MOV      #BIT13,R5  ;RELOAD THE BIT
4423 020336 010513          MOV      R5,(R3)       ;WRITE BIT 13 TO THE REG
4424 020340 052777 000400 161044  BIS      #MRESET,@TXCSR ;RESET THE DEVICE
4425 020346 004737 005044          JSR      PC,SMALL      ;WAIT FOR RESET TO FINISH
4426 020352 011304          MOV      (R3),R4       ;GET BIT 13
4427 020354 032704 020000  BIT      #BIT13,R4       ;TEST BIT 13 FOR RESET CLR
4428 020360 001401          BEQ      7$            ;BIT 13 IS OK
4429 020362 104003          HLT      3             ;BIT FAILED TO CLEAR
4430 020364 010513          7$:  MOV      R5,(R3)      ;SET BIT 13
4431 020366 005013          CLR      (R3)           ;CLR TRANSMITTER BUFFER REGISTER
4432 020370 011304          MOV      (R3),R4       ;READ THE TRANSMITTER BUFFER REGISTER
4433 020372 005005          CLR      R5             ;SET 'EXPECTED'
4434 020374 020504          CMP      R5,R4         ;R5=GOOD,R4= ?
4435 020376 001401          BEQ      10$           ;BIT 13 IS OK
4436 020400 104003          HLT      3             ;BIT FAILED TO CLEAR
4437 020402 104400          10$:  SCOPE            ;SCOPE THIS TEST
4438
4439
```

```
:***** TEST 116 *****
;*TRANSMITTER BUFFER REGISTER BIT 14 READ ONLY DEVICE RESET AND CLEAR TEST
```

TRANSMITTER BUFFER REGISTER READ ONLY TEST BIT 14

4442 ;*WRITE BIT 14 A ONE AND VERIFY A ZERO IS READ BACK
4443 ;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
4444 ;:*****
4445

4446 :*****
4447 :*
4448 : TEST 116
4449 :*
4450 :*****
4451 :*****

```
4452 020404 012737 000116 001226 TST116: MOV #116,@TSTNO
4453 020412 012737 020516 001216 MOV #TST117,NEXT
4454 020420 013703 001414 MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
4455 020424 012705 040000 MOV #BIT14,R5 ;GET BIT 14
4456 020430 010513 MOV R5,(R3) ;WRITE BIT 14 TO TRANSMITTER BUFFER REGISTER
4457 020432 011304 MOV (R3),R4 ;READ TRANSMITTER BUFFER REGISTER BACK
4458 020434 005005 CLR R5 ;SET 'EXPECTED'
4459 020436 020504 CMP R5,R4 ;R5=GOOD,R4=?
4460 020440 001401 BEQ 5$ ;BIT 14 IS OK
4461 020442 104003 HLT 3 ;BIT FAILED TO CLR
4462 020444 012705 040000 5$: MOV #BIT14,R5 ;RELOAD THE BIT
4463 020450 010513 MOV R5,(R3) ;WRITE BIT 14 TO THE REG
4464 020452 052777 000400 160732 BIS #MRESET,@TXCSR ;RESET THE DEVICE
4465 020460 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
4466 020464 011304 MOV (R3),R4 ;GET BIT 14
4467 020466 032704 040000 BIT #BIT14,R4 ;TEST BIT 14 FOR RESET CLR
4468 020472 001401 BEQ 7$ ;BIT 14 IS OK
4469 020474 104003 HLT 3 ;BIT FAILED TO CLEAR
4470 020476 010513 7$: MOV R5,(R3) ;SET BIT 14
4471 020500 005013 CLR (R3) ;CLR TRANSMITTER BUFFER REGISTER
4472 020502 011304 MOV (R3),R4 ;READ THE TRANSMITTER BUFFER REGISTER
4473 020504 005005 CLR R5 ;SET 'EXPECTED'
4474 020506 020504 CMP R5,R4 ;R5=GOOD,R4=?
4475 020510 001401 BEQ 10$ ;BIT 14 IS OK
4476 020512 104003 HLT 3 ;BIT FAILED TO CLEAR
4477 020514 104400 10$: SCOPE ;SCOPE THIS TEST
```

4478
4479
4480 :***** TEST 117 *****
4481 ;*TRANSMITTER BUFFER REGISTER BIT 15 READ ONLY DEVICE RESET AND CLEAR TEST
4482 ;*WRITE BIT 15 A ONE AND VERIFY A ZERO IS READ BACK
4483 ;*REPEAT FOR DEVICE RESET AND CLR INSTRUCTIONS.
4484 ;:*****
4485

4486 :*****
4487 :*
4488 : TEST 117
4489 :*
4490 :*****
4491 :*****

```
4492 020516 012737 000117 001226 TST117: MOV #117,@TSTNO
4493 020524 012737 020630 001216 MOV #TST120,NEXT
4494 020532 013703 001414 MOV TXDBUF,R3 ;GET THE TRANSMITTER BUFFER REGISTER
4495 020536 012705 100000 MOV #BIT15,R5 ;GET BIT 15
4496 020542 010513 MOV R5,(R3) ;WRITE BIT 15 TO TRANSMITTER BUFFER REGISTER
4497 020544 011304 MOV (R3),R4 ;READ TRANSMITTER BUFFER REGISTER BACK
```

TRANSMITTER BUFFER REGISTER READ ONLY TEST BIT 15

```
4498 020546 005005 CLR R5 ;SET 'EXPECTED'  
4499 020550 020504 CMP R5,R4 ;R5=GOOD,R4=?  
4500 020552 001401 BEQ 5$ ;BIT 15 IS OK  
4501 020554 104003 HLT 3 ;BIT FAILED TO CLR  
4502 020556 012705 100000 5$: MOV #BIT15,R5 ;RELOAD THE BIT  
4503 020562 010513 MOV R5,(R3) ;WRITE BIT 15 TO THE REG  
4504 020564 052777 000400 160620 BIS #MRESET,@TXCSR ;RESET THE DEVICE  
4505 020572 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH  
4506 020576 011304 MOV (R3),R4 ;GET BIT 15  
4507 020600 032704 100000 BIT #BIT15,R4 ;TEST BIT 15 FOR RESET CLR  
4508 020604 001401 BEQ 7$ ;BIT 15 IS OK  
4509 020606 104003 HLT 3 ;BIT FAILED TO CLEAR  
4510 020610 010513 7$: MOV R5,(R3) ;SET BIT 15  
4511 020612 005013 CLR (R3) ;CLR TRANSMITTER BUFFER REGISTER  
4512 020614 011304 MOV (R3),R4 ;READ THE TRANSMITTER BUFFER REGISTER  
4513 020616 005005 CLR R5 ;SET 'EXPECTED'  
4514 020620 020504 CMP R5,R4 ;R5=GOOD,R4=?  
4515 020622 001401 BEQ 10$ ;BIT 15 IS OK  
4516 020624 104003 HLT 3 ;BIT FAILED TO CLEAR  
4517 020626 104400 10$: SCOPE ;SCOPE THIS TEST  
4518  
4519  
4520
```

```
;***** TEST 120 *****  
;*PARAMETER STATUS REGISTER BIT 9 WRITE ONLY DEVICE RESET AND CLEAR TEST  
;*TEST THAT BIT 9 CANNOT BE WRITTEN AND READ  
;*BACK THE SAME. READ BIT 9,COMPLEMENT IT AND WRITE IT  
;*VERIFYING THAT IT DID NOT CHANGE. WRITE BIT 9,  
;*DO A DEVICE RESET AND VERIFY THE BIT WAS CLEARED.  
;*REPEAT FOR A CLR INSTRUCTION.  
;*****
```

```
4521  
4522  
4523  
4524  
4525  
4526  
4527  
4528  
4529  
4530  
4531  
4532  
4533  
4534  
4535 020630 012737 000120 001226 TST120: MOV #120,@TSTNO  
4536 020636 012737 020756 001216 MOV #TST121,NEXT  
4537 020644 013703 001410 MOV PARCSR,R3 ;GET THE PARAMETER STATUS REGISTER  
4538 020650 012705 001000 MOV #BIT9,R5 ;GET BIT 9  
4539 020654 011305 MOV (R3),R5 ;READ THE REGISTER  
4540 020656 010504 MOV R5,R4 ;SAVE THE BIT  
4541 020660 032704 001000 BIT #BIT9,R4 ;CHECK BIT 9  
4542 020664 001401 BEQ 1$ ;BIT 9 IS OK  
4543 020666 104003 HLT 3 ;BIT FAILED TO CLEAR  
4544 020670 005104 1$: COM R4 ;REVERSE THE BIT  
4545 020672 010413 MCV R4,(R3) ;WRITE THE BIT TO THE REG  
4546 020674 011304 MOV (R3),R4 ;READ IT BACK  
4547 020676 020504 CMP R5,R4 ;R5=GOOD, R4=?  
4548 020700 001401 BEQ 3$ ;BR IF OK  
4549 020702 104003 HLT 3 ;COMPARE ERROR  
4550 020704 012705 001000 3$: MOV #BIT9,R5 ;LOAD THE BIT  
4551 020710 010513 MOV R5,(R3) ;WRITE THE BIT TO THE REG  
4552 020712 052777 000400 160472 BIS #MRESET,@TXCSR ;RESET THE DEVICE  
4553 020720 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
```

PARAMETER STATUS REGISTER WRITE ONLY TEST BIT 9

```
4554 020724 011304      MOV      (R3),R4      ;GET BIT 9
4555 020726 032704 001000  BIT      #BIT9,R4     ;TEST BIT 9 FOR 0 AFTER RESET
4556 020732 001401      BEQ      4$          ;BIT 9 IS OK
4557 020734 104003      HLT      3          ;BIT IS NOT A 0
4558 020736 010513      4$:  MOV      R5,(R3)  ;WRITE THE BIT TO THE REG
4559 020740 005013      CLR      (R3)       ;CLR THE PARAMETER STATUS REGISTER
4560 020742 011304      MOV      (R3),R4     ;GET THE PARAMETER STATUS REGISTER
4561 020744 005005      CLR      R5         ;SET 'EXPECTED'
4562 020746 020504      CMP      R5,R4      ;R5=GOOD,R4= ?
4563 020750 001401      BEQ      10$        ;BIT 9 IS OK
4564 020752 104003      HLT      3          ;BIT FAILED TO CLEAR
4565 020754 104400      10$:  SCOPE        ;SCOPE THIS TEST
```

```
:***** TEST 121 *****
;*PARAMETER STATUS REGISTER BIT 12 WRITE ONLY DEVICE RESET AND CLEAR TEST
;*TEST THAT BIT 12 CANNOT BE WRITTEN AND READ
;*BACK THE SAME. READ BIT 12,COMPLEMENT IT AND WRITE IT
;*VERIFYING THAT IT DID NOT CHANGE. WRITE BIT 12,
;*DO A DEVICE RESET AND VERIFY THE BIT WAS CLEARED.
;*REPEAT FOR A CLR INSTRUCTION.
:*****
```

```
:*****
: TEST 121
:*****
```

```
4583 020756 012737 000121 001226 TST121: MOV      #121,@TSTNO
4584 020764 012737 021104 001216      MOV      #TST122,NEXT
4585 020772 013703 001410      MOV      PARCSR,R3   ;GET THE PARAMETER STATUS REGISTER
4586 020776 012705 010000      MOV      #BIT12,R5   ;GET BIT 12
4587 021002 011305      MOV      (R3),R5     ;READ THE REGISTER
4588 021004 010504      MOV      R5,R4      ;SAVE THE BIT
4589 021006 032704 010000      BIT      #BIT12,R4   ;CHECK BIT 12
4590 021012 001401      BEQ      1$          ;BIT 12 IS OK
4591 021014 104003      HLT      3          ;BIT FAILED TO CLEAR
4592 021016 005104      1$:  COM      R4      ;REVERSE THE BIT
4593 021020 010413      MOV      R4,(R3)    ;WRITE THE BIT TO THE REG
4594 021022 011304      MOV      (R3),R4     ;READ IT BACK
4595 021024 020504      CMP      R5,R4      ;R5=GOOD, R4= ?
4596 021026 001401      BEQ      3$          ;BR IF OK
4597 021030 104003      HLT      3          ;COMPARE ERROR
4598 021032 012705 010000      3$:  MOV      #BIT12,R5 ;LOAD THE BIT
4599 021036 010513      MOV      R5,(R3)    ;WRITE THE BIT TO THE REG
4600 021040 052777 000400 160344  BIS      #MRESET,@TXCSR ;RESET THE DEVICE
4601 021046 004737 005044      JSR      PC,SMALL   ;WAIT FOR RESET TO FINISH
4602 021052 011304      MOV      (R3),R4     ;GET BIT 12
4603 021054 032704 010000      BIT      #BIT12,R4   ;TEST BIT 12 FOR 0 AFTER RESET
4604 021060 001401      BEQ      4$          ;BIT 12 IS OK
4605 021062 104003      HLT      3          ;BIT IS NOT A 0
4606 021064 010513      4$:  MOV      R5,(R3)  ;WRITE THE BIT TO THE REG
4607 021066 005013      CLR      (R3)       ;CLR THE PARAMETER STATUS REGISTER
4608 021070 011304      MOV      (R3),R4     ;GET THE PARAMETER STATUS REGISTER
4609 021072 005005      CLR      R5         ;SET 'EXPECTED'
```

PARAMETER STATUS REGISTER WRITE ONLY TEST BIT 12

```
4610 021074 020504          CMP    R5,R4          ;R5=GOOD,R4= ?
4611 021076 001401          BEQ    10$            ;BIT 12 IS OK
4612 021100 104003          HLT    3              ;BIT FAILED TO CLEAR
4613 021102 104400          10$:  SCOPE          ;SCOPE THIS TEST
4614
4615
4616
```

```
***** TEST 122 *****
;*PARAMETER STATUS REGISTER BIT 15 WRITE ONLY DEVICE RESET AND CLEAR TEST
;*TEST THAT BIT 15 CANNOT BE WRITTEN AND READ
;*BACK THE SAME. READ BIT 15, COMPLEMENT IT AND WRITE IT
;*VERIFYING THAT IT DID NOT CHANGE. WRITE BIT 15,
;*DO A DEVICE RESET AND VERIFY THE BIT WAS CLEARED.
;*REPEAT FOR A CLR INSTRUCTION.
*****
```

```
*****
*
* TEST 122
*
*****
```

```
*****
*****
4631 021104 012737 000122 001226 TST122: MOV    #122,@TSTNO
4632 021112 012737 021232 001216      MOV    #TST123,NEXT
4633 021120 013703 001410          MOV    PARCSR,R3      ;GET THE PARAMETER STATUS REGISTER
4634 021124 012705 100000          MOV    #BIT15,R5      ;GET BIT 15
4635 021130 011305          MOV    (R3),R5        ;READ THE REGISTER
4636 021132 010504          MOV    R5,R4          ;SAVE THE BIT
4637 021134 032704 100000          BIT    #BIT15,R4      ;CHECK BIT 15
4638 021140 001401          BEQ    1$              ;BIT 15 IS OK
4639 021142 104003          HLT    3              ;BIT FAILED TO CLEAR
4640 021144 005104          1$:  COM    R4          ;REVERSE THE BIT
4641 021146 010413          MOV    R4,(R3)        ;WRITE THE BIT TO THE REG
4642 021150 011304          MOV    (R3),R4        ;READ IT BACK
4643 021152 020504          CMP    R5,R4          ;R5=GOOD, R4= ?
4644 021154 001401          BEQ    3$              ;BR IF OK
4645 021156 104003          HLT    3              ;COMPARE ERROR
4646 021160 012705 100000          3$:  MOV    #BIT15,R5   ;LOAD THE BIT
4647 021164 010513          MOV    R5,(R3)        ;WRITE THE BIT TO THE REG
4648 021166 052777 000400 160216      BIS    #MRESET,@TXCSR ;RESET THE DEVICE
4649 021174 004737 005044          JSR    PC,SMALL       ;WAIT FOR RESET TO FINISH
4650 021200 011304          MOV    (R3),R4        ;GET BIT 15
4651 021202 032704 100000          BIT    #BIT15,R4      ;TEST BIT 15 FOR 0 AFTER RESET
4652 021206 001401          BEQ    4$              ;BIT 15 IS OK
4653 021210 104003          HLT    3              ;BIT IS NOT A 0
4654 021212 010513          4$:  MOV    R5,(R3)        ;WRITE THE BIT TO THE REG
4655 021214 005013          CLR    (R3)           ;CLR THE PARAMETER STATUS REGISTER
4656 021216 011304          MOV    (R3),R4        ;GET THE PARAMETER STATUS REGISTER
4657 021220 005005          CLR    R5             ;SET 'EXPECTED'
4658 021222 020504          CMP    R5,R4          ;R5=GOOD,R4= ?
4659 021224 001401          BEQ    10$            ;BIT 15 IS OK
4660 021226 104003          HLT    3              ;BIT FAILED TO CLEAR
4661 021230 104400          10$:  SCOPE          ;SCOPE THIS TEST
4662
4663
4664
4665
```

```
***** TEST 123 *****
;*TRANSMITTER CONTROL REGISTER BIT 8 WRITE ONLY DEVICE RESET AND CLEAR TEST
```

TRANSMITTER CONTROL REGISTER WRITE ONLY TEST BIT 8

4666
4667
4668
4669
4670
4671
4672
4673
4674
4675
4676
4677
4678
4679
4680
4681
4682
4683
4684
4685
4686
4687
4688
4689
4690
4691
4692
4693
4694
4695
4696
4697
4698
4699
4700
4701
4702
4703
4704
4705
4706
4707
4708
4709
4710
4711
4712
4713
4714
4715
4716
4717
4718
4719
4720
4721

;*TEST THAT BIT 8 CANNOT BE WRITTEN AND READ
;*BACK THE SAME. READ BIT 8, COMPLEMENT IT AND WRITE IT
;*VERIFYING THAT IT DID NOT CHANGE. WRITE BIT 8,
;*DO A DEVICE RESET AND VERIFY THE BIT WAS CLEARED.
;*REPEAT FOR A CLR INSTRUCTION.
:*****

:*****
: TEST 123
:*****

```
TST123: MOV #123, @TSTNO  
MOV #TST124, NEXT  
MOV TXCSR, R3 ;GET THE TRANSMITTER CONTROL REGISTER  
MOV #BIT7, R5 ;SET EXPECTED BIT  
MOV (R3), R4 ;READ THE REGISTER  
BIT #BIT8, R4 ;CHECK BIT 8  
BEQ 1$ ;BIT 8 IS OK  
HLT 3 ;BIT FAILED TO CLEAR  
1$: COM R4 ;REVERSE THE BIT  
MOV R4, (R3) ;WRITE THE BIT TO THE REG  
JSR PC, SMALL ;WAIT FOR DEVICE RESET TO FINISH  
MOV (R3), R4 ;READ IT BACK  
CMP R5, R4 ;R5=GOOD, R4= ?  
BEQ 3$ ;BR IF OK  
HLT 3 ;COMPARE ERROR  
3$: MOV #BIT8, R4 ;LOAD THE BIT  
MOV R4, (R3) ;WRITE THE BIT TO THE REG  
BIS #MRESET, @TXCSR ;RESET THE DEVICE  
JSR PC, SMALL ;WAIT FOR RESET TO FINISH  
MOV (R3), R4 ;GET BIT 8  
BIT #BIT8, R4 ;TEST BIT 8 FOR 0 AFTER RESET  
BEQ 4$ ;BIT 8 IS OK  
HLT 3 ;BIT IS NOT A 0  
4$: MOV #BIT8, R4 ;LOAD THE BIT  
MOV R4, (R3) ;WRITE THE BIT TO THE REG  
CLR (R3) ;CLR THE TRANSMITTER CONTROL REGISTER  
MOV (R3), R4 ;GET THE TRANSMITTER CONTROL REGISTER  
CMP R5, R4 ;R5=GOOD, R4= ?  
BEQ 10$ ;BIT 8 IS OK  
HLT 3 ;BIT FAILED TO CLEAR  
10$: SCOPE ;SCOPE THIS TEST
```

:***** TEST 124 *****
;*RECEIVER CONTROL REGISTER READ/WRITE BIT TEST.
;*SET BIT8, VERIFY BIT8 WAS SET.
;*CLEAR BIT8, VERIFY BIT8 WAS CLEARED.
:*****

:*****
: TEST 124
:*****

RECEIVER CONTROL REGISTER READ/WRITE TEST BIT 8

```
4722 ;:*****
4723 ;:*****
4724 021364 012737 000124 001226 TST124: MOV #124,@TSTNO
4725 021372 012737 021440 001216 MOV #TST125,NEXT
4726 021400 013703 001404 MOV RXCSR,R3 ;SET REGISTER TO BE TESTED.
4727 021404 012705 000400 MOV #BIT8,R5 ;SET 'EXPECTED'
4728 021410 010513 MOV R5,(R3) ;WRITE THE REGISTER.
4729 021412 011304 MOV (R3),R4 ;READ THE REGISTER.
4730 021414 020504 CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.
4731 021416 001401 BEQ 1$ ;ARE THEY THE SAME?
4732 021420 104003 HLT 3 ;COMPARISON ERROR.
4733 021422 040513 1$: BIC R5,(R3) ;CLEAR BIT8
4734 021424 011304 MOV (R3),R4 ;READ THE REGISTER.
4735 021426 005005 CLR R5 ;SET 'EXPECTED'
4736 021430 020504 CMP R5,R4 ;R5=GOOD; R4=?
4737 021432 001401 BEQ 2$ ;BR IF OK
4738 021434 104003 HLT 3 ;COMPARISON ERROR
4739 021436 104400 2$: SCOPE ;SCOPE THIS TEST
4740
4741
4742 ;:***** TEST 125 *****
4743 ;*RECEIVER CONTROL REGISTER READ/WRITE BIT TEST.
4744 ;*SET BIT6, VERIFY BIT6 WAS SET.
4745 ;*CLEAR BIT6, VERIFY BIT6 WAS CLEARED.
4746 ;:*****
4747
4748 ;:*****
4749 ; *
4750 ; TEST 125
4751 ; *
4752 ;:*****
4753 ;:*****
```

```
4754 021440 012737 000125 001226 TST125: MOV #125,@TSTNO
4755 021446 012737 021514 001216 MOV #TST126,NEXT
4756 021454 013703 001404 MOV RXCSR,R3 ;SET REGISTER TO BE TESTED.
4757 021460 012705 000100 MOV #BIT6,R5 ;SET 'EXPECTED'
4758 021464 010513 MOV R5,(R3) ;WRITE THE REGISTER.
4759 021466 011304 MOV (R3),R4 ;READ THE REGISTER.
4760 021470 020504 CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.
4761 021472 001401 BEQ 1$ ;ARE THEY THE SAME?
4762 021474 104003 HLT 3 ;COMPARISON ERROR.
4763 021476 040513 1$: BIC R5,(R3) ;CLEAR BIT6
4764 021500 011304 MOV (R3),R4 ;READ THE REGISTER.
4765 021502 005005 CLR R5 ;SET 'EXPECTED'
4766 021504 020504 CMP R5,R4 ;R5=GOOD; R4=?
4767 021506 001401 BEQ 2$ ;BR IF OK
4768 021510 104003 HLT 3 ;COMPARISON ERROR
4769 021512 104400 2$: SCOPE ;SCOPE THIS TEST
4770
4771
4772 ;:***** TEST 126 *****
4773 ;*RECEIVER CONTROL REGISTER READ/WRITE BIT TEST.
4774 ;*SET BIT5, VERIFY BIT5 WAS SET.
4775 ;*CLEAR BIT5, VERIFY BIT5 WAS CLEARED.
4776 ;:*****
4777
```


RECEIVER CONTROL REGISTER READ/WRITE TEST BIT 5

4778
4779
4780
4781
4782
4783
4784
4785
4786
4787
4788
4789
4790
4791
4792
4793
4794
4795
4796
4797
4798
4799
4800
4801
4802
4803
4804
4805
4806
4807
4808
4809
4810
4811
4812
4813
4814
4815
4816
4817
4818
4819
4820
4821
4822
4823
4824
4825
4826
4827
4828
4829
4830
4831
4832
4833

```
*****  
: TEST 126  
*****  
*****  
TST126: MOV #126, @TSTNO  
MOV #TST127, NEXT  
MOV RXCSR, R3 ;SET REGISTER TO BE TESTED.  
MOV #BIT5, R5 ;SET 'EXPECTED'  
MOV R5, (R3) ;WRITE THE REGISTER.  
MOV (R3), R4 ;READ THE REGISTER.  
CMP R5, R4 ;R5=GOOD; R4=UNKNOWN.  
BEQ 1$ ;ARE THEY THE SAME?  
HLT 3 ;COMPARISON ERROR.  
1$: BIC R5, (R3) ;CLEAR BIT5  
MOV (R3), R4 ;READ THE REGISTER.  
CLR R5 ;SET 'EXPECTED'  
CMP R5, R4 ;R5=GOOD; R4=?  
BEQ 2$ ;BR IF OK  
HLT 3 ;COMPARISON ERROR  
2$: SCOPE ;SCOPE THIS TEST
```

***** TEST 127 *****
*RECEIVER CONTROL REGISTER READ/WRITE BIT TEST.
*SET BIT4, VERIFY BIT4 WAS SET.
*CLEAR BIT4, VERIFY BIT4 WAS CLEARED.

```
*****  
: TEST 127  
*****  
*****  
TST127: MOV #127, @TSTNO  
MOV #TST130, NEXT  
MOV RXCSR, R3 ;SET REGISTER TO BE TESTED.  
MOV #BIT4, R5 ;SET 'EXPECTED'  
MOV R5, (R3) ;WRITE THE REGISTER.  
MOV (R3), R4 ;READ THE REGISTER.  
CMP R5, R4 ;R5=GOOD; R4=UNKNOWN.  
BEQ 1$ ;ARE THEY THE SAME?  
HLT 3 ;COMPARISON ERROR.  
1$: BIC R5, (R3) ;CLEAR BIT4  
MOV (R3), R4 ;READ THE REGISTER.  
CLR R5 ;SET 'EXPECTED'  
CMP R5, R4 ;R5=GOOD; R4=?  
BEQ 2$ ;BR IF OK  
HLT 3 ;COMPARISON ERROR  
2$: SCOPF ;SCOPE THIS TEST
```

***** TEST 130 *****
*TRANSMITTER CONTROL REGISTER READ/WRITE BIT TEST.

```

4834 ;*SET BIT6, VERIFY BIT6 WAS SET.
4835 ;*CLEAR BIT6, VERIFY BIT6 WAS CLEARED.
4836 ;:*****
4837
4838 ;:*****
4839 ;:
4840 ; TEST 130
4841 ;:
4842 ;:*****
4843 ;:*****

```

```

4844 021644 012737 000130 001226 TST130: MOV #130,@TSTNO
4845 021652 012737 021730 001216 MOV #TST131,NEXT
4846 021660 013703 001412 MOV TXCSR,R3 ;SET REGISTER TO BE TESTED.
4847 021664 012705 000100 MOV #BIT6,R5 ;SET 'EXPECTED'
4848 021670 010513 MOV R5,(R3) ;WRITE THE REGISTER.
4849 021672 011304 MOV (R3),R4 ;READ THE REGISTER.
4850 021674 042704 000200 BIC #BIT7,R4 ;CLEAR UNWANTED BITS
4851 021700 020504 CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.
4852 021702 001401 BEQ 1$ ;ARE THEY THE SAME?
4853 021704 104003 HLT 3 ;COMPARISON ERROR.
4854 021706 040513 1$: BIC R5,(R3) ;CLEAR BIT6
4855 021710 011304 MOV (R3),R4 ;READ THE REGISTER.
4856 021712 042704 000200 BIC #BIT7,R4 ;CLEAR UNWANTED BITS
4857 021716 005005 CLR R5 ;SET 'EXPECTED'
4858 021720 020504 CMP R5,R4 ;R5=GOOD; R4=?
4859 021722 001401 BEQ 2$ ;BR IF OK
4860 021724 104003 HLT 3 ;COMPARISON ERROR
4861 021726 104400 2$: SCOPE ;SCOPE THIS TEST
4862
4863

```

```

4864 ;:***** TEST 131 *****
4865 ;*RECEIVER CONTROL REGISTER READ/WRITE BIT TEST.
4866 ;*SET BIT1, VERIFY BIT1 WAS SET.
4867 ;*CLEAR BIT1, VERIFY BIT1 WAS CLEARED.
4868 ;:*****
4869

```

```

4870 ;:*****
4871 ;:
4872 ; TEST 131
4873 ;:
4874 ;:*****
4875 ;:*****
4876 021730 012737 000131 001226 TST131: MOV #131,@TSTNO
4877 021736 012737 022014 001216 MOV #TST132,NEXT
4878 021744 013703 001404 MOV RXCSR,R3 ;SET REGISTER TO BE TESTED.
4879 021750 012705 000002 MOV #BIT1,R5 ;SET 'EXPECTED'
4880 021754 010513 MOV R5,(R3) ;WRITE THE REGISTER.
4881 021756 011304 MOV (R3),R4 ;READ THE REGISTER.
4882 021760 042704 1770C1 BIC #177001,R4 ;CLEAR UNWANTED BITS
4883 021764 020504 CMP R5,R4 ;R5=GOOD; R4=UNKNOWN.
4884 021766 001401 BEQ 1$ ;ARE THEY THE SAME?
4885 021770 104003 HLT 3 ;COMPARISON ERROR.
4886 021772 040513 1$: BIC R5,(R3) ;CLEAR BIT1
4887 021774 011304 MOV (R3),R4 ;READ THE REGISTER.
4888 021776 042704 177001 BIC #177001,R4 ;CLEAR UNWANTED BITS
4889 0220C2 005005 CLR R5 ;SET 'EXPECTED'

```

RECEIVER CONTROL REGISTER READ/WRITE TEST BIT 1

```

4890 022004 020504      CMP    R5,R4      ;R5=GOOD; R4=?
4891 022006 001401      BEQ    2$         ;BR IF OK
4892 022010 104003      HLT    3          ;COMPARISON ERROR
4893 022012 104400      2$:  SCOPE       ;SCOPE THIS TEST
4894
4895

```

```

:***** TEST 132 *****
:*RECEIVER CONTROL REGISTER READ/WRITE BIT TEST.
:*SET BIT2, VERIFY BIT2 WAS SET.
:*CLEAR BIT2, VERIFY BIT2 WAS CLEARED.
:*****

```

```

:*****
: *
: TEST 132
: *
:*****

```

```

4907
4908 022014 012737 000132 001226 TST132: MOV    #132,@TSTNO
4909 022022 012737 022100 001216      MOV    #TST133,NEXT
4910 022030 013703 001404      MOV    RXCSR,R3      ;SET REGISTER TO BE TESTED.
4911 022034 012705 000004      MOV    #BIT2,R5      ;SET 'EXPECTED'
4912 022040 010513      MOV    R5,(R3)       ;WRITE THE REGISTER.
4913 022042 011304      MOV    (R3),R4       ;READ THE REGISTER.
4914 022044 042704 177001      BIC    #177001,R4    ;CLEAR UNWANTED BITS
4915 022050 020504      CMP    R5,R4         ;R5=GOOD; R4=UNKNOWN.
4916 022052 001401      BEQ    1$           ;ARE THEY THE SAME?
4917 022054 104003      HLT    3            ;COMPARISON ERROR.
4918 022056 040513      1$:  BIC    R5,(R3)    ;CLEAR BIT2
4919 022060 011304      MOV    (R3),R4       ;READ THE REGISTER.
4920 022062 042704 177001      BIC    #177001,R4    ;CLEAR UNWANTED BITS
4921 022066 005005      CLR    R5            ;SET 'EXPECTED'
4922 022070 020504      CMP    R5,R4         ;R5=GOOD; R4=?
4923 022072 001401      BEQ    2$           ;BR IF OK
4924 022074 104003      HLT    3            ;COMPARISON ERROR
4925 022076 104400      2$:  SCOPE       ;SCOPE THIS TEST
4926
4927

```

```

:***** TEST 133 *****
:*RECEIVER CONTROL REGISTER READ/WRITE BIT TEST.
:*SET BIT3, VERIFY BIT3 WAS SET.
:*CLEAR BIT3, VERIFY BIT3 WAS CLEARED.
:*****

```

```

:*****
: *
: TEST 133
: *
:*****

```

```

4939
4940 022100 012737 000133 001226 TST133: MOV    #133,@TSTNO
4941 022106 012737 022164 001216      MOV    #TST134,NEXT
4942 022114 013703 001404      MOV    RXCSR,R3      ;SET REGISTER TO BE TESTED.
4943 022120 012705 000010      MOV    #BIT3,R5      ;SET 'EXPECTED'
4944 022124 010513      MOV    R5,(R3)       ;WRITE THE REGISTER.
4945 022126 011304      MOV    (R3),R4       ;READ THE REGISTER.

```

RECEIVER CONTROL REGISTER READ/WRITE TEST BIT 3

```
4946 022130 042704 177001      BIC    #177001,R4      ;CLEAR UNWANTED BITS
4947 022134 020504              CMP    R5,R4          ;R5=GOOD; R4=UNKNOWN.
4948 022136 001401              BEQ    1$             ;ARE THEY THE SAME?
4949 022140 104003              HLT    3              ;COMPARISON ERROR.
4950 022142 040513      1$:    BIC    R5,(R3)      ;CLEAR BIT3
4951 022144 011304              MOV    (R3),R4        ;READ THE REGISTER.
4952 022146 042704 177001      BIC    #177001,R4      ;CLEAR UNWANTED BITS
4953 022152 005005              CLR    R5             ;SET 'EXPECTED'
4954 022154 020504              CMP    R5,R4          ;R5-GOOD; R4=?
4955 022156 001401              BEQ    2$             ;BR IF OK
4956 022160 104003              HLT    3              ;COMPARISON ERROR
4957 022162 104400      2$:    SCOPE          ;SCOPE THIS TEST
```

```
***** TEST 134 *****
;*RECEIVER CONTROL REGISTER READ/WRITE BIT 6 RESET AND CLEAR TEST
;*WRITE BIT 6,AND TEST THAT IT WILL BE CLEARED AFTER A
;*DEVICE RESET AND RECEIVER CONTROL REGISTER CLR INSTRUCTION
*****
```

```
*****
:
: TEST 134
:
: *****
```

```
4972 022164 012737 000134 001226 TST134: MOV    #134,@TSTNO
4973 022172 012737 022260 001216      MOV    #TST135,NEXT
4974 022200 013703 001404              MOV    RXCSR,R3      ;GET THE RECEIVER CONTROL REGISTER
4975 022204 052713 000100              BIS    #BIT6,(R3)    ;SET BIT 6 AT RECEIVER CONTROL REGISTER
4976 022210 005005              CLR    R5             ;SET 'EXPECTED'
4977 022212 052777 000400 157172      BIS    #MRESET,@TXCSR ;RESET THE DEVICE
4978 022220 004737 005044              JSR    PC,SMALL      ;WAIT FOR RESET TO FINISH
4979 022224 032713 000100              BIT    #BIT6,(R3)    ;TEST BIT 6
4980 022230 001402              BEQ    1$             ;BIT 6 IS CLEARED
4981 022232 011304              MOV    (R3),R4        ;LOAD 'FOUND'
4982 022234 104003              HLT    3              ;BIT 6 IS SET AND SHOULDN'T BE
4983 022236 052713 000100      1$:    BIS    #BIT6,(R3) ;SET BIT 6 AGAIN
4984 022242 005013              CLR    (R3)           ;CLEAR THE RECEIVER CONTROL REGISTER
4985 022244 032713 000100              BIT    #BIT6,(R3)    ;TEST TO SEE IF BIT 6 CLEARED
4986 022250 001402              BEQ    2$             ;BIT 6 IS OK
4987 022252 011304              MOV    (R3),R4        ;LOAD 'FOUND'
4988 022254 104003              HLT    3              ;BIT 6 FAILED TO CLEAR
4989 022256 104400      2$:    SCOPE          ;SCOPE THIS TEST
```

```
***** TEST 135 *****
;*RECEIVER CONTROL REGISTER READ/WRITE BIT 5 RESET AND CLEAR TEST
;*WRITE BIT 5,AND TEST THAT IT WILL BE CLEARED AFTER A
;*DEVICE RESET AND RECEIVER CONTROL REGISTER CLR INSTRUCTION
*****
```

```
*****
:
: TEST 135
:
: *****
```

5000
5001

RECEIVER CONTROL REGISTER RESET AND CLEAR TEST BIT 5

```
5002      ::*****  
5003      ::*****  
5004 022260 012737 000135 001226 TST135: MOV #135,@TSTNO  
5005 022266 012737 022354 001216      MOV #TST136,NEXT  
5006 022274 013703 001404      MOV RXCSR,R3 ;GET THE RECEIVER CONTROL REGISTER  
5007 022300 052713 000040      BIS #BIT5,(R3) ;SET BIT 5 AT RECEIVER CONTROL REGISTER  
5008 022304 005005      CLR R5 ;SET 'EXPECTED'  
5009 022306 052777 000400 157076      BIS #MRESET,@TXCSR ;RESET THE DEVICE  
5010 022314 004737 005044      JSR PC,SMALL ;WAIT FOR RESET TO FINISH  
5011 022320 032713 000040      BIT #BIT5,(R3) ;TEST BIT 5  
5012 022324 001402      BEQ 1$ ;BIT 5 IS CLEARED  
5013 022326 011304      MOV (R3),R4 ;LOAD 'FOUND'  
5014 022330 104003      HLT 3 ;BIT 5 IS SET AND SHOULDN'T BE  
5015 022332 052713 000040 1$: BIS #BIT5,(R3) ;SET BIT 5 AGAIN  
5016 022336 005013      CLR (R3) ;CLEAR THE RECEIVER CONTROL REGISTER  
5017 022340 032713 000040      BIT #BIT5,(R3) ;TEST TO SEE IF BIT 5 CLEARED  
5018 022344 001402      BEQ 2$ ;BIT 5 IS OK  
5019 022346 011304      MOV (R3),R4 ;LOAD 'FOUND'  
5020 022350 104003      HLT 3 ;BIT 5 FAILED TO CLEAR  
5021 022352 104400 2$: SCOPE ;SCOPE THIS TEST
```

```
::***** TEST 136 *****  
;*TRANSMITTER CONTROL REGISTER READ/WRITE BIT 6 RESET AND CLEAR TEST  
;*WRITE BIT 6,AND TEST THAT IT WILL BE CLEARED AFTER A  
;*DEVICE RESET AND TRANSMITTER CONTROL REGISTER CLR INSTRUCTION  
::*****
```

```
5022  
5023  
5024      ::*****  
5025      : *TEST 136 *  
5026      : *TEST 136 *  
5027      : *TEST 136 *  
5028      : *TEST 136 *  
5029      : *TEST 136 *  
5030      : *TEST 136 *  
5031      : *TEST 136 *  
5032      : *TEST 136 *  
5033      : *TEST 136 *  
5034      : *TEST 136 *  
5035      : *TEST 136 *  
5036 022354 012737 000136 001226 TST136: MOV #136,@TSTNO  
5037 022362 012737 022450 001216      MOV #TST137,NEXT  
5038 022370 013703 001412      MOV TXCSR,R3 ;GET THE TRANSMITTER CONTROL REGISTER  
5039 022374 052713 000100      BIS #BIT6,(R3) ;SET BIT 6 AT TRANSMITTER CONTROL REGISTER  
5040 022400 005005      CLR R5 ;SET 'EXPECTED'  
5041 022402 052777 000400 157002      BIS #MRESET,@TXCSR ;RESET THE DEVICE  
5042 022410 004737 005044      JSR PC,SMALL ;WAIT FOR RESET TO FINISH  
5043 022414 032713 000100      BIT #BIT6,(R3) ;TEST BIT 6  
5044 022420 001402      BEQ 1$ ;BIT 6 IS CLEARED  
5045 022422 011304      MOV (R3),R4 ;LOAD 'FOUND'  
5046 022424 104003      HLT 3 ;BIT 6 IS SET AND SHOULDN'T BE  
5047 022426 052713 000100 1$: BIS #BIT6,(R3) ;SET BIT 6 AGAIN  
5048 022432 005013      CLR (R3) ;CLEAR THE TRANSMITTER CONTROL REGISTER  
5049 022434 032713 000100      BIT #BIT6,(R3) ;TEST TO SEE IF BIT 6 CLEARED  
5050 022440 001402      BEQ 2$ ;BIT 6 IS OK  
5051 022442 011304      MOV (R3),R4 ;LOAD 'FOUND'  
5052 022444 104003      HLT 3 ;BIT 6 FAILED TO CLEAR  
5053 022446 104400 2$: SCOPE ;SCOPE THIS TEST
```

```
::***** TEST 137 *****  
;*THIS TEST CHECKS THE MAINTENANCE CLOCK
```

5054
5055
5056
5057

```
5058                                     ;*USED THROUGHOUT THE REMAINING DIAGNOSTICS
5059                                     ;:*****
5060
5061                                     ;:*****
5062                                     ;*
5063                                     ;: TEST 137
5064                                     ;*
5065                                     ;:*****
5066                                     ;:*****
5067 022450 012737 000137 001226 TST137: MOV #137,@TSTNO
5068 022456 012737 022604 001216      MOV #TST140,NEXT
5069 022464 052777 000400 156720      BIS #MRESET,@TXCSR ;RESET THE DEVICE
5070 022472 004737 005044              JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5071 022476 005037 001236              CLR TEMP1 ;TEST TIM SETUP
5072 022502 052777 004000 156702      BIS #SYSTST,@TXCSR ;ENTER SYSTEM TST MODE TO TURN ON CLOCK
5073 022510 032777 004000 156676 1$: BIT #TIMER,@TXDBUF ;CHECK THE CLOCK BIT
5074 022516 001407                    BEQ 2$ ;BR IF OFF
5075 022520 005237 001236              INC TEMP1 ;INC WAIT LOOP
5076 022524 022737 177777 001236      CMP #-1,TEMP1 ;CHECK FOR LOOP TO BE DONE
5077 022532 001366                    BNE 1$ ;BR IF MORE TIME TO WAIT
5078 022534 104000                    HLT ;TIMER CLOCK BIT FAILED TO CLEAR
5079 022536 005037 001236 2$: CLR TEMP1 ;SECOND HALF SETUP
5080 022542 032777 004000 156644 3$: BIT #TIMER,@TXDBUF ;CHECK THE CLOCK BIT
5081 022550 001007                    BNE 4$ ;BR IF ON
5082 022552 005237 001236              INC TEMP1 ;INC THE WAIT LOOP
5083 022556 022737 177777 001236      CMP #-1,TEMP1 ;CHECK FOR LOPP DONE
5084 022564 001366                    BNE 3$ ;BR IF MORE TIME TO WAIT
5085 022566 104000                    HLT ;TIMER BIT FAILED TO SET
5086 022570
5087 022570 052777 000400 156614 4$: BIS #MRESET,@TXCSR ;RESET THE DEVICE
5088 022576 004737 005044              JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5089 022602 104400                    SCOPE ;SCOPE THIS TEST
5090
5091
5092
5093                                     ;***** TEST 140 *****
5094                                     ;*THIS TEST WILL PERFORM STATIC TRANSMITTER FUNCTIONS
5095                                     ;*IN MAINTENANCE MODE. IT WILL PROVE THE INTERACTION
5096                                     ;*OF SEND, DONE AND TSOM.
5097                                     ;:*****
5098
5099                                     ;:*****
5100                                     ;*
5101                                     ;: TEST 140
5102                                     ;*
5103                                     ;:*****
5104                                     ;:*****
5105 022604 012737 000140 001226 TST140: MOV #140,@TSTNO
5106 022612 012737 022760 001216      MOV #TST141,NEXT
5107 022620 013.02 001414              MOV TXDBUF,R2 ;LOAD TX BUFFER
5108 022624 013703 001412              MOV TXCSR,R3 ;LOAD TX CONTROL REGISTER
5109 022630 005012                    CLR (R2) ;CLEAR BUFFER
5110 022632 052777 000400 156552      BIS #MRESET,@TXCSR ;RESET THE DEVICE
5111 022640 004737 005044              JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5112 022644 052777 001000 156536      BIS #CRCEN,@PARCSR ;TURN OFF CRC
5113 022652 052713 014000              BIS #MODE,(R3) ;ENTER M/M - PROGRAM NOW CLOCKING
```

STATIC TEST OF SEND,DONE AND TSOM

```
5114 022656 052713 000020      BIS      #SEND,(R3)      ;ASSERT SEND
5115 022662 052705 014220      BIS      #SEND.TXDONE!MMODE,R5 ;SET 'EXPECTED'
5116 022666 011304      MOV      (R3),R4      ;READ TX CONTROL REGISTER
5117 022670 020504      CMP      R5,R4        ;ARE THEY EQUAL?
5118 022672 001401      BEQ      1$          ;BR IF YES
5119 022674 104003      HLT      3           ;NO
5120 022676 005005      1$:     CLR      R5          ;'SET EXPECTED'
5121 022700 011204      MOV      (R2),R4      ;READ TX BUFFER
5122 022702 042704 170000      BIC      #170000,R4    ;MASK
5123 022706 020504      CMP      R5,R4        ;R5=GOOD, R4=?
5124 022710 001405      BEQ      2$          ;ARE THEY EQUAL?
5125 022712 013703 001414      MOV      TXDBUF,R3    ;ERROR MESSAGE SETUP
5126 022716 104003      HLT      3           ;NO
5127 022720 013703 001412      MOV      TXCSR,R3     ;RETURN TO NORMAL
5128 022724 010512      2$:     MOV      R5,(R2)    ;LOAD BUFFER
5129 022726 032713 000200      BIT      #TXDONE,(R3) ;TEST DONE
5130 022732 001401      BCC      3$          ;
5131 022734 104005      HLT      5           ;BIT FAILED TO CLR
5132 022736 052712 000400      3$:     BIS      #TSOM,(R2) ;SET TSOM
5133 022742 104412 000017      PKCLK    ,15.
5134 022746 032713 000200      BIT      #TXDONE,(R3) ;TEST DONE
5135 022752 001001      BNE      4$          ;
5136 022754 104006      HLT      6           ;BIT FAILED TO SET
5137 022756 104400      4$:     SCOPE          ;SCOPE THIS TEST
```

5138
5139
5140
5141
5142
5143
5144
5145

```
***** TEST 141 *****  
*THIS TEST CHECKS THE STATIC FUNCTIONS OF THE TRANSMITTER  
*IN MAINTENANCE MODE. THIS TEST PROVES THE INTERACTION OF  
*TXDBUF, TXACT, TSOM, TRANSMITTED DATA AND DONE.  
*****
```

5146
5147
5148
5149
5150
5151

```
*****  
*  
* TEST 141  
*  
*****
```

```
5152 022760 012737 000141 001226 TST141: MOV      #141,@TSTNO
5153 022766 012737 023274 001216      MOV      #TST142,NEXT
5154 022774 013703 001412      MOV      TXCSR,R3     ;LOAD CONTROL REGISTER
5155 023000 013702 001414      MOV      TXDBUF,R2    ;LOAD BUFFER
5156 023004 052777 000400 156400      BIS      #MRESET,@TXCSR ;RESET THE DEVICE
5157 023012 004737 005044      JSR      PC,SMALL    ;WAIT FOR RESET TO FINISH
5158 023016 005012      CLR      (R2)        ;RESET TXDONE
5159 023020 052713 014000      BIS      #MMODE,(R3) ;ENTER M/M--PROGRAM CLOCKING
5160 023024 052777 001000 156356      BIS      #CRCEN,@PARCSR ;TURN OFF CRC
5161 023032 052713 000020      BIS      #SEND,(R3)  ;SET SEND
5162 023036 005005      CLR      R5          ;SET 'EXPECTED'
5163 023040 010512      MOV      R5,(R2)     ;LOAD TX BUFFER
5164 023042 012712 000400      MOV      #TSOM,(R2)  ;TURN ON TSOM
5165 023046 104412 000006      PKCLK    ,6.        ;SYNC UP DUP
5166 023052 052777 020000 156332      BIS      #CLK,@TXCSR ;POKE CLOCK UP
5167 023060 032713 001000      BIT      #TXACT,(R3) ;IS TXACT HIGH?
5168 023064 001001      BNE      1$          ;BR IF SET
5169 023066 104007      HLT      7           ;TXACT FAILED TO SET
```

INTERACTIVE TEST OF TXDBUF, TXACT, TSOM AND DONE

```

5170 023070          1$:
5171 023070 042777 020000 156314      BIC    #CLK,@TXCSR      ;POKE CLOCK DOWN
5172 023076 104412 000015              PKCLK  .13.            ;PUSH OUT DATA
5173 023102 032713 000020              BIT    #SEND,(R3)      ;CHECK SEND
5174 023106 001001                    BNE    2$              ;BR IF YES
5175 023110 104017                    HLT    17              ;BIT FAILED TO SET
5176 023112 012737 023112 001220 2$:  MOV    #2$,LOCK        ;SETUPFOR SW 09
5177 023120 012705 000400              MOV    #TSOM,R5        ;SET 'EXPECTED'.
5178 023124 011204                    MOV    (R2),R4         ;GET THE BUFFER REG
5179 023126 042704 170000              BIC    #170000,R4      ;MASK CRC BITS
5180 023132 020504                    CMP    R5,R4           ;R5=GOOD, R4=?
5181 023134 001406                    BEQ    3$              ;BR IF A MATCH
5182 023136 013703 001414              MOV    TXDBUF,R3       ;ERROR MESSAGE SETUP
5183 023142 104003                    HLT    3               ;BIT FAILED TO SET
5184 023144 104401                    SCOPE1                ;SW09=1?
5185 023146 012703 001412              MOV    #TXCSR,R3       ;LOAD TRANSMITTER CSR
5186 023152 012737 023152 001220 3$:  MOV    #3$,LOCK        ;SW09 SETUP
5187 023160 042712 000400              BIC    #TSOM,(R2)      ;CLR TSOM
5188 023164 032713 000200              BIT    #TXDONE,(R3)    ;TEST DONE
5189 023170 001402                    BEQ    4$              ;BR IF CLEAR
5190 023172 104005                    HLT    5               ;DONE BIT IS SET AND SHOULD BE CLEARED
5191 023174 104401                    SCOPE1                ;SW09=1?
5192 023176 012737 023176 001220 4$:  MOV    #4$,LOCK        ;SW09 SETUP
5193 023204 032712 000400              BIT    #TSOM,(R2)      ;TEST TSOM
5194 023210 001402                    BEQ    5$              ;BR IF CLEAR
5195 023212 104010                    HLT    10              ;BIT FAILED TO CLR
5196 023214 104401                    SCOPE1                ;SW09=1?
5197 023216 042713 000020 5$:      BIC    #SEND,(R3)      ;TURN OFF SEND
5198 023222 104412 000020              PKCLK  .16.            ;POKE 8 BITS
5199 023226 032713 000200              BIT    #TXDONE,(R3)    ;CHECK DONE
5200 023232 001401                    BEQ    .+4             ;BR IF OFF
5201 023234 104017                    HLT    17              ;DONE SET AND SHOULDN'T BE
5202 023236 104412 000002              PKCLK  .2              ;POKE ONE FULL CLOCK
5203 023242 032713 001000              BIT    #TXACT,(R3)     ;CHECK ACTIVE
5204 023246 001401                    BEQ    6$              ;BR IF OFF
5205 023250 104011                    HLT    11              ;ACTIVE SETS AND SHOULDN'T BE
5206 023252 032713 000200 6$:      BIT    #TXDONE,(R3)    ;IS DONE UP?
5207 023256 001001                    BNE    7$              ;BR IF YES
5208 023260 104006                    HLT    6               ;NO-REPORT ERROR
5209 023262 032713 040000 7$:      BIT    #MTDATA,(R3)    ;CHECK DATA OUT
5210 023266 001401                    BEQ    10$             ;BR IF OFF
5211 023270 104012                    HLT    12              ;DATA SET SHOULD BE CLEAR
5212 023272 104400 10$:      SCOPE                    ;SCOPE THIS TEST

```

```

5213
5214
5215          :***** TEST 142 *****
5216          :*THIS TEST VERIFIES THAT THE DEVICE IDLES FLAGS
5217          :*IDLE A MINIMUM OF 64. FLAGS.
5218          :*****
5219
5220          :*****
5221          : *
5222          : TEST 142
5223          : *
5224          :*****
5225          :*****

```



```
5226 023274 012737 000142 001226 TST142: MOV #142,@TSTNO
5227 023302 012737 023364 001216 MOV #TST143,NEXT
5228 023310 013702 001414 MOV TXDBUF,R2 ;LOAD TX BUFFER
5229 023314 013703 001412 MOV TXCSR,R3 ;LOAD TX CONTROL REGISTER
5230 023320 052777 000400 156064 BIS #MRESET,@TXCSR ;RESET THE DEVICE
5231 023326 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5232 023332 005012 CLR (R2) ;RESET TXDONE
5233 023334 052713 014000 BIS #MMODE,(R3) ;ENTER M/MODE
5234 023340 052713 000020 BIS #SEND,(R3) ;SET SEND
5235 023344 052712 000400 BIS #TSOM,(R2) ;TURN ON START OF MSG
5236 023350 104412 000004 PKCLK .4. ;SYNC UP DUP
5237 023354 004137 007052 JSR R1,FLG ;SEND 64. FLAGS
5238 023360 000100 64. ;64. FLAGS
5239 023362 104400 SCOPE ;SCOPE THIS TEST
```

```
5240
5241 ;***** TEST 143 *****
5242 ;*THIS TEST PUSHES DATA THRU THE TRANSMITTER
5243 ;*IN MAINTENANCE MODE. THE TEST SENDS A FLAG,
5244 ;*AND TWO ALTERNATING ONES AND ZEROES CHARACTERS,
5245 ;*AN ALL ZEROES CHARACTER AND AN ALL ONES
5246 ;*CHARACTER TO VERIFY THE BIT STUFF CAPABILITY OF
5247 ;*THE DUP WITHOUT A CRC CHECK.THE TEST ROTATES
5248 ;*THE BITS THRU,SAMPLING THE DATA ON A BIT-BY-BIT
5249 ;*BASIS,LSB FIRST. IT STORES THE BIT IN THE MSB OF
5250 ;*THE SAVE LOCATION,COMPARES AND ROTATES RIGHT UNTIL
5251 ;*THE CHARACTER IS ASSEMBLED.
5252 ;*****
```

```
5253
5254 ;*****
5255 ;
5256 ; TEST 143
5257 ;
5258 ;*****
5259 ;*****
```

```
5260 023364 012737 000143 001226 TST143: MOV #143,@TSTNO
5261 023372 012737 023740 001216 MOV #TST144,NEXT
5262 023400 013703 001412 MOV TXCSR,R3 ;LOAD TRANSMITTER CONTROL REGISTER
5263 023404 013702 001414 MOV TXDBUF,R2 ;LOAD TRANSMITTER BUFFER
5264 023410 052777 000400 155774 BIS #MRESET,@TXCSR ;RESET THE DEVICE
5265 023416 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5266 023422 005012 CLR (R2) ;RESET TXDONE
5267 023424 052713 014000 BIS #MMODE,(R3) ;ENTER MINT MODE--PROGRAM CLOCKING
5268 023430 052777 001000 155752 BIS #CRCEN,@PARCSR ;TURN OFF CRC
5269 023436 052713 000020 BIS #SEND,(R3) ;ASSERT SEND
5270 023442 052712 000400 BIS #TSOM,(R2)
5271 023446 005037 001236 CLR TEMP1 ;CLEAR
5272 023452 005037 001240 CLR TEMP2 ;CLEAR
5273 023456 005037 001242 CLR TEMP3 ;CLEAR
5274 023462 005037 001244 CLR TEMP4 ;CLEAR
5275 023466 012704 000004 MOV #4,R4 ;LOAD THE # OF CHARACTERS TO DO
5276 023472 012705 023726 MOV #TBL1,R5 ;LOAD THE TABLE POINTER
5277 023476 012701 023726 MOV #TBL1,R1 ;DITTO
5278 023502 011137 001246 MOV (R1),TEMP5 ;DITTO
5279 023506 104412 000010 PKCLK .8. ;START A FLAG
5280 023512 012512 MOV (R5)+,(R2) ;LOAD THE FIRST CHARACTER AND CLR TSOM
5281 023514 104412 000014 PKCLK .12. ;FINISH THE FLAG
```


DATA TEST OF A ZERO,ONE AND ALTERNATING ZERO-ONE CHARACTER

5338 ;R1 = SOFTWARE TABLE POINTER
5339 ;R2 = TXDBUF
5340 ;R3 = TXCSR
5341 ;R4 = CHAR COUNTER
5342 ;R5 = HARDWARE TABLE POINTER
5343 ;TEMP1 = HARDWARE BIT
5344 ;TEMP2 = 1'S COUNT
5345 ;TEMP3 = SOFTWARE BIT
5346 ;TEMP4 = CHARACTER BIT COUNTER
5347 ;TEMP5 = SOFTWARE BYTE

***** TEST 144 *****
*THIS TEST VERIFIES THE ABORT SEQUENCE AND
*NORMAL DATA SEQUENCE OF FLAG, DATA, FLAG
*FOLLOWED BY IDLE LINE. THIS TEST ALSO PROVES
*THE FUNCTIONING OF ACTIVE, TSOM, TEOM, SEND AND DONE.
*WITHOUT USING A CRC CHECK.

*
: TEST 144
*

5364	023740	012737	000144	001226	TST144: MOV	#144,@TSTNO	
5365	023746	012737	024226	001216	MOV	#TST145,NEXT	
5366	023754	013703	001412		MOV	TXCSR,R3	:LOAD CONTROL REGISTER
5367	023760	013702	001414		MOV	TXDBUF,R2	:LOAD TRANSMITTER BUFFER
5368	023764	052777	000400	155420	BIS	#MRESET,@TXCSR	:RESET THE DEVICE
5369	023772	004737	005044		JSR	PC,SMALL	:WAIT FOR RESET TO FINISH
5370	023776	005012			CLR	(R2)	:RESET TXDONE
5371	024000	052713	014000		BIS	#MMODE,(R3)	:ENTER M/MODE
5372	024004	052777	001000	155376	BIS	#CRCEN,@PARCSR	:SHUT OFF CRC
5373	024012	052713	000020		BIS	#SEND,(R3)	:SET SEND
5374	024016	052712	000400		BIS	#TSOM,(R2)	:TURN ON START OF MSG
5375	024022	104412	000010		PKCLK	,8.	:SYNC UP DUP AND START PUSHING OUT A FLAG
5376	024026	052712	002000		BIS	#TABORT,(R2)	:SET ABORT
5377	024032	104412	000014		PKCLK	,12.	:PUSH OUT THE ABORT
5378	024036	005037	001236		CLR	TEMP1	:CLEAR HOLD
5379	024042	104412	000002	1\$:	PKCLK	,2	:PUSH A BIT
5380	024046	032713	040000		BIT	#MTDATA,(R3)	:CHECK DATA
5381	024052	001001			BNE	2\$:BR IF SET
5382	024054	104013			HLT	13	:DATA FAILED TO SET
5383	024056	005237	001236	2\$:	INC	TEMP1	:INC HOLD
5384	024062	022737	000002	001236	CMP	#2,TEMP1	:CHECK FOR FINISH
5385	024070	001364			BNE	1\$:BR IF NO
5386	024072	032713	0010C0		BIT	#TXACT,(R3)	:TEST TRANSMITTER ACTIVE
5387	024076	001001			BNE	64\$:BR IF ACTIVE SET
5388	024100	104007			HLT	7	:ACTIVE IS RESET AND SHOULDN'T BE
5389	024102			64\$:			
5390	024102	042712	002000		BIC	#TABORT,(R2)	:CLEAR ABORT
5391	024106	005037	001236		CLR	TEMP1	:CLEAR HOLD
5392	024112	104412	000002	3\$:	PKCLK	,2	:PUSH A BIT
5393	024116	032713	040000		BIT	#MTDATA,(R3)	:CHECK DATA

5394	024122	001001				BNE	4\$:BR IF SET
5395	024124	104013				HLT	15		:DATA OUT FAILED TO SET
5396	024126	005237	001236		4\$:	INC	TEMP1		:INC # TO DO
5397	024132	022737	000006	001236		CMP	#6,TEMP1		:AND CHECK IT
5398	024140	001364				BNE	3\$:BR IF MORE TO GO
5399	024142	104412	000006			PKCLK	.6.		:POKE CLOCK
5400	024146	012712	000252			MOV	#252,(R2)		:CLEAR TSOM AND LOAD DATA
5401	024152	104412	000024			PKCLK	.20.		:FINISH THE FLAG AND DATA
5402	024156	052712	001000			BIS	#TEOM,(R2)		:SET TEOM
5403	024162	104412	000006			PKCLK	.6		:POKE CLOCK
5404	024166	004137	007052			JSR	R1,FLG		:SEND THREE FLAGS
5405	024172	000003				3			:DITTO
5406	024174	042713	000020			ZIC	#SEND,(R3)		:CLEAR SEND
5407	024200	104412	000004			PKCLK	.4		:POKE CLOCK
5408	024204	032713	040000			BIT	#MTDATA,(R3)		:TEST TXDAT
5409	024210	001001				BNE	65\$:MARK OUT
5410	024212	104013				HLT	13		:TXDAT A SPACE - SHOULD BE 1
5411	024214	032713	000200		65\$:	BIT	#TXDONE,(R3)		:IS DONE UP
5412	024220	001001				BNE	66\$:YES
5413	024222	104006				HLT	6		:NO - BUT IT SHOULD BE.
5414	024224	104400			66\$:	SCOPE			:SCOPE THIS TEST

5415
5416
5417
5418
5419
5420
5421
5422
5423
5424
5425
5426
5427
5428
5429
5430

:***** TEST 145 *****
:THIS TEST VERIFIES THAT A DATA
:UNDER RUN CONDITION WILL CAUSE
:THE TRANSMITTER DATA LATE BIT TO SET
:AND THAT THE DEVICE WILL ABORT
:UNTIL SEND IS CLEARED WHEN THE OUTPUT GOES TO A SPACE
:*****

:*****
:TEST 145
:*****

5431	024226	012737	000145	001226	TST145:	MOV	#145,@TSTNO		
5432	024234	012737	024430	001216		MOV	#TST146,NEXT		
5433	024242	013703	001412			MOV	TXCSR,R3		:LOAD TRANSMITTER CONTROL REGISTER
5434	024246	013702	001414			MOV	TXDBUF,R2		:LOAD TRANSMITTER BUFFER
5435	024252	052777	000400	155132		BIS	#MRESET,@TXCSR		:RESET THE DEVICE
5436	024260	004737	005044			JSR	PC,SMALL		:WAIT FOR RESET TO FINISH
5437	024264	005012				CLR	(R2)		:RESET TXDONE
5438	024266	052713	014000			BIS	#MODE,(R3)		:ENTER MINT MODE--PROGRAM CLOCKING
5439	024272	052777	001000	155110		BIS	#CRCEN,@PARCSR		:TURN OFF CRC
5440	024300	052713	000020			BIS	#SEND,(R3)		:ASSERT SEND
5441	024304	052712	000400			BIS	#TSOM,(R2)		
5442	024310	104412	000006			PKCLK	.6.		:START OUTPUTING FLAG
5443	024314	012777	000000	155072		MOV	#0,@TXDBUF		:CLEAR TSOM-LOAD BUFFER WITH ZEROES
5444	024322	104412	000016			PKCLK	.14.		:FINISH FLAG
5445	024326	104412	000017			PKCLK	.15.		:OUTPUT UP TO 7 1/2 CLOCK TICKS
5446	024332	032777	100000	155052		BIT	#TXDLAT,@TXCSR		:MAKE SURE DNA IS NOT SET
5447	024340	001401				BEQ	1\$:BR IF CLEARED
5448	024342	104014				HLT	14		:BIT IS SET TOO SOON
5449	024344	104412	000002		1\$:	PKCLK	.2		:FINISH LAST CLOCK

```

5450 024350 032777 100000 155034 BIT #TXDLAT,@TXCSR ;NOW CHECK DNA
5451 024356 001001 BNE 2$ ;BRANCH IF SET
5452 024360 104015 HLT 15 ;BIT IS CLEARED AND SHOULD BE SET
5453 024362 2$:
5454 024362 042777 000020 155022 BIL #SEND,@TXCSR ;TURN OFF SEND
5455 024370 104412 000020 PKCLK .16. ;PUSH 8 BITS
5456 024374 012737 000010 001236 MOV #8.,TEMP1 ;SETUP FOR IDLE LINE
5457 024402 104412 000002 3$: PKCLK .2 ;OUTPUT BIT
5458 024406 032777 040000 154776 BIT #MTDATA,@TXCSR ;CHECK IT
5459 024414 001401 BEQ 4$ ;BRANCH IF ZERO
5460 024416 104012 HLT 12 ;BIT IS A 1
5461 024420 005337 001236 4$: DEC TEMP1 ;LOWER COUNT
5462 024424 001366 BNE 3$ ;NOT DONE? - GO BACK
5463 024426 104400 SCOPE ;SCOPE THIS TEST

```

```

5464
5465
5466
5467
5468
5469
5470
5471
5472
5473
5474
5475
5476
5477
5478

```

```

:***** TEST 146 *****
:*THIS TEST VERIFIES THAT DROPPING OF
:*SEND BEFORE SETTING TEOM CAUSES
:*A SPACE TO BE OUTPUT AFTER COMPLETION OF
:*A CHARACTER WITH AND WITHOUT BIT STUFF.
:*****

```

```

:*****
: *
: TEST 146
: *
:*****

```

```

5479 024430 012737 000146 001226 TST146: MOV #146,@TSTNO
5480 024436 012737 025002 001216 MOV #TST147,NEXT
5481 024444 013703 001412 MOV TXCSR,R3 ;LOAD TRANSMITTER CONTROL REGISTER
5482 024450 013702 001414 MOV TXDBUF,R2 ;LOAD TRANSMITTER BUFFER
5483 024454 052777 000400 154730 BIS #MRESET,@TXCSR ;RESET THE DEVICE
5484 024462 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5485 024466 005012 CLR (R2) ;RESET TXDONE
5486 024470 052713 014000 BIS #MMODE,(R3) ;ENTER MINT MODE--PROGRAM CLOCKING
5487 024474 052777 001000 154706 BIS #CRCEN,@PARCSR ;TURN OFF CRC
5488 024502 052713 000020 BIS #SEND,(R3) ;ASSERT SEND
5489 024506 052712 000400 BIS #TSOM,(R2)
5490 024512 104412 000006 PKCLK .6. ;PUSH 2 BITS
5491 024516 012777 000252 154670 MOV #252,@TXDBUF ;LOAD DATA
5492 024524 104412 000014 PKCLK .12. ;PUSH 6 BITS
5493 024530 042777 000020 154654 BIC #SEND,@TXCSR ;TURN OFF TRANSMITTER
5494 024536 104412 000002 PKCLK .2 ;POKE A FULL CLOCK
5495 024542 012737 000010 001236 MOV #8.,TEMP1 ;LOAD TEMP1
5496 024550 104412 000012 1$: PKCLK .10. ;PUSH 5 BITS
5497 024554 032777 040000 154630 BIT #MTDATA,@TXCSR ;CHECK DATA
5498 024562 001401 BEQ 2$ ;BR IF CLEAR
5499 024564 104012 HLT 12 ;DATA IS SET - SHOULD BE CLEAR
5500 024566 005337 001236 2$: DEC TEMP1 ;LOWER THE # OF TIMES TO REPEAT
5501 024572 001366 BNE 1$ ;BR IF TO GOE MSG
5502 024574 032777 001000 154610 BIT #TXACT,@TXCSR ;CHECK ACTIVE
5503 024602 001401 BEQ 7$ ;BR IF OFF
5504 024604 104011 HLT 11 ;ACTIVE FAILED TO CLEAR
5505 024606 7$:

```

```
5506 024606 052777 000400 154576 BIS #MRESET,@TXCSR ;RESET THE DEVICE
5507 024614 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5508 024620 013703 001412 MOV TXCSR,R3 ;LOAD TRANSMITTER CONTROL REGISTER
5509 024624 013702 001414 MOV TXDBUF,R2 ;LOAD TRANSMITTER BUFFER
5510 024630 052777 000400 154554 BIS #MRESET,@TXCSR ;RESET THE DEVICE
5511 024636 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5512 024642 005012 CLR (R2) ;RESET TXDONE
5513 024644 052713 014000 BIS #MMODE,(R3) ;ENTER MINT MODE--PROGRAM CLOCKING
5514 024650 052777 001000 154532 BIS #CRCEN,@PARCSR ;TURN OFF CRC
5515 024656 052713 000020 BIS #SEND,(R3) ;ASSERT SEND
5516 024662 052712 000400 BIS #TSOM,(R2)
5517 024666 104412 000006 PKCLK .6 ;PUSH TWO BITS
5518 024672 012777 000177 154514 MOV #177,@TXDBUF ;LOAD DATA
5519 024700 104412 000020 PKCLK .16 ;PUSH 8 BITS
5520 024704 042777 000020 154500 BIC #SEND,@TXCSR ;TURN OFF TRANSMITTER
5521 024712 104412 000014 PKCLK .12 ;PUSH 6 BITS
5522 024716 032777 040000 154466 BIT #MTDATA,@TXCSR ;CHECK DATA OUT FOR BIT STUFF FUNCTION
5523 024724 001001 BNE 3$ ;BR IF SET
5524 024726 104013 HLT 13 ;BIT IS A 0, SHOULD BE A 1 - DEVICE
5525 ;FAILED TO BIT STUFF
5526 024730 104412 000004 3$: PKCLK .4 ;PUSH 2 BITS
5527 024734 012737 000010 001236 MOV #8.,TEMP1 ;LOAD TEMP1
5528 024742 104412 000002 4$: PKCLK .2 ;PUSH A BIT
5529 024746 032777 040000 154436 BIT #MTDATA,@TXCSR ;CHECK DATA
5530 024754 001401 BEQ 5$ ;BR IF OFF
5531 024756 104012 HLT 12 ;DATA WINDOW SET - SHOULD BE CLEAR
5532 024760 005337 001236 5$: DEC TEMP1 ;LOWER THE # OF TIMES TO CHECK
5533 024764 001366 BNE 4$ ;BR IF MORE TOGO
5534 024766 032777 001000 154416 BIT #TXACT,@TXCSR ;CHECK ACTIVE
5535 024774 001401 BEQ 6$ ;BR IF OFF
5536 024776 104011 HLT 11 ;ACTIVE FAILED TO CLEAR
5537 025000 104400 6$: SCOPE ;SCOPE THIS TEST
```

```
5538
5539 ;***** TEST 147 *****
5540 ;*THIS TEST VERIFIES THAT A DATA UNDERRUN
5541 ;*CONDITION WILL CAUSE THE TRANSMITTER DATA
5542 ;*LATE BIT TO SET AND THAT THE DUP WILL GO TO
5543 ;*A MARK OUTPUT
5544 ;:*****
```

```
5545
5546 :*****
5547 : *
5548 : TEST 147
5549 : *
5550 :*****
5551 :*****
```

```
5552 025002 012737 000147 001226 TST147: MOV #147,@TSTNO
5553 025010 012737 025176 001216 MOV #TST150,NEXT
5554 025016 013703 001412 MOV TXCSR,R3 ;LOAD TRANSMITTER CONTROL REGISTER
5555 025022 013702 001414 MOV TXDBUF,R2 ;LOAD TRANSMITTER BUFFER
5556 025026 052777 000400 154356 BIS #MRESET,@TXCSR ;RESET THE DEVICE
5557 025034 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5558 025040 005012 CLR (R2) ;RESET TXDONE
5559 025042 052713 014000 BIS #MMODE,(R3) ;ENTER MINT MODE--PROGRAM CLOCKING
5560 025046 052777 001000 154334 BIS #CRCEN,@PARCSR ;TURN OFF CRC
5561 025054 052713 000020 BIS #SEND,(R3) ;ASSERT SEND
```

5562	025060	052712	000400			BIS	#TSOM,(R2)		
5563	025064	104412	000006			PKCLK	,6.	:START FLAG	
5564	025070	112777	000176	154316		MOVB	#176,@TXDBUF	:LOAD CHARACTER TO BE BIT-STUFFED	
5565	025076	042777	000400	154310		BIC	#TSOM,@TXDBUF	:SHUT OFF TSOM	
5566	025104	104412	000016			PKCLK	,14.	:FINISH CLOCKING FLAG	
5567	025110	104412	000017			PKCLK	,15.	:CLOCK TO WITHIN 1 1/2 CLOCKS	
5568	025114	032777	100000	154270		BIT	#TXDLAT,@TXCSR	:CHECK DATA LATE	
5569	025122	001401				BEQ	1\$:BRANCH IF CLEAR	
5570	025124	104014				HLT	14	:BIT IS SET TOO SOON	
5571	025126	104412	000002		1\$:	PKCLK	,2	:CLOCK TO WITHIN A HALF-CLOCK OF DNA	
5572	025132	032777	100000	154252		BIT	#TXDLAT,@TXCSR	:CHECK DNA	
5573	025140	001401				BEQ	2\$:BR IF OFF	
5574	025142	104014				HLT	14	:BIT SET TOO SOON, DEVICE FAILED TO BIT-STUFF	
5575	025144	104412	000004		2\$:	PKCLK	,4	:FINISH CHARACTER	
5576	025150	032777	100000	154234		BIT	#TXDLAT,@TXCSR	:CHECK DNA	
5577	025156	001001				BNE	3\$:BRANCH IF SET	
5578	025160	104016				HLT	16	:BIT SHOULD BE SET AND IS CLEARED	
5579	025162	032777	040000	154222	3\$:	BIT	#MTDATA,@TXCSR	:CHECK DATA	
5580	025170	001001				BNE	4\$:BR IF SET	
5581	025172	104013				HLT	13	:DATA WAS CLEAR - SHOULD BE SET	
5582	025174	104400			4\$:	SCOPE		:SCOPE THIS TEST	

5583
5584
5585
5586
5587
5588
5589
5590
5591
5592
5593
5594
5595
5596

```
***** TEST 150 *****  
:THIS TEST VERIFIES THAT SETTING TEOM  
:AND TSOM AT THE SAME TIME WILL HOLD  
:ACTIVE UP AND SEND A FLAG  
:*****
```

```
*****  
:TEST 150  
*****
```

5597	025176	012737	000150	001226		TST150: MOV	#150,@TSTNO		
5598	025204	012737	025332	001216		MOV	#TST151,NEXT		
5599	025212	013703	001412			MOV	TXCSR,R3	:LOAD TRANSMITTER CONTROL REGISTER	
5600	025216	013702	001414			MOV	TXDBUF,R2	:LOAD TRANSMITTER BUFFER	
5601	025222	052777	000400	154162		BIS	#MRESET,@TXCSR	:RESET THE DEVICE	
5602	025230	004737	005044			JSR	PC,SMALL	:WAIT FOR RESET TO FINISH	
5603	025234	005012				CLR	(R2)	:RESET TXDONE	
5604	025236	052713	014000			BIS	#MMODE,(R3)	:ENTER MINT MODE--PROGRAM CLOCKING	
5605	025242	052777	001000	154140		BIS	#CRCEN,@PARCSR	:TURN OFF CRC	
5606	025250	052713	000020			BIS	#SEND,(R3)	:ASSERT SEND	
5607	025254	052712	000400			BIS	#TSOM,(R2)		
5608	025260	104412	000006			PKCLK	,6.	:SYNC UP DUP	
5609	025264	012777	000252	154122		MOV	#252,@TXDBUF	:LOAD DATA	
5610	025272	104412	000032			PKCLK	,26.	:FINISH THE FLAG AND DATA	
5611	025276	052777	001400	154110		BIS	#TEOM!#TSOM,@TXDBUF	:TURN ON START AND END OF MSG	
5612	025304	104412	000004			PKCLK	,4	:PUSH 2 BITS	
5613	025310	032777	001000	154074		BIT	#TXACT,@TXCSR	:TEST ACTIVE	
5614	025316	001001				BNE	1\$:BR IF SET	
5615	025320	104007				HLT	7	:ACTIVE SHOULD BE SET AND IS CLEAR	
5616	025322	004137	007052		1\$:	JSR	R1,FLG	:PUSH OUT A FLAG	
5617	025326	000001					1	:ONE FLAG	

```
5618 025330 104400 SCOPE ;SCOPE THIS TEST
5619
5620 :***** TEST 151 *****
5621 :*TEST OF THE BCC OPERATION USING
5622 :*CRC.CCITT FOR THE POLYNOMIAL. SPECIFIC
5623 :*DATA PATTERNS ARE USED TO ISOLATE FAULTS.
5624 :*****
5625
5626 :*****
5627 : *
5628 : TEST 151
5629 : *
5630 :*****
5631 :*****
5632 025332 012737 000151 001226 TST151: MOV #151,@TSTNO
5633 025340 012737 026402 001216 MOV #TST152,NEXT
5634 025346 012737 102010 026374 MOV #CRC.CCITT,XPOLY ;SET THE POLYNOMIAL
5635 025354 012737 026212 001244 MOV #5$,TEMP4 ;GET THE TABLE POINTER
5636 025362 012737 025370 001220 MOV #1$,LOCK ;SETUP FOR SW09-1
5637 025370
5638 025370 052777 000400 154014 1$: BIS #MRESET,@TXCSR ;RESET THE DEVICE
5639 025376 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5640 025402 005077 154006 CLR @TXDBUF ;RESET TXDONE
5641 025406 052777 014000 153776 BIS #MMODE,@TXCSR ;ENTER M/MODE
5642 025414 052777 000020 153770 BIS #SEND,@TXCSR ;TURN ON DUP
5643 025422 052777 000400 153764 BIS #TSOM,@TXDBUF ;TURN ON START OF MSG
5644 025430 104412 000006 PKCLK ,6. ;SYNC UP DUP
5645 025434 017777 153604 153752 MOV @TEMP4,@TXDBUF ;LOAD DATA
5646 025442 104412 000020 PKCLK ,16. ;PUSH 8 BITS
5647 025446 005037 026400 CLR CALBCC ;CLEAR OUT OLD BCC
5648 025452 004537 026222 JSR R5,SIMBCC ;CALCULATE A SOFTWARE BCC
5649 025456 000010 8. ;BASED
5650 025460 000000 0 ;ON THESE
5651 025462 177777 -1 ;PARAMETERS
5652 025464 012777 001000 153722 MOV #TEOM,@TXDBUF ;CLEAR TSOM, SET TEOM
5653 025472 104412 000016 PKCLK ,14. ;PUSHOUT DATA
5654 025476 004137 006750 JSR R1,ACC ;DO A BCC CALCULATION (HDWR)
5655 025502 100000 BIT15 ;FOR 16 BITS
5656 025504 013705 026400 MOV CALBCC,R5 ;MOV SOFTWARE BCC TO EXPECTED
5657 025510 005105 COM R5 ;INVERT IT
5658 025512 020504 CMP R5,R4 ;DOES EXPECTED=FOUND?
5659 025514 001401 BEQ 64$ ;BR IF OK
5660 025516 104020 HLT 20 ;BCC CALCULATION ERROR
5661 ;TO DEBUG CRC USE THE CRC
5662 ;DEBUG AID TEST. SEE FROM* OF THE
5663 ;LISTING FOR TEST LOCATION
5664 025520 104401 64$: SCOP1 ;SW09=1?
5665 025522 062737 000002 001244 ADD #2,TEMP4 ;MOVE THE TABLE POINTER
5666 025530 012737 025536 001220 MOV #2$,LOCK ;SETUP FOR SW09=1
5667 025536
5668 025536 052777 000400 153646 2$: BIS #MRESET,@TXCSR ;RESET THE DEVICE
5669 025544 004737 005044 JSR PC,SMALL ;WAIT FOR RESET TO FINISH
5670 025550 005077 153640 CLR @TXDBUF ;RESET TXDONE
5671 025554 052777 014000 153630 BIS #MMODE,@TXCSR ;ENTER M/MODE
5672 025562 052777 000020 153622 BIS #SEND,@TXCSR ;TURN ON DUP
5673 025570 052777 000400 153616 BIS #TSOM,@TXDBUF ;TURN ON START OF MSG
```


5674	025576	104412	000006		PKCLK	.6.		:SYNC UP DUP
5675	025602	017777	153436	153604	MOV	@TEMP4,@TXDBUF		:LOAD DATA
5676	025610	104412	000020		PKCLK	.16.		:PUSH 8 BITS
5677	025614	005037	026400		CLR	CALBCC		:CLEAR OUT OLD BCC
5678	025620	004537	026222		JSR	R5,SIMBCC		:CALCULATE A SOFTWARE BCC
5679	025624	000010				8.		:BASED
5680	025626	000252				^B<10101010>		:ON THESE
5681	025630	177777				-1		:PARAMETERS
5682	025632	012777	001000	153554	MOV	#TEOM,@TXDBUF		:CLEAR TSOM, SET TEOM
5683	025640	104412	000016		PKCLK	.14.		:PUSHOUT DATA
5684	025644	004137	006750		JSR	R1,ACC		:DO A BCC CALCULATION (HDWR)
5685	025650	100000			BIT15			:FOR 16 BITS
5686	025652	013705	026400		MOV	CALBCC,R5		:MOV SOFTWARE BCC TO EXPECTED
5687	025656	005105			COM	R5		:INVERT IT
5688	025660	020504			CMP	R5,R4		:DOES EXPECTED=FOUND?
5689	025662	001401			BEQ	65\$:BR IF OK
5690	025664	104020			HLT	20		:BCC CALCULATION ERROR
5691								:TO DEBUG CRC USE THE CRC
5692								:DEBUG AID TEST. SEE FRONT OF THE
5693								:LISTING FOR TEST LOCATION
5694	025666	104401			65\$:	SCOPI		:SW09=1?
5695	025670	062737	000002	001244	ADD	#2,TEMP4		:MOVE THE TABLE POINTER
5696	025676	012737	025704	001220	MOV	#3\$,LOCK		:SETUP FOR SW09=1
5697	025704				3\$:			
5698	025704	052777	000400	153500	BIS	#MRESET,@TXCSR		:RESET THE DEVICE
5699	025712	004737	005044		JSR	PC,SMALL		:WAIT FOR RESET TO FINISH
5700	025716	005077	153472		CLR	@TXDBUF		:RESET TXDONE
5701	025722	052777	014000	153462	BIS	#MMODE,@TXCSR		:ENTER M/MODE
5702	025730	052777	000020	153454	BIS	#SEND,@TXCSR		:TURNON DLP
5703	025736	052777	000400	153450	BIS	#TSOM,@TXDBUF		:TURN ON START OF MSG
5704	025744	104412	000006		PKCLK	.6.		:SYNC UP DUP
5705	025750	017777	153270	153436	MOV	@TEMP4,@TXDBUF		:LOAD DATA
5706	025756	104412	000020		PKCLK	.16.		:PUSH 8 BITS
5707	025762	005037	026400		CLR	CALBCC		:CLEAR OUT OLD BCC
5708	025766	004537	026222		JSR	R5,SIMBCC		:CALCULATE A SOFTWARE BCC
5709	025772	000010				8.		:BASED
5710	025774	000125				^B<01010101>		:ON THESE
5711	025776	177777				-1		:PARAMETERS
5712	026000	012777	001000	153406	MOV	#TEOM,@TXDBUF		:CLEAR TSOM, SET TEOM
5713	026006	104412	000016		PKCLK	.14.		:PUSHOUT DATA
5714	026012	004137	006750		JSR	R1,ACC		:DO A BCC CALCULATION (HDWR)
5715	026016	100000			BIT15			:FOR 16 BITS
5716	026020	013705	026400		MOV	CALBCC,R5		:MOV SOFTWARE BCC TO EXPECTED
5717	026024	005105			COM	R5		:INVERT IT
5718	026026	020504			CMP	R5,R4		:DOES EXPECTED FOUND?
5719	026030	001401			BEQ	66\$:BR IF OK
5720	026032	104020			HLT	20		:BCC CALCULATION ERROR
5721								:TO DEBUG CRC USE THE CRC
5722								:DEBUG AID TEST. SEE FRONT OF THE
5723								:LISTING FOR TEST LOCATION
5724	026034	104401			66\$:	SCOPI		:SW09=1?
5725	026036	062737	000002	001244	ADD	#2,TEMP4		:MOVE THE TABLE POINTER
5726	026044	012737	026052	001220	MOV	#4\$,LOCK		:SETUP FOR SW09=1
5727	026052				4\$:			
5728	026052	052777	000400	153332	BIS	#MRESET,@TXCSR		:RESET THE DEVICE
5729	026060	004737	005044		JSR	PC,SMALL		:WAIT FOR RESET TO FINISH

5730	026064	005077	153324		CLR	@TXDBUF		:RESET TXDONE
5731	026070	052777	014000	153314	BIS	#MMODE,@TXCSR		:ENTER M/MODE
5732	026076	052777	000020	153306	BIS	#SEND,@TXCSR		:TURN ON DUP
5733	026104	052777	000400	153302	BIS	#TSOM,@TXDBUF		:TURN ON START OF MSG
5734	026112	104412	000006		PKLLK	.6.		:SYNC UP DUP
5735	026116	017777	153122	153270	MOV	@TEMP4,@TXDBUF		:LOAD DATA
5736	026124	104412	000020		PKCLK	.16.		:PUSH 8 BITS
5737	026130	005037	026400		CLR	CALBCC		:CLEAR OUT OLD BCC
5738	026134	004537	026222		JSR	R5,SIMBCC		:CALCULATE A SOFTWARE BCC
5739	026140	000010			B.			:BASED
5740	026142	000377			^B<11111111>			:ON THESE
5741	026144	177777			-1			:PARAMETERS
5742	026146	012777	001000	153240	MOV	#TEOM,@TXDBUF		:CLEAR TSOM, SET TEOM
5743	026154	104412	000020		PKCLK	.16.		:PUSH 8 BITS
5744	026160	004137	006750		JSR	R1,ACC		:DO A BCC CALCULATION (HDWR)
5745	026164	100000			BIT15			:FOR 16 BITS
5746	026166	012705	157400		MOV	#157400,R5		:LOAD THE BCC
5747	026172	020504			CMR	R5,R4		:DOES EXPECTED-FOUND?
5748	026174	001401			BEQ	67\$:BR IF OK
5749	026176	104020			HLT	20		:BCC CALCULATION ERROR
5750								:TO DEBUG CRC USE THE CRC
5751								:DEBUG AID TEST. SEE FRONT OF THE
5752								:LISTING FOR TEST LOCATION
5753	026200	104401			67\$:	SCOPI		:SW09=1?
5754	026202	062737	000002	001244	ADD	#2,TEMP4		:MOVE THE TABLE POINTER
5755	026210	104400			5\$:	.WORD	0	:SCOPE THIS TEST
5756	026212	000000				.WORD	252	
5757	026214	000252				.WORD	125	
5758	026216	000125				.WORD	377	
5759	026220	000377			SIMBCC:	MOV	R0,-(SP)	
5760	026222	010046				MOV	R1,-(SP)	
5761	026224	010146				MOV	R2,-(SP)	
5762	026226	010246				MOV	(R5)+,TEMP1	
5763	026230	012537	001236			MOV	(R5)+,TEMP2	
5764	026234	012537	001240			MOV	(R5)+,TEMP3	
5765	026240	012537	001242		1\$:	CLR	BCCFBK	
5766	026244	005037	026376			MOV	TEMP3,R0	
5767	026250	013700	001242			ROR	TEMP2	
5768	026254	006037	001240			ADC	R0	
5769	026260	005500				BIT	#BIT0,R0	
5770	026262	032700	000001			BEQ	2\$	
5771	026266	001402				COM	BCCFBK	
5772	026270	005137	026376		2\$:	MOV	XPOLY,R0	
5773	026274	013700	026374			COM	R0	
5774	026300	005100				BIC	R0,BCCFBK	
5775	026302	040037	026376			CLC		
5776	026306	000241				ROR	TEMP3	
5777	026310	006037	001242			MOV	BCCFBK,R0	
5778	026314	013700	026376			MOV	TEMP3,R1	
5779	026320	013701	001242			MOV	R1,R2	
5780	026324	010102				BIC	R1,R0	
5781	026326	040100				BIC	BCCFBK,R2	
5782	026330	043702	026376			BIS	R2,R0	
5783	026334	050200				BIC	XPOLY,TEMP3	
5784	026336	043737	026374	001242		BIS	R0,TEMP3	
5785	026344	050037	001242					

5786 026350 005337 001236
5787 026354 001333
5788 026356 013737 001242 026400
5789 026364 012602
5790 026366 012601
5791 026370 012600
5792 026372 000205
5793 026374 000000
5794 026376 000000
5795 026400 000000
5796 120001
5797 102010
5798
5799
5800
5801
5802
5803
5804
5805
5806
5807
5808
5809
5810
5811
5812
5813
5814
5815
5816
5817

DEC TEMP1
BNE 1\$
MOV TEMP3,CALBCC
MOV (SP)+,R2
MOV (SP)+,R1
MOV (SP)+,R0
RTS R5
XPOLY: 0
BCCFBK: 0
CALBCC: 0
CRC16=120001
CRC.CCITT=102010

***** TEST 152 *****
;THIS TEST IS AN AID FOR DEBUGGING CRC
;ERRORS. A CHARACTER IS LOADED INTO THE
;DUP AND PUSHED OUT BIT BY BIT WHILE
;ALLOWING THE OPERATOR TO MONITOR THE CRC
;CHARACTER AS IT IS GENERATED. THE DATA CHARACTER
;CAN ALSO BE CHANGED BY THE OPERATOR.
;PUT SW09=1 TO LOCK ON BITS. TO CONTINUE HIT
;ANY KEY ON THE TTY. AFTER 16 TIMES PUT DOWN SW09 TO LEAVE
;NOTE: REMEMBER--IN SDLC A ONE IS A LOGIC LOW IN
;THE CRC GENERATOR.

: TEST 152

5818 026402 012737 000152 001226
5819 026410 012737 002764 001216
5820 026416 052777 000400 152766
5821 026424 004737 005044
5822 026430 012737 102010 026374
5823 026436 012737 000125 026604
5824 026444 013737 026604 001252
5825 026452 012737 177777 026400
5826 026460 013737 026400 026606
5827 026466 005037 001242
5828 026472 005037 001244
5829 026476 005037 001246
5830 026502 005077 152706
5831 026506 052777 014000 152676
5832 026514 052777 000020 152662
5833 026522 052777 000020 152662
5834 026530 012777 000400 152656
5835 026536 104412 000044
5836 026542 013777 026604 152644
5837 026550 104412 000020
5838 026554 104412 000002
5839 026560 013737 001244 001254
5840 026566 005237 001242
5841 026572 005237 001244

TST152: MOV #152,@TSTNO
MOV #.EOP,NEXT
BIS #MRESET,@TXCSR ;RESET THE DEVICE
JSR PC,SMALL ;WAIT FOR RESET TO FINISH
MOV #CRC.CCITT,XPOLY ;LOAD THE POLYNOMIAL
MOV #125,3\$;LOAD DATA TO SOFTWARE BCC-CHANGE CHARACTER HERE
MOV 3\$,SAVR1
MOV #-1,CALBCC ;CLEAR FOR SOFTWARE BCC
MOV CALBCC,4\$
CLR TEMP3 ;CLR SOFTWARE MEMORY
CLR TEMP4 ;CLEAR BIT COUNTER
CLR TEMP5
CLR @TXDBUF ;RESET TXDONE
BIS #MMODE,@TXCSR ;ENTER MAINT MODE-PROGRAM CLOCKING
BIS #RCVEN,@RXCSR ;TURN ON RECEIVER
BIS #SEND,@TXCSR ;TURN ON TRANSMITTER
MOV #TSOM,@TXDBUF ;
PKCLK ,36. ;PUSH OUT 2
MOV 3\$,@TXDBUF ;LOAD DATA
PKCLK ,16. ;PUSH OUT ANOTHER
PKCLK ,2. ;PUSH OUT A BIT
MOV TEMP4,SAVR2 ;SET UP TO TYPE
INC TEMP3 ;UPDATE THE COUNT
INC TEMP4 ;UPDATE BIT COUNTER

```

5842 026576 004537 026222      2$:   JSR     R5,SIMBCC      ;CALCULATE SOFTWARE BCC BASED ON THESE PARAMETERS
5843 026602 000001                1      ;SHIFTS
5844 026604 000000                3$:   .WORD 0      ;DATA
5845 026606 000000                4$:   .WORD 0      ;PREVIOUS BCC
5846 026610 004737 026706      JSR     PC,5$      ;CHECK TO SEE IF WE SHOULD WAIT FOR SCOPING
5847 026614 000241                CLC                ;CLEAR FOR NEXT ROTATE
5848 026616 106037 026604      RORB    3$        ;SET UP THE NEXT BIT
5849 026622 013737 026400 026606  MOV     CALBCC,4$   ;FOR THE SOFTWARE BCC
5850 026630 022737 000006 001244  CMP     #6,TEMP4
5851 026636 001002                BNE     .+6
5852 026640 005077 152550      CLR     @TXDBUF
5853 026644 022737 000014 001242  CMP     #12.,TEMP3
5854 026652 001003                BNE     12$
5855 026654 012777 001000 152532  MOV     #TEOM,@TXDBUF
5856 026662 022737 000020 001244  12$:   CMP     #16.,TEMP4      ;ALL DONE WITH THE CHARACTER?
5857                                ;INCREASE THE COMPARE NUMBER TO
5858                                ;ALLOW CRC TO BE OUTPUT
5859 026670 001331                BNE     1$        ;BR IF MORE TO GO
5860 026672 052777 000400 152512  BIS     #MRESET,@TXCSR ;RESET THE DEVICE
5861 026700 004737 005044      JSR     PC,SMALL   ;WAIT FOR RESET TO FINISH
5862 026704 104400                SCOPE            ;SCOPE THIS TEST
5863
5864 026706 032777 001000 152266  5$:   BIT     #SW09,@SWR   ;SW09=1?
5865 026714 001432                BEQ     6$        ;BR IF NO
5866 026716 013704 026400      MOV     CALBCC,R4  ;THE DATA CHARACTER IS
5867 026722 012737 000001 001256  MOV     #1,SAVR3   ;FOLLOWED BY A ZERO CHARACTER.THE
5868 026730 000241                CLC                ;DATA BIT IN CRC SHOWS WHICH BIT
5869 026732 006004                ROR     R4        ;OF THE TWO CHARACTERS IS BEING
5870 026734 006137 001256      ROL     SAVR3     ;GENERATED
5871 026740 103374                BCC     11$
5872 026742 105737 001246      TSTB   TEMP5
5873 026746 001006                BNE     10$
5874 026750 104402 027503      TYPE   ,EM1      ;TYPE MSG
5875 026754 104402 027532      TYPE   ,MH1      ;TYPE HEADER
5876 026760 105137 001246      COMB   TEMP5
5877 026764 104410                10$:  CONVRT
5878 026766 030174                DT1
5879 026770 105777 152210      7$:   TSTB   @TKCSR    ;CHECK TTY DONE--GO SCOPE THE CRC GENERATOR
5880 026774 100375                BPL     7$        ;BR IF NOT YET
5881 026776 017701 152204      MOV     @TKDBR,R1 ;READ THE BUFFER
5882 027002 000207                6$:   RTS     PC      ;RETURN
5883
5884

```

5885

(1)	027004	005015	051124	047101	EM2:	.ASCIZ	<15><12>/TRANSMITTER /	
(1)	027024	005015	042522	042503	EM3:	.ASCIZ	<15><12>/RECEIVER /	
(1)	027041	015	052412	042516	EM4:	.ASCIZ	<15><12>/UNEXPECTED INTERRUPT/	
(1)	027070	005015	051120	046511	EM6:	.ASCIZ	<15><12>^PRIMARY REGISTER TEST ^	
(1)	027121	377	051124	047101	EM10:	.ASCIZ	<377>/TRANSMITTER DATA ERROR. /	
(1)	027153	377	044103	041505	EM11:	.ASCIZ	<377>/CHECK CARRY AND OUTBIT. /	
(1)	027207	104	047117	020105	EM12:	.ASCIZ	/DONE BIT /	
(1)	027222	040506	046111	042105	EM13:	.ASCIZ	/FAILED TO CLEAR /	
(1)	027243	106	044501	042514	EM14:	.ASCIZ	/FAILED TO SET /	
(1)	027262	041501	044524	042526	EM15:	.ASCIZ	/ACTIVE BIT /	
(1)	027277	124	047523	020115	EM16:	.ASCIZ	/TSOM BIT /	
(1)	027312	052517	050124	052125	EM17:	.ASCIZ	/OUTPUT DATA /	
(1)	027330	042523	020124	047524	EM22:	.ASCIZ	/SET TOO SOON /	
(1)	027346	052377	042130	040514	EM23:	.ASCIZ	<377>/TXDLAT BIT /	
(1)	027364	041777	041522	041440	EM24:	.ASCIZ	<377>/CRC CALCULATION ERROR /	
(1)	027414	047111	042524	052522	DH2:	.ASCIZ	/INTERUPTED UNEXPECTEDLY./	
(1)	027445	377	054105	042520	DH6:	.ASCIZ	<377>/EXPECTED FOUND PRI REG /	
(1)	027503	377	051103	020103	EM1:	.ASCIZ	<377>/CRC GENERATOR STATUS /	
(1)	027532	042377	052101	020101	MH1:	.ASCIZ	<377>/DATA CHAR DATA BIT IN CRC GEN. CRC FOR THIS BIT /	
(1)	027625	106	044501	042514	DH7:	.ASCIZ	/FAILED TO BIT-STUFF. /	
(1)	027653	015	050012	044522	EM5:	.ASCIZ	<15><12>/PRIMARY REGISTER ADDRESSING TIME-OUT /	
(1)	027723	015	050012	044522	EM7:	.ASCIZ	<15><12>/PRIMARY REGISTER RESET TEST /	
(1)	027763	377	042522	044507	DH5:	.ASCIZ	<377>/REGISTER REFERENCED TRAPPED FROM /	
(1)						.EVEN		
(1)	030026					.ERRTAB:		
(1)	030026	000000				0		
(1)	030030	000000				0		
(1)	030032	000000				0		
(1)	030034	027653				EM5		
(1)	030036	027763				DH5	:HALT 1	
(1)	030040	030212				DT5		
(1)								
(1)	030042	027723				EM7		
(1)	030044	027445				DH6	:HALT 2	
(1)	030046	030224				DT6		
(1)								
(1)	030050	027070				EM6		
(1)	030052	027445				DH6	:HALT 3	
(1)	030054	030224				DT6		
(1)								
(1)	030056	027121				EM10		
(1)	030060	000000				0	:HALT 4	
(1)	030062	000000				0		
(1)								
(1)	030064	027207				EM12		
(1)	030066	027222				EM13	:HALT 5	
(1)	030070	000000				0		
(1)								
(1)	030072	027207				EM12		
(1)	030074	027243				EM14	:HALT 6	
(1)	030076	000000				0		
(1)								
(1)	030100	027262				EM15		
(1)	030102	027243				EM14	:HALT 7	
(1)	030104	000000				0		

(1)					
(1)	030106	027277		EM16	
(1)	030110	027222		EM13	:HALT 10
(1)	030112	000000		0	
(1)					
(1)	030114	027262		EM15	
(1)	030116	027222		EM13	:HALT 11
(1)	030120	000000		0	
(1)					
(1)	030122	027312		EM17	
(1)	030124	027222		EM13	:HALT 12
(1)	030126	000000		0	
(1)					
(1)	030130	027312		EM17	
(1)	030132	027243		EM14	:HALT 13
(1)	030134	000000		0	
(1)					
(1)	030136	027346		EM23	
(1)	030140	027330		EM22	:HALT 14
(1)	030142	000000		0	
(1)					
(1)	030144	027346		EM23	
(1)	030146	027243		EM14	:HALT 15
(1)	030150	000000		0	
(1)					
(1)	030152	027346		EM23	
(1)	030154	027222		EM13	:HALT 16
(1)	030156	000000		0	
(1)					
(1)	030160	027207		EM12	
(1)	030162	027330		EM22	:HALT 17
(1)	030164	000000		0	
(1)					
(1)	030166	027364		EM24	
(1)	030170	027445		DH6	:HALT 20
(1)	030172	030224		DT6	
(1)					
(1)	030174	000003		DT1:	3
(1)	030176	006	021	.BYTE	6,17.
(1)	030200	001252		SAVR1	
(1)	030202	006	017	.BYTE	6,15.
(1)	030204	001254		SAVR2	
(1)	030206	006	002	.BYTE	6,2
(1)	030210	001256		SAVR3	
(1)	030212	000002		DT5:	2
(1)	030214	006	017	.BYTE	6,15.
(1)	030216	001252		SAVR1	
(1)	030220	006	002	.BYTE	6,2
(1)	030222	001254		SAVR2	
(1)	030224	000003		DT6:	3
(1)	030226	006	004	.BYTE	6,4
(1)	030230	001262		SAVR5	
(1)	030232	006	002	.BYTE	6,2
(1)	030234	001260		SAVR4	
(1)	030236	006	002	.BYTE	6,2
(1)	030240	001256		SAVR3	

- (1)
- (1)
- (1)
- (1)
- (1)
- (1)
- (1)
- (1)
- (1)

030242 000001

CORMAX:
.END

ABRT	007000	1720#												
ACC	006750	1711#	5654	5684	5714	5744								
ADRCNT=	003735	1300*	1336*	1345#										
BCCFBK	026376	5766*	5772*	5775*	5778	5782	5794#							
BINWRD	004240	1387*	1388	1425#										
R!TW =	002000	777#												
BIT0 =	000001	639#	759	2200	2882	2886	2890	2892	3290	3297	3302	3650	3657	3662
		5770												
BIT1 =	000002	638#	758	2230	2530	2534	2538	2540	2914	2918	2922	2924	3690	3697
		3702	4879											
BIT10 =	00 000	629#	749	764	777	797	2072	2500	2754	2758	2762	2764	3202	3206
		3210	3212	3410	3417	3422	4050	4057	4062					
BIT11 =	004000	628#	748	776	796	2104	2786	2790	2794	2796	3450	3457	3462	
BIT12 =	010000	627#	747	763	770	775	795	2136	2818	2822	2826	2828	3490	3497
		3502	4090	4097	4102	4375	4382	4387	4586	4589	4598	4603		
BIT13 =	020000	626#	746	774	794	2168	2850	2854	2858	2860	3530	3537	3542	4415
		4422	4427											
BIT14 =	040000	625#	745	762	773	793	1059	1207	3570	3577	3582	4130	4137	4142
		4291	4299	4304	4455	4462	4467							
BIT15 =	100000	624#	744	761	768	772	792	1056	3610	3617	3622	4170	4177	4182
		4333	4341	4346	4495	4502	4507	4634	4637	4646	4651	5655	5685	5715
		5745												
BIT2 =	000004	637#	757	1145	2260	2562	2566	2570	2572	2946	2950	2954	2956	3730
		3737	3742	4911										
BIT3 =	000010	636#	756	783	2008	2290	2594	2598	2602	2604	2690	2694	2698	2700
		2978	2982	2986	2988	3770	3777	3782	4943					
BIT4 =	000020	635#	755	782	2040	2320	2626	2630	2634	2636	2722	2726	2730	2732
		3010	3014	3018	3020	3810	3817	3822	4817					
BIT5 =	000040	634#	754	2350	3042	3046	3050	3052	3850	3857	3862	4787	5007	5011
		5015	5017											
BIT6 =	000100	633#	753	781	2380	3074	3078	3082	3084	3890	3897	3902	4757	4847
		4975	4979	4983	4985	5039	5043	5047	5049					
BIT7 =	000200	632#	752	780	1809	1810	1826	1849	1961	2011	2017	2043	2049	2075
		2081	2107	2113	2139	2145	2171	2177	2410	3106	3110	3114	3116	3330
		3337	3342	3930	3937	3942	4211	4223	4253	4269	4295	4311	4337	4353
		4682	4850	4856										
BIT8 =	000400	631#	751	766	779	799	2440	2658	2662	2666	2668	3138	3142	3146
		3148	3970	3977	3982	4684	4694	4699	4702	4727				
BIT9 =	001000	630#	750	765	769	778	798	2470	3170	3174	3178	3180	3370	3377
		3382	4010	4017	4022	4249	4257	4262	4538	4541	4550	4555		
BRW	003306	1151	1229#											
BRX	003310	1152	1230#											
CALBCC	026400	5647*	5656	5677*	5686	5707*	5716	5737*	5788*	5795#	5825*	5826	5849	5866
CARDET=	010000	747#												
CHRCNT	004236	1385*	1389	1405*	1423#	1424								
CLK =	020000	774#	1555	1558	5166	5171								
CLK.A	001433	885#	1671											
CLRVEC	005104	1580#												
CNVRT =	104411	852#	1168	1170	1172	1174	1498	1500						
CONVRT=	104410	850#	1104	1514	5877									
CORMAX	030242	5885#												
CRCEN =	001000	769#	5112	5160	5268	5372	5439	5487	5514	5560	5605			
CRCERR=	010000	763#												
CRC.CC=	102010	5634	5797#	5822										
CRC16 =	120001	5796#												
CREAM	001316	739#	966*	1625*	1626	1628*	1633	1634*	1635	1638*				

CZDPBC MACV11 30A(1052) 02-MAY-78 13:58 PAGE 125
 CZDPBC.P11 02-MAY-78 08:23 CROSS REFERENCE TABLE -- USER SYMBOLS

TST126	021514	4755	4784#	
TST127	021570	4785	4814#	
TST13	010244	2070	2101#	
TST130	021644	4815	4844#	
TST131	021730	4845	4876#	
TST132	022014	4877	4908#	
TST133	022100	4909	4940#	
TST134	022164	4941	4972#	
TST135	022260	4973	5004#	
TST136	022354	5005	5036#	
TST137	022450	5037	5067#	
TST14	010330	2102	2133#	
TST140	022604	5068	5105#	
TST141	022760	5106	5152#	
TST142	023274	5153	5226#	
TST143	023364	5227	5260#	
TST144	023740	5261	5364#	
TST145	024226	5365	5431#	
TST146	024430	5432	5479#	
TST147	025002	5480	5552#	
TST15	010414	2134	2165#	
TST150	025176	5553	5597#	
TST151	025332	5598	5632#	
TST152	026402	5633	5818#	5885
TST153=	***** U	5819		
TST16	010500	2166	2197#	
TST17	010554	2198	2227#	
TST2	007272	1766	1799#	
TST20	010630	2228	2257#	
TST21	010704	2258	2287#	
TST22	010760	2288	2317#	
TST23	011034	2318	2347#	
TST24	011110	2348	2377#	
TST25	011164	2378	2407#	
TST26	011240	2408	2437#	
TST27	011314	2438	2467#	
TST3	007536	1800	1881#	
TST30	011370	2468	2497#	
TST31	011444	2498	2527#	
TST32	011540	2528	2559#	
TST33	011634	2560	2591#	
TST34	011730	2592	2623#	
TST35	012024	2624	2655#	
TST36	012120	2656	2687#	
TST37	012214	2688	2719#	
TST4	007600	1882	1905#	
TST40	012310	2720	2751#	
TST41	012404	2752	2783#	
TST42	012500	2784	2815#	
TST43	012574	2816	2847#	
TST44	012670	2848	2879#	
TST45	012764	2880	2911#	
TST46	013060	2912	2943#	
TST47	013154	2944	2975#	
TST5	007636	1906	1929#	
TST50	013250	2976	3007#	

ERRORS DETECTED: 0

DSKZ:CZDPBC,DSKZ:CZDPBC,SEQ=DSKZ:DUP11.MAC,DSKZ:CZDPBC.P11

RUN-TIME: 20 29 1 SECONDS

RUN-TIME RATIO: 250/52=4.7

CORE USED: 24K (47 PAGES)

DOCUMENT PAGES: 127