

DOCUMENT INFORMATION

This page provides a sequential record of changes for a multi-page drawing. Each "Revision Description" shall also include the appropriate page number(s). The change on the numbered page(s) shall be indicated with the new revision letter located in the right hand margin of the paragraph that has changed. (The term "Extensive Changes" may be entered if the loss of history is acceptable). All pages of this drawing shall carry the same revision letter as shown on this page.

Title:	795XB DISC DRIVE ERS		
Written By:	MIKE WAITE		
Model:	7957B / 7958B / 7959B		
Part Numbers:			
Supersedes:	(R8505XT A-5959-1468-1)		
Doc. Users:	ER:48 D/H: C6, H5, 22		

REVISION HISTORY

Rev	Revision Description	Date	Approved by: (name)	MF
A	AS ISSUED PER C0483042 (REV.A=REV.9)	871208	MO/MIKE WAITE <i>MW</i>	M

12

**DISC DRIVE ERS FOR
MODEL NUMBERS**

7957B

7958B

7959B

TABLE OF CONTENTS	PAGE
1.0 PURPOSE AND SCOPE	3
2.0 RELATED DOCUMENTS	4
3.0 GENERAL DESCRIPTION	5
4.0 PHYSICAL CHARACTERISTICS	8
5.0 PRODUCT CAPABILITIES	9
6.0 ENVIRONMENTAL SPECIFICATIONS	10
7.0 POWER SPECIFICATIONS	13
8.0 INTERFACE SPECIFICATIONS	15
9.0 RELIABILITY	17
10.0 SERVICEABILITY	19
11.0 REGULATORY COMPLIANCE	21
12.0 OPERATOR CONTROLS AND INDICATORS	22

1.0 PURPOSE AND SCOPE

1.1 PURPOSE

This document defines all product specifications and operating characteristics that may be offered on a warranted basis in 7957B, 7958B, and 7959B disc drives.

1.2 SCOPE

In addition to product capabilities, this document describes all mechanical, electrical, environmental, and reliability specifications for the top level product. It does not cover specifications for individual sub-assemblies. Sub-assembly IMS documents should be consulted for such details.

Also, this document does not cover specifics of the CS80 command set implemented by the 795XB disc controller. Consult the FALSTAFF III CONTROLLER ERS and the FALSTAFF III UTILITY ERS for these details.

REV. A	DATE THIS ISSUE 12/4/87	DWG. NO. A-5959-1468-1	PAGE 3	23 OF
--------	-------------------------	------------------------	--------	-------

2.0 RELATED DOCUMENTS

- 1) HP 9753X Series Product Description
- 2) HP 9753X Series OEM Product Manual
- 3) 795XB/796XB Controller ERS (A-5959-3912-1)
- 4) 795XB/796XB Controller Utilities ERS (A-5959-3913-1)
- 5) Falstaff II Power-On Self-Test Description
- 6) Falstaff III Reliability Plan (includes specification and test definitions)
- 7) Controller Board IMS (A-07957-60010-3)
- 8) Panasonic Power Supply Specification

REV. A	DATE THIS ISSUE 12/4/87	DWG. NO. A-5959-1468-1	PAGE 4	23 OF
--------	-------------------------	------------------------	--------	-------

3.0 GENERAL DESCRIPTION

3.1 Product Overview

The 7957B, 7958B, and 7959B disc drives are high performance, random access, fixed media mass storage devices. They are packaged in a compact 130mm high "Rosebud" style desktop cabinet that looks identical to the 7941/45. Formatted capacities are 81, 152, and 304 megabytes, respectively.

Seek times less than 18 msec, full HPIB bandwidth data transfer rate, and a high performance HPIB controller combine to yield performance that will meet or exceed 791X levels. In addition, the drives will be extremely rugged, with unsurpassed shock, vibration, and temperature performance.

Factory cost at introduction will be under \$1800 for the 7959B, under \$1700 for the 7958B, and under \$1600 for the 7957B. It is expected that this combination of mid-range capacity, low cost, high performance, and compact size will quickly make the 795XB the preferred choice over today's 7941/45 and 7912/14 products.

The drives are based on Hewlett-Packard designed and built disc mechanisms. The 7959B uses the HP 97536A mechanism, while the 7958B uses the HP 97533A, and the 7957B uses the HP 97532A. All mechanisms use 5.25" thin film media with thin film read/write heads. Each has a rotary actuator with one head per surface, and all use embedded servo on each surface. The interface to the mechanism conforms to the ESDI industry standard.

The 795XB series have four major sub-assemblies: the disc mechanism, HPIB Controller PCA, power supply, and cabinet (with associated cables, etc.)

The standard configuration for this product is the desktop package. The desktop unit can also be installed into any floor mount "pod" style cabinets that accept "Rosebud" stack-modules (the feet must be removed from the drive package in this case). The drives can also be installed in 19" EIA racks using the 19500B Rackmount Kit.

REV. A	DATE THIS ISSUE 12/4/87	DWG. NO. A-5959-1468-1	PAGE 5	23 OF
--------	-------------------------	------------------------	--------	-------



3.0 GENERAL DESCRIPTION (cont'd)

3.2 Feature Summary

- * Multi-user capabilities with low entry cost
 - 304, 152, and 81 megabyte capacities
 - High performance (greater than or equal to 7914)
 - Unsurpassed shock/temperature performance
- * Compact 130 mm Rosebud stack-module package
- * HP-IB/CS80 interface
- * 794X/5XA software compatible (in both on-line and diagnostic modes)
- * Environmental specifications broader than 791X, 794X, or 795XA
- * Improved serviceability/reliability through new controller features
 - Autosparing
 - Gate Array which reduces component count
- * Improved performance
 - Reduced F/W overhead (0.8 msec)
 - Enhanced channel utilization algorithm during both reads and writes

REV. A	DATE THIS ISSUE 12/4/87	DWG. NO. A-5959-1468-1	PAGE 6	23 OF
--------	-------------------------	------------------------	--------	-------

3.0 GENERAL DESCRIPTION (cont'd)

3.3 Products and Configurations

3.3.1 Standard Configuration

The standard configuration for either drive is a desktop enclosure.

7957B	81 Mbyte desktop unit
7958B	152 Mbyte desktop unit
7959B	304 Mbyte desktop unit

3.3.2 Options

Option 015: 230 Volt operation
Option 550: Delete HPIB cable

3.3.3 Accessories

19500B	19" EIA Rackmount Kit
92211A	Pod-type floor mount cabinet

4.0 PHYSICAL CHARACTERISTICS

4.1 Desktop

Length - 285 mm (11.2")

Width - 325 mm (12.8")

Height - 132 mm (5.2") with cabinet feet
129 mm (5.1") without cabinet feet

Weight - 10.6 kg (23.2 lb)

Shipping weight - 13.6 kg (29.9 lb)

4.2 Rackmount

The desktop package is placed on a 19500B Rackmount Tray. See 19500B documentation for rack mount specifications.

5.0 PRODUCT CAPABILITIES

5.1 Capacity

Item	Data Bits Per	Data Bytes Per	Sectors Per	Tracks Per	Heads Per
Byte	8				
Sector	2,048	256			
Track	129,024	16,128	63		
7957B Hd	163,731,456	20,466,432	79,947	1,269	
58/9B Hd	202,825,728	25,353,216	99,036	1,572	
HP 7957B	654,925,824	81,865,728	319,788	5,076	4
HP 7958B	1,216,954,368	152,119,296	594,216	9,432	6
HP 7959B	2,433,908,736	304,238,592	1,188,432	18,864	12

5.2 Seek Times:

	TYPICAL	WORST CASE
Track-to-track	3 milliseconds	4 milliseconds
Average	17 milliseconds*	19 milliseconds
Full stroke	32 milliseconds	36 milliseconds
Incremental Head Switch	3 milliseconds	4 milliseconds

* Aggressive seeks option turned on.

5.3 Spindle Speed

3348.2 RPM +/- 1%

8.96 millisecond average latency

5.4 Transfer Rates

Burst: 1000 kbytes/sec

Typical: 853 kbytes/sec (multi-sector transfers with all sectors contiguous within one track)

5.5 HPiB Controller Firmware Overhead

0.8 milliseconds per read or write request

6.0 ENVIRONMENTAL SPECIFICATIONS

6.1 Temperature

- 6.1.1 Operating 5 to 45 degrees C (41 to 113 degrees F)
- 6.1.2 Non-Operating -40 to +65 degrees C (-40 to +149 degrees F)
- 6.1.3 Recommended 20 to 25.5 degrees C (68 to 78 degrees F)
- 6.1.4 Slew Rate ≤ 20 degrees C per hour
- 6.1.5 SPECIAL NOTE:
If shipment or storage is at temperatures of 32 degrees F or below, allow two hours of warmup at room temperature before operating. Failure to do so may result in severe damage to the unit.

6.2 Humidity

- 6.2.1 Operating * 8-80% non-condensing
- 6.2.2 Non-Operating* 8-80% non-condensing
- 6.2.3 Non-Operating Humidity Supersoak *
+65 C @ 80% relative humidity for 24
hours, no permanent damage (other than
cosmetic change to internal and exterior
plated metal surfaces)

* Excludes all conditions which can cause condensation in or on the disc drive.

6.3 Shock

- 6.3.1 Operating [half sine, duration ≤ 11 ms]
 $\leq 4g$ peak, no data loss, and no damage
- 6.3.2 Non-Operating
20g peak half sine, ≤ 11 ms duration, no damage or data loss
- 6.3.3 RECOMMENDED LIMIT: $< 1g$ peak in operating or non-operating state

7.0 POWER SPECIFICATIONS

7.1 Input Voltage (rms) [see chart below]

7.2 Input Frequency [see chart below]

7.3 Maximum Current (rms) [see chart below]

7.4 Typical Current (rms) [see chart below]

7.5 Maximum Power [see chart below]

7.6 Typical Power [see chart below]

Setting	Input Voltage (V rms)	Frequency (Hz)	Current (A rms) (Max/Typical)	Power (V-A) Max/Typical
115 V	90-132	47.5-66	1.8 / 1.0	144 / 92
230 V	180-264	47.5-66	1.2 / 0.6	198 / 115

7.0 POWER SPECIFICATIONS (cont'd)

7.7 Power Fail Recovery

On loss of power, no damage or data loss will occur.

7.8 Transient Susceptibility

7.8.1 Oscillatory (100 kHz ringing wave): < 1.5 kV and < 50 A

RECOMMENDED LIMIT: < 500 V

7.8.2 Unidirectional (one 20 usec pulse): < 1.0 kV and < 100 A

RECOMMENDED LIMIT: < 500 V

Transients within the ranges above will cause no operator perceivable degradation in performance or damage.

7.9 Conducted Susceptibility

Power line noise below the following levels will cause no operator perceivable errors, data loss, or damage.

30 Hz to 50 kHz <= 3V rms

50 kHz to 400 MHz <= 1V p-p

RECOMMENDED LIMIT: below 0.5 V rms, any frequency

7.10 Line Surge/Sag From Nominal

+ or - 20% of typical line voltage for 30 seconds, or + or - 30% of typical line voltage for 0.5 seconds will cause no damage, data loss, or require no operator intervention.

7.11 Distortion

< 5% with flat harmonic distortion

8.0 INTERFACE SPECIFICATIONS

8.1 Mechanical/Electrical

This product interfaces to host computer systems via HPIB as implemented by HP's proprietary MEDUSA interface chip.

8.2 Command Set

The 7957B, 7958B, and 7959B use a CS80 implementation that is software compatible with the 795XA and 796XB products. This compatibility is guaranteed for all on-line commands and status conditions, and also for all diagnostic and utility commands as well.

8.3 Host CPU Software Compatibility - On-Line & Diagnostic

The 7957B, 7958B, and 7959B are "plug-compatible" with all host system hardware/software implementations that support the 795XA. All OS, utility, and diagnostic software for such systems will be compatible.

In the event the host system does not use the CS80 DESCRIBE feature to acquire configuration information, minor updates to system software may be needed in order to utilize the drive's full address space.

8.4 HPIB Identify Bytes

Responses to an HPIB identify are as follows:

7957B: 02H, 2CH
7958B: 02H, 2DH
7959B: 02H, 2EH

8.0 INTERFACE SPECIFICATIONS (cont'd)

8.5 CS80 'DESCRIBE' Command Response

In response to a CS80 'describe' command, the 795XB disc controller will return the following information to the attached computer.

CONTROLLER DESCRIPTION FIELD

INSTALLED UNIT (1 bit for each unit) :
 **** 1000 0000 0000 0001 ****
 MAXIMUM TRANSFER RATE: 1000 K-BYTES/SEC
 CONTROLLER TYPE: 0
 (INTEGRATED SINGLE-UNIT CONTROLLER)

UNIT 0 DESCRIPTION FIELD	7959B	7958B	7957B
--------------------------	-------	-------	-------

GENERIC DEVICE TYPE: 0 (FIXED DISC)			
HP PRODUCT NUMBER	079591	079581	079571
NUMBER OF BYTES PER BLOCK	256	256	256
NUMBER OF BLOCKS WHICH CAN BE BUFFERED .	64	64	64
RECOMMENDED BURST SIZE	0	0	0
BLOCK TIME (microseconds)	265	265	265
CONTINUOUS AVG TRANS RATE (KBYTES/SEC) .	768	768	768
OPTIMAL RETRY TIME (tens of millisec) ..	80	80	80
ACCESS TIME PARAMETER	500	500	500
MAXIMUM INTERLEAVE FACTOR	1	1	1
FIXED VOLUME BYTE (one bit per vol): **** 0000 0001 ****			
REMOVEABLE VOLUME BYTE (one bit per vol): **** 0000 0000 ****			

VOLUME 0 DESCRIPTION FIELD

MAXIMUM CYLINDER ADDRESS	1571	1571	1268
MAXIMUM HEAD ADDRESS	11	5	3
MAXIMUM SECTOR ADDRESS	62	62	62
MAXIMUM SINGLE-VEC ADDRESS	1188431	594215	319787
CURRENT INTERLEAVE FACTOR	1	1	1

9.0 RELIABILITY

9.1 Data Error Rate:

9.1.1 Definitions

A recoverable error is a data error that has been successfully corrected by use of either retries or ECC (error correction code). Unrecoverable implies that neither retries or ECC could recover incorrect data.

9.1.2 On-Line Data Error Rate

When running under the file system control of any HP machine, and when operated within environmental specifications, the following error rates are warranted:

RECOVERABLE \leq 10 recoverable errors in 1.0 E11 bits transferred

UNRECOVERABLE \leq 10 unrecoverable errors in 1.0 E13 bits transferred

9.1.3 Data Error Rate Under Internal Utilities

The 795XB disc controller can execute special utility programs contained in controller firmware. Among other functions, these utilities perform special error rate tests. The internal error rate tests can only be initiated by a diagnostic program running on a host computer, and are not accessible by a user interacting through a standard HP file system. The error rate tests are intended to be used for diagnostic purposes, and hence report more detailed information than would be supplied under file system access. Much of this detailed "error" information is not indicative of impaired storage or retrieval capabilities, but is monitored in the factory for process control purposes. Many of these "errors" would never be seen by a user or operator running under file system control. As a result, the recoverable data error rate allowed when running these tests is slightly higher than that allowed under file system access. The unrecoverable error rate remains unchanged.

Recoverable \leq 10 recoverable errors in 1.0 E10 bits transferred

Unrecoverable \leq 10 unrecoverable errors in 1.0 E13 bits transferred.

9.0 RELIABILITY (cont'd)

9.2 Seek Error Rate

The seek error rate is ≤ 1 error in $10 E6$ seeks.

9.3 Failure Rate

Warranty failure rate at ship release: $\leq 4\%$

Warranty failure rate within 12 months of ship release: $\leq 3\%$

9.4 Lifetime Power-On Hours & Start/Stop Cycles

Minimum Useful Life: 5 years or 40,000 hours

Start/Stop Cycles: 7,000

REV. A	DATE THIS ISSUE 12/4/87	DWG. NO. A-5959-1468-1	PAGE 18	23 OF
--------	-------------------------------	---------------------------	---------	----------

10.0 SERVICEABILITY

10.1 BMMC

The maintenance charges, as of Dec. 1, 1987, for the 795XB drives are listed below:

	7957B	7958B	7959B
FMMC:	\$14.00	\$15.00	\$16.00
BMMC:	\$28.00	\$29.00	\$30.00
SMMC:	\$35.00	\$37.00	\$39.00

The products also have a media retention option to the service contract. This option, R01, allows customers with sensitive data to keep their HDA upon failure.

10.2 Mean Time to Repair (MTTR)

Since the drive has only three field replaceable assemblies and has extensive diagnostic tools, the mean time to repair has been estimated at 1/2 hour. This figure is based on the assumption that the CE has been trained on the product and has a working knowledge of the diagnostic tools.

10.3 Preventive Maintenance Cycle

There are no operating or maintenance adjustments on the 795XB Disc Drives. Therefore, an annual PM is not required.

10.0 SERVICEABILITY (cont'd)

10.4 Special Service Features

Because of their nature, disc drives continue to develop media defects throughout their useful life. As a result, the local CE is called out in many cases to spare out these defects. The 795XB disc drives include a special feature intended to greatly reduce this type of service call. This new feature, called autosparing, allows the disc drive to automatically spare out any marginal or unrecoverable media defects occurring during normal operation. Although normally available, this feature may be deselected by the host during the "Set Options" command.

A further enhancement of the autosparing feature provides the user with the capability to initialize media and spare defects offline. This additional feature may be invoked by selecting unused positions of the HPIB thumbwheel and then powering up the drive.

The drives have an extensive power-on self-test that tests the general functionality of the mechanism, the controller PCA, and the ESDI interface linking them. Pass/fail results are displayed on the two LEDs on the disc drive's front panel. See Section 12.3 for an LED state table.

System diagnostic capabilities include support on the following utilities:

HP1000:	EXER
HP3000:	CS80 UTIL
HP85:	EX795X

The drives are also supported on the Response Center's Predictive Support program. If a customer opts for this capability, the drives' logs are monitored periodically to ensure that predetermined threshold values for faults and data errors have not been exceeded. If a threshold is exceeded, a service call is generated.

The 795XB drives that are on HP3000 systems also have the capability for Remote Support from the Response Centers. This program gives the Response Centers the ability to access systems remotely and perform diagnostics on the disc drive, thus possibly preventing a service call.

If, in the troubleshooting process the CE needs to verify that the mechanism is bad, cables W1 and W3 are long enough to allow a replacement mechanism to be tested without removing the suspect mechanism from the cabinet. This feature saves time for the CE by making troubleshooting easier and more efficient.

11.0 REGULATORY COMPLIANCE

11.1 RFI

- 11.1.1 USA: Complies with the limits for a Class B computing device pursuant to Sub part J of Part 15 of the FCC Rules.
- 11.1.2 EUROPE: Meets EMI level FTZ 1046/84 and provides manufacturer's declaration.

11.2 Safety

- 11.2.1 CSA certified to CSA 22.2 No. 154
- 11.2.2 Meets all applicable safety standards of IEC 380 and IEC 435
- 11.2.3 UL listed to UL 114 and UL 478
- 11.2.4 VDE 0730 Part II

REV. A	DATE THIS ISSUE 12/4/87	DWG. NO. A-5959-1468-1	PAGE 21	23 OF
--------	-------------------------	------------------------	---------	-------

12.0 OPERATOR CONTROLS AND INDICATORS

12.1 Power-On Switch

The power-on switch is located on the bottom left-hand corner of the front panel. A switch on the back of the drive allows conversion from 115V operation to 230V operation. This switch should be properly adjusted to operate at the customer's existing line voltage.

12.2 HPIB Address Switch

A thumb wheel on the back panel is used as the HPIB Address Switch. Positions 0-7 select the HPIB address; the drive should be powered off when changing the HPIB address between positions 0-7. Positions 8 and 9 are used in conjunction with the offline format and autospare capability.

12.3 Fault/On-Line Indicator

The fault/on-line indicator is the red/green display on the front panel that signals the operating status of the drive. The table on the next page shows the states of the indicator for various conditions of the drive.

REV. A	DATE THIS ISSUE 12/4/87	DWG. NO. A-5959-1468-1	PAGE 22	23 OF
--------	-------------------------------	---------------------------	---------	----------



12.0 OPERATOR CONTROLS AND INDICATORS (cont'd)

12.3 Fault/On-Line Indicator (cont'd)

RED	GREEN	DRIVE STATUS
ON	ON	On for 5 seconds at POWER ON while controller runs self test and disc mechanism spins up. If either controller self test or mechanism spin up fails, then both LEDs remain on.
OFF	Flashing	On for 10 seconds for mechanism self test.
ON	OFF	Disc drive has failed mechanism self test. The disc drive may still be accessed by the Host CPU to run diagnostics.
OFF	ON	Disc drive is in a ready state.
OFF	Flashing	Disc drive is active (i.e., processing a command).

LED STATE TABLE