

Mini-Micro Systems

THE MAGAZINE FOR COMPUTER SYSTEMS INTEGRATION

A CAHNERS PUBLICATION

SPECIAL REPORTS: DATA COMMUNICATIONS

- Real-time UNIX seizes new products, markets
- FEPs ease migration to new LAN protocols
- IBM's Token-Ring: What are the alternatives?
- Chip set paves the way to Token-Ring access



With modularity, Counterpoint builds multiuser computers

ALL IN ONE.



Introducing the Freedom[®] ONE from Liberty Electronics

The Freedom ONE is the one terminal for all of your ASCII needs. With the Freedom ONE you don't pay more for advanced features. With the Freedom ONE you don't sacrifice features just because you pay less. At \$449 the Freedom ONE gives you the best of all worlds—in one terminal.


The Freedom ONE is designed to be there with all the features you need whatever your application. A 14-inch flat screen gives you the ultimate in crisp, clear characters in either 80 or 132 column display formats. Popular emulations like Freedom 200, WY-50, Viewpoint A2, TeleVideo 950, and ADM 31 let you fully utilize all

your existing applications programs. An adjustable height keyboard with 44 easy to program keys (88 with shift) lets you tailor the key layout and functions to your liking. Compact and attractive styling gives your workspace a state-of-the-art look with room to spare. These are just a few of the no-compromise, unbeatable features you get standard with the Freedom ONE.

For more information call Liberty Electronics today (415) 543-4353, and ask for it all. Ask for the ONE.

 **Liberty**
We Make Terminals

CIRCLE NO. 1 ON INQUIRY CARD



How many more reasons do you need to Unplug your computer?

Until now, connecting 128 terminals to your computer meant one thing. A myriad of cards taking up precious space on the backplane. And accomplishing nothing but communications. All of which could frustrate almost any self-respecting system designer into hanging up his calculator.

Well, at Systech, we understand the serial communications problems of a multi-user system. So we developed The Unplug™ asynchronous distributed multiplexer that can be used with any Multibus®, VMEbus or Multibus® II system.

The Unplug can take those 128 connections off the back of the computer and turn them into just one. And presto, you've got all the expansion slots you need for more important things. Like disks. Streaming tapes. More CPU power. A synchronous communications processor. And your imagination.

You see, what we did was move part of the computer's operating system—the part devoted to managing traffic to and from the terminals—out of the computer and into The Unplug. Giving the host computer the freedom to concentrate on more important tasks.

We know it sounds simple. And the truth is, it is. In fact, you might wonder why no one thought of it before. Then again, no one else has our commitment to make your job easier. And a lot more gratifying.

Just give us a call at Systech to hook up with The Unplug. Then you can start figuring out what you want to add on next.

Instead of trying to figure out how to untangle all those wires.

Systech Corporation, 6465 Nancy Ridge Drive, San Diego, CA 92121, (619) 453-8970.


CIRCLE NO. 2 ON INQUIRY CARD

The Unplug.

An outlet for your frustrations.


When you're ready to expand, you simply run one cable from the last Unplug to the next. And you've hooked up 8 new users, without ever opening the computer cabinet.

The Unplug is a trademark of Systech Corporation. Multibus is a registered trademark of Intel Corporation.



SYSTECH

© 1986 Systech Corporation.
The Unplug patent pending.



SCIENTIFIC
CLOPEDIA

ENCYCLOPEDIA

DIGITAL

BLACK BOOK - ILLUSTRATION - PRINTING

DO WEST COAST ARTISTS

ESKES JAMES

TEXAS INSTRUMENTS

ADVANTAGE

IBM


IBM

TI's new OmniLaserTM page printer can turn your PC into a desktop publishing system.

Combined with the right software, you can now have a publishing house right on your desk top.

If you have a personal computer, you are ready to get started. TI's OmniLaser with any IBM[®]-compatible, Macintosh[™], or virtually any PC, and the right software, can help you eliminate costly typesetting, outside design work and printing. At 300-dots-per-inch resolution, the difference between laser printing and daisy wheel or dot matrix is more than mere improvement. It's light years ahead.

The OmniLaser Series 2000 family from Texas Instruments is available in three desktop models designed to address workstation and shared-resource environments at 8 and 15 pages per minute, respectively. Both the 2108 and 2115 feature the



PostScript[®] page-description language, which allows full integration of text, graphics and scanned images on a single page. Your business communications will be more eye-appealing and carry more credibility. And the Model 2015 was designed to handle text and business graphics in a shared-resource environment. All three OmniLasers, with their standard interfaces and emulators, allow you to take full advantage of your present business computer applications, as well. And they'll give you unparalleled resolution in both text and graphics. Blacks are black, whites are white, and you control the shades of gray.

Overall, TI's second-generation laser printers offer up to 10 times the duty cycle, 15 times the machine life and 5 times the paper capacity offered on their first-generation counterparts. These advances, coupled with lower maintenance cost and user-replaceable consumables, significantly reduce the costs of ownership. In fact, at pennies per page, the OmniLaser's per-page cost is among the lowest in the industry.


TI OmniLasers and the power of PostScript.

PostScript is the page-description language that drives OmniLaser Model 2108 and 2115 printers to their full

capabilities, including rotated type, textures, patterns, halftones, images in any size and shape, and a wide variety of typefaces. Each font has one definition that is used as the basis for any point size. You have complete control over the size and positioning of your text and graphics. PostScript also has built-in commands for point specification, circular arcs, curves, etc. You can perfect your text and graphics on your OmniLaser and PC, and then take your original to a high-quality production facility and skip all the headaches of mechanical assembly. Whether you're composing newsletters, product data bulletins, ad proofs, business presentations, technical manuals, or any type of document, you'll find that with the power of PostScript, you are only limited by your imagination.

OmniLasers. They bring power, flexibility and affordability to the world of desktop publishing.

Turn your desk top into a publishing house. For more information on the new OmniLaser 2000 Series page printers from Texas Instruments, call toll-free 1-800-527-3500.



Ours Theirs

The OmniLaser uses the direct positive-imaging exposure process as opposed to the reverse-imaging exposure process used by many other laser printers. The difference, as shown above, is obvious.

31638

© 1986 TI

OmniLaser is a trademark of Texas Instruments Incorporated.


IBM is a registered trademark of International Business Machines Corporation.

Macintosh is a trademark of McIntosh Laboratory, Inc.

PostScript is a registered trademark of Adobe Systems Incorporated.



TEXAS INSTRUMENTS



p. 25 . . . Counterpoint introduces its System 19K multiuser computers. Art direction and design by Blankenship-Tavares. Courtesy of Counterpoint Computers.

INTERPRETER

With modularity, Counterpoint builds multiuser computers 25
Strong OEM alliances should knock down entry barriers

Software views: In battle over UNIX, POSIX is a peacemaker 27
Interface standard could put an end to shell game

Yes, this really is the year of the LAN 28
Corporate activity signals opportunities for system integrators


New satellites provide links to remote terminals 37
Clean Ku-band frequencies dish out data economically

IBM 'fixes' System/36 as part of product blitz 43
Improved connectivity will strengthen weak middle tier

Artificial intelligence rides out the slump 50
Boomlet helps stabilize emerging AI market

*DEC DIRECTIONS

(begins opposite Page 128)



p. 50 AI survives the slump

Mini-micro hybrids rival local networks D1
A hybrid system combines a DEC minicomputer with IBM microcomputers to obtain higher speed and lower cost than are possible with local area networks

DEXPO West New Products D11

Other New Products D15

*Appearing in issues of subscribers who indicate they have DEC computers

Cahners Publishing Company • A Division of Reed Publishing USA • Specialized Business Magazines for Building and Construction • Electronics and Computers • Foodservice • Manufacturing • Book Publishing & Libraries • Medical/Health Care. MINI-MICRO SYSTEMS (ISSN 0364-9342) is published monthly with additional issues in February, April, June and November by Cahners Publishing Company, A Division of Reed Publishing USA, 275 Washington St., Newton, MA 02158. William M. Platt, President; Terrence M. McDermott, Executive Vice President; Jerry D. Neth, Vice President of Publishing Operations; J.J. Walsh, Financial Vice President/Magazine Division; Thomas J. Dellamaria, Vice President Production and Manufacturing; Terrence M. McDermott, Group Vice President. Copyright 1986 by Reed Publishing USA, a division of Reed Holdings Inc., Saul Goldweitz, Chairman; Ronald G. Segel, President and Chief Executive Officer. Circulation records are maintained at Cahners Pub-

INTEGRATION

FEATURES

Feature Highlights57

Real-time UNIX seizes new products, markets61
 Real-time UNIX, long considered a contradiction in terms, suddenly becomes a growth industry due to government and large corporation mandates

Linking databases forces new strategies83
 As data communications options multiply, applications developers must cope with distributed processing as a basic rule of programming

FEPs ease migration to new LAN protocols93
 An established technology, front-end processors help users preserve investments in local area networks while offering a direct path for incorporating standard, and future, network protocols

IBM's Token-Ring: What are the alternatives?105
 IBM's "serious" LAN has finally arrived, but other LANs should be able to coexist with the Token-Ring

Chip set paves the way to Token-Ring access121
 A chip set is essential for system integrators who want to build their own custom LAN adaptor cards to achieve system-to-system dialogue

DEPARTMENTS

Editorial Staff6

Editorial9


Letters12

Breakpoints15


New Products135

Index to Advertisers154

Mini-Micro Marketplace155



p. 93 FEPs offer path



p. 105 This is Token-Ring's year

lishing Co., 270 St. Paul St., Denver, CO 80206. Second class postage paid at Denver, CO 80202 and additional mailing offices. Postmaster: Send address changes to MINI-MICRO SYSTEMS, 270 St. Paul St., Denver, CO 80206. MINI-MICRO SYSTEMS is circulated without charge by name and title to U.S.- and Western European-based corporate and technical management, systems engineers and other personnel who meet qualification procedures. Available to others at the rate of \$65 per year in the United States; \$70 in Canada and Mexico; \$95 surface mail in all other countries; air mail surcharge, \$35 (16 issues). Special HANDBOOK issues, \$15. Single issues, \$5 in the United States; \$6 in Canada and Mexico; \$7 in all other countries.



RICH COBOL

LPI-COBOL runs on a host of high-performance UNIX super-micros, it's compatible with RM/COBOL, and it has the features of a mainframe COBOL: powerful debugger, informative error messages, cross-language calls, and sophisticated optimization.

And, because LPI-COBOL is a true compiler, your applications will run up to 30 times faster than with competitive products.

For more information, contact Language Processors, Inc., 400-1 Totten Pond Rd., Waltham, MA 02154 (617) 890-1155.




LPI-RPGII, LPI-COBOL, LPI-PL/I, LPI-BASIC, LPI-FORTRAN, LPI-PASCAL, LPI-C, LPI-DEBUG
LPI is a trademark of Language Processors, Inc. UNIX is a trademark of AT&T. RM/COBOL is a trademark of Ryan-McFarland Corp.

CIRCLE NO. 3 ON INQUIRY CARD

Stay Informed

Turn to the Inmac catalog for helpful hints and problem solving advice from our engineers. And for over 2,400

computer supplies and accessories displayed and described in detail. All have our exclusive 45-day trial and minimum 1-year guarantee.



FREE!

Call or write today. Yes...
rush me your catalog
today.

800-547-5444

inmacTM

Name _____
Company _____
Address _____
City _____ State _____ Zip _____
Phone (____) _____
2465 Augustine Drive, Santa Clara, Ca. 95054

CIRCLE NO. 4 ON INQUIRY CARD

STAFF

Vice President/Publisher
S. Henry Sacks

Editor-in-Chief
George V. Kotelly

Managing Editor
James F. Donohue

Senior Editor: **David Simpson**
Senior Editor: **Doug Pryor**

Western Editor: **Carl Warren**
Irvine, (714) 851-9422
Associate Western Editor: **Mike Seither**
San Jose, (408) 296-0868
European Editor: **Keith Jones**
London: (011-441-661-3040)

Associate Editor: **Michael Tucker**
Associate Editor: **Jesse Victor**

Assistant Editor/New Products: **Megan Nields**
Assistant Editor/Research: **Frances C. Michalski**

Contributing Editors

Andrew Allison
Mini/Micro Computer
Product and Market Consultant
Raymond C. Freeman Jr.
Freeman Associates
Special Features Editor: **Wendy Rauch-Hindin**
Dix Hills, N.Y.
(516) 667-7278
Washington, D.C.: **Stephen J. Shaw**
(202) 387-8666
Gene R. Talsky
Professional Marketing Management Inc.
Robert E. Peterson, Jr., Edward Teja
Freehold Corp.

Editorial Production

Senior Copy Editor: **Arsene C. Davignon**
Production Editor: **Mary Anne Weeks**

Editorial Services

Lisa Kramer, Terri Gellegos
Assistant to the Publisher: **Linda L. Lovett**

Art Staff

Art Director: **Cynthia McManus**
Director of Art Dept.: **Norm Graf**

Production Staff

VP Production: **Wayne Hulitzky**
Director/Production: **John Sanders**
Supervisor: **William Tomaselli**
Production Manager: **Betsy Cooper**
Composition: **Diane Malone**

Editorial Offices

Boston: 275 Washington St., Newton, MA 02158, (617)964-3030. **Irvine:** 2041 Business Center Dr., Suite 109, Irvine, CA 92715. **Los Angeles:** 12233 W. Olympic Blvd., Los Angeles, CA 90064. **San Jose:** 3031 Tisch Way, San Jose, CA 95128. **London:** P.O. Box 37E, Worcester Park, Surrey, KT4 8RQ, England.

Reprints of Mini-Micro Systems articles are available on a custom printing basis at reasonable prices in quantities of 500 or more. For an exact quote, contact Katie Pyziak, Cahners Reprint Service, Cahners Plaza, 1350 E. Touhy Ave., Box 5080, Des Plaines, IL 60018. Phone (312)635-8800.



Persyst. The wise choice for PC data comm. Take a look!

Persyst's DCP-88 is a PC data comm solution worth eyeing. A front-end processor smart enough to offload comm processing so your PC can sink its claws into your application.

And the DCP-88 works with your IBM-PC, PC/XT, PC-AT, PC/RT or PC-compatible. To turn any PC into a real communications work station—not a way station.

DCP-88's processor keeps your PC working on applications, not protocol overhead. The onboard processor offloads comm overhead, freeing your PC to focus on applications.

Choose from two DCP-88 models—each with a processor poised to swoop into action. The DCP-88/VM with its 4.77 MHz 8088 is capable of handling most applications. Or, for nearly twice the throughput, select the DCP-88/VMX with a 7.16 MHz processor.

Either way, you get a powerful co-processor so your system's comm performance soars.

Dual-ported onboard memory speeds data transfer. With up to 512 KB memory, the DCP-88 has more than enough capacity to handle the most sophisticated comm applications.



And the board's dual ported memory architecture allows data to pass directly between processors at memory speed—so communications fly through your system.

Multiple lines and protocols for a multitude of applications. Adaptable as it is wise, the DCP-88 blends into your comm environment. With up to four serial ports, for example, you can tie to multiple hosts or PCs. Plus, the DCP-88 fully supports asynch, bisynch, SDLC and HDLC protocols so your system's smart enough for any application.

Supports printers up to 1200 lpm. The DCP-88 spans all your comm needs, providing high speed printer support via its optional parallel port. Up to 600 lpm on the DCP-88/VM and 1200 lpm on the DCP-88/VMX.

So don't let your PC comm stick you out on a limb. Not when the solution is staring you in the face. Call or write Persyst for a complete look at our DCP-88 line.

EMULEX PERSYST PERSYST


Emulex/Persyst, 3545 Harbor Boulevard,
P.O. Box 6725, Costa Mesa, California 92626
In California, call 714/662-5600 • Outside California,
call toll free 800/854-7112

IBM, PC, PC/XT, PC-AT and PC-RT are registered trademarks of International Business Machines.
8088 is a registered trademark of Intel Corporation.


CIRCLE NO. 5 ON INQUIRY CARD

Make the Connection


IBM PC/XT® and Compatibles




Leading Edge Personal Computers



IBM AT™ and Compatibles



The Leading Edge® Model "L" Series™ Modems *Hayes® Compatible*



Databases
Mainframes
Telecommuting
Networking
Telex
Electronic Mail
Data Transfer
Tele-Communicating
Wall Street
News

	Model "L"™	Hayes®
1200B	\$149.95	\$549.00
2400B	\$289.00	\$799.00*

Leading Edge®, the first company to develop affordable IBM®-compatible personal computers, now offers the first affordable Hayes-compatible modems: The Model "L" Series™ Modems.

Like our personal computers, the Model "L" Series Modems do everything the industry standard modems do, except cost a lot.

For example, they can access databases. And databases represent what could be considered one of the largest compilations of information in the world, with data on every topic from the stock market quotes to corporate histories to the current exchange rates.

Model "L" Series Modems can send and receive data to and from personal computers all over the world. You can send electronic letters to locations all over the country or over the ocean. It's infinitely faster than conventional mail and a lot less expensive.

They allow you to use your own personal computer to send and receive Telexes.

They can also provide access to mainframes, making

your personal computer a personal work station wherever it is — in the office, at home or on the road.

And Model "L" Series Modems allow you to network with other personal computers. You can share data or share programs. You can even transfer files between two completely incompatible systems (i.e. Apples® and IBMs).

Yet at \$149.95 and \$289 respectively, the 1200B and 2400B Model "L" Series Modems are priced below equivalent Hayes Modems. In fact the Model "L" Series 1200B, including software and a 24-month warranty, is priced at one third the price of an equivalent Hayes Modem.

We're just reaffirming what we proved with personal computers. You don't have to pay a lot to get a lot.

To make the connection for yourself, call **1-800-USA-LEAD** for more information and a dealer near you, (617) 828-8150 in MA.



Leading Edge Hardware Products, Inc.
225 Turnpike Street, Canton, MA 02021 (617) 828-8150


Leading Edge Hardware Products, Inc. Fortune Fleet Division
55 Providence Highway, Norwood, MA 02062

Leading Edge is a registered trademark and Model "L" Series and Model "D," "L," "M," and "MH" are trademarks of Leading Edge Products, Inc. IBM and XT are registered trademarks and AT is a trademark of International Business Machine Corp. Hayes is a registered trademark of Hayes Microcomputer Products, Inc. Apple is a registered trademark of Apple Computer, Inc. *Full Size Card

CIRCLE NO. 6 ON INQUIRY CARD

EDITORIAL

SOFTWARE INDUSTRY GOES CORPORATE



The spectacular growth period for the personal computer software market has ended. In its place has come stability and maturity. For some companies, these market conditions have proved advantageous. For many others, though, the results have proved disastrous. Numerous acquisitions, mergers, and bankruptcies have weeded out the weak, solidified the strong, and neutralized the new. And seemingly overnight, the software industry changed from a pop culture to a corporate structure. But more important, users should benefit immensely from the transformation.

Until recently, software products were sold via technology hype and accompanied by flashy and dazzling promotion. It worked for a long time. Software sales skyrocketed off the charts, fortunes were made and personalities achieved international fame.

Sometime last year, though, the software market saturated. At that time, according to *Business Week*, it had blossomed into a \$5 billion industry with about 14,000 companies and some 27,000 different products.

But the flood of software has produced an equal flood of user complaints. For example, a recent *PC World* magazine survey about software education revealed that more than 70 percent of the respondents were dissatisfied with their software. Nearly 50 percent stated that programs did not meet advertised performance and that adequate software support was offered only occasionally. Another 30 percent felt they were misled as to a program's capabilities. And 85 percent believed that software publishers should be held responsible for product performance.

And that's not all. Other user complaints include deficient documentation, lack of telephone help lines, and few money-back warranties. What's more, in a related *PC World* survey, almost 70 percent of the respondents claimed they had illegally copied software to try it out before purchase.

It's understandable, then, that market researcher InfoCorp expects personal computer

software sales to plummet to a 15 percent compound annual rate over the next five years, down from the 64 percent yearly growth over the past five years. Most new companies, says *Business Week*, are being forced to go after small niche markets or to sell their products to the market leaders. The result? Market leaders (Lotus Development Corp., Ashton-Tate, IBM Corp., Apple Computer Inc., Microsoft Corp. and Micro Pro International Corp.) have markedly increased their market share. In fact, claims InfoCorp, the top 15 software companies accounted for 72 percent of the \$2.2 billion general-applications software market in 1985.

But, whether an industry leader or a new challenger, all software companies must now deal with new pricing and distribution rules. Before, companies made the majority of their sales through retail channels. Now, however, after retail saturation, large corporations have entered the market and have dominated the software sales scene.

And in these corporations, data processing/management information service managers want to buy via direct sales channels. In addition, corporate managers insist on pre- and post-sales support, service and training. They also insist on getting volume discounts, doing away with copy protection and implementing site licensing.

All of these efforts are infusing much-needed professionalism into the software industry. And satisfied software users can dramatically affect the software business climate. Analysts unanimously agree that corporate purchases of personal software should rise significantly this year. Undoubtedly, if software companies adhere to corporate purchase agreements, then even small-volume and individual buyers will come out on top.

George V. Kotelly

George V. Kotelly
Editor-in-Chief

The Thinking

Looks for typeset-quality printing and demands perfection in text and graphics integration.


Requires extensive networking and strong emulator support to handle Sun, Apollo, DEC and IBM host environments.

Needs to wrap both CAE and document processing needs in one laser printing system.

Wants to protect his investment with a versatile system that is easily upgraded as his needs change.

Expects his system to stand up to heavy demands with advanced page management features like duplexing.

Requires printing systems that actually run at the rated speeds—even on original pages.



Printer's Man.

Who is The Thinking Printer's Man? At IMAGEN, we believe it's the kind of person who recognizes the advantages of dealing with the industry's leading manufacturer of laser printing systems. Someone who can appreciate our understanding of the workgroup environment's need to integrate text and graphics. In both high-volume *and* high-quality printing.

Six years ago, we perfected the technology that optimized laser printing. And at IMAGEN today, we build intelligent laser printing systems with an independent "brain" that allows them to do what they do best, and frees your host computer to do what it does best.

Our printing systems feature a dedicated image processor with three MC68000s that, along with our sophisticated page description languages, offers more flexibility than simple printer controllers can. Like clean text fonts and publication-quality graphics. Anywhere you want them on the page. The kind of quality that can turn documents that need to be read into ones that want to be read.

But our printing systems don't compromise quantity for quality.

For example, some suppliers claim their printers can deliver a certain number of pages per minute. But what they really

do is print multiple copies of the same original per minute. With IMAGEN's newest system, you can print 20 completely different pages in the same 60 seconds.

IMAGEN laser printing systems offer a variety of innovative page management features that handle automatic duplexing, page reversal, electronic collation and jam recovery. This, combined with the ability to print on 11 x 17-inch paper, allows you to produce as much high-volume, high-quality documentation as you want. With as much technical detail as you need. And all our printers can be connected through Ethernet and other networks.

So, if you'd like to learn more about our laser printing systems, call IMAGEN today at (800) 556-1234 extension 199 in the Continental U.S. In California, call 1-800-441-2345 extension 199.

Because it's time you have a printer that's nearly as smart as you.



 **IMAGEN**
INTELLIGENT PRINTING

CIRCLE NO. 7 ON INQUIRY CARD

QUICK MUX


Reduces costly equipment requirements.
Allows simultaneous 8 channel operation.

Input ports can accept full duplex data at any rate up to 19,200 bps. Different speeds in each direction are easily accommodated. The composite port which links multiplexers features a built-in line driver.

Diagnostic features of the QUICK MUX include displays of Receive Data and Transmit Data for each port, Data Error and Data Loss Indicators for the composite link. Switches provide a local loopback or remote multiplexer test.

The Model 570 QUICK MUX with 8-25' cables sells for \$548 in single quantity.

Contact us today at Telebyte Technology Inc., 270 E. Pulasky Road, Greenlawn, New York 11740, 800-835-3298 or (516) 423-3232.



CIRCLE NO. 90 ON INQUIRY CARD



**Think
of a Viking
workstation as another
way to add value.**

If you're not integrating ergonomic support furniture in your system, you may be missing an easy way to increase margins and add even more value. Users don't like shopping around to complete the system any more than you do. Try buying a good workstation in your area sometime. It's tough, and it sometimes opens the door to competition and criticism.

We think a lot of users care about the system environment, and well-designed support furniture can make your system more comfortable. And therefore more useful and productive.

Call us on our toll-free line. Everyone wins: users get good furniture at no more cost; you increase margins; and we win through economy of scale, even if the scale is just a few units a month.

Call today, or write our OEM Department:
Viking Acoustical, Airlake Industrial Park,
Lakeville, MN 55044. 612/469-3405, or Telex 290693.

VIKING
Call toll free
1-800-328-8385

CIRCLE NO. 91 ON INQUIRY CARD

LETTERS

ADA STANDARD

To the editor:

I would like to provide a correction to your article, "Software tools slash development time" (MMS, June, Page 95).

On page 99, you note that "Ada is so standardized that binary code produced from one company's compiler should look exactly the same as binary code generated by another company's compiler." This statement is simply not true.

Yes, Ada (a registered trademark of the U.S. government) is standardized, probably more so than any other computer language. But the standardization is at the source code level, not the binary code level. Before a compiler may be legally declared an "Ada" compiler, it must successfully pass a series of over 2,800 validation tests. These tests [comprise] Ada programs whose output and execution [are] checked to insure conformity to the ANSI MIL-STD-1815A.

There are no restrictions placed on the binary code generated from an Ada compiler. To do so would mean standardizing on one particular company's computer hardware, operating system, etc. This would contradict a major goal of Ada: portability of applications among different computer systems.

Bill Bryczynski
Research Staff Member
Institute for Defense Analyses
Alexandria, Va. 22311

Editor's response:

You correctly point out that binary code is not the issue. The sentence should have read, "Ada is so standardized that source code for one company's compiler should look exactly the same as source code for another company's compiler."

—Michael Tucker

The VME BUS and OS-9:

Ultimate Software for the Ultimate Bus.

Modularity. Flexibility. High Performance. Future growth. These are probably the prime reasons you chose the VME bus. Why not use the same criteria when selecting your system software? That's why you should take a look at Microware's OS-9/68000 Operating System—it's the perfect match for the VME bus.


When you're working with VME you must have access to every part of the system. Unlike other operating systems that literally scream KEEP OUT!, OS-9's open architecture invites you to create, adapt, customize and expand. Thanks to its unique modular design, OS-9 naturally fits virtually any system, from simple ROM-based controllers up to large multiuser systems.

And that's just the beginning of the story. OS-9 gives you a complete UNIX-application compatible environment. It is multitasking, real time, and extremely fast. And if you're still not impressed, consider that a complete OS-9 executive and I/O driver package typically fits in less than 24K of RAM or ROM.

Software tools abound for OS-9, including outstanding Microware C, Basic, Fortran, and Pascal compilers. In addition, cross C compilers and cross assemblers are available for VAX systems under Unix or VMS. You can also plug in other advanced options, such as the GSS-DRIVERS™ Virtual Device Interface for industry-standard graphics support, or the OS-9 Network File Manager for high level, hardware-independent networking.

Designed for the most demanding OEM requirements, OS-9's performance and reliability has been proven in an incredible variety of applications. There's nothing like a track record as proof: to date, over 200 OEMs have shipped more than 100,000 OS-9-based systems.

Ask your VME system supplier about OS-9. Or you can install and evaluate OS-9 on **your own** custom system with a reasonably priced Microware PortPak™. Contact Microware today. We'll send you complete information about OS-9 and a list of quality manufacturers who offer off-the-shelf VME/OS-9 packages.



Microware Systems Corporation

1866 N.W. 114th Street • Des Moines, Iowa 50322
Phone 515-224-1929 • Telex 910-520-2535

Microware Japan, Ltd.

41-19 Honcho 4-Chome, Funabashi City • Chiba 273,
Japan • Phone 0474-22-1747 • Telex 298-3472

Micomaster Scandinavian AB
St. Persgatan 7
Box 1309 S-751 43 Uppsala
Sweden
Telex: 76129 microma s
Phone: 018-138595

Dr. Rudolf Keil, GmbH
Porphyrrstrasse 15
D-6905 Schriesheim
West Germany
Telex: 465025 keil d
Phone: 06203-6741

Elsoft AG
Bankstrasse 9
CH-5432 Neuenhof
Switzerland
Telex: 57136 elso ch
Phone: 056-862724

Vivaway, Ltd.
36-38 John Street, Luton
Bedfordshire LU1 2JE
England
Telex: 825115
Phone: 0582-423425

Microprocessor Consultants, Ltd.
16 Bandera Avenue
Waga Waga, 2650
NSW Australia
Phone: (069) 312331

Modular Hardware Deserves Modular Software

OS-9 is a trademark of Microware and Motorola. PortPak is a trademark of Microware. GSS-Drivers is a trademark of Graphic Software Systems, Inc. VAX and VMS are trademarks of DEC. Unix is a trademark of AT&T.

CIRCLE NO. 9 ON INQUIRY CARD

THINK SMART.

T

E

K

Hundreds of leading edge organizations develop practical applications using Tek's Family of AI Workstations. The 4400 Series offers you excellent productivity for rapid prototyping, expert systems building and advanced software development.

This productivity results from Tek's commitment to practical research and development goals. Goals we can help you achieve with tools like Common Lisp and Prolog as well as object-oriented languages like Smalltalk. All optimized to run on Tek's low-cost, high-performance 32-bit workstations.

Add to this the outstanding training and support, and you know why more and more innovative developers are selecting Tek AI systems when they want to think smart.

For more information, circle the reader service card or write to: Tektronix, Inc., AI Marketing, P.O. Box 1000, M.S. 63-635, Wilsonville, OR 97070.

Copyright © 1986, Tektronix, Inc. All rights reserved. VTT-101

Tektronix
COMMITTED TO EXCELLENCE

CIRCLE NO. 10 ON INQUIRY CARD

BREAKPOINTS

DEC AIMS PROPRIETARY VAXBI ARCHITECTURE AT OFFICE MARKET

Digital Equipment Corp. has moved aggressively to challenge IBM Corp. in office automation with high-end entries in its proprietary VAXBI series, the VAX 8550 and VAX 8700. One scenario: The two machines, both rated at 6.1 MIPS, would sit in a "regional office" where they would handle an IBM mainframe at the "home office" and a wide range of minicomputers and microcomputers in "sales offices." The pitch is that, while IBM might need up to six operating systems to handle only its own machines, DEC would need just one. The 8550 (\$364,000 starting price) has I/O up to 16M bytes per second; maximum memory is 80M bytes. For the 8700 (\$433,000 starting price), the maximum I/O is 30M bytes per second; the maximum memory is 128M bytes.—*Jim Donohue*

DATA GENERAL BRINGS OUT FIRST TEO PRODUCTS

Marking its return as an active player in technical/engineering markets, Data General Corp., Milford, Mass., unveiled the first two application programs that ride on its Technical Electronic Office (TEO) software platform. One, TEO/Electronics, is for designers of electrical/electronic circuits; the other, TEO/3D, is for architects, mechanical engineers and people who draw maps. Prices for TEO/Electronics range from \$9,000 per user; for TEO/3D, from \$25,000 for up to five users to \$170,000 for up to 200 users. Running in DG's AOS/VS operating system, TEO integrates seamlessly with DG's office-automation software, Comprehensive Electronic Office (CEO).

—*Jim Donohue*

GOLD HILL DISPLAYS LISP FOR '386, PLUG-IN BOARD

Gold Hill Computers, Cambridge, Mass., has announced that it has ported its Common LISP compiler to the Intel Corp. 80386 microprocessor. Gold Hill claims that this is the first Common LISP to come to market for the '386-based systems. Moreover, Gold Hill and AI Architects Inc., Cambridge, Mass., announced a '386-based plug-in board for the IBM PC, PC/XT, PC/AT and compatibles that, the companies say, gives the PC nearly the performance of a dedicated LISP computer. The board, called the HummingBoard, and associated software convert the PC's native processor into a high-volume I/O coprocessor while its own 80386 performs large, memory-demanding operations. With 6M bytes of RAM and the Gold Hill's LISP, HummingBoard costs \$7,000.—*Michael Tucker*

TANDY GETS DOWN TO BUSINESS WITH MODEL 3000HL

Tandy Corp., Fort Worth, Texas, has launched its long-awaited assault on the business microcomputer market with the model 3000 HL, designed to be a competitor of the IBM Corp. PC/XT. An upgrade of Tandy's existing model 3000 (launched in 1985), the new computer is powered by the Intel Corp. 80286 microprocessor, as is the PC/XT. Tandy says the 3000 HL runs

four times faster than the PC/XT and, at \$1,699 without a monitor, costs 30 percent to 40 percent less. A rigid-disk model will sell for \$4,299. Shipments start in September.—*Jim Donohue*

HP ADDS PC CONNECTIVITY TO LOW-END MULTIUSER SYSTEM

Look for November shipments of a new Hewlett-Packard Co. HP 260 multiuser system that will allow personal computers, including HP's Vectra, to be used as terminals. Two versions—Series 30 and Series 40—support up to 15 users, compared to 11 on earlier 260s. The Palo Alto, Calif., company is also telling VARs that applications for the 260 will run on the HP 3000. Reason: Those minicomputers now support HP's Business BASIC, the language of the HP 260. The Series 30, with a 20M-byte rigid disk drive and 512K bytes of RAM, starts at \$8,500. The Series 40, which features a disk-caching scheme, 40M-byte Winchester, tape drive and 1M-byte RAM, begins at \$15,000.—*Mike Seither*

LUCID LOCKS ON TO THE '386, IBM and XEROX

Common LISP-vendor Lucid Inc., Menlo Park, Calif., has announced an agreement with Intel Corp. to port its compiler to Intel's 80386 micro-processor. A similar agreement has been inked to bring Lucid LISP to the IBM Corp. RT PC. Moreover, Lucid and Xerox Corp.'s Artificial Intelligence Systems revealed an on-going contract whereby Lucid will provide consulting services to Xerox during the development of Xerox's own Common LISP. Lucid is already known as the LISP supplier to such market powerhouses as Sun Microsystems Inc., but these announcements bring the company into the personal computer arena for the first time.

—*Michael Tucker*


SBE MOVES TO VME WITH LOW-COST MEMORY, COMMUNICATIONS BOARDS

SBE Inc., which has a reputation among OEMs as a supplier of Multibus I products, is now in the VMEbus business. The Concord, Calif., company hopes to make a dent in that market with two low-priced boards it introduced this month. Priced at \$1,195 in quantities of 100, the V-MEM-4 offers OEMs up to 4M bytes of global memory, selectable in 1M-byte blocks, and supports 8-, 16- and 32-bit transfers. SBE is also bringing to market the V-COM-8, a \$795 eight-channel, serial-port communications board that supports an asynchronous data-transfer rate of 34K baud per channel. Target applications: cluster controllers for terminals or VMEbus data concentrators.—*Mike Seither*

GM LEADS USERS AND VENDORS TOWARD REAL-TIME UNIX STANDARDS

The General Motors Corp. Task Force met for the third time at Industrial Technology Inc. (ITI) in July, to lay the groundwork for a standardized, real-time version of UNIX. Based on users' and vendors' presentations on the subject, the task force will submit to the IEEE P1003 UNIX standards committee a white paper summarizing user requirements for a real-time operating system. The report is expected to serve as the basis for real-time extensions to the UNIX operating system. Anyone wishing to participate

Thinking of tying low-speed terminals onto a high-speed network?



Think again!

A high-speed LAN is ideal for file transfer, distributed processing and CPU-to-CPU communications. But using it for terminal traffic can cause problems.

You may be tying up bandwidth.

Low-speed terminal traffic on a high-speed network can rob bandwidth where it's needed most. That means slow file transfers and sluggish response for all network users. The protocol overhead required for a terminal to send small data packets across an Ethernet® link can mean that only 10% of the 10 Mbps bandwidth is available.

By connecting your terminals through an Equinox® Data PBX and connecting your computers together with Ethernet, your LAN runs at top efficiency. An Equinox Data PBX dedicates a full 12 Mbps to terminal data traffic. More than 1300 devices can run continuous 9600 bps data at the same time, providing the best possible response through the network.

You'll tie up about \$500 per terminal. When you consider the cost of Ethernet Terminal Servers, Taps, and

Cable, Ethernet can cost between \$300 and \$800 per terminal. An equivalent solution using an Equinox Data PBX with our 8-channel Terminal Servers and twisted pair wiring is about \$100 per terminal.

You could tie up your computer.

Some Ethernet LANs handle terminal switching by running special software in your computer. So adding terminal traffic means your computer spends more time running the network and less time running applications. An Equinox Data PBX requires no special

software and handles all terminal network processing without disturbing the host. It even allows you to monitor the network load and provides additional security for access control.


We won't tie you down.

Putting your terminals on an Equinox Data PBX provides more terminal switching features for less money with greater efficiency, so you can get the most out of your LAN. And because it works with all types of computers and terminals you're not tied to a one-vendor solution.

Don't think twice. Call Equinox.
1-800-DATA-PBX
In Florida Call (305) 255-3500

Equinox Systems Inc.
12041 S.W. 144th Street
Miami, FL 33186-6108





Equinox is a registered trademark of Equinox Systems Inc. Ethernet is a registered trademark of the Xerox Corporation.



CIRCLE NO. 11 ON INQUIRY CARD

EQUINOX

We Make The Right Connections.



THE MODGRAPH PRISM PC COLOR GRAPHICS CONTROLLER

The Modgraph PRISM is a high resolution color or gray scale raster scan display controller designed for the IBM PC, XT or AT and compatibles. Utilizing the NEC-7220 graphics controller, bit plane architecture, and dual ported memory, the PRISM is a high performance, cost effective, graphics generator designed for use with popular CAD/CAM/CAE and windowing software packages.



CIRCLE NO. 12 ON INQUIRY CARD

Screen image courtesy of Pointline Comp. Corp. Other images courtesy of Engineering Systems Corp. and Microsoft Corp.

in the creation of the paper should contact David Greenstein, General Motors Technical Center, Warren, Mich., at (313) 947-0571.

—Wendy Rauch-Hinden

SYMBOLICS DEBUTS ENHANCED ENTRY-LEVEL, MID-RANGE PROCESSORS

Symbolics Inc., Concord, Mass., is replacing its entry-level 3640 and mid-range 3670 symbolic-processing machines with higher performance VLSI CMOS-based models. With 20 percent greater processing speed than the 3640, and one-fourth the size, the new 3620 has I/O controllers, 4M bytes of main memory (expandable to 16M bytes), a 190M-byte rigid disk and three expansion slots. The new mid-range 3650 is 40 percent faster than its 3670 predecessor and one-half the size. It comes with up to 32M bytes of main memory and a 368M-byte rigid disk. Basic configurations costing \$49,000 and \$65,000, respectively, are configured with development software.—*Jesse Victor*

Q-BUS, VMEBUS GRAPHICS CARDS FEATURE CONCURRENT WINDOWS

Look for a pair of high-performance graphics display systems for VMEbus computers and Digital Equipment Corp.'s MicroVAX II early next year from Advanced Electronic Design Inc., Sunnyvale, Calif. The board sets will support eight display-memory planes at a resolution of 1,280 by 1,024 pixels and draw 50,000 vectors a second. They furnish multiple concurrent windows for text and graphics. The Q-bus system for the MicroVAX II uses standard facilities of the MicroVMS operating system and costs about \$6,500. The double-height VME board is aimed at the UNIX market and will cost about \$8,000. Both products are expected to be available in the first quarter of 1987.—*Mike Seither*

XYLOGICS CONTROLLER SUPPORTS 16 PORTS WITH 32-BIT TRANSFERS

If you need full 32-bit data transfers over the VMEbus, consider the model 780 communications controller from Xylogics Inc., Burlington, Mass. It provides 16 full-duplex ports at 9,600 baud or eight ports at 19.2K baud. The dual-height card boosts throughput for UNIX-based multiprocessing, multitasking systems with 10M-byte-per-second direct-memory access and I/O message pipes. Full UNIX TTY subsystem emulation offloads host-computer processing. The \$2,495 10-MHz Intel Corp. 80186-based card comes with Xylogics' version of Hunter and Ready Inc.'s VRTX real-time multitasking executive.—*Jesse Victor*

LAPINE, CONNER RETAIN FAITH IN 3½-INCH WINCHESTERS

California disk drive manufacturers LaPine Technology Inc. and Conner Peripherals are so zealous about 3½-inch Winchester that they build only that size. This month, Milpitas-based LaPine is boosting the capacity of its present line by using run length limited (RLL) encoding to reach 30M bytes. The new Titan RLL 30, with an access time of 65 msec, will be priced under \$400 and aimed at the personal computer drive-card market. Meanwhile, Conner is bringing out its first product, the CP 340, a high-performance 50M-byte drive with an embedded SCSI interface. Conner

claims the 340 has an access time of 29 msec. OEM pricing will be about \$750. The company, founded by disk-drive veteran Finis Conner and backed by Compaq Computer Corp., has just opened its manufacturing plant in San Jose.—*Mike Seither*

NEW COMPANY READIES HIGH-CAPACITY 3½-INCH WINCHESTERS

Yes, Virginia, there still are disk-drive start-up companies—the newest, Peripheral Technology Inc., Chatsworth, Calif., is betting that their Korean-built 3½-inch Winchesters will match up favorably with similar products. The 20M-byte PT325 and the 30M-byte PT338 supply a 40-msec average access time. Evaluation models are expected to be shipped this month.—*Carl Warren*

VENTURCOM INTRODUCES VENIX E-NET 205 FOR MULTIVENDOR COMMUNICATIONS

VenturCom Inc., Cambridge, Mass., has introduced VENIX E-Net 205. This software program allows IBM Corp. PC/XTs, PC/ATs and compatibles running VenturCom's UNIX-based VENIX System V operating system to be linked to Digital Equipment Corp. VAX minicomputers, and other hardware, via Ethernet using the Transport Control Protocol/Internet Protocol. VENIX E-Net 205, aimed at system integrators, uses Excelan Inc.'s EXOS 205 intelligent Ethernet controller to provide TCP/IP services to the host. This increases networking throughput and application-processing capabilities by downloading CPU-intensive protocol-processing functions to the EXOS controller. That frees the CPU for application processing. VENIX E-Net 205's price of \$595 includes two months of telephone support.—*Frances Granville*

SIGMA DESIGNS SHIP 'COOL' PC/AT EXPANSION CHASSIS

System integrators who pack an IBM Corp. PC/AT with high-powered boards often come up short on cooling capacity or slots. Sigma Designs Inc., San Jose, Calif., is offering a solution: the 12-slot ATE Expansion Chassis with four cooling fans. The ATE features its own 275-watt power supply, support for direct memory access and a programmable configuration table. In OEM quantities: \$1,500.—*Mike Seither*

TRUVEL'S SCANNER YIELDS X-RAY-LIKE RESOLUTION AND GRAY SCALE

Truvel Corp. of Torrance, Calif., claims its 300-dpi ZComp prototype digital scanner offers users a 3-to-1 zoom capability that effectively yields 900 dpi. The product supports up to 256 levels of gray for scanned pixels, thus allowing proper handling of halftones that have 64 levels of gray per halftone dot—something no other scanner has achieved. The ZComp, expected to be priced at \$5,000, uses a special IBM Corp. PC-compatible interface card. Product availability is planned for early 1987.—*Carl Warren*

TANDY... Better Again™

The New Tandy 3000 HL

Four times the power
of the IBM® PC/XT
...for less.



The Tandy 3000 HL isn't just compatible with IBM's PC/XT—it's better. Better because of its new 16-bit microprocessor that lets you process twice the data of IBM's older, 8-bit design. Better because it has nearly twice the clock speed of the PC/XT.

Better because you get more for less: only \$1699.

The Tandy 3000 HL's 512K RAM lets you run the software that you've grown accustomed to—at a much higher speed for greater efficiency. And you can expand with hard disk drives, modems, and more.

The high power and low price of the Tandy 3000 HL make it perfect for offices requiring several workstations. And the ViaNet local area network can bring your 3000 HLs together with your existing MS-DOS based computers. Users and departments can be more efficient.

Plus, the American-made Tandy 3000 HL is backed with total support, including our leasing, service and training plans.

Get the facts today, and you'll agree: the Tandy 3000 HL (25-4070) is your basic building block for total office automation.

Available at over 1200
Radio Shack Computer Centers and at
participating Radio Shack stores and dealers.

Radio Shack®
COMPUTER CENTERS

A DIVISION OF TANDY CORPORATION

Send me an RSC-17 Computer Catalog.

Mail To: Radio Shack, Dept. 87-A-147
300 One Tandy Center, Fort Worth, TX 76102

Name _____

Company _____

Address _____

City _____


State _____ ZIP _____

Phone _____

Price applies at Radio Shack Computer Centers and participating stores and dealers. Monitor sold separately. IBM/Registered TM International Business Machines Corp. MS-DOS / Registered TM Microsoft Corp. ViaNet/TM ViaNet, Inc.

CIRCLE NO. 13 ON INQUIRY CARD

GUESS WHO WINS THE DATA BASE RACE?




VAROOOM!

No contest.

When it comes to data base engines, nobody, not DEC[®], not HP, not even the mighty IBM[®], can out-last, out-blast Pyramid. And the chart below tells the tale.

What it doesn't tell is why. So hold onto your hat.



Other superminis have a very pronounced "knee" in their curve. That's where their I/O subsystems hit the wall. But not Pyramid. Thanks to our distributed processor architecture, we deliver crowd-pleasing performance. For as little as 2/3 the cost of our competitors' systems.

Smooth data base management requires high *aggregate* throughput. So you need MIPS, but you also need performance from every other part of your system, too. And that's why Pyramid comes in first.

Our main power plant is the Pyramid 98x ISOPROCESSOR[™] system. With its two symmetrical 32-bit processors, it out-runs both uni- and multi-processor-based systems. Our optimizing compilers kick in to boost performance even higher. And they're boosted even more by our RISC-based architecture.

We also have processors for everything that needs one. Namely, the disks, the terminals, and any attached networks. That means the peripherals always have a green light, and the CPU can go its own way.

And our XTEND[™] bus is the ultimate in handling. With an advanced cacheing scheme

and a message-based, 40 Mb/S bandwidth, it's no wonder.

But performance isn't the only thing we offer. There's comfort, too.

Yours.


We have strong relationships with every major relational data base manufacturer. So not only will you have a choice of what to run, you'll get support from both us and them. No matter who "them" is.

And since Pyramid systems are open systems, built on widely-supported industry standards, we can give you more different ways to go. Without locking you in. Or locking your other suppliers out. Chances are, they support the same standards. Like UNIX[®], for instance.

It's that wide openness that'll have everybody cheering, including you, because a Pyramid can give more people more data base access. From individual users on pc's, workstations or terminals, to departmental micros and super-minis, to mainframes running batch, transaction processing, or scientific applications.

DBMS PROCESSING REQUIREMENTS

While raw MIPS are important to a data base system's performance, the system still spends most of its time on terminal and disk I/O. That's why we use multiple distributed processors. They put the computing power where you need it. So you're not sitting there spinning your wheels.



A Pyramid can run with all of them. Which should get you running for the phone. Call us at 1-415-965-7200, Ext. 3450. Or write, 1295 Charleston Road, P.O. Box 7295, Mountain View, CA 94039-7295.

We'll respond with more information faster than you can say, "Gentlemen, start your engines!"

 **PYRAMID TECHNOLOGY**

The Shape of Performance.

Pyramid Power

IBM is a registered trademark of International Business Machines Corp. DEC is a registered trademark and VAX is a trademark of Digital Equipment Corporation. UNIX is a registered trademark of AT&T Bell Laboratories. ISOPROCESSOR and XTEND are trademarks of Pyramid Technology Corporation. © 1986 Pyramid Technology Corporation.

CIRCLE NO. 14 ON INQUIRY CARD



If Keyboard Data Entry Is Slowing You Down, Have A Talk With Your Computer

For fast, accurate data entry, Verbox voice input is the answer. Our voice data entry products are helping companies in material handling, inventory control, inspection, test and other applications save thousands of dollars in labor, time and equipment costs, often with productivity gains of 100% and more. Now you can take advantage of this proven technology in a new, low-cost voice data entry peripheral—the Verbox Series 4000 Voice Recognizer.

Integrating seamlessly with your existing data entry operation, the Voice Recognizer works with virtually any mainframe, mini-, micro- or personal computer. Unique, reusable, CMOS cartridges hold each user's voice patterns

and vocabulary words. He or she simply drops the pocket-sized cartridge into the Voice Recognizer console and it instantly responds to verbal commands despite accent, dialect, or interference from loud background noise.

Simple software tools let you create your own vocabularies.

With our IBM® PC-compatible Voice Developer software, programming custom vocabularies is no sooner said than done. Simple software tools let you select words of any length using terminology specific to your application, your industry, and your firm. Training your users is fast, retraining is typically unnecessary, and you may change your vocabulary at any time.

True continuous speech recognition: the key to your success.

With Verbox, the user inputs data in a natural voice, so there's no risk of fatigue or irritation caused by the staccato diction that other products require. And while others may claim it, only Verbox's patented continuous speech recognition algorithm achieves this natural man/machine interface without sacrificing accuracy or vocabulary size.

For details on the Series 4000 or our OEM/VAR programs, call (201)267-7507. Or write on company letterhead and ask for a free video tape of voice applications: Verbox, VOICE INDUSTRIES CORPORATION, Ten Madison Avenue, Morristown, NJ 07960.

Verbox

VOICE INDUSTRIES CORPORATION

CIRCLE NO. 15 ON INQUIRY CARD

IBM is a registered trademark of International Business Machines Corp.

INTERPRETER

With modularity, Counterpoint builds multiuser computers

Mike Seither

Associate Western Editor

When you try to muscle your way into a crowded market, it helps to have Rambo at your side. That's what Counterpoint Computers hopes it has with AT&T Co.—and other big investors—as it tries to sell its new System 19K multiuser computers.


Counterpoint, based in San Jose, Calif., offers OEMs wide latitude in configuring systems that serve from six to 56 users. The company claims it can do this at prices starting at \$9,650 in OEM quantities, which begin at about 50 units, much lower than many key competitors. That could rank Counterpoint among the price leaders for multiuser systems using the Motorola Inc. MC68020 processor.

For example, two competitors based in San Jose, Calif.—Altos Computer Systems and Convergent Technologies Inc.—ask for OEM quantities of 300 units before they cut prices to, respectively, about \$8,000 and \$6,000 for entry-level versions of their multiuser products.

'Nice and aggressive'

Sandra Gant, an analyst with InfoCorp., a market research concern in Cupertino, Calif., says: "They have a nicely engineered, aggressively priced product that's expandable. It will ultimately be up to Counterpoint's resellers to define the markets."

Other market analysts like Gwen Peterson, director of computer industry service for Dataquest Inc., a San Jose market researcher, are as much interested in Counterpoint's backers and resellers as they are in its products. Peterson says the alliances are



sure to open doors. "It's not [Counterpoint's] products so much as its window on world markets that will be interesting to watch," she says.

The biggest name: AT&T, which signed OEM agreements with Counterpoint and is expected to use, and resell, System 19K.

Other major investors include Kyocera Corp., the Japanese giant in ceramic packaging of integrated circuits, and British and Commonwealth Shipping Ltd., a U.K. company with large holdings in high technology.

Multiprocessing is key

Offering multiprocessing capability at the low end of the market is one of Counterpoint's main marketing thrusts, says marketing vice president Paul Rosenfeld. He points out that most of Counterpoint's competitors rely on UNIX-based single-CPU

technologies.

"We believe System 19K will redefine what the low-end multiuser computers are going to be," Rosenfeld says. "Our goal is to have a simple but complete line that spans a broad range of price and performance."

Besides Altos and Convergent, the competition includes Burroughs Corp., Charles River Data Systems Inc., Digital Equipment Corp., Hewlett-Packard Co., IBM Corp., NBI Inc., and NCR Corp.

System 19K is based on Counterpoint's Advanced System Platform (ASP), a 32-bit multiprocessing architecture the company originally introduced in March. The first product to roll out of Counterpoint was a stand-alone monochrome graphics workstation. But with that announcement, Counterpoint emphasized that the basic ASP architecture would be the foundation for not only graphics sys-

tems but also for multiuser computers and network servers.

For the System 19K multiuser system, Counterpoint has augmented the ASP architecture with processors to handle file I/O and tie into peripherals using the small computer system interface (SCSI). In addition, Counterpoint has made networking an integral part of the System 19K by building in an Ethernet adapter as standard equipment—a feature that, if available at all on competing systems, is usually an option only.

'Seamless growth path'

Counterpoint's pitch to OEMs and system integrators is that ASP allows them to address the needs of a variety of vertical markets by offering customers a "seamless growth path." OEMs can begin with a bare-bones one-processor system and build on it. Meanwhile, the packaging and product line remain the same. All processors, disk drives and tape drives, as well as expansion devices, fit inside common cabinet sizes about the size of an IBM PC.

War in a crowd

Counterpoint was formed two years ago under the guidance of company president Pauline Alker. Alker, a former Convergent Technologies executive, was involved in Convergent's major OEM deals with AT&T.

Although it is well-funded, has AT&T in its corner and is strategically allied with large international investors, success is not assured for Counterpoint: It faces formidable competition from a number of entrenched vendors.

At least 150 manufacturers now produce multiuser systems. Of those, about three dozen make UNIX-based multiuser computers driven by Motorola's MC68000 microprocessor family, says InforCorp's Gant. It is the 32-bit MC68020 and Counterpoint's version of the UNIX operating system that form System 19K's backbone.

In its CXIX operating system, Counterpoint has implemented AT&T's UNIX System V 2.2 and has added features of Berkeley UNIX

HOW REPRESENTATIVE 68020-BASED MULTIUSER SYSTEMS STACK UP

Vendor	Model	Maximum memory (M bytes)	Operating system	Maximum users	Maximum disk capacity (bytes)	Entry price (\$)
Alpha Micro	AM2000	28	AMOS	240	2.4G	19,000 (list)
Altos	3068	16	UNIX	30	570M	7,900 (Q300)
Charles River	Universe	16	UNIX	96	3.2G	19,000 (list)
Convergent	S320	16	UNIX	32	4G	6,000 (Q500)
Cromemco	CS420	16	UNIX	64	280M	27,995 (list)
Counterpoint	System 19K	40	UNIX	56	560M	9,650 (Q50)
NCR	Tower 32	16	UNIX	32	4.7G	21,700 (list)
Plexus	P75	16	UNIX	80	6.5G	23,500 (Q50)

Source: Manufacturers, Mini-Micro Systems



Counterpoint has designed its multiuser computer to support from six to 56 users. The UNIX-based system can simultaneously balance the work load of up to six application, terminal and display processors.

Version 4.2, including the libraries and commands for local area networking.

OEMs may begin with a single bus structure at the low end, or choose to use a double bus designed for higher performance, while still using the same system components and operating system.

Modular cabinets

For low-end applications using up to two processors, Counterpoint offers an asynchronous 32-bit-wide System Composition Bus that can move data at 12M bytes per second. It's the System Composition Bus that ties together up to seven Counterpoint

stacked modular cabinets. Using serial arbitration, the bus provides access to all processors, peripherals, Counterpoint's built-in Ethernet interface and custom boards.

For more performance, OEMs can add a synchronous Interprocessor Bus, which has a maximum data rate of 33M bytes per second and uses parallel arbitration. In high-end systems, the Interprocessor Bus handles communication between the terminal, application and graphics processors, while the System Composition Bus takes care of I/O activities.

Counterpoint's Rosenfeld says ASP balances the load of up to six processors in any combination as they exe-

cute applications, I/O functions and bit-mapped graphics. Using a distributed dual-port architecture, each processor has local tightly coupled memory; yet each can use the memory of companion processors. Counterpoint

is not short on memory. A system can have up to 40M bytes of RAM.

To help accomplish multiprocessing, Counterpoint locates copies of a small part of the UNIX kernel—containing memory and process manage-

ment, as well as paging—on each processor so that those functions can be handled independently. The drivers for Ethernet and storage peripherals, however, remain in the central processor. □

SOFTWARE VIEWS

In battle over UNIX, POSIX is a peacemaker



Michael Tucker, Associate Editor

The trouble with UNIX is that you can never tell what's news and what isn't. For instance, at this year's NCC, AT&T Co. announced UNIX System V Release Three. The new release—which may have been the subject of more speculation than any technology since the Manhattan Project—was greeted with a yawn heard round the world. The trade press, market analysts and informed users responded grumpily that there was nothing in Version Three that they couldn't have gotten elsewhere.

In all fairness, Release Three wasn't all that bad. The way it handles distributed computing problems, for example, proves it to be good and solid software. But, apparently, good and solid wasn't enough. What was wanted was something Big and Blue. As Three was being analyzed with universal and militant apathy, another version of UNIX was being hailed as a genuine revolution: AIX, the UNIX-compatible operating system used by the IBM Corp. RT PC.

Some observers said AIX proved that UNIX was the wave of the future. Of course, there was another view: that AIX might be a Trojan Horse, bringing an end to UNIX. Speaking informally, one developer told me, "If you look very closely, you'll see that's what really in there is a [IBM] VM kernel with a UNIX shell."

Meanwhile, almost unnoticed, the

IEEE computer society's P1003 working group on UNIX standards (the group includes IBM and AT&T as members) announced POSIX. And, perhaps, it's POSIX that's news in the long run. AIX and Three, because of IBM and AT&T, may dominate events in the large and flashy way of short-lived phenomenon. POSIX, on the other hand, could be as inevitable and eternal as continental drift.

The IEEE working group can't use the name "UNIX" because that is a trademark of AT&T. Therefore, when P1003 set out to build a trial standard that would provide application portability between UNIX-compatible systems, it also had to produce a name for that standard. It came up with POSIX, which combines "Portable Operating System" with the "IX" designation of many UNIX-compatible systems.

POSIX now exists as an IEEE "trial use document." That is to say, it is a specification for software rather than actual software. It spells out exactly how the IEEE thinks applications should interface with UNIX-compatible operating systems like AIX, Three, XENIX and all the rest of that crew. POSIX is concerned solely with the UNIX interface. The people who wrote it deliberately set out to ignore what goes on in the kernel. Their Eleventh Commandment was, "Thou shalt not muck about below the shell."

The history of UNIX has been a story of repeated kernel-level

changes. Originally meant as an operating system for software development, UNIX has been gradually forced to do things that it simply wasn't designed to do—for example, jobs in office automation and real time processing. These jobs required extensive revisions at its very heart. Indeed, maybe that was why Three appeared such a dud: It did not contain the fundamental, kernel-level changes that many UNIX fans feel are necessary. But then, since those same UNIX fans are using UNIX for quite dissimilar purposes, requiring quite different kernel-level changes, maybe AT&T would have been damned no matter what it did. Perhaps, too, that was what made AIX so exciting: it did something really dramatic with the kernel, even if that meant throwing it away completely.

A good many people would argue that the very nature of computing, with all those different applications and mutually incompatible requirements, makes a single, all-things-to-all-users super-kernel impossible. If so, then the future of UNIX may be its interface, below which different specialized kernels will be switched in and out, depending on the unique requirements of the application. That interface is POSIX. One could envision a UNIX industry in which vendors would develop vertical-market kernels. Users would then purchase those kernels secure in the knowledge that they would interface with anything else that also maintained POSIX-compatibility.

Yes, this really is the Year of the LAN

Lori Valigra
Contributing Correspondent

After several jump starts, the local area network industry is roaring this year, ignited by the big engines of IBM Corp. Next year could be even better. When IBM revealed key elements of its token ring LAN strategy last October, it brought order to a market awaiting a standard from its largest would-be leader.

"The local area network market has come into its year," says Mark D.

Stahlman, research analyst with the Sanford C. Bernstein & Co. Inc., New York, investment research concern. He says IBM introduced a LAN that is easy to use and set up: It will stimulate business for system integrators and value-added resellers. "IBM has accelerated the pace of token ring product introductions and is working closely with a number of independent LAN vendors to push the token ring among them. There will be big opportunities in 1987."

Among those opportunities are

products connecting or bridging token ring LANs and the other industry standard LAN, Ethernet. Although Xerox Corp., Stamford, Conn., launched a strategy similar to IBM's five years ago with Ethernet, Xerox lacked the strong computer line and installed base needed to popularize LANs. Ethernet got a much needed boost three years ago when Digital Equipment Corp., Maynard, Mass., began selling products using it, explains George Colony, president of Forrester Research Inc., a Cambridge, Mass., market research concern.

Activity increases

Colony and other industry analysts have noticed a marked increase in activity among system integrators

Token-Ring inventor levies license fees

There was a hitch when IBM Corp. announced its Token-Ring Network local area network last year. IBM didn't own the patent for token ring technology, and some industry participants feared they'd have to pay hefty royalties to the man who did: Olof Soderblom, a former IBM employee.

This summer, Soderblom said he wants royalty fees of 1 percent of the net selling price, to a \$275 maximum, depending on the price or volume of product sold. There also is an initial \$15,000 sign-up fee and a \$10,000 advance for future royalties.

Soderblom claims to have 16 licensees, with 10 pending. Ungermann-Bass Inc. and Bridge Communications Inc. have licenses. The royalties don't apply to IBM, which bought a flat fee license in 1980. Industry analysts estimate the license cost Big Blue's World Trade operation about \$5 million.

The right to collect royalties was granted Soderblom after a 16-year, \$1-million battle defending repeated challenges to his invention (he invented the token ring concept, not the actual LAN). The patent was reissued in March 1985. "Little did I know that this would become a career of mine," says George Vande Sande, Soderblom's attorney and a partner at Pollock, Vande Sande & Priddy, Washington, which took the case in 1968.

Soderblom came up with the token ring concept in 1967 when he worked for Swedish bank Svenska Handelsbanken. The bank needed an on-line system to attach 2,000 terminals in 500 branch offices spread over 1,500 miles. Soderblom's concept was to use unaddressed or decentralized polling, subsequently called token ring. IBM was one of the primary contrac-

SODERBLOM PATENT LICENSING FEES

Basic fees	\$15,000, sign up \$10,000 advance or future royalties	
4M-bps PC board fees	No. of boards sold per quarter	Percentage of net selling price
	1-6,000	2.75
	6,001-12,000	2
	12,001-XXX	1
Other board fees	Net selling price (\$)	Percentage of royalties
	1-600	4
	601-10,000	2.67+7.98
	10,001-XXX	\$275 maximum
Node (box) fees	Net selling price (\$)	Percentage of royalties
	1-10,000	2.75
	10,001-XXX	\$275 maximum

Source: Olof Soderblom

tors supplying equipment for the network, and it subsequently used the technology in its retail and banking computer systems and in its Token-Ring Network LAN.

Soderblom, who worked for IBM in Sweden from 1969 to 1975, believes he won't face more patent fights. "I can now walk the tightrope without a safety net" he says. His U.S. patent does not expire until 1998.

He's gotten a tidy remuneration for his troubles. Royalty income last year was \$750,000, and it topped \$1 million in the first five months of this year. He says he's spent about \$1 million to prosecute and address patent claims internationally.




When McDonnell Douglas, Teledyne Controls, and SAI Technology had special requirements for their military and avionics products, they came to Carroll Touch for a solution.

Carroll Touch offers a line of high-performance, cost-effective infrared touch systems and EL displays equipped with touch. Providing exceptional functionality and exceptional flexibility, these MIL SPEC-qualified units make user interaction easier, faster, and more accurate than any other type of input device. They are rugged, reliable, and especially well-suited for harsh or hostile environments, from the flight deck to the battlefield.

It's no wonder more and more companies are using Carroll Touch products in their systems. Discover solutions you can touch. Contact Carroll Touch today.

Solutions you can touch



Carroll Touch

a subsidiary of AMP Incorporated

In Touch with Technology

P.O. Box 1309
Round Rock, TX 78680
512/244-3500, Telex 881906

Carroll Touch is a registered trademark of Carroll Touch, Inc.

CIRCLE NO. 16 ON INQUIRY CARD

The people who make Seagate



the first name in disc drives:

Sam

There's no substitute for experience when you're designing disc drives. There's no substitute for Sam Geller either.

When he built the models for the first Winchester drives, Sam helped start an industry. Now 15 years later, our model shop manager knows so much about making drives that we've made him promise not to retire unless he gives us five years notice.

"I've been making precision mechanical components since Roosevelt was president," Sam said. "Teddy Roosevelt."

Sam makes his experience pay off in improved drive performance and reliability. As part of the design team that perfects each prototype before a drive goes into production, he knows when a piece is built right.

"If we can't build it here," Sam said, "it can't be built anywhere."

OEMs have come to expect this kind of relentless emphasis on quality from Seagate. That's one reason they've bought more than 3 million of our 5¼" hard disc drives.

Seagate's reputation is built by its people. If you think your drives should be designed by dedicated experts like Sam, call us.

800-468-DISC. In California, 800-468-DISK.



 **Seagate**

The first name in disc drives.

CIRCLE NO. 17 ON INQUIRY CARD

who are using LANs within departments or small work groups and, increasingly, tying them to larger corporate networks.

Examples:

Bankers Trust Co., New York, is moving to get 18 personal computer networks to communicate with one another and with other computers and networks.

The Travelers, Hartford, Conn., plans to install 1,000 IBM token ring networks nationwide and has spent millions of dollars wiring its renovated buildings for the IBM network.

"Large organizations are making commitments worth \$10 million or more to corporate-wide networking," says Ralph Ungermann, president of Ungermann-Bass Inc., Santa Clara, Calif. The company, the largest supplier of general purpose LANs, sold \$72 million worth of networks based on Ethernet technology last year.

Judging from the size of some recent LAN purchases (the National Security Agency has awarded AT&T Co. a \$50 million-plus contract), the existence of more than 300 equipment suppliers and estimates that only 3 percent of the 14.9 million computer workstations in U.S. companies were attached to LANs last year, the market for the products is large. According to estimates by the investment research concern, Sanford C. Bernstein, the \$405 million world-

wide LAN market in 1984 should grow to \$1.2 billion in 1986 and to \$4.9 billion in 1990, an average annual growth rate of 50 percent.

Fortune 1000 firms will buy about 45 percent of the LANs, says Forrester's Colony. He expects IBM to gain a 43 percent market share with the Token-Ring Network and its other network, the PC Network. Colony says IBM could draw in about \$1.5 billion in revenues by 1990 from Token-Ring.

Creates opportunities

As did the IBM PC, the Token-Ring Network will create opportunities for system integrators, analysts believe. Already, Apple Computer Inc., Cupertino, Calif.; Bridge Communications Inc., Mountain View, Calif.; 3Com Corp., Mountain View; Ungermann-Bass and software companies such as Microsoft Corp., Bellevue, Wash., have announced support for connections to the Token-Ring Network or other products for it.

Jon Shirley, Microsoft president, says LAN software, particularly applications programs, will represent a bigger portion of his company's revenues. "There's a lot of potential out there. Almost no existing software is designed to take advantage of local area networks, especially software for personal computers," he claims. Microsoft sells its MS-Net software to

help programmers write software for any type of LAN.

Another potentially booming market will be for hardware and software that can connect Ethernet and token ring networks. 3Com, Banyan Systems Inc. of Westboro, Mass., and others offer such gateways. Colony says the market for such products was \$53 million in 1984 and should expand to \$743 million in 1990.

Even IBM sees the need to offer connections to both types of LANs. In late June it announced both Ethernet and token ring connections for its RT PC reduced instruction set computer. The Ethernet adapter card (\$850) runs at 10M bits per second; the token ring card (\$1,095), at 4M bps.

There'll be opportunities for system integrators and VARs to connect LANs to more complex networks such as DEC's DECnet and IBM's Systems Network Architecture. Companies like Apple, 3Com and Ungermann-Bass are positioned to sell larger network-systems solutions to capture market share in the maze of corporate networks.

3Com is moving from being a LAN-adapter supplier to offering systems for work groups, says president Bill Krause, who estimates there are about 5 million users in 10 million work groups who are potential customers.

DEC is furthest along in tying together all levels of networks, says Colony. DEC includes built-in Ethernet hardware in all new products; the price of the LAN attachment is as little as \$50 per computer or terminal. DEC has about 3,400 Ethernet customers, and about half of its VAX minicomputers are sold with networks.

Consultant Stahlman estimates DEC drew \$165 million in LAN revenues last year and should sell \$220 million worth this year.


AT&T's ambitions

AT&T, another major competitor, has high ambitions for its LANs and is building sales from its 44,000 customers of private branch exchange (PBX) telephone systems. George Martin, director of computer market-

IBM WILL COME ON STRONG

	Market share (%)			Revenues (\$ millions)			Revenue growth (%)		
	1985	1986	1990	1985	1986	1990	1985	1986	1990
Ungermann-Bass	21.0	19.9	15.8	53.6	93.1	268.6	44.0	73.8	10.1
Sytek	11.3	11.8	9.0	28.9	55.1	152.9	85.0	90.6	18.0
Bridge	8.3	8.6	10.1	21.1	40.3	171.6	82.0	90.7	28.0
Micom/Interlan	9.7	8.7	5.4	24.8	41.0	92.3	42.2	65.5	8.9
Network Systems	5.4	6.8	8.2	13.8	31.7	139.1	173.9	129.0	28.9
Other datacomm	25.5	21.2	8.4	65.2	99.2	143.6	143.6	52.2	(12.5)
IBM	0	1.6	8.3	0	7.7	141.8	0	0	57.1
DEC	4.2	4.4	5.8	10.6	20.8	98.5	73.0	95.7	29.9
Other computer	14.6	15.5	18.9	37.3	72.4	321.2	0	94.4	24.9
AT&T	0	1.0	6.4	0	4.5	109.1	0	0	51.7
Other PBX	0	0.6	3.6	0	2.6	61.3	0	0	54.4
TOTAL	100	100	100	255.3	468.4	1,700.0	80.5	83.5	21.5

Source: Sanford C. Bernstein & Co.




Introducing the VMEbus boards that need practically no introduction.

Getting acquainted can get expensive. Especially if your VMEbus CPU boards require extensive modification of your existing software.

Fortunately, now ISKRA makes CPU boards with Intel and Digital microprocessors that show up ready for work, Day 1. ISKRA's VMEx286, with an 8MHz 80286 microprocessor, is already fluent in XENIX[†], iRMX^{**}, and MS-DOS[†]. And our VMExJ11 has an equally firm grasp of Digital's DCJ11[†] and RSX-11M[†], and adapts to single and dual processor configurations.

If you want to skip over the formal introductions and get right down to business, then write to us at 222 Sherwood Ave., Farmingdale, NY-11735 or call toll-free 1-800-862-2101. In New York, call us at 516-753-0400.

VMEx286
with
Intel 80286




VMExJ11
with
Digital DCJ11

ISKRA
VME TECHNOLOGIES
A DIVISION OF ISKRA ELECTRONICS INC

HIGH PERFORMANCE VME BOARDS

^{*}Trademark of Digital Equipment Corp. [†]Trademark of Microsoft Corp. ^{**}Trademark of Intel Corp. VMEx286 and VMExJ11 are trademarks of Iskra VME Technologies.

CIRCLE NO. 18 ON INQUIRY CARD



NEC'S PINWRITER P5XL HAS

Our Pinwriter® P5XL printer has changed forever the way people look at dot matrix printing.

It's the first and only dot matrix that can use a letter-quality multistrike film ribbon—the same ribbon used in typewriters and letter-quality printers, such as our Spinwriter®. Which means for the first time in computer history you can produce important letters and documents with crisp, black, true letter-quality printing without sacrificing speed or graphics capability.

Fast, black letter-quality printing will be the primary reason many people will buy a P5XL printer. But there are plenty of other good reasons. In fact, it's the most versatile printer ever created for personal computers.

It can use an optional ribbon to print seven other colors plus black. And it has the best graphics resolution of any impact printer you can buy, due in part to our advanced 24-pin printhead. Plus it can print more typefaces automatically than any other dot matrix printer. And it's quiet and fast.

You can also expect a P5XL printer to turn out millions of characters before it will need service because it has the highest reliability rating in the industry. And there's a nationwide network

Dear Mr. Black:

Actual line printed
with a Pinwriter P5XL printer.



MADE BLACK A PRIMARY COLOR.

of NEC Customer Engineering Service Centers to take care of maintenance.

Now, while the Pinwriter P5XL performs a little black magic, you won't have to go in the red to buy it.

The Pinwriter P5XL is the latest addition to the most advanced and extensive family of 24-pin printers available.

See it at your dealer or for an information package that includes actual print samples, call 1-800-343-4418 (in MA 617-264-8635).

Or write: NEC Information Systems, Dept. 1610,
1414 Massachusetts Ave., Boxborough, MA 01719.

**NEC PRINTERS. THEY ONLY STOP
WHEN YOU WANT THEM TO.**



NEC

NEC Information Systems, Inc.

CIRCLE NO. 98 ON INQUIRY CARD

Invest in BIZCOMP'S Insurance Policy...



the NonRisk™ Modem
comes *free*.

Our Insurance Policy is a major portion of what you get with Bizcomp's NonRisk™ Modem. In today's world the only constant is change. The value of Bizcomp's Insurance is the flexibility to handle system requirements which may change over time.

Why the NonRisk Modem for Your New Application

Unlike commodity modems that are "frozen in silicon," the Bizcomp NonRisk Modem is based on **software** that can handle changing system requirements and installation difficulties. Granted, modem chips lower prices, but at whose cost? Yours — or the modem vendor? It may look like an attractive offer at first, but modern business decision-makers are wary of additional costs downstream due to being "frozen in silicon" by modem chips.

Business managers demand open options for unexpected problems. The NonRisk Modem provides the answer to that challenge.

Why Bizcomp for Your Company


- Customer-proven field reliability
- Efficient, "no run-around" factory-direct relationship
- Experience from eight years of solid, profitable growth
- Technical expertise as the patent-holder on auto-dial modems

That's just part of our NonRisk Modem Solution. You can discover the rest by calling **408/733-7800**. We'll help you keep your options open. Call us today.

CIRCLE NO. 21 ON INQUIRY CARD

copyright © 1986 Bizcomp Corporation

Bizcomp Corporation 532 Mercury Drive Sunnyvale, CA 94086



WWW BIZCOMP

ing at AT&T in Morristown, N.J., says, "We want to come from our communications strength and initially go after the PBX base to capitalize on our heritage."

AT&T offers several LANs, including a competitor to token ring offerings called Starlan. Martin is keeping all options open. "If a token ring connection is needed in a network, we'll offer it." A minimum Starlan connection—including cable, hardware and software—is \$720. Colony says Ethernet costs about \$1,000 per computer connection; Token-Ring Network, \$1,500. AT&T also offers a PC PBX connection board to connect AT&T or IBM and compatible personal computers to the PBX for \$700.

To capitalize on the market potential, independent LAN companies are forming strategic alliances to expand their product lines and distribution channels. Ungermann-Bass and IBM, for example, will codevelop industri-

al-automation LAN products with Industrial Networking Inc., Santa Clara, Calif., a joint venture company of Ungermann-Bass and General Electric Co. And Ungermann-Bass has signed to work with Hewlett-Packard Co., Palo Alto, Calif., to coordinate support for customers owning Ungermann-Bass broadband Net/One networks and HP 1000 and 3000 minicomputer systems.

3Com and fiber optic company Codenoll Technology Corp., Yonkers, N.Y., have become strategic partners in an agreement that will enable 3Com products to transmit over fiber-optic cable.

Even IBM expanded its distribution by creating a new type of value-added dealer. Instead of just being able to sell one token ring package with each PC sold, the new VADs design, install and maintain LANs for customers with large numbers of standalone personal computers. □

New satellites provide links to remote terminals

Stephen J. Shaw
Washington Editor

A combination of small, inexpensive earth stations and a new generation of communication satellites offers new ways to interconnect host computer systems and remote terminals. Satellite-based data networks, scheduled to appear this year, may permit providers of long-distance telephone service to reach customers directly, bypass local telephone lines and eliminate network access charges now paid to local telephone companies.

Several satellite-system operators have teamed with earth-station manufacturers and providers of recently announced data communications services. A handful of large organizations has also unveiled plans to use thousands of small, interactive satellite "dishes" to beam data between host systems and processors at remote locations.


In May, AT&T Communications

began its Skynet Star Network Service. The first customer was AT&T Communications, which will use satellite transponders leased from RCA American Communications Inc., Princeton, N.J., to transmit data at rates between 9.6K bits per second (bps) and 56K bps from a central earth station hub to an unspecified number of remote locations.

According to John Smart, vice president of business markets and services for AT&T Communications, the service is aimed at customers like large retail concerns and financial-service organizations that collect and disseminate data over wide areas.

AT&T joins a number of other communications carriers that have entered the market to provide interactive data services by satellite. GTE Spacenet Corp., McLean, Va., which markets its service under the Skystar-200 label, provides throughput rates ranging from 2.4K bps to 56K bps. MCI Communications Corp., Washington, is expected to announce a

Clearpoint High Density System and VMEbus Peripheral Local Memory



■ The Sun 3-Series

The SNXRAM is the first 12 MB Sun 3-compatible memory card that delivers the full 16 MB address space using a single slot. Replacing up to 3 Sun memory cards, it frees two VMEbus slots for expansion.

- Available in 2, 4, 8, or 12 MB capacities.
- No Dip Switches, it comes factory configured for correct starting address and memory sizing.
- Using the 32-bit wide private memory bus, the SNXRAM frees the system bus from processor-memory transfers.

The VMERAM provides 4 MB of local memory for the VMEbus. This highly reliable EDC memory can be used to support peripherals such as array processors operating in parallel with the main processor.

Write or call for our new designer literature packages.

Sun is a trademark of Sun Microsystems



CLEARPOINT INC.

99 South Street • Hopkinton, MA 01748


U.S.A. 1-800-CLEARPT
Telex: 298281 CLEARPOINT UR
Massachusetts 617-435-5395/435-2301
Europe Steptrade, Ltd. (Netherlands)
Telex: 71080 ACT H NL Tel: (31) 23-256073

CIRCLE NO. 22 ON INQUIRY CARD

WIN WITH THE WORLD'S FASTEST 300 PPI THERMAL PLOTTER ...VERSATEC VERSACOLOR.

The winning thermal color plotter, Versatec Versacolor, gives you better hard copy faster. You get 300 point-per-inch resolution A-size color plots in 45 seconds; B-size in 60 seconds. International users can plot on A3 or A4 media.

Simplify operation with exclusive donor cartridge and cut sheet media. Plot on paper or clear film. Versatec Versacolor is the easiest to use thermal plotter available.



CIRCLE NO. 26 ON INQUIRY CARD

See Versatec electrostatic and thermal plotters at AUTOFACT.

Save space. Just 21" wide, 19.7" deep and 9.5" high, the typewriter-size Versatec Versacolor is the perfect desktop companion for your computer, workstation, or display.

Plot sooner. Capture data directly from the CRT screen with Versatec's low-cost video controller. Or simplify plot processing with Versatec's low-cost rasterizer controllers. Plug right into standard Versatec hardware interfaces.

Gain higher resolution, more speed, and exclusive convenience features. All at a price that meets or beats other thermal color plotter competitors. And protect that investment with single-source service and supplies for both electrostatic and thermal plotting.

To learn more about the Versatec Versacolor thermal plotter, circle the readers' service number, call toll-free 800/538-6477*, or visit your nearby Versatec sales office.


VERSATEC
A XEROX COMPANY

2710 Walsh Avenue
Santa Clara, California 95051
Telephone: (408) 988-2800
TWX: 910-338-0243
Telex: 334421

Versatec and Versacolor are trademarks of Versatec, Inc. Xerox is a trademark of Xerox Corporation.

*In California, call toll-free 800/341-6060.

Plot data courtesy of Zeh Engineering.
Car courtesy of Allfire Equipment.



similar service. It would use the three satellites and the marketing staff it acquired last year from Satellite Business Systems, McLean, Va., in the deal that brought in IBM Corp., a former part owner of SBS, as an investor in MCI.


For ground hardware, AT&T has signed a "teaming arrangement" with Harris Corp., Melbourne, Fla. Harris is expected to provide the earth-station terminals, packet-switching and interface equipment to link the stations with host computers and remote processors. In turn, Harris has signed an agreement with Matsushita Electrical Industrial Co. of Osaka, Japan, that will permit Harris to market Matsushita-built earth stations to AT&T and others in the United States.

In a similar fashion, GTE has reached an agreement with NEC America Inc., Fairfax, Va., for NEC to supply its Nexstar line of small earth stations. The stations, designed by NEC's Japanese parent corporation and manufactured in the United States, weigh less than 250 pounds and can be mounted directly at customers' premises on rooftops, outside walls, in parking lots or other locations adjacent to a building. Delivery of the stations is expected to begin sometime next year.

Users line up for networks

Despite this recent activity, potential corporate users of these satellite data networks have not been content to wait for the service providers to develop their offerings. In the past 12


HOW VSAT NETWORKS TRANSMIT DATA



SOURCE: MINI-MICRO SYSTEMS

In a VSAT network, data goes from remote VSAT earth stations at relatively low speeds through a satellite down to a hub earth station. The station is connected with a central host processing system. The network packetizes, addresses and transmits outgoing data from the hub at higher rates to the remote terminals, which pass data to interconnected terminal equipment.

Clearpoint
Combining
High Density with
Error Detection
and Correction



■ The VMEbus

With the VMERAM, Clearpoint presents the ultimate memory for the VMEbus. Our first entry into this growing market, the VMERAM offers the highest density—an incredible 4 MB capacity on a standard dual-high VME card containing 256K ZIP DRAMs. Using Clearpoint's custom EDC chip set, the VMERAM features full single-bit correction and double-bit detection. Because of the chip set caching feature, the VMERAM benchmarks favorably with parity memory. It also supports block mode transfers (BMT) and unaligned transfers (UAT).

Write or call for our new designer literature packages.


- Clearpoint's 80-page Designers Guide to Add-in Memory
- The 20-page Add-in Memory Catalog and Selection Guide



CLEARPOINT INC.

99 South Street • Hopkinton, MA 01748
 U.S.A. 1-800-CLEARPT
 Telex: 298281 CLEARPOINT UR
 Massachusetts 617-435-5395/435-2301
 Europe Steptrade, Ltd. (Netherlands)
 Telex: 71080 ACT H NL Tel: (31) 23-256073
 Asia EPRO Ltd. (Hong Kong)
 Telex: 51853 JUNWI HX Tel: 3-7213300

CIRCLE NO. 23 ON INQUIRY CARD



2400 bps modems: Do you Really need another speed?

- Is the shift from 300 to 1200 bps going to repeat itself at 2400 bps? The answer is both yes and no. There certainly are applications for 2400 bps asynch dial-up modems, but we shouldn't expect 1200 bps to die overnight.
- 2400 bps modems can improve throughput, thereby getting tasks done quicker and more economically. However, 1200 bps has become the virtual standard for professional dial-up communications, and most users are satisfied with it. So why consider a 2400 bps modem at all?
- One reason is flexibility. If the modem you select operates at all three speeds (300, 1200 & 2400) in accordance with accepted industry standards, it will serve virtually all dial-up applications now and in the foreseeable future.
- The modem you select should be the MultiModem224. It is Bell 212A and 103 compatible at 1200 and 300 bps, and CCITT V.22bis compatible at 2400. It is also 100% compatible with the Hayes command set, meaning that it will work with virtually all communications software packages, at all three speeds. Other features include both synchronous and asynchronous operation, full intelligence and a phone number memory.
- The MultiModem224 is available in both desktop and IBM PC™ internal card versions. (There is also a rack-mounted version for central sites.) And as a bonus, we provide free offers from ten of the most popular on-line information services, including CompuServe™, Dow Jones™ and The Source.™
- A 2400/1200/300 bps modem is just a plain good investment. Why not let the MultiModem224 provide your communications for both today and tomorrow?

For more information, call us toll-free at
1-800-328-9717 (in Minnesota, call 1-612-631-3550).

CIRCLE NO. 27 ON INQUIRY CARD

MultiTech
Systems 

The right answer every time.

82 Second Ave. S.E., New Brighton, MN 55112 (612) 631-3550, TWX: 910-563-3610

MultiTech
Systems 

MultiModem 224
2400/1200/300 BPS Intelligent Modem

1200 Ans
300

months, a number of large organizations have announced plans to establish their own networks.

Southland Corp., the Dallas-based parent company of the 7-11 convenience stores, intends to build a network of 8,000 earth stations for low- and medium-speed data applications. Federal Express Corp., Memphis, Tenn., expects to have as many as 25,000 satellite earth stations in place at company facilities by 1990 to carry its Zapmail electronic facsimile service. Retail chains, including several department stores, have also announced their intentions to install satellite data networks averaging 2,000 stations each.

Two related technical developments have converged to attract unprecedented attention to space-based data networks. The first is the emergence of a new class of communication satellites. Launched by RCA and GTE last year, these satellites operate at Ku-band frequencies, or between 12 GHz and 14 GHz. Unlike the 4-GHz-to-6-GHz C-band frequencies, employed by the majority of commercial communications satellites launched in the late 1970s, the new frequency band is not subject to interference from terrestrial microwave systems. These microwave communications systems, prevalent in metropolitan areas, effectively limited the markets for satellite earth terminals in those cities and towns with a large concentration of potential business users.

Secondly, these Ku-band satellites utilize more powerful signal amplifiers than do their C-band counterparts. This has allowed the development of a new class of earth stations, called very small-aperture terminals (VSAT). Measuring no more than 5 feet in diameter, these VSATs are smaller, lighter, easier to install and far less expensive than the 16- and 23-foot-diameter earth terminals that are typically employed in the lower frequency satellite networks.

The VSAT data networks designed by AT&T and others are arranged in a "star" configuration. A central hub earth station, with a larger antenna ranging from about 11 feet to 23 feet in diameter, is connected to the host system. The hub station also performs

the packetizing of the data traffic and directs the overall management of the network, including adding the addresses of the remote station where data is to be sent outbound at data rates of up to 56K bps.

The smaller, remote VSATs send data inbound (remote-to-hub) at typical rates of 2,400 bps. The data packets contain address headers that inform the hub station if the data is to be processed by the host computer and stored, or transmitted to any combination of other VSATs.

Lower cost than leased lines


"The combination of satellites and VSATs basically form a sophisticated pipeline for data communications," comments Robert Hendee, vice president for Harris' communications division.

That pipeline is expected to provide a highly economical alternative to leased telephone channels that are traditionally employed for data networks that interconnect a large number of end-user facilities. Although AT&T provides the bulk of the long-distance terrestrial circuits for data traffic, the company and its customers must still rely on local telephone operating companies to provide the local loops. Ordering and installing service for new nodes, modifying traffic rates, or reconfiguring the network through the local telephone companies is often a time-consuming and expensive procedure.

"The local loops are still a problem, and I'm sure AT&T is frustrated with the [former] Bell operating companies," comments telecommunications analyst Walter Morgan, president of the Communications Center of Clarksburg, a consulting organization in Clarksburg, Md. "With VSAT networks, AT&T can bypass the local telephone companies and go directly to their customers' premises."

Under the AT&T Skynet tariff, a 500-node network utilizing two-way data VSATs would cost the user between \$250 and \$400 per month per location under a seven-year lease. This price includes network design, management and maintenance, as well as the ground hardware and transponder capacity on the satellite. Users do not pay any access charges to

Clearpoint
The Full 16 MB
Address Space with
4 or 8 MB
Expansion Cards



■ **The IBM PC/RT**

Another memory design first: the **RTRAM** is the first 100% PC/RT compatible memory. This Clearpoint memory comes fully tested with soldered-in memory devices.

The 4 MB card offers twice the density of comparable memories from IBM by using 256K ZIP DRAMs. The 8 MB RTRAM uses megabit DRAMs to quadruple the capacity per slot. Other features are on-board interleaving and low power consumption. Fully-populated testing ensures the highest reliability and full functionality.

Write or call for our new designer literature packages.

- Clearpoint's 80-page Designer's Guide to Add-in Memory**
- The 20-page Add-in Memory Catalog and Selection Guide**

IBM PC/RT is a registered trademark of International Business Machine Corporation



CLEARPOINT INC.

99 South Street • Hopkinton, MA 01748

U.S.A. 1-800-CLEARPT
Telex: 298281 CLEARPOINT UR
Massachusetts 617-435-5395/435-2301
Europe Steptrade, Ltd. (Netherlands)
Telex: 71080 ACT H NL Tel: (31) 23-256073
Asia EPRO Ltd. (Hong Kong)
Telex: 51853 JUNWI HX Tel: 3-7213300

CIRCLE NO. 24 ON INQUIRY CARD

If you want a better controller, why haven't you called us?



This proprietary chip transfers data as fast as the head can read the disk.

The developers of the original PC hard drive card called us when they first had the idea. The resulting technology spawned an entire new industry.

System developers all over the world call us when they're looking for controllers with higher performance and more functions per board. They get the controllers they want.

And so can you. Just call us.

Our latest controllers for PC/XT, AT, SCSI, Multibus® and Q-Bus® systems employ proprietary VLSI CMOS ASICs. So one chip does the work of several, with greater reliability and lower power consumption. The result: data throughput 25% to 300% faster than other controllers.

OMTI™ PC controllers are available with Run Length Limited (RLL 2,7) encoding that stores 50% more data on many disks than with MFM encoding — 30Mb on a 20Mb hard drive card, for instance.

OMTI
The mark of better PC and SCSI controllers.

They can handle Winchester, floppies and tape backup from a single board. They're so reliable we include a full one-year warranty.

If you want to build a leaner, faster system, call us. Now. The demand is already heavy. Because when we trimmed down the electronics, we also trimmed down the price.

Scientific Micro Systems,
339 N. Bernardo Avenue, Mountain View, CA 94043
Telephone (415) 962-5494 • Telex 184160.

Scientific Micro Systems

Dear Scientific Micro Systems:
Here's the controller I want:

BUS:
 PC/XT
 PC/AT
 SCSI
 Q-Bus
 Multibus

ENCODING:
 MFM
 RLL

DRIVES:
 ST506/412
 ESDI
Megabytes Winchester capacity
 3 1/2" floppies
 5 1/4" floppies

BACKUP:
 Streaming tape
 Removable disk cartridge

Name _____ Title _____
Company _____ Phone _____
Address _____ State/Zip _____
City _____

Distributors: U.S.—Arrow Electronics (516) 694-6800 • Anthem Electronics (408) 295-4200 • Quality Components (214) 733-4300
Canada—Allan Crawford Assoc. (416) 890-2010 • SMS EUROPE: West Germany—49-821-572095 TWX 533810 SMS D.
Multibus is a registered trademark of Intel. Q-Bus is a registered trademark of Digital Equipment Corp. OMTI is a trademark of Scientific Micro Systems, Inc. © 1986 Scientific Micro Systems, Inc.

CIRCLE NO. 28 ON INQUIRY CARD

the local telephone company and can reconfigure their networks quickly by adding or subtracting VSAT stations. According to an AT&T spokesman, customers could realize savings between 20 percent and 25 percent compared with standard terrestrial data service, depending upon the number of sites, their exact locations and the data rates required.

Standard network integration

Integrating satellite-based data networks with existing data-processing systems also promises to be a relatively simple chore. As Harris' Hendee explains, the network's host mainframe or minicomputer would typically be located with the central hub earth station. A Zilog Inc. Z8000-based I/O processor links the front-end processor of the host computer

with the station's radio transmission equipment.

The I/O processor utilizes standard RS232 and RS442 connectors. The unit performs the packetizing of the data and otherwise adds the communications protocol, such as the address of the ultimate remote destination, but does not affect the computer protocol. Thus, says Hendee, the satellite pipeline is transparent to the computer system itself.

At the remote terminals, I/O processors reverse the signal processing and pass the data to or from the local processors through the RS232 or RS442 connectors. "The computer system really isn't aware that a satellite link is being employed rather than conventional telephone lines. To the host processor, it all looks the same," Hendee says. □

IBM 'fixes' System/36 as part of product blitz

Lynn Haber, Associate Editor

Last summer, with the announcement of more than 125 products, IBM Corp. attempted to remedy its highly criticized System/36 minicomputer and to accommodate network standards via an Ethernet connection.

Many industry watchers praise IBM's actions. Craig Symons, vice president at the Gartner Group Inc., a research and consulting company in Stamford, Conn., says IBM has taken "a step in the right direction." He contends, however, that Big Blue has more work to do. The most difficult task will be overcoming the negative publicity surrounding the perceived lack of System/36 performance as a departmental computer.

What about the adoption of Ethernet for the IBM RT PC and the various other efforts to make IBM equipment talk to other vendors' machines?

Vicki J. Brown, senior analyst at International Data Corp. (IDC), Framingham, Mass., says of the Ethernet move, "They had to do it if they want to be a major player in the workstation market." Brown says ap-

proximately 75 percent of all workstations are shipped with Ethernet. "It's a de facto industry standard."


Even the competition is happy. Bill Johnson, vice president of distributed systems at Digital Equipment Corp., Maynard, Mass., believes IBM's endorsement of Ethernet is a good thing. "IBM has faced up to reality and the fact that Ethernet is something they have to offer their customers," he says.

Gartner's Symons concedes that IBM improved the company's mid-range product lines both in terms of price/performance and communications, but says that, in overall performance and connectivity, DEC has the upper hand. "DEC has the product and technology edge, though not as much as before," he contends, adding: "But, in terms of marketing and aggressiveness, DEC is not IBM."

IDC's Brown estimates that IBM will ship 8,000 to 10,000 RT PCs this year. And with continued improvements in networking, software and price/performance, RT shipments could double in 1987, she says.

IBM introduced three new models of System 36, including a high-end

Clearpoint
High Reliability
and High Performance
in 4 or 16 MB
Capacities



■ **The VERSAbus**

Using megabit DRAMs, the VERSARAM demonstrates Clearpoint's commitment to the most advanced technology for the VERSAbus. With a capacity range of 512 KB to 16 MB, the VERSARAM offers maximum capacity combined with maximum flexibility. Clearpoint's custom EDC chip set provides single-bit correction, double-bit detection, error scrubbing and the high performance of 64-bit cacheing.

Write or call for our new designer literature packages.

□ **Clearpoint's 80-page Designers Guide to Add-in Memory**

Contents: Important information on over 20 system buses; details on how to design memory for high performance buses; considerations in configuring a system and selecting memory products; analysis of economic factors; and an industry overview of this genuinely unique market.

□ **The 20-page Add-in Memory Catalog and Selection Guide**




CLEARPOINT INC.

99 South Street • Hopkinton, MA 01748

U.S.A. 1-800-CLEARPT
Telex: 298281 CLEARPOINT UR
Massachusetts 617-435-5395/435-2301
Europe Steptrade, Ltd. (Netherlands)
Telex: 71080 ACT H NL Tel: (31) 23-256073
Asia EPRO Ltd. (Hong Kong)
Telex: 51853 JUNW1 HX Tel: 3-7213300


CIRCLE NO. 25 ON INQUIRY CARD

HI-TECH NOISE KILLER



Class 1
fire-rated material
now available. Send
for free color
literature.

SONEX acoustic foam is deadly to annoying computer room noise. And it'll look great in your hi-tech environment. Simply hang sheets of this patented, professional foam to quiet the combined clatter of fans, motors and printers. Call or write for complete facts and a free brochure: 3800 Washington Ave. North, Minneapolis, MN 55412. (612) 521-3555.



illbruck

CIRCLE NO. 29 ON INQUIRY CARD

POWER PORTS

If you are using multiple asynchronous lines on your 80286-based machine, our intelligent serial expansion cards provide significant performance improvements and programmable features.

- 8088-2 and 80186 on-board-co-processors
- Up to 8 RS-232/422 ports per card
- On-board buffering, XON/XOFF busy/ready protocols
- XENIX™ and DOS drivers available
- Development kit for custom applications

COMPUTONE
SYSTEMS INCORPORATED

One Dunwoody Park
Atlanta, GA 30338

Call (800) 241-3946 and
ask for the

Computer Products Division.

XENIX™ is a registered trademark of Microsoft Corporation.

CIRCLE NO. 30 ON INQUIRY CARD

INTERPRETER

version and two mid-range devices, along with enhanced software, functionality and communications. According to IBM, the new high-end unit offers 3.5 times more memory—a maximum of 7M bytes—than the current system.

Earlier models of the System/36 satisfied small-business needs—the machine originally was designed as a follow-on to the System/34. But industry consensus was that IBM made a big mistake when, about two years ago, it promoted the System/36 as the cornerstone of its departmental strategy, a market niche it was never intended to serve. Large-business customers soon discovered that the System/36 didn't live up to its billing—and the lights on IBM's marquee, in this arena, faded.

DEC, equipped with the VAX computer system, gracefully took the limelight.

"On a price-per-seat basis, the System/36 wasn't comparable to what some other computer companies were offering," says Gartner's Symons. "Users couldn't get adequate performance to justify it," he adds.

In addition, DEC and others offered users smooth migration paths across their product lines. This allowed users to pick and choose systems according to the individual performance needs of departments and divisions.

Sales of mid-range computer systems, priced between \$15,000 and \$250,000, are expected to grow at a compound annual rate of 13.9 percent between 1986 and 1991, according to Symons. During the same years, the numbers for mainframes growth is predicted at 7.4 percent; for microcomputers, 9.9 percent.

In a rare move, IBM stepped out of the IBM universe and introduced an \$850 baseband adapter card that allows the RT PC workstation to communicate in an Ethernet local area network. Developed in 1981 by DEC, Intel Corp. and Xerox Corp., Ethernet was the basis for the IEEE 802.3 networking standard. Ethernet, a popular industry LAN, has more than 100 vendors.

IBM further expanded communications capability for the RT PC by

The right 3½" can put your system ahead of the competition.



Chinon offers OEM's the widest range of quality 3½" floppy disk drives.

Ready to deliver. Now.

A lot of disk drive manufacturers have seen the writing on the wall, and claim to be able to supply the 3½" drives you need. But in many cases their product lines are still severely limited. And they can't deliver them when you need them. Now.

Chinon can. No other company has as wide a range as we offer—more than 10 different 3½" floppy disk drives. All already proven in systems around the world. All with Chinon's renowned quality and reliability. All ready to go.

And this wide range means we have the drive with just the specifications you need.

So don't let a mere 3½ inches delay your entire product introduction. Call Chinon. We have what you need.


Chinon has built a solid reputation providing proven 5¼" floppy disk drives.

CHINON

The name for disk-drive quality.

Chinon America, Inc., 6374 Arizona Circle,
Los Angeles, CA 90045. (213) 216-7611 FAX: (213) 216-7646

CIRCLE NO. 31 ON INQUIRY CARD



Here's the best resolution to your terminal needs.

The Wyse WY-60.

It's everything we know you want in an ASCII terminal, and then some.

Higher resolution. Hidden attributes. Multiple personalities, with emulation of just about anything you'd ever be interested in emulating. Multiple display formats, with up to 132 columns and 44 lines of information on one screen. And soft fonts, so it can be crisp, clean and easily readable in any language.



We've even added WYSEWORKS, a nifty clock/calendar/calculator combination, for extra productivity.

You choose the screen color, and the keyboard layout that suits your application: Wyse WY-60, IBM PC AT or IBM 3161. The adjustable arm option lets you

choose the perfect height and screen position. You can even choose the service plan that works best for you, from a range of options. Behind the WY-60's innocent

good looks is actually the face of unparalleled experience. When it comes to terminals, we ship more than anybody but IBM*. So it's natural we'd come up with a terminal with a lot of years of wisdom behind its good looks.

Call toll-free today, for more information.

Call 1-800-GET-WYSE

WYSE

YOU NEVER REGRET A WYSE DECISION.

WYSE is a registered trademark of Wyse Technology. WY-60 and the "V" shaped design are trademarks of Wyse Technology. IBM PC AT and IBM 3161 are trademarks of International Business Machines Corporation. © 1986 Wyse Technology, 3571 N. First Street, San Jose, CA 95134. *Dataquest 1985 terminal shipment update.

CIRCLE NO. 32 ON INQUIRY CARD

announcing a \$1,095 adapter card that allows the workstation to be connected to the company's proprietary Token-Ring Network.

DEC's Johnson says he isn't too worried about losing position in the workstation market because of the RT networking options. However, Robert Djurdjevic, president of Annex Research Corp., Phoenix, Ariz., thinks the Ethernet connectivity is aimed directly at DEC, which is heavily dependent on Ethernet. IDC's Brown says traditional workstation vendors like Apollo Computer Corp. and Sun Microsystems Inc. are threatened along with DEC.

Brown asserts, however, that IBM's Token-Ring Network is not as sophisticated a product as Apollo's DOMAIN network or Sun's Network File Service (NFS). "But the Token-Ring is a network solution," she adds, "a feature that the RT desperately lacked, if it was to be a viable workstation product." In a design environ-



IBM replaced its System/38 minicomputer line with six new models—100, 200, 300, 400, 600, 700. Integrated with the IBM 9335 (far left) and 9332 storage devices, they provide greater flexibility, options in configuration and capacity.

ment, the ability of workers to easily share project information via networking is a necessity.

Sprucing up the middle tier

IBM's new System/36 line includes the high-end 5360 model D, which offers a maximum of 7M bytes of main memory, and the mid-size 5362


models B and C, both of which provide a maximum of 2M bytes of memory. Up to 16 local workstations can now be attached to the entry-level System/36 PC model 5364 with new software, 1M byte of main memory and two workstation ports. Symons notes that, while the number of attachable workstations has been in-

NEURON

VERSATILE, RELIABLE & FRIENDLY!

SRD Upgrades Data Flow Efficiency With RS232C PC Interfacing.

Innovative SRD sensing and data communication technology gives the NEURON magnetic card reader/writer family a leading edge. Especially in handling ease, reliability and cost-efficiency.



NEURON CT Series Magnetic Card Reader/Writer Units With Built-In RS232C Interface for Direct PC Connection.

- Simple, direct interfacing with IBM* PC and most other computers to boost network system capabilities. (No software or hardware modification using SRD keyboard interface unit for CT-270.)
- Easy, accurate data encoding.
- Superior cost-efficiency and reliability.
- Compact, simple design for excellent handling ease.
- Wide-range models—reader and reader/writer units (manual and motor-driven types). Paper-card reader/writers also available.

Contact us today for details on the advanced CT Series and entire NEURON data scanning product family. OEM inquiries welcome.

SRD CORPORATION

3-7-16, Iwamoto-cho, Chiyoda-ku, Tokyo 101, Japan
 Phone: 03-864-1331 Telex: 265-5008 SRD CO J Fax: 03-866-7486
SRD INC.
 2250 E. Imperial Hwy., Suite 252, El Segundo, CA 90245
 Phone: 213-417-5114 Fax: 213-416-9769

* IBM is a registered trademark of Int'l Business Machines Co.

creased, performance remains the same.

For previous System/36 users, existing 5360 models are field-upgradable to the model D and existing models of the 5362 are field-upgradable to models B and C.

To enhance performance, IBM

added an Advanced Peer-to-Peer Networking (APPN) communications facility to Release 5 of the System/36 System Support Program (SSP). According to the company, APPN allows users to communicate across a network of System/36s and System/38s without the need for a central

controlling systems network architecture host.

IBM also brought out products that permit operation between a System/36 and a System/38 or a System/370, via Distributed Data Management (DDM). DDM provides System/36 users access to data residing on another System/36, System/38 or System/370 processor using the IBM Customer Information Control System/Virtual Storage (CICS/VS).

Additionally, enhanced features were added to four System/36 office applications—DisplayWrite/36, Personal Services/36, PC Support/36 and Query/36.

Replaces System/38 line

In one fell swoop, IBM also replaced System/38 models 4, 6, 18, 20 and 40 with six new computers—the models 100, 200, 300, 400, 600 and 700. Previous models can be upgraded, on site, with the exception of the model 100, IBM says.

In addition to better price/performance features, which include enhancements to the system's operating system, IBM says they've improved connectivity between the System/38 and System/36, in addition to other computer systems.

Djordjevic says that IBM is promoting the System/38 as the migration path for users looking to move up from System/36. "The conversion process from the S/36 to the S/38 is still one of some magnitude," he says, "but this an attempt on IBM's part to keep customers within the IBM fold." He contends that, despite the IBM logo, the diverse architectures of IBM's various computer systems put the company at a competitive disadvantage compared to the product offerings of other major computer vendors.

At the low end of System/38 line is the model 100 with 2M bytes of memory expandable to 4M bytes. Top of the line model 700 offers up to 32M bytes of internal memory, double that of the current model 40. Prices for the products range from \$37,500 to \$385,490. □

DO YOU WANT TO BE A HERO?



Solve your customers' problems. Fast. That's what makes you valuable. And brings them back to you.

Let us help.

Our cable assemblies are the finest available. All built to IBM specs. Every part we use is QPL. No substitutions of cheap components; no shortcuts in assembly. More than the years' experience has taught us there are no shortcuts to quality.

And our service? Fast. And helpful. If you know what you need, call us at 1-800-323-6604 and order it. If you don't, call us and ask. Either way, you can expect same day shipping of built-to-length assemblies.

And you get all the credit.



**NATIONAL
ELECTRIC
CABLE**

Cable Specialists for IBM Systems

1730 Elmhurst Road
Elk Grove Village, Ill. 60007

Chicago (312) 593-8100
Portland (503) 620-9400
San Francisco (415) 785-1277
Houston (713) 464-8555

CALL TOLL FREE 1-800-323-6604

SIEMENS

High Performance Data Storage

310


125

Siemens, a world leader in advanced data processing technology, has the total solution for today's high demand data storage needs.

310 Megabyte capacity 5¼" MegaFile Disk Drive Series offers a wide range of design and performance features for high capacity, high performance data storage and transfer.

125 Megabyte capacity ¼" Streaming Cartridge Tape Drive is the performance solution for backup requirements of high capacity 5¼" disk drives.

Increase your system performance level with reliable, accurate, high capacity data storage and backup. The total solution from Siemens.



Siemens Information Systems, Inc.
Memory Products Division
5655 Lindero Canyon Road, Suite 325
Westlake Village, California 91362
818-706-8872
TX 181528
FAX 818-706-2083

Eastern Region 617-870-0715
Western Region 408-559-7099

Siemens.
Technological leadership for
OEM professionals.

CIRCLE NO. 25 ON INQUIRY CARD

CC/4110-057 WLM 474

Artificial intelligence rides out the slump

Michael Tucker, Associate Editor

While most of the computer industry continues to feel the effects of a hard-dying slump, the artificial-intelligence business grows from strength to strength. AI hardware vendors are enjoying a modest boom, AI software companies are finding themselves on the stock market, and mainstream computer makers continue to invest heavily in AI technology.

Most telling of all, though, is the demand for AI professionals. "Everyone in the conventional computer-recruiting industry is hurting," says Marilyn Dee of Marilyn Dee Associates Inc., Boston, which specializes in placing AI experts. "I'm not. If a resume comes in with two years or so of experience, I can place that person almost immediately."

Says Rod Khanna, director of marketing for LISP Machine Inc., Andover, Mass., makers of LISP "engines" (computers designed to run AI applications): "If it hadn't been for the slump we might have done even better than we did. But, on the average, we were much less hurt than the rest of the industry. I'd say we doubled our business last year."

Symbolics Corp., Cambridge, Mass., one of the first companies to commercialize AI hardware, reports similar gains. Revenues went up 73 percent in 1985, to over \$69 million, and profits boomed 300 percent.

In late March, Symbolics moved into the value-added reseller market and signed up its first VAR, ICAD Inc. of Woburn, Mass. ICAD will use Symbolics' machines to produce an intelligent workstation for design engineers.

Other makers of LISP machines, including such titans as Xerox Corp., Stamford, Conn., and Texas Instruments Inc., Dallas, are equally bullish.

But the real proof of AI's commercial success may be in software development. Programmers and software developers are enjoying an AI gold

rush. "I would say that nearly 30 percent to 40 percent of all programmers have some interest in exploiting AI," notes Bruce Lynch, president of The Programmer's Shop, Hanover, Mass., a remarketing company that specializes in tools for programmers. "AI tools are becoming a lot more common," he says, "and for us, they're a stable market."


It's a stable market with a lot of players, among them such well-known names as Carnegie Group Inc., Pittsburgh; Inference Corp., Los Angeles; and IntelliCorp, Mountain View, Calif.—all makers of tools for LISP machines and other AI computers. These developers demonstrate faith in their products by taking their stock public.

Teknowledge Inc. of Palo Alto,

Calif., is a company that has gone public for the first time. Teknowledge develops expert-system generators for such machines as the Xerox Series 1100 workstation, the Digital Equipment Corp. VAX and, as of this year, the IBM Corp. PC/AT and RT PC. Teknowledge took its stock public in March with an offering of 2,180,000 shares. Despite strong competition from other AI software companies, a volatile market and an uncertain customer base, investors eagerly bought out the entire initial offering at \$13 a share—not bad for a company that was incorporated a mere five years ago.

Lotus looks to AI

Mainstream software companies are also getting into the AI business. Most publicized, of course, are companies such as Lotus Development Corp., Cambridge, Mass., which is attempting to mate traditional business applications such as 1-2-3 with more exotic AI software. Lotus is attempting to solve





Newbury's solution to The Great American Printer Hang-up.

We've taken all the wrinkles out of paper handling.

Now you can have reliable paper handling for more high-speed, dot matrix printing time. Newbury Office Systems Printers (OSP) are designed to more than match the capabilities of your Personal Computer — whether your application is word processing or financial modeling, using shared resources or local area networks.

Set-ups and change-overs have never been easier with our 3-way paper handling.

In addition to speedy printing, Newbury gives you a new standard in 3-mode convenience and flexibility. We've integrated a unique, automatic paper-feed mechanism that is fast and reliable. It features self-registration auto-load for single sheets. Simply snap in an interlocking paper cassette for faster automatic sheet-feeder applications. Or, snap in the interlocking tractor option with single belt and gear for true alignment of continuous forms.

Newbury offers more things for more offices.

Even at speeds of 200 cps, noise levels are quieted to less than 50 dBA. For print quality that is truly outstanding Newbury offers 9, 12 or 18-wire OSP models. All feature high-speed printing thru-put with Newbury's exclusive 3-line look-ahead logic, low-mass, high-efficiency printheads, and fast-line advance. And when you're ready for color, you have it by just inserting a clip-in color ribbon cartridge.

CIRCLE NO. 35 ON INQUIRY CARD

Document after document, Newbury delivers faster thru-put rates and a total-feature-package that just makes more sense for more offices.

Get more details immediately.

Newbury Data

A member of the DRI Group

Europe's Leading Peripherals Manufacturer

Newbury Data, Inc. U.S. Headquarters

2200 Pacific Coast Hwy., Suite 208

Hermosa Beach, CA 90254

Phone: **So. West** 213/372-3775, **No. West** 415/254-8350,

No. East 617/273-2161, **So. East** 512/477-1221


mms 9 86

For OEMs and Distributors Only.

- Rush details on Newbury's OSP Printers.
- Send info on Newbury's 8850 300 lpm serial dot matrix printer.
- Send info on Newbury's model 8933 240 cps Text Processing Printer.
- Send data on Newbury's 3.5" /60MB and 5.25" /65 to 380MB high-performance Disk Drives.

Name _____ Title _____
 Company _____ Phone _____
 Address _____
 City _____ State _____ Zip _____

If you can't put a Hayes modem on every PC in your IBM network, here's the next best thing.



© 1986 Hayes Microcomputer Products, Inc.

*Manufacturer's estimated retail price.

It's new communications software from Hayes called Smartcom II® for the PC Network.

It lets you share modems. So even PCs without their own modems can communicate outside the network.

Before now, if you needed to communicate outside the network, you had to physically go to wherever the modem was. That, in turn, meant bumping the operator off his modem-equipped PC, so that you could handle your communications.

Hayes Smartcom II for the PC Network puts an end to all the delay and inconvenience. Now, when a PC needs the modem, the user is automatically connected from his own desk. So communications

capabilities are immediately available to everyone on your network, whether their PC has a modem or not.

You only buy one software package per modem. The workstation part of the software can then be duplicated for each PC on the network, at no extra cost. It's better than having a site license!

Each PC can have its own password, define its own log-on procedures, set its own macros, and use

all the other outstanding operating features of our standard Smartcom II while connecting with any of the shared modems on the network.

You get all this for only \$599*! And it's backed by Hayes, the PC communications leader.

So if you currently utilize, or are contemplating adding, IBM PC networks, you should also add Smartcom II for the PC Network. For efficient communications. Without delay.

See your authorized Hayes dealer for details. Or contact Hayes at 404/441-1617.

Hayes Microcomputer Products, Inc., P.O. Box 105203, Atlanta, Georgia 30348.

Hayes®

Say yes to the future

CIRCLE NO. 36 ON INQUIRY CARD

the technology transfer by helping create an AI development shop, Arity Corp., Concord, Mass. Arity has developed a series of AI products that interface with such Lotus applications as 1-2-3 and Symphony. These new packages include an expert-system generator and an implementation of Prolog, second only to LISP in its popularity as an AI language.

Lotus' strategy in all this has been rather unusual, and other established software concerns would do well to study it. Arity president Peter Gabel was formerly a Lotus employee and a key figure in the development of 1-2-3. Paul Weiss, Arity vice president of research and development, is also a former Lotus employee. Lotus also is one of several sources of Arity's funding along with UST Capital Corp., the venture capital division of United States Trust Company. As a result, Lotus has the best of many worlds. A less savvy firm might have tried to do the kind of research Arity is doing but in an entirely captive R&D division.

Indeed, in-house research has considerable advantages, but given the nature of software development—where the real value of any operation lies in personnel rather than in capital equipment—that approach could have exposed the company to the risk of its employees setting up shop as competitors. With Lotus' approach, where the company effectively plays venture capitalist, those former employees have been converted to suppliers with strong incentives to see their customer succeed.

Moreover, Lotus gains the fruit of Arity R&D without having to foot the entire bill. Since Arity is an independent company, a significant part of its funding (as well as a share of the risk of its failure) has been shouldered by other investors, particularly UST Capital.

Lotus calls this kind of arrangement a "spin-out," and there are risks in it for the parent company. It could be balkanized quickly if "entrepreneur fever" should strike an entire R&D staff. But Lotus seems to believe that whatever risks are involved are well worth the rewards of AI products.

Less prominent than Lotus and its child, but perhaps more important to the growth of AI, are the compiler makers. Will a programming language be successful? One need only look at who is writing a compiler for it. And judging by the compiler support teams, AI languages are suddenly very hot markets.

The two languages most often used in AI programming are LISP and Prolog. LISP has long had the lion's share of American AI research, and it's no news that the language has powerful friends in high places. What is news is that some of those friends are manufacturing large-scale concurrent computers. One of the leading LISP merchants is Gold Hill Computers, Cambridge, Mass., whose Common LISP implementation has the largest installed base of Common LISP users around. Last December, Intel Corp. announced that it would be working with Gold Hill to produce a LISP that would work on concurrent, multiprocessing computers—specifically Intel's own iPSC machines.

Prolog is also gaining adherents. For a long time, the language's relative unpopularity in the United States led some experts to believe that Prolog compilers couldn't be sold profitably. Yet companies such as Quintus Computer Systems Inc., Palo Alto, Calif., have become successful by selling Prolog to developers who are looking for an AI language that is easier to use than LISP. Prolog is starting to appear on IBM Corp. PCs. Spencer Leyton, president of software vendor Borland International, Scotts Valley, Calif., announced recently that his company would be marketing a Prolog compiler "in the near future." Borland has been known primarily for its Pascal compiler.

Recently, artificial intelligence came to the the Apple Computer Inc. Macintosh. ExperTelligence Inc., Santa Barbara, Calif., began shipping ExperLisp last year. ExperLisp is a LISP compiler with a lot of Macintosh touches, such as extensive use of graphics, pull-down menus and multiple windows. Perhaps its most unusual characteristic, though, is its use of vir-

tual memory, where the compiler loads code from the disk only when it's actually needed for running the program.

Recruiting to success

The real sign of AI's success, however, may lie in its star players. Companies can conceal their intentions, but not their recruiting. "Everybody's hiring," says Marilyn Dee. "Start-ups, military companies, small firms, large companies—everybody. If I had to give one answer to what they want, I'd say it's expert-system engineers, because expert systems are where they think they can make money. The other thing they're looking for, of course, is LISP hackers."

Dee says that AI experts are experiencing a seller's market. Most of her clients are currently looking for practiced developers who can command salaries in the \$50,000 to \$100,000 range. In fact, American companies have become so hungry for AI skills that they've begun to raid Europe for talent. Early this year, Dee began wooing software experts at such traditional European AI centers as Edinburgh, Scotland and Paris.

Some proponents of AI argue that mainstream computing, traditionally user-unfriendly and removed from the thought processes of human beings, was desperate for a way to integrate itself with the real world. AI, with its ability to imitate human thought, promises a way to eventually do just that.

Larry Walker, director of the Knowledge Systems Group for Sperry Corp.'s AI research in Bloomington, Minn., explains, "I think AI will create a real revolution. It will close the gap between computers and computer users."

All the same, even the strongest advocates of AI warn integrators against leaping into the field without looking first. "They should be cautious, because there's so much hype in AI," says Dee. "My formula would be to move slowly, make certain you have top-notch technical people, and make just as certain you have top-notch management people." □

IN SEARCH BUSINESS TO



I OF YOUR BUSINESS I.D.

Fulfilling your idea of the perfect peripheral involves an evaluation that goes deeper than what first meets the eye.

In effect, it entails a peripheral that is right in terms of technology, price and performance. A product that guarantees integration and function, while also adding to the value of your own system.

Getting everything right also involves evaluating your supplier's ability to deal with the special demands imposed by your operations and system solution.

When evaluating a Facit Peripheral you should also look closely at the company behind the product. At our organization, production capacity, quality control, support and service. And – not least – assessing whether our technical expertise and vision matches your business concept.

Then, our joint business-to-business operations can really take shape. We impose the most stringent demands on ourselves to earn and keep your confidence. In the long run, too.

Our frank approach is aimed at establishing lasting relationships. And our open-door R&D policy offers you all the possibilities to influence the development of tomorrow's products.

Nice words! But they are not just shallow promises. Our printers, plotters and video terminals already carry many Datamation 100 I.Ds.

We would be proud to carry yours, too.





FACIT

Your original peripheral equipment supplier

Head Office: *Facit AB, S-172 91 Sundbyberg, Sweden. Phone: (8) 764 30 00.*
USA: *Facit Inc. P.O. Box 334, Merrimack, NH 03054. Phone: (603) 424-8000.*

CIRCLE NO. 252 ON INQUIRY CARD

This bus won't make you wait.



The Motorola VMEbus Microprocessor Modules from Hall-Mark.

You won't fall behind schedule with Motorola's line of VME Microprocessor Modules from Hall-Mark Electronics.

The MVME line is a family of versatile, VMEbus-compatible board-level computers that offer the performance required for data processing, data management and industrial control. Applications for these products range from high-speed single processor systems through systems of complex multi-

processor architecture.

- M68000-based
- Open architecture
- No fees
- Flexible
- 1000+ compatible products
- In stock now

Hall-Mark won't make you wait, either, with 32 stocking locations nationwide and a real-time, on-line computer system. So don't wait. Call Hall-Mark today.

Alabama
Huntsville (205) 837-8700
Arizona
Phoenix (602) 437-4200
California
Bay Area (408) 946-0900
Orange County (714) 669-4700
Sacramento (916) 722-8600
San Diego (619) 268-1201
San Fernando Valley (818) 716-7300
West Los Angeles (213) 217-8400
Colorado
Denver (303) 790-1662

Connecticut
Connecticut (203) 269-0100
Florida
Ft. Lauderdale (305) 971-0280
Orlando (305) 855-4030
Tampa Bay (813) 530-4543
Georgia
Atlanta (404) 447-8000
Illinois
Chicago (312) 860-3800
Indiana
Indianapolis (317) 872-8875


Kansas
Kansas City (913) 888-4747
Maryland
Baltimore (301) 988-9800
Massachusetts
Boston (617) 935-9777
Minnesota
Minneapolis (612) 941-2600
Missouri
St. Louis (314) 291-5350
New Jersey
Fairfield (201) 575-4415

New York
Long Island (516) 737-0600
North Carolina
Raleigh (919) 872-0712
Ohio
Cleveland (216) 349-4632
Southern Ohio (614) 888-3313
Oklahoma
Tulsa (800) 238-0253
Pennsylvania
Philadelphia (215) 355-7300

Texas
Austin (512) 258-8848
Dallas (214) 553-4300
Houston (713) 781-9100
Utah
Salt Lake City (801) 972-1008
Wisconsin
Milwaukee (414) 797-7844




FEATURE HIGHLIGHTS



p. 61 A real possibility

REAL-TIME UNIX SEIZES NEW PRODUCTS, MARKETS.61


The widespread acceptance of UNIX in the manufacturing arena depends on the ability of vendors to develop real-time capabilities for the operating system. What functions and features are necessary for an OS to be real-time, and how can UNIX be extended or redesigned to provide those capabilities? Who's doing what, and how are they doing it?



p. 83 New game rules

LINKING DATABASES FORCES NEW STRATEGIES ..83

Vendors of database management systems are under tremendous pressure to fit their products into distributed environments. However, there are various ways to achieve that goal. Some companies believe that data should be truly distributed, others argue for centralization, and a third camp argues against handling distributed file management within the applications software. We look at the strategies.



p. 93 FEPs offer path

FEPs EASE MIGRATION TO NEW LAN PROTOCOLS .93

A confusing plethora of LAN protocol standards has finally emerged. But LAN users and integrators need not fear that the proliferation of these protocols—or of new protocols that emerge in the future—will make current installations obsolete. Front-end processors (FEPs) allow system integrators to preserve their capital investments in LAN equipment while gracefully migrating to new protocols that might better suit their applications.

IBM'S TOKEN-RING: WHAT ARE THE ALTERNATIVES?105

Big Blue's Token-Ring Network isn't the only game in town. A variety of companies offer some combination of competing or compatible LANs and related equipment and software. But sorting out the LAN selection criteria isn't easy.

CHIP SET PAVES THE WAY TO TOKEN-RING ACCESS121


Texas Instruments Inc.'s TMS380 chip set allows system integrators and designers to build their own adapter cards for products such as personal computers and printers that can benefit from attachment to IBM's Token-Ring Network. The goal, of course, is to differentiate products in a market that is already crowded.

Digital
has
it
now.



Presenting the MicroVAX II™ computer: a low-cost per user, high-powered system that's part of a single computing architecture extending from the team level clear up to data centers.

Because this architecture features a full range of communications and networking protocols for both Digital and non-Digital environments, MicroVAX II users can connect to any system in your organization, anywhere in the world. They can run thousands of applications that have been developed for other




A departmental computer that puts the computing resources of the entire corporation in the hands of any user, anywhere.

VAX™ computers, even integrated software packages such as All-in-1™ or A-to-Z.™ In addition, a MicroVAX II system can function in the office as an inexpensive front end to off-load larger VAX computers, or as a central server for personal computers and workstations. Instead of an "island of automation," the departmental computer is now a full-fledged member of the corporate team.

To get the competitive advantage MicroVAX II can give your departmental groups now, call your local sales office or Authorized Digital Dealer, or write: Digital Equipment Corporation, 200 Baker Avenue, West Concord, MA 01742.

digital™

A 100 USER 14 MIPS BUSINESS COMPUTER FOR UNDER \$6,000?



BIG COMPUTER
... Little Price!
AMAZING

Amazing? Not really when you consider who manufactures this system: IBC. We have been building multi-user super-micros for the past seven years, and we are good at delivering the most bang for the buck!

? ? ? **Under \$6,000.00** ? ? ?

Now for the disclaimer: For under \$6,000 you get the IBC Ensign S-6810, and by adding three serial expansion boards, and two dual 68020 CPU boards, the Ensign II really will support 100 users. Its four 20MHz 68020's running in parallel will perform at 14 MIPS. Without going into a lot of detail on MIPS just remember a half million dollar Digital VAX*8650 performs at a maximum of 6 MIPS. Also the \$6,000 Ensign S-6810 comes with a 25MB hard disk. With 100 users you may wish to add a few of our 280MB hard disks.

A Fifth the Price of a Competitive System

To be honest, a 100 user Ensign with four 20MHz 68020 CPU's, four 10 MHz 68010 CPU's, 2MB high speed static memory, 16MB dynamic memory, over 1MB of disk and serial I/O buffers, with a 280MB hard disk, and 60MB tape drive will cost about \$75,000 plus the cost of your 100 terminals, and printers. But even at \$75K it is a steal when you consider it is about a fifth of the price of a competitive system.

Now after all is said and done, what IBC can deliver is the only low cost multi-user super-micro that can easily expand to compete against computers costing five times as much.

Look at these specifications and let us make a believer out of you.

LOW END

10MHz 68010 CPU Four 20MHz 68020 CPU's*
1MB memory 2MB high speed static memory
25Mbyte hard disk 16MB dynamic memory
8 serial I/O ports 280MB hard disks (up to three)
100 serial I/O ports

HIGH END

*Disk I/O and serial I/O are controlled by four 10MHz 68010 CPU's with over 1MB I/O buffer

And remember that low end system for under \$6,000 can easily expand to the high end system—or anywhere in between.

If you use UNIX* systems, and need low prices, and high performance then give us a call. We are the only company that can sell you a low cost computer that will **last you for life.**

The IBC Ensign II...The computer you won't outgrow.

VARS, call IBC now to find the best dealer discounts in the industry. Remember, if you don't, your competition will.



21621 NORDHOFF STREET, CHATSWORTH, CA 91311
TELEX: 215349 TELEPHONE: **(818) 882-9007**

Nationwide on-site service available from
REI/Recognition Equipment, Inc.
(800) 225-8515

*VAX is a trademark of Digital Equipment Corporation.
*UNIX is a trademark of AT&T Bell Laboratories.

REAL-TIME UNIX SEIZES NEW PRODUCTS, MARKETS

Real-time UNIX, long considered a contradiction in terms, suddenly becomes a growth industry due to government and large corporation mandates

Wendy Rauch-Hindin
Special Features Editor

Anyone who has ever had to migrate operational software from one computer and operating system to another knows that application portability leaves much to be desired. In fact, it is sometimes less difficult and expensive to retain a no longer adequate computer than it is to buy a new one and rewrite software.

Realizing that the dominant cost of a computer system today is the development and maintenance of the software, several large-scale users have taken steps to promote software transportability by standardizing on the UNIX operating system.

General Motors Corp., for example, is pushing to make UNIX a standard operating system for its manufacturing plants. As part of this effort, GM has formed a UNIX Task Force, which is comparable in purpose and function to its Manufacturing Automation Protocol (MAP) Task Force and may prove to be as far-reaching. The GM UNIX Task Force is cooperating with the IEEE and /usr/group standards committees to develop general-purpose UNIX standards and also to develop real-time UNIX standards for time-critical manufacturing applications. In fact, an IEEE trial-use UNIX standard was approved in March.

Nor is General Motors alone in its efforts to drive the market toward UNIX. In 1985, the federal government specified UNIX in 80 percent of its RFQs (requests for quotations). Certain financial institutions are looking to decouple their applications from hardware by migrating to UNIX. And large manufacturing

firms, like Hughes Aircraft Co. and Chrysler Corp., are experimenting with real-time UNIX pilot programs.

But it's GM that vendors must watch when planning their future UNIX directions. The desire for software transportability is particularly important in manufacturing environments. They are typically multivendor and characterized by rapid advances in technology that require equipment replacement and corresponding application rewrites. So, fresh from its success in organizing manufacturers and vendors to specify and supply MAP-standard communications products, GM is now attempting the same aggressive tactics in regard to UNIX.

Skeptics raise questions

Success is far from assured, though. The development of real-time capabilities for UNIX will determine UNIX's widespread acceptance in the manufacturing market. Many factory, area, cell, and intelligent-device management and control tasks require a real-time operating system (RTOS). UNIX, however, was designed as a systems-and-development operating system, and it lacks many features that an RTOS needs.

In order to adapt UNIX for manufacturing environments, the real-time standards committees must address two questions: What functions and features are necessary for an operating system to be real-time, and how can UNIX be extended or redesigned to provide these capabilities? Skeptics question whether real-time extensions, or patches, to UNIX are the most efficient way to support real-time capabil-

ities, and they wonder how much UNIX can be changed before it is no longer UNIX. Moreover, system integrators are uncertain whether the plans of the computer-manufacturer pacesetters will help or hinder them.

With cooperation from technical experts, users and vendors, details about real-time UNIX's promise, problems and feasibility have been pieced together. But real-time means different things to different people. Therefore, insight into UNIX trends requires some understanding of how the standards group are defining real-time systems.

Concerning the pacesetters, IBM Corp. supports real-time capabilities in its UNIX-based RT PC. AT&T Co. also has been investigating methods to integrate real-time features with UNIX since the late 1970s. Several types of real-time UNIX systems are up and running internally, and AT&T says it will soon have a

draft form of real-time extensions for its System V Interface Definition (SVID). Digital Equipment Corp. says it will comply with the IEEE P1003 standard, and will have SVID real-time extensions as the market demands them. Hewlett-Packard Co. will shortly announce a real-time version of System V UNIX for its computers. Gould Inc. is moving toward a real-time UNIX for its superminicomputers. Allen-Bradley Co. already offers real-time UNIX in its Vista 2000 computer.

Earmarks of real-time described

An RTOS differs from a general-purpose system in being deterministic—that is, it responds to asynchronous, external events within a set amount of time. The response time may vary from μ sec to seconds, depending on the application. High bandwidth, throughput and fast execution are desirable, but are not as funda-

When is an operating system real-time?

The following items are among the requirements for a real-time operating system (RTOS) as agreed on by the IEEE and /usr/group real-time UNIX subcommittees:

- **Response to asynchronous events:** Real-time systems need asynchronous I/O and interrupt-handling capabilities to respond to asynchronous external events within the bounded time required by the real-time system. The I/O response time is often limited by the time needed for memory access, disk access and the speed of the processor bus.

- **Context-switching time:** Real-time systems must service critical tasks immediately, within specific time constraints, regardless of what they are doing when the time-critical event occurs. Context-switching time—a key real-time metric—is the time required to switch between tasks. It is determined by how long it takes the operating system to store the state of the computer and the contents of the registers so that it can return to processing its previous task after servicing the interrupt.

- **Interrupt latency:** Perhaps the most important real-time system metric, interrupt latency is the longest period of time possible for a system to acknowledge the highest priority interrupt and dispatch a process to service it. Unfortunately, interrupt latency is a non-deterministic (not predictable) metric and, therefore, difficult to measure. For various reasons, in most cases, a system cannot guarantee that an interrupt will always be serviced in the same amount of time. The time lag before an interrupt can be serviced is influenced by factors such as the speed of the bus and of the processor (both deterministic) as well as

the overhead to select the appropriate routine to service the interrupt, the loading of interrupts on the system and the amount of state that needs to be saved (all non-deterministic). For example, an interrupt may have to wait while an undeterministic number of higher priority interrupts are serviced. The time lag is further complicated because in an operating system there are often critical processing paths that must be completed before an interrupt can actually be processed.

- **Priority interrupts and scheduling:** An RTOS must allow users to define priorities for interrupts and tasks to be scheduled and specify how interrupts are to be serviced. This ensures that the most important tasks are serviced within the allotted allowable time constraints, regardless of other system events.

- **Pre-emptive scheduling:** To guarantee response times, RTOSes must allow a high-priority task to pre-empt execution of a lower priority task as soon as the high-priority task is ready to run.

- **Memory-locking:** Real-time systems generally must allow a program or part of a program to be defined as memory-locked. Locking a program in memory guarantees fast response times because it eliminates time-consuming disk accesses to obtain the program.

- **Contiguous files:** RTOSes should provide the means to optimize data storage on a disk to minimize the seek time when retrieving or writing data. Generally, this calls for storing data in contiguous files.

- **Synchronization:** Real-time systems need a means to synchronize and coordinate the use of shared data and task execution.

HOW TO BE IN 6 PLACES AT ONCE.

Only a Falco 500 Multi-Host Terminal can open windows onto all these worlds-today.

No other product in its class delivers productivity like the Falco 500 Multi-Host Terminal.

1. THE ANSI WORLD OF DEC MINICOMPUTERS.

Because no one can match its high-performance specs. Which are—in a word—spectacular.

For openers, take the Falco 500's multi-host capabilities. They let you communicate with separate computers through two bidirectional ports—concurrently. Ports that can be configured automatically



2. THE UNIX WORLD.

as RS232C or RS422. So you can enter or retrieve data from any of the computer worlds shown here—plus hundreds of others. And switch between any of them with a single keystroke. No other terminal today offers this kind of multi-host capability. Period.



Then too, nobody does win.

dows like the Falco 500. Nobody. It lets you create six windows on one screen—each one configured as a separate terminal. That means each one has its own operating

3. THE REMOTE TELECOM WORLD.

mode, compatible with virtually all ANSI and ASCII terminal protocols. Plus its own set of 64 programmable function key levels. And its own segment of dedicated display memory. Meanwhile, the competition's only got split screens. No contest there, either.



4. THE ELECTRONIC-MAIL WORLD.

Maybe you don't need to talk to this many applications from a single terminal—today.



But if you're getting ready to install multiple computers or replace single-function terminals—don't. Until you look at the Falco 500.

It's the only terminal that lets your operators be in six places at once—getting lots more work done. And the only one that doesn't mind if those places are ANSI- or ASCII-oriented; mainframe, mini or micro; or located in an office, factory or engineering lab. Plus the

5. THE LOCAL AREA NETWORK WORLD.

adaptability of the Falco 500 means you no longer need several terminals doing just one thing at a time. Because it does six things on one terminal—half a dozen on another.

To start opening windows today on a more productive,



6. THE ASCII WORLD OF SUPERMINIS AND MICROS.

multi-host world, contact your Falco distributor. For the one nearest you, contact Falco Data Products, 1294 Hammerwood Avenue, Sunnyvale, CA 94089; (408) 745-7123. Toll-free (800) 835-8765.



FALCO 500

THE SPECTACULAR PRODUCTIVITY MACHINE.

DEC and Digital are registered trademarks of Digital Equipment Corp.

CIRCLE NO. 43 ON INQUIRY CARD



The STR[®]-STREAM II 1/2" Tape Drive.

200 million bytes can't be wrong.

If you've got a lot of data to backup off your system hard disk (up to 200 Mbytes) and can't afford a lot of time to make sure it's done accurately, then you should take note of the new EPI STR-STREAM II 1/2" cartridge tape drive. It features up to 150 Mbyte (formatted) capacity in a single 1/2" tape cartridge, one of the lowest cost-per-Mbyte figures of any competing mass storage device, and the proven accuracy of reel-to-reel technology.

The screamin' streamer.

You get an almost unbelievable 225 kbytes/sec transfer rate. That coupled with an EPI controller means it can operate continuously in streaming mode to backup a full 200 Mbytes (unformatted) in under 19 minutes. And deliver a guaranteed bit error rate of less than one hard error in 10¹¹ bits.

Compatibility, innovation, and reliability complete the story.

Tape guide accuracy of $\pm .001$ inch means that tapes can be freely interchanged between any STR-STREAM II drives. And our proprietary multi-bump, constant-curvature head assures accurate and repeatable head-to-tape contact. The drive fits in the same space as a standard 5 1/4" disk drive, operates off the same supply voltages, and features a superior MTBF of 15,000 power-on hours.

For more information on the STR-STREAM II 1/2" cartridge tape drive, call us today at (303) 761-8540, or write Electronic Processors, Inc., 1265 W. Dartmouth Ave., Englewood, CO 80110.

 **ELECTRONIC PROCESSORS
INCORPORATED**

"Let EPI remember for you."

CIRCLE NO. 44 ON INQUIRY CARD

080601

mental to real-time performance as is deterministic (predictable) response time. Reliable, fault-tolerant performance, however, is necessary to an RTOS. Any other case results in a loss of data and the inability of a possibly critical action to occur.

Many factors must be weighed to decide if an RTOS can meet its response time objectives (see "When is an operating system real-time?" Page 62). Among them, an RTOS must be able to quickly store the state of a machine and switch to a critical task (context switching time). It must be able to quickly respond to an interrupt (interrupt latency). It must allow tasks to be scheduled according to priority and allow high-priority tasks to instantly pre-empt processing of lower priority ones. Contiguous storage of files on disk, a means to synchronize tasks and use shared data, the ability to lock part of a program in memory, and asynchronous I/O are still other RTOS requirements proposed at the IEEE and /usr/group meetings.

What about UNIX?

UNIX, in its current form, is not appropriate for real-time use because it lacks several features necessary for real-time operation. For example, UNIX does not support priority scheduling. It uses a round-robin scheduling technique wherein all users are assigned an equal time-slice. It supports interrupts, but they are all equal. Also, UNIX does not store files contiguously on disk.

In addition, UNIX systems use synchronization methods that many IEEE UNIX standards developers consider inadequate. One method, signals, can be limited and unreliable under certain conditions. For example, if two signals arrive faster than the signal handler can take control, only one bit of status information gets set and the system misses the occurrence of an event. System V also supports semaphores—a more sophisticated synchronization method, but believed by some to be overly complex for a real-time environment and not extensible to local area network environments.

These shortcomings are surmountable, however. But many users and vendors question the ability of a real-time UNIX to match the capabilities of a real-time executive and wonder whether the trade-offs involved make it practical to try.

For many users, though, the prospect of application portability more than makes up for the effort to develop a UNIX standard for real-time computing. As it stands, GM has real-time UNIX pilots controlling and managing its paint shops. Chrysler has real-time

UNIX applications in its testing facilities. Several automotive, communications equipment and semiconductor manufacturers are using real-time UNIX for robot control, monitoring, data collection, shop-floor control and production-line tracking. The Navy is investigating a Gould-developed fully functional flight simulator running under real-time UNIX.

How to make UNIX real-time

There are three major methods of providing UNIX with real-time capabilities. These are in addition to a fourth alternative where a dedicated real-time executive is integrated with traditional UNIX.

The first technique for making UNIX real-time is to add real-time extensions to the UNIX operating system kernel. Typical examples come from Charles River Data Systems Inc. and Masscomp. Charles River created its real-time Unos operating system out of UNIX, as Masscomp did its RTU, by adding real-time extensions such as priority interrupt and scheduling, contiguous files and enhanced-performance and interprocess communications.

Charles River Data also added, as a real-time extension, a non-UNIX synchronization mechanism known as "Eventcounts." Eventcounts was designed originally at the Massachusetts Institute of Technology for multiprocessor synchronization because up-down counting semaphores (one of System V's synchronization techniques) could lose count of event occurrences if one processor increments a semaphore at the same time as another decrements it.

The Eventcounts mechanism avoids this by providing a monotonically increasing counter. This facility is contained in the file name space, so that unrelated routines can use the same counters. This permits passive monitoring and broadcast events—neither of which are supported by signaling (UNIX's other synchronization facility), and only some are supported by semaphores.

A second way to give UNIX real-time features is to change the kernel. For example, when Gould developed its real-time UNIX for a Navy simulation project, it substantially changed certain system calls (such as the "ioctl" call). This gave user tasks more effective control over physical devices.

Actually, many real-time UNIXes, including some of those already discussed, employ a combination of kernel modifications and extensions. Extensions leave the kernel intact and are simple to implement. But certain important real-time capabilities, such as pre-emption of interrupts, must be achieved through kernel

UNIX, in its current form, is not appropriate for real-time.

The Convergent Principle Applied:

Our networks let you share


For a business to succeed, great ideas must be shared throughout the company. But a single network can't connect all the different kinds of computers you find in business today. That's why we offer a choice of networks that let you link workstations, PCs, minicomputers and mainframes in the specific arrangement that best suits your needs.

THE BUILT-IN NETWORK

For simplicity of networking, we built the Convergent Cluster™ into every NGEN® workstation. This inherent

network eliminates specification and installation problems. All you do is connect the cables. And with CT-Net™, you can link Clusters together as easily as you connect workstations, so that your networks can grow as your organization grows.

Through the Cluster, workstations share databases, modems, printers, files, programs and communication resources. Because the network operates invisibly, people can use the Cluster without changing the way they normally work.



great ideas with others.


THE EXTENDED NETWORKS

Obviously, not all computers are designed for the Cluster. So we offer SNA or X.25 communication packages that link workstations to large mainframes or public data bases.

All our networks are backed by Convergent's commitment to excellence in engineering, craftsmanship in manufacturing and fast turn-around in high-volume production.

We'd like to show you how this convergence of thinking can work for you. Call us for more information at 800-538-8157, ext. 951 (in California call 800-672-3470, ext. 951; in Europe call 44-2404-4433). Or write us: Convergent Technologies, 2700 North First Street, P.O. Box 6685, San Jose, CA 95150-6685, Attention: Mail Stop 10-015.

That is, if great computers and total networking sound like good ideas to you.



Convergent

When great ideas converge, great products emerge.

Real-time UNIX application portability must wait for standards.

modification.

Unmodified, "vanilla," UNIX allows a pre-emption and a context switch to a higher priority process only at the beginning or end of a kernel service. This can cause interrupt latencies in the range of 1 second or more—unacceptable for some real-time applications.

In one hybrid real-time UNIX, Hewlett-Packard modified the HP-UX kernel by inserting kernel pre-emption points throughout the kernel code. This allows pre-emption of an in-process kernel service in order to schedule a higher priority real-time program in response to an interrupt. The kernel modification improved the worst-case response time of the system by 1 to 2 orders of magnitude, depending on the application and the interrupt loading of a system. But HP implemented other HP-UX real-time features as extensions, such as priority-based scheduling, pre-allocation of disk space and certain kinds of performance tuning.

The modified, extended operating system is still compatible with AT&T's SVID because the real-time services are transparent to the SVID and, in fact, run beneath it. But, once IEEE standards are established, and the SVID has real-time extensions, then individual real-time extensions and kernel modifications will no longer be transparent to the SVID. AT&T says that it will probably implement the SVID real-time extensions by providing a UNIX-level real-time interface to communicate with a kernel-process task performing the real-time function. Creation of that task would be transparent to the user.

Developers throw away the kernel

The third technique for developing a real-time version of UNIX is to keep the UNIX interface but replace the UNIX kernel with a real-time kernel. Alcyon Corp., AT&T, and IBM used this technique in developing Alcyon's Regulus; AT&T's Mert and RTR/

Companies mentioned in this article

Alcyon Corp.

5010 Shoreham Place
San Diego, Calif. 92122-3954
(619) 578-1155
Circle 438

Allen-Bradley Co.

747 Alpha Drive
Highland Heights, Ohio 44143
(216) 449-6700
Circle 439

AT&T Information Systems

100 Southgate Parkway
Morristown, N.J. 07960
(201) 898-8000
Circle 440

Automation Engineering

P.O. Box 341106
Memphis, Tenn. 38138-1106
(901) 382-5544
Circle 441

Charles River

Data Systems Inc.
983 Concord St.
Framingham, Mass. 01701
(617) 626-1000
Circle 442

Concurrent Computer Corp.

197 Hance Ave.
Tinton Falls, N.J. 07724
(201) 758-7000
Circle 443

Digital Equipment Corp.

146 Main St.
Maynard, Mass. 01754-2198
(617) 897-5111
Circle 444

Gould Inc.

Computer Systems Division
6901 W. Sunrise Blvd.
Fort Lauderdale, Fla. 33313-4499
(305) 587-2900
Circle 445

Heurikon Corp.

3201 Latham Drive
Madison, Wisc. 53713
(608) 271-8700
Circle 446

Hewlett-Packard Co.

3404 E. Harmony Road
Fort Collins, Colo. 80525
(303) 226-3800
Circle 447

Hunter & Ready

445 Sherman Ave.
Palo Alto, Calif. 94306
(415) 326-2950
Circle 448

IBM Corp.

Old Orchard Road
Armonk, N.Y. 10504
(914) 765-1900
Circle 449

Industrial Programming Inc.

100 Jericho Quadrangle
Jericho, N.Y. 11753
(516) 938-6600
Circle 450

Masscomp

1 Technology Park
Westford, Mass. 01886
(617) 692-6200
Circle 396

Software Components Group

4655 Old Ironsides Drive
Santa Clara, Calif. 75054
(408) 727-0707
Circle 397



Technical Systems Consultants Inc.

111 Providence Road
Chapel Hill, N.C. 27514
(919) 493-1451
Circle 398

Wind River

Systems Inc.
1316 67th St.
Emeryville, Calif. 94608
(415) 428-2623
Circle 399

And the Lone Ranger didn't settle for ordinary bullets.



And, in a sense, neither should you. If you're not getting extraordinary performance from your current multiuser system, you're settling for the ordinary.

Which brings us to Plexus.

And what we can bring to you.

At Plexus, we're keenly aware of what you're looking for in a business system. Because we've been delivering the right systems to business for years. Systems that have earned a name for performance and reliability in over 2000 organizations worldwide. Customizable 4 to 80 user systems with innovative multiprocessor architectures—coupled with a finely tuned version of UNIX™ System V Release 2. And on-site service and support even our competition envies.

Take our top-of-the-line P/75. An expandable 32-bit, 68020-based system designed to exceed the demands of today's database-intensive applications. With advanced communications processors—offering a variety of standard or custom protocols and fast terminal response. Plus high-speed enhanced mass storage processors (EMSPs) to speed up disk I/O. (You can even run multiple EMSPs in parallel for lightning-quick access to enormous databases.)

The P/75 also offers storage capacities up to 6.5 Gbytes. A floating-point processor option. Choice of tape backups—from cartridge to GCR. And industry-standard interfaces to keep your expansion options open and flexible.

If you'd like more information on the P/75 or any of our other systems, call (800) 523-8874; in California call collect (408) 943-9433. Or write us at 3833 North First Street, San Jose, CA 95134.

Plexus. The lone solution for a wide range of companies.

Just like yours.

UNIX is a trademark of AT&T.

PLEXUS
Plexus Computers, Inc.

CIRCLE NO. 46 ON INQUIRY CARD



If you want to raise your sales, raise your hand. Create new markets with TI-Speech.™

TI-Speech offers you speech capabilities designed to give you a hand in opening the doors to untapped markets. With it, your system designs will be more innovative. You'll provide customers with better solutions, and have an opportunity to make more money.

Simply put, TI-Speech provides voice I/O for computer applications in a wide variety of fields. Applications include voice mail and telephone access to computers for businesses of any kind, robot-calling for telemarketing, hands-free data entry for

manufacturing, medicine and research and development. It can even act as a learning aid in computer-based training.

TI-Speech was designed with you in mind, too. Its handy, modular design means that you use only the hardware and software you need for your applications. And it's affordable. For under \$1,000, a plug-in option board delivers voice I/O capabilities on most IBM®-compatible PCs.

Chances are, you've been looking for new ways to expand your customer base. TI-Speech is an effective, cost-

efficient answer. Put it to work, and watch your business opportunities increase.

For an example of TI-Speech at work, call 1-512-250-4114. For more information on TI-Speech, call us toll-free at 1-800-527-3500.



TEXAS INSTRUMENTS

TI-Speech is a trademark of Texas Instruments Incorporated.
IBM is a registered trademark of International Business Machines Corporation.
TI reserves the right to change its prices and product offerings at any time without notice.

31596
© 1986 TI

Dmert; and IBM's AIX/UNIX for the IBM RT PC. This technique provides application portability by fooling UNIX applications. They think they are running on UNIX, and they have no idea of what exists under the UNIX-application interface.

Alcyon attributes its ability to deliver task switch times as low as 700 μ sec and interrupt response times as low as 125 μ sec, on a 10-MHz Motorola Inc. MC68000 microprocessor, to its replacement of the UNIX kernel with a proprietary one. This response time depends on the interrupt loading and the device drivers on the system.

Despite the kernel replacement, Regulus programmers see a UNIX environment with some extra system calls added to perform real-time tasks. Ordinary UNIX applications are portable because the program interface that they see is UNIX System V Release 2. With UNIX's "nice" command, programmers can transport a UNIX task, assign it a priority, and start it up as a real-time task under Regulus. However, programmers can make changes to increase responsiveness.

For the most part, however, the lack of standards limits real-time application portability across any real-time UNIX. Real-time UNIX applications cannot generally be ported to standard System V because it does not yet support real-time capabilities. Developers cannot count on portability to another vendor's real-time UNIX because every vendor's real-time UNIX is different. But, as real-time UNIX standards, and SVID real-time extensions, are established, real-time application portability will be possible across conformant systems.

AT&T first with real-time

AT&T's real-time UNIX work in the late 1970s began with the Mert operating system for DEC's PDP/11 computers. Mert grew into Dmert, which is now used in telephone switching applications. Dmert was subsequently renamed RTR (Real-Time Reliable) and it runs on ATTIS' 3B20 computers, where it can use the 3B20's duplicated CPUs and fault-tolerant features.

Mert and RTR/Dmert factor out a two-layer kernel (core kernel and kernel process), which provides the lowest level, and most difficult to change in UNIX, real-time services. These include pre-emptive and priority scheduling mechanisms, asynchronous I/O, synchronization and contiguous files. The UNIX supervisor sits on top of the kernel and interfaces to the kernel services (as did DEC's RSX real-time




Fig. 1. A real-time UNIX with a non-UNIX kernel has recently been introduced for the IBM RT PC. The RT PC has the UNIX supervisor and part of the UNIX kernel (the AIX system) on top of a real-time kernel, the virtual resource manager).

system at one time).

The UNIX supervisor provides the environment the user sees and provides UNIX functionality to applications that run on top of the UNIX supervisor in user mode. The supervisor can also access the kernel's real-time services via system calls. However, running the real-time functions below UNIX, rather than embedded in it, provides faster response to external interrupts.

As with Regulus, RTR supports standard UNIX application portability (from any System V to RTR) and access to the priority mechanism through the nice command. But real-time UNIX application portability must wait for standards.

Meanwhile, programmers can do most of their real-time programming work at the UNIX level, without needing to learn a new environment. UNIX automatically handles basic real-time functions, like pre-emption of kernel processes and scheduling priorities, via system calls to the kernel.

However, to develop those parts of high-end applications, where it is necessary to achieve particularly rapid response to external events, programmers need to program at the kernel-process level rather than in UNIX. The kernel-process environment is different from that of UNIX. Typically, programmers might write a kernel process to optimize the file system in a

Any operating system becomes UNIX when neither the application nor the programmer can tell the difference.

certain way or to perform specialized tasks, such as event management, at the kernel level—with the ability to pass information to other programs.

A similar, real-time UNIX layered architecture, with a non-UNIX kernel, was recently introduced by IBM for its RT PC. The RT PC has an underlying real-time kernel, the virtual resource manager (VRM), which provides most real-time features. IBM and Interactive Systems Corp. developers built the UNIX supervisor and part of the kernel (the AIX system) on top of the VRM (Fig. 1).

UNIX applications run on top of the UNIX supervisor. This preserves the interface between the user program and the supervisor even though the internals of the UNIX system have

been changed.

IBM incorporated its real-time services on the VRM side of the Virtual Machine Interface (VMI) boundary to decrease overhead and to support faster context-switching times with a simpler context-switching method. IBM admits that it could have achieved the same results by modifying the kernel on the AIX side of the boundary. But the RT PC developers felt it was more expedient to start from scratch rather than retrofit extensive changes to part of the kernel.

Like RTR, the RT PC supports two different environments: a UNIX environment (with AIX) and a real-time environment (with VRM). Programmers developing a demanding real-time application will stay pretty much in the VRM environment. However, RT PC developers claim that the VRM has UNIX features because they tried to make it a natural extension of the UNIX environment.

When does UNIX stop being UNIX?

Replacing the kernel raises two questions: What parts of traditional UNIX should be preserved in a real-time UNIX, and when is UNIX so changed that it is no longer UNIX? Concerning the first, the UNIX standards bodies agree that, regardless of any changes, the IEEE P1003 core UNIX standard should remain to ensure applications portability.

Concerning the second question, because portability is the objective of a UNIX standard, then, regardless of what code exists beneath a software or user interface, any operating system—real-time or otherwise—becomes UNIX when neither the application nor the programmer can tell the difference between that operating system and UNIX.

This premise goes a long way toward resolving such questions as the efficiency of an operating system as old and as patched as UNIX. UNIX was developed in the 1970s when software technology was young. It has been repeatedly patched, and will be patched still more to add real-time features, until, over time, some people argue that it will become a kludge.

Jim Isaak, chairman of the IEEE P1003 committee, is firmly convinced that the patch-and-kludge controversy is a red herring. "To get real-time features, you add, change, or replace more and more until finally you have to replace the kernel," he says. "When you do, you eliminate the kludge problem."

Not every UNIX insider is so sure that changing UNIX is the best way to provide UNIX with real-time capabilities. "For high-end real-time applications, it is very difficult to





Fig. 2. One example of distributed processing is the automated process control system used internally by AT&T. A host processor supports a UNIX development environment and then downloads the compiled applications to multiple satellite processors for real-time execution.

The TeleVideo 905 terminal. What a difference \$10 makes.



Let's face it; there are a lot of \$399 terminals being sold these days. You get a basic box, a few tacked-on bells and whistles, and not a whole lot more.

But now there's the TeleVideo® 905. At \$409, it has a feature set so powerful, your customers

TELEVIDEO 905 VS. WYSE WY-30		
FEATURES	TELEVIDEO 905	WYSE WY-30
Individual programmable function keys	16	4
Tilt and swivel standard	Yes	No
High contrast super dark Matsushita screen	Yes	No
WordStar® mode	Yes	No
Full-size keyboard	Yes	No

100,000,000 strokes. Even an enhanced numeric keypad.

There's also a buffered printer port. And, of course, compatibility with the TeleVideo 925 command set, the most popular and widely emulated ASCII command set in the world.

If you'd like more information just get in touch with the nearest TeleVideo regional office listed below, and we'll give you the name of your nearest distributor.

The TeleVideo 905. What a difference \$10 makes.

 **TeleVideo®**
Settle for more.



will think they're sitting at an expensive workstation.

For example, there's a sleekly designed monitor case with full tilt and swivel.

A full-size keyboard

with sculptured keycaps for smooth, comfortable typing. Sixteen non-volatile, programmable function keys. Keyswitches that have been tested to

TeleVideo Systems, Inc., 1170 Morse Avenue, Sunnyvale, CA 94088-3568, (408) 745-7760, Regional Offices: Northwest (408) 745-7760, Southwest (714) 476-0244, South Central (214) 550-1060, Southeast (404) 447-1231, Midwest (312) 397-5400, East (516) 496-4777, Northeast (617) 890-3282. AMSTERDAM: 31.2503.35444, PARIS: 33.1.4687.34.40, LONDON: 44.9905.6464.

©1986 TeleVideo Systems, Inc. WYSE is a trademark of Wyse Technology. WordStar is a registered trademark of MicroPro International Corporation.

CIRCLE NO. 47 ON INQUIRY CARD

NO ONE
OUTRUNS
CONTROL
DATA.





Introducing the highest MTBF and longest warranty in the industry.

We're talking reliability. And no other OEM storage peripheral supplier in the industry matches the 30,000-hour MTBF and 3-year HDA warranty we're offering with our high performance EMD, FSD & XMD drives.

The EMD is a fast, high performance 8" disk drive that mounts in any plane and is perfect for tower-

mounted office systems and rack configurations. It has a seek time to 18 ms and a capacity of 368 MB.

The FSD family was the first ½ rack drive in the world and has capacities of 300, 340 and 516 MB. The fact that we have more FSD units installed than all our competitors combined is a sure sign of customer satisfaction.

And the XMD is the world's highest capacity, highest performance 14" rack mount, with transfer rates as fast as 24 MHz and capacities to 858 MB.

The EMD, FSD II and the XMD offer a wide variety of industry

standard interfaces including SMD, SMD-E and IPI-2. In addition, the EMD has a SCSI interface making it suitable for either low or high end applications.

We believe these are the most reliable drives in the world. And as the world's leading supplier of OEM storage peripherals, we're backing them with a warranty and MTBF unmatched in the industry. Proof that no one can outrun Control Data.

For more information, call 1-800-828-8001 ext. 82. (In Minnesota, call 612-921-4400 ext. 82.) Or call your local Arrow or Kierulff distributor.

GD CONTROL DATA

CIRCLE NO. 48 ON INQUIRY CARD

Turn Your System/3X Into The Perfect Host With PCOX Technology.

PCOX™ 5250 products make your System/3X treat your PCs like members of the family.

Your System/3X and your PCs already live together. Now they can work together, too. Thanks to PCOX Technology.

With PCOX 5250 connections, your PCs enjoy the full privileges of a 5251 Model 11, 5291 or 5292.

Which means your PCs can access and transfer files from your System/3X data base, use its host as a departmental processor, or participate in your company's distributed SNA network.



*MORE WAYS TO SAY HELLO.
The PCOX 5250 series comes in
twinax and remote versions—one
for local connections, and one for
connections over phone lines.*

PCOX 5250 products come in twinax and remote versions, so PCs can enjoy S/3X connections in person or over phone lines.

And both versions support up to seven concurrent host sessions. No competing product delivers more.

So let PCOX Technology open doors between your System/3X and your PCs.

Call CXI today, toll-free.

800-225-PCOX.


In California, call 415-424-0700.

CXI

CXI, Inc., 3606 West Bayshore Road
Palo Alto, CA 94303. Telex: 821945

PCOX and all PCOX products are trademarks of CXI, Inc.

CIRCLE NO. 49 ON INQUIRY CARD



mix time-sharing and real-time applications on one system," says Bruce Weiner, president of /usr/group.

Time-sharing UNIX incurs overhead to support resource sharing. Resource sharing, by nature, creates a non-deterministic situation and is therefore antithetical to real-time tasks that want their resources immediately available. UNIX's interactive, user-friendly features also consume overhead and slow UNIX down. Regardless of the real-time features added, "such a general-purpose system may not be able to guarantee real-time responses in the low- μ sec range," Weiner says. "In these cases, you may need a real-time executive, running on a processor dedicated to a particular application and possibly customized for that application."

An alternative real-time UNIX architecture integrates UNIX and a dedicated real time executive via distributed processing techniques. A host processor supports an environment for development of real-time applications and for execution of traditional applications and parts of real-time applications. Outboard satellite processors run dedicated real-time executives.

AT&T uses one such distributed-processing system to internally perform automated process control (Fig. 2). In this system, the host processor supports a UNIX development environment. It downloads the compiled applications to satellite processors for real-time execution. Communications with the satellites are bidirectional via high-speed communications lines.

The satellite processors are UNIX systems, but they are not full-blown SVID UNIX because features like compilers, debuggers and even file systems and schedulers may not be needed for the real-time execution environment. However, the satellite UNIXes may have customized features, specific for the task at hand.

This satellite technique can also be used to distribute real-time processing across UNIX hosts and traditional real-time executives. Many companies have done so.

Automation Engineering, for example, has implemented various real-time systems on VME-compatible intelligent devices that act as front ends to UNIX System V.2 (Xelos) running on Concurrent Computer Corp.'s superminicomputers. Any RTOS can interface to the superminicomputers through the VMEbus. The VME-based external device and the UNIX-based superminicomputer communicate through shared memory, using a direct-memory access connection.

UniFLEX, a modularized UNIX-like system from Technical Systems Consultants Inc., is often used as the real-time satellite executive. UniFLEX can be configured as a 178K-byte set of modules with full UNIX functionality, or users can strip away what they do not need and configure it down to a 9K-byte module. The 9K-module provides the same kind of response times as does the MTOS/PSOS/VRTX-type of real-time executives, claims Don Sinkiewicz, company president.

One typical system, developed by Automation Engineering, is a conveyer/sorting system that sorts packages for loading onto trucks. The application, except for the real-time mechanism controlling the conveyer apparatus, runs on the superminicomputer under UNIX. The superminicomputer passes data from an inventory-control system, a UNIX database and the conveyer/sorting application to the outboard microprocessor to inform the resident real-time system which package to dump or load at different gates in the conveyer system. The outboard microprocessor, acting as an intelligent controller, reacts in real-time as the package reaches the appropriate point. It also passes back information to the UNIX system for further processing.

According to Bud O'Rick, market manager for manufacturing and process control at Concurrent Computer, this distributed technique preserves a great deal of application portability in the absence of a real-time UNIX standard. O'Rick explains that an individual real-time process may be specific to the sensor or to the device it is collecting data from or controlling. But the rest of the application, running under UNIX, is portable to other UNIX computers.

UNIX gets real-time connections

Small, fast, multitasking executives provide real-time capabilities, but little functionality. In fact, they may not even provide a file system. However, they can achieve task-switch times in the 100-to-200- μ sec range.

Consequently, most real-time UNIX vendors feel that such systems will always be in demand for critical real-time applications. These systems will be integrated with UNIX systems via high-speed buses, networks and serial links.

Heurikon Corp., for example, offers a distributed real-time system. Its UNIX system is tightly coupled with Hunter & Ready's VRTX on a board, and interfaces to it via a Multibus connection. Another example is Wind River Systems Inc., which integrates UNIX with its real-time VxWorks (an extended version of VRTX that provides run-time and debugging

features) via a Berkeley UNIX Version 4.2 socket interface and Transmission Control Protocol/Internet Protocol (TCP/IP) networking.

The techniques for integrating UNIX and real-time systems do not reflect the potential uses of such systems. For example, in MTOS-UX, from Industrial Programming Inc., communication links between UNIX and real-time MTOS are simple. MTOS logs on to any UNIX over an RS232C serial line. A follow-up system will feature shared memory. But MTOS-UX's real power is in its unusual design that enables it to trigger the downloading and execution of programs from a UNIX machine to an MTOS-based processor, while the real-time program is running.

The design feature responsible is MTOS' support of dynamic memory allocation and dynamic linking and loading. These capabilities allow MTOS to perform an autoconfiguration. That is, a programmer can write an initialization task, running under MTOS, which can be used to load, locate, initialize and start up a complete application from a UNIX host. That task can also dynamically create (or delete)

system objects such as semaphores, memory pools, event flags, mailboxes and drivers needed for the program's execution.

Although these dynamic capabilities are useful for many applications, users first think of applying them to diagnostic areas. In one manufacturing application under investigation, users want to connect an MTOS-based machine to a UNIX workstation. The idea is to monitor and control machines, and to detect errors, while assemblies are being put together. When the errors reach a critical level, then the real-time program would be partially replaced by a diagnostic program, which would execute and provide feedback that would help maintenance personnel correct the problem.

For some distributed real-time UNIX systems, a real-time UNIX facilitates integration of the host UNIX and dedicated real-time systems. A real-time, board-level solution at Alcyon, for example, integrates real-time UNIX/Regulus with the real-time kernel PSOS (from Software Components Group). The boards plug into the same backplane. This multiprocessor system can connect to UNIX on the host.

In this integrated system, the application task performs high-speed data collection and analysis under PSOS. The Regulus processor performs the system's overall executive functions, the operator-interface and file-server functions and some real-time tasks. It also supports software development. Regulus also is the intermediary between the UNIX host and PSOS. Because of its real-time capabilities, it communicates more easily with PSOS than could UNIX. Similarly, because it is UNIX-based, Regulus communicates more easily with the host UNIX than could real-time PSOS.

There is no doubt that a real-time version of UNIX not only is possible, but also will be seriously considered as the operating system for many future manufacturing applications. At the same time, it seems there will always be a place for smaller, dedicated real-time kernels.

It is generally accepted that a common operating system, by itself, will not solve all application transportability problems. However, in conjunction with high-level languages, runtime libraries (to execute device-dependent code) and clever software engineering, users and vendors will significantly improve on today's degree of application transportability. □

9-TRACK MAG. TAPE SUBSYSTEM FOR THE IBM PC/XT/AT AND...



For information interchange, backup and archival storage, IBEX offers a 9-track, IBM format-compatible 1/2" magnetic tape subsystem for the IBM PC, featuring:

- IBM format 1600/3200 and 800 cpi.
- Software for PC-DOS, MS-DOS.
- Also for DEC, VAX, VME, S-100, RS-232, IEEE 488.

IBEX

IBEX COMPUTER CORP.
20741 Marilla St.
Chatsworth, CA 91311
(818) 709-8100
TWX: 910-493-2071

Write, phone or TWX for information.

CIRCLE NO. 50 ON INQUIRY CARD

Interest Quotient (Circle One)
High 483 Medium 484 Low 485

**SATELLITE
MODULES
NOW \$99**



The Most Powerful LAN Fits on a Disk.

Network Power. You knew that someday there would be a powerful LAN that didn't need old-technology network boards. It would be fast, easy to install, and run 99% of PC-DOS software. It would be expandable, provide remote access, password-protection, and enable you to use inexpensive terminals as workstations in a PC-DOS environment.

Dream no more, because the power is here.

Its name is LANLink™.

A Software-Driven LAN Powerful Enough To Use RS-232 Ports for Network Communications. In development for over three years, LANLink™ represents the next generation of local area networks. All of the logic which has traditionally resided on network boards is on LANLink's Satellite and Server Diskettes.

No additional hardware is required. Inexpensive serial ports replace "Kilobuck" Network Interface Boards making installation costs one-third that of a board-driven network.

How To Configure a Smart Network...With Dumb Terminals, But Without Dedicated Servers. Boasting a wide variety of configurations, LANLink™ is most often set up as a "Star" having up to eight satellites connected to a central, nondedicated server. Larger networks can have multiple servers, supporting a total of 73 or more network users.

R-LAN™ (Remote-LAN) gives users the ability to interact with a LANLink™ network in real time via modem. Plus, if MultiLink Advanced™ is run on a Satellite, inexpensive dumb terminals can be used to access network disks, files, and programs.

THE SOFTWARE LINK, INC./CANADA 250 Cochrane Drive, Suite 12
Markham, Ontario L3R 6B7 CALL: 416/477-5480

LANLink™ MultiLink Advanced™ & R-LAN™ are trademarks of
The Software Link, Inc.

IBM, PC, & PC-DOS are trademarks of IBM Corp. WordStar 2000,
dBASE III, and Lotus 1-2-3 are trademarks of MicroPro, Ashton-
Tate, and Lotus Development Corp., respectively.

99% of PC-DOS Applications Run in a Totally-Transparent Network Environment. If you know DOS, you already know how to use LANLink™ COPY transfers files among users, and a 2-drive PC Satellite boots 1-2-3 from the Server's hard disk with the entry c:\lotus. Each satellite's access can be limited to specific disks, printers, and sub-directories. A wide variety of software including Lotus 1-2-3, dBASE III, and WordStar 2000 is fully compatible. LANLink™ has a collision-free data transfer rate which exceeds 115,000 BPS.

Power Up Your PCs Today. For complete details and the authorized dealer nearest you, call The Software Link TODAY. The LANLink™ Starter Kit is \$495 and includes modules for both a Server and a Satellite. For a limited time, 50 feet of shielded RS-232 cable will be included free of charge. Additional Satellite Modules are only \$195, each.

LANLink™ is immediately available and comes with a money-back guarantee. VISA, MC, AMEX accepted.

LANLink™



THE SOFTWARE LINK, INC.

Developers of LANLink™ and MultiLink Advanced™

8601 Dunwoody Place, Suite 632, Atlanta, GA 30338 Telex 4996147 SWLINK

CALL: 404/998-0700

Dealer Inquiries Invited

CIRCLE NO. 51 ON INQUIRY CARD

Peace of Mind

Compliments of Hitachi's 1500 Disk Drive Design Engineers.

That's right. . . Hitachi has 1500 design engineers who work on nothing but disk drives. We design, build, and qualify all key components ourselves, to our famous ultra-high specifications. We don't simply assemble stock items. Since we build our own motors, heads, micro-processors and custom LSI, we subject these parts to the most stringent Quality Assurance program in the industry.

This may seem like an awful lot of work, but during the 15 years of producing disk drives, we've learned that this is the only way to make drives good enough to use in our own systems. . . the only way to get the peace of mind that comes from knowing that the drives work.

Your peace of mind can come easy too. Use the most reliable disk drives available: Hitachi disk drives.

A serious, historic commitment to the disk drive business.

Hitachi's involvement with memory peripherals goes back to the earliest days of mag tape. We still produce mag tape equipment. And, today we have one of the broadest lines of disk drives you'll ever find—including 3.5", 5.25",


8", and 8.8" Winchesters. We've even made the enormous R & D expenditures necessary to be one of the pioneers in optical storage technology.

You don't make these kinds of commitments to a product line unless you're serious about its long-term success. Hitachi is serious. Very serious. We believe in forging long-lasting relationships supported by highly reliable products that can stand the test of time.

When you decide to use Hitachi disk products, you'll have a business partner who will be here to work with you, today and tomorrow. . . helping you to satisfy your customers. . . giving you peace of mind.

Fast Action:

To obtain product literature immediately, CALL TOLL FREE, 1-800/842-9000, Ext. 6901. Ask for literature number PB-001.






Hitachi America, Ltd.
Computer Division
950 Elm Avenue, San Bruno, CA 94066
Telephone 1-415/872-1902



CIRCLE NO. 52 ON INQUIRY CARD

Networking... see your way clear



You're not alone. It's easy to get confused by the enormous spectrum of networking requirements, products and technologies that blur the way.

Let Augat bring your picture into focus.

Augat is one of the world's most respected names in electronic interconnection technology. We possess a unique capability for network solutions, because of unequalled product breadth coupled with vast experience in the OEM and CATV marketplaces.

Augat offers an unusual combination; the resources of a large (\$250,000,000.00), vigorous growth company plus a willingness and ability to go beyond merely selling products.

Our commitment to total solutions comes from years of experience in the CATV market, where total support is an integral service.

Let us help you enjoy a better view. Call or write "NETWORKING", Augat/Broadband Communications Group, 710 Narragansett Park Drive, Pawtucket, Rhode Island 02861, (401) 724-4400.

Broadband Network Electronics • Coaxial Connectors • Fiberoptics • Test Equipment
• System Compatible Cross Connections

AUGAT® **BROADBAND COMMUNICATIONS GROUP**

Quality and Innovation

CIRCLE NO. 53 ON INQUIRY CARD

LINKING DATABASES FORCES NEW STRATEGIES

As data communications options multiply, applications developers must cope with distributed processing as a basic rule of programming

Michael Tucker, Associate Editor

Increasingly, system integrators are not asking if their machines will be required to communicate with other computers but, rather, how. The new realities of computing find the user wanting data transfer and the hardware vendor being forced to configure machines so that they can accommodate local area and wide area networks, packet switching networks, RS232C-based limited area networks and numerous other, often exotic, technologies.

Software vendors, too, are being forced to respond to networking, shaping their products for situations in which distribution of resources and files is the norm. In particular, database management systems are under tremendous pressure to fit distributed environments. At the same time, such database systems are being

asked to do something they've never done before outside the mainframe world—manage distributed files. So, DBMS vendors are gradually forming philosophically opposed schools on how that distribution should be done. The major divisions comprise, roughly, those who feel data should be truly distributed, those who feel it should be centralized and, as an emerging third camp, those who would attempt the distribution of data via software removed from DBMS products.

Networking problems appear

In the mainframe world, the problems of distributed file management have been handled for years. But, historically, developers of software for microcomputers have had neither the motivation nor the tools for distributed computing. Personal computers, by nature, were

Networks branch out

Programmers sometimes find it useful to think of a computer network as a single, loosely coupled multi-processing machine. So, too, can marketers. If a local area network is conceived of as a single machine, so can its potential for modification for vertical markets. Here are two of the newest specialized LANs:

GCLISP Network from Gold Hill Computers Inc., Cambridge, Mass. Introduced last January, GCLISP Network provides an Ethernet link between IBM Corp. PCs or compatibles and LISP engines (or powerful multiuser systems)—running Gold Hill's LISP compiler. GCLISP Network gives developers working in artificial intelligence an inexpensive means of centralizing

their investment in LISP, while still bringing the power of the language to the desktops of individuals.

VSLAN from Verdex Corp., Chantilly, Va. Introduced last May, the Verdex secure LAN is one of the first LANs to address both the military and civilian markets. VSLAN is an extremely secure product that encrypts everything that passes through it. Buyers can purchase either the entire LAN, or merely the encryption technology for application in their own networks. In addition to the obvious military and intelligence applications of the product, VSLAN could find uses in such applications as electronic funds transfer and financial-information processing.

meant as standalone systems with little need for communications beyond occasional dial-up access to mainframes.

While the rapid appearance of the networked office and factory is providing the motivation for communications, the tools—standards, protocols, etcetera—aren't coming as quickly. But they are finally starting to appear. And, although the obstacles to microcomputer networking are by no means fully overcome, the efforts of standards committees, network vendors, and multivendor R&D organizations, such as the Corporation for Open Systems, are starting to pay off.

This is particularly true of operating systems, where applications developers are finding major vendors ready to provide networking facilities as basic components of the operating system. For example, in single-user systems, where MS-DOS and PC-DOS dominate, the cooperation of IBM Corp. and Microsoft Inc. has produced NETBIOS, a layer of software that gives DOS-based machines a standard link to networks. In multiuser microcomputers, where AT&T Co. would like UNIX to reign, ATTIS has recently released UNIX System V.3, which specifies mechanisms to handle files in a distributed environment.

But, the existence of these communications facilities doesn't clearly establish how any one piece of software can use them. Developers themselves must answer some basic questions on how their products may be spread over a network. Nowhere is this truer than with DBMSes, which must distribute information across wide areas and multiple users, yet still ensure the integrity of that data despite the

chances for error inherent in such a complex, decentralized system.

Specifically, a distributed DBMS should provide users the illusion that they are working on a single database, on a single machine. Users should never have to worry about the physical location of any file, how files are protected from conflicting updates and network failures or how copies of any file might exist at any given moment. In other words, a DBMS must provide transparency in file location, replication and failure.


Ingres' Star shines

While virtually every DBMS vendor is experimenting with different approaches to distributed file management, two methods seem to be emerging as the most common. Either the data is completely decentralized and truly distributed among different machines, or the data is centralized in one or more dedicated server machines.

One partisan in the truly distributed camp is Relational Technology Inc. RTI's Ingres relational DBMS (RDBMS) was originally introduced for Digital Equipment Corp. machines running on the VAX/VMS operating system. Over the years, Ingres expanded to include IBM products running under IBM's VM operating system and a host of UNIX-based systems from several different vendors. An MS-DOS version for IBM PCs and compatibles is scheduled for release sometime this year.

Ingres has been particularly popular in large technical applications such as aircraft design (it's been used extensively at Boeing Co., for instance). But this has meant multiple installa-

A truly distributed DBMS, Relational Technology's Ingres/Star runs on heterogeneous networks and protocols. It uses a distributed database manager (DDBM) to link individual relational database management systems (RDBMS).



tions of the DBMS running on different machines in different locations. In turn, this has meant that, like all the other DBMS makers, RTI has come under severe pressure from users to turn the product into a distributed system.

In response, RTI announced Ingres/Star in June. Running atop the RTI communications product, Ingres/Net, Ingres/Star will eventually be a truly distributed DBMS. It runs on heterogeneous networks, protocols and machines that will eventually range from microcomputers to mainframes. Initially, it will offer multisite reads and single-site updates of files. But, in a second release scheduled for 1987, the company plans to include multisite updates as well.

Ingres/Star is a distributed database manager (DDBM) that operates as a local DBMS on each node of the network. The nodes must then cooperate in file management. The common language between the different Ingres/Star installations is the Structured Query Language (SQL), made popular by IBM. Essentially, each local DBMS regards every other DBMS with which it has contact as a virtual user. So long as the transaction is in proper SQL, the local Ingres/Star doesn't care whether a query or update comes from a local keyboard or from another DBMS located a hundred miles away.

This means, in turn, that the network can comprise different machines. Because the only information passing between individual Ingres/Star installations is SQL and data, no one local DBMS need concern itself with the hardware, software or operating system of any other copy of Ingres/Star.

Moreover, because SQL is an emerging standard in databases, Ingres/Star will eventually

be able to communicate directly with other SQL-based DBMSes. Although that startling possibility is still confined to the future, RTI hopes to open "gateways" to other DBMSes by 1987. And by 1988, RTI hopes to open similar gateways to DBMSes that don't use SQL.

Integration of heterogeneous DBMSes has been called the Holy Grail of the MIS world (MMS, April, Page 63). Many large companies have made huge investments in several different DBMS-products, which they would now like to link via some common interface. Obviously, the product that provides such a link would have a profound effect on the entire computer industry.


Centralists strike back

Still, the decentralized approach has its critics. While virtually everyone agrees on true distribution as the ultimate goal of database research, another school of thought holds that data should be centralized somewhere in the network, at least as an interim measure. This "centralist" school thinks, first, that the technology of DBMSes is not yet mature enough to handle the problems of true distribution and, second, that users prefer their data in a single location where it can be carefully controlled and protected.

One member of the centralist school is Sybase Inc., which recently introduced the DataServer, an RDBMS for distributed environments. The DataServer sits on a dedicated node anywhere in the network and controls the actual database. File management is thus done almost as easily and safely as it would be in a single-user system. Users at other nodes of the

DBMSes are under pressure to fit distributed environments.

...WHILE SYBASE CALLS FOR UNITY



SOURCE: SYBASE, INC.

One example of the centralized approach is Sybase's distributed DBMS, which concentrates data within dedicated server machines.

Developers must answer basic questions on how their products can be spread over a network.

network send SQL queries over the network and the results return to them.

Here, more than one server can operate in a network. In the current version of DataServer, a single SQL query may search or update two or more databases within one machine acting as server, but not in separate server computers. "Eventually, we will ease that restriction," says Robert Epstein, Sybase's executive vice president. "However, the one thing users have told us again and again is that they want centralization. They want control of data."

Unify Corp., makers of the Unify database for UNIX and MS-DOS machines, is another centralist. Unify too has prototypes, rather than products, each of which operate in a distributed environment. The company also envisions data contained in centralized servers, though for reasons having more to do with human nature than technology. "I predict that there will be considerably fewer machines containing data than accessing data," says Unify president Nicolas Nierenberg. "Not because the DBMSes won't be capable of handling more than a few disks, but because database administrators won't be willing to deal with the complexities of DBMSes."

Relational Database Systems Inc. (RDS), makers of the Informix DBMS, leans even more toward centralization. The company can

currently support some communications between Informix installations operating MS-DOS based machines. In the future, the company hopes to develop a centralized capacity, with data kept on a UNIX-based server. The DBMS would consist of "back ends" on the server, communicating via SQL with users operating "front ends" at their individual workstations. Later, the company plans to turn this setup into a truly distributed system. "We'll probably have front ends at each personal computer, with each front-end having a corresponding back end at the server," says Jeff Poole, product manager for network products at RDS. "Then, gradually, we'll introduce back ends for personal computers, so that files can be truly distributed."

Other DBMS vendors are certain to enter the distributed database business one way or another. In fact, several companies have recently introduced products that are not distributed databases. These products clearly indicate intentions to get into the game, with SQL as the probable method. One such company is Oracle Corp., vendor of the popular Oracle DBMS for IBM, DEC and compatible machines. In releasing the fifth version of DBMS, Oracle also introduced SQL-Link, a communications product. SQL-Link allows an Oracle DBMS on a microcomputer to send SQL queries to another Oracle DBMS running on a multiuser system.

ASCII and ye shall receive

Although SQL may prove the best route to truly distributed DBMSes, there are problems that the language cannot address. Beyond the distribution of DBMSes, beyond even the integration of heterogeneous databases, lies another challenge—the integration of distributed DBMSes with other distributed applications. Just as users would like to be able to manage data over large areas and in a number of formats, so, too they would like to display and analyze that data via different devices and software, themselves distributed over wide areas. This is difficult, because it requires a universal interface.

But it has led to what might be called a third school of distributed file management—a group of vendors who propose that software integration cannot be done within applications software itself. Instead, they feel an additional, insulating layer of software must exist somewhere in a network to translate between different applications. Needless to say, such a layer of software would be extremely difficult to create, yet here, too, there are signs of progress.

One of the few broadly accepted standards in

Companies mentioned in this article

Command Technologies Inc.

1 Monarch Drive
Quincy, Mass. 02171
(617) 472-7900
Circle 361

Oracle Corp.

2710 Sand Hill Road
Menlo Park, Calif.
(415) 854-7350
Circle 362

Relational Database Systems Inc.

4100 Bohannon Drive
Menlo Park, Calif. 94025
(415) 322-4100
Circle 363

Relational Technology Inc.

1080 Marina Village Parkway
P.O. Box 4006
Alameda, Calif. 94501
(415) 769-1400
Circle 364

Sybase Inc.

2910 Seventh St.
Suite 110
Berkeley, Calif. 94710
(415) 548-4500
Circle 365

Unify Corp.

4000 Kruse Way
Building 2
Lake Oswego, Ore. 97034
(503) 635-6265
Circle 366

VenturCom Inc.

215 First St.
Cambridge, Mass. 02142
(617) 661-1230
Circle 367

HOW TO STAY ON TOP OF THE CHARTS.

One thing is certain. You have to present a quality image. And you have to maintain it with absolute consistency.

That's why you should look into the new Seiko Hardcopier. You can get a variety of output sizes. With strong vibrant colors and clear, sharp lines on both paper and transparency.

Plus you can get those copies in as little as 45 seconds each. For a lot less money than you thought possible.

The Seiko Hardcopier can make a hundred copies for you off-line. Because its frame buffer holds the image data

and frees your terminal. You just set the quantity you want and go on working.

You even get independent image control at the hardcopier. You can change colors without changing the image on the screen. And get hardcopy or overheads that look great even if the colors on the display aren't quite right for presentation purposes.


So make one phone call. We'll present you with the whole quality story. And make sure you have the hardcopier that will keep you on top of the charts.

Call Martin Nelson
at (408) 943-9100
today.

SEIKO
INSTRUMENTS

© 1986 Seiko Instruments U.S.A., Inc.

CIRCLE NO. 54 ON INQUIRY CARD



**Last year, people like you got away with
nearly \$200 million from us.**



Hewlett-Packard's VAR discounts added up to some pretty good getaway money. Enough for a lot of trips to exotic, faraway places.

Take a look at Hewlett-Packard's commercial VAR Program and think how far you could go.

It offers discounts up to 35% on HP 3000 computers and peripherals. 40% discounts on demo/development systems. 10% credits on system upgrades if your customer decides to upgrade through us.

Of course, Hewlett-Packard's commercial VAR Program offers more than discounts. For instance, service and support that have given HP a worldwide reputation.

And now the program is even more profitable.

We've raised the entry discount on the HP3000 Series 37 mini-computer to 25%. We've also increased the memory to 1 MB and added HP installation, all for a lower system price of \$21,860 (before quantity discounts).

So first get it all from Hewlett-Packard. Then get away from it all.



The HP Program for Value-Added Resellers

- Send me information on your commercial VAR program and the HP 3000 Series 37.
- Have an HP representative call me right away.

Name/Title _____

Company _____

Address _____

City/State/Zip _____

Phone _____ Market _____

Mail to: Bob Hall, Hewlett-Packard, Dept. 694C,
10520 Ridgeview Court, Cupertino, CA 95014 ISO2603

computing today is ASCII code. It is slow, laborious and nearly 20 years old. But ASCII is nearly universal because it's been the widely accepted means by which machines and human beings have communicated, and human beings are notoriously difficult to reprogram for new formats.

One company that takes advantage of ASCII is VenturCom Inc., with its Prelude Information System. Prelude is a tool kit for developers building distributed applications for groups of UNIX machines—specifically, those that are compatible with AT&T's UNIX V.3 or above.

Prelude consists of over 100 individual modules of code—performing functions ranging from database management to application generation. These modules can run on a single computer or be farmed out to separate machines. Communications between them is conducted by standard ASCII strings, which can be transferred via local or wide area network, dial-up access, or the physical transfer of disks.

In effect, the application builder who works with Prelude designs not for a network but for a single, multiprocessing machine that happens to be loosely coupled. Moreover, because Prelude uses ASCII, it can and does access other software that also uses ASCII. In fact, the company claims that Prelude has been successfully linked to DBMSes from other vendors. This raises the interesting possibility that DBMS vendors will not achieve distributed file management but, rather, have it thrust upon them by increasingly sophisticated ASCII-based systems.

Command Technologies Inc. demonstrates just how sophisticated ASCII-based, distributed systems can be. This small company's chief scientist and co-founder is Calvin Mooers, one of the genuinely grand old names in computing. Mooers has been in the field since 1945. In addition to doing pioneering work in file management, he also helped lead the effort that led to the standardization of ASCII in the early 60s.

Command Technologies markets an I/O-based programming language and operating environment for distributed computing called VXM. Among other attributes, VXM gives the programmer the ability to create a VXM Entity, a semiautonomous module of code that can reside on any node of a network, or even travel from node to node in a network, like a "ghost" in the machine. Moreover, VXM Entities may communicate with one another via ASCII code, and they may control other, non-VXM programs and read their output as long as those programs work in ASCII.

Thus, VXM could give developers the ability to manage distributed applications as they never have before. A developer might, for instance, unite diverse DBMSes by giving each database a resident Entity. The Entity would then act as a virtual user, controlling the database, performing queries and passing the results in ASCII to users or other Entities and their databases.

But, no matter what tool becomes the common language of distributed software, products like VXM, Prelude, Sybase and Ingres/Star show there's no doubt that such a language will eventually come about. What is far less clear is what networking will do for, and to, software developers. In effect, communications networks, rather than individual computers, have become the machines for which developers write—and their products must now take into account both the increased power and complexity that networks provide. □

Interest Quotient (Circle One)
High 486 Medium 487 Low 488

**Ingres/Star
will eventually
be a truly
distributed
DBMS.**

The RPC50 does what your IBM PC AT® can, where your IBM PC AT can't

The Allen-Bradley RPC50 is a transportable, Ruggedized Personal Computer System. It does the same things your IBM personal computer AT can do, but it can do them in harsh environments (0-50° ambient, 2.5G operating shock, 30G non-operating.)

- 80286 Processor
- 1 MB Internal RAM Memory
- 10 MB Hardened Hard Disk
- 3-1/2", 720 KB Microfloppy
- 9" High-Resolution (640 x 200 pixel) amber CRT
- Integral 5-1/4" external floppy connection
- Integral Serial and Parallel Ports
- \$6600 OEM Net Price



TO ORDER, CALL OUR 24-HOUR RESPONSE CENTER, 1-800-346-6600, Ext. B540. For further details contact Allen-Bradley, Industrial Computer Group, Commercial Services, 747 Alpha Drive, Cleveland, Ohio 44143.






IBM PC AT is a registered trademark of International Business Machines Corporation.



ALLEN-BRADLEY
A Rockwell International Company

CIRCLE NO. 56 ON INQUIRY CARD

The perfect way to accent Big



The IBM-compatible NEC printers from Hall-Mark.

You've got an IBM or compatible personal computer. And you're looking for a flexible printer that can deliver the quality you want at an affordable price. Your search is over. NEC makes your printer, and Hall-Mark has it in stock.

Maybe you need the letter-quality performance of the Spinwriter 3500 or 8800 Series with its famous

print thimble and over 70 type fonts to choose from.

Or perhaps the Spinwriter e•l•f 300 Series printer would suit your needs. It's a good, reliable, letter-quality printer for medium-usage environments at a remarkably low price.

Looking for versatility? Then the Pinwriter P2 and P3 dot matrix printers are for you. From 180 cps

Alabama
Huntsville (205) 837-8700
Arizona
Phoenix (602) 437-2200
California
Bay Area (408) 946-0900
Orange County (714) 669-4700
Sacramento (916) 722-8600
San Diego (619) 268-1231
San Fernando Valley (818) 716-7300
West Los Angeles (213) 217-8400

Colorado
Denver (303) 790-4662
Connecticut
Connecticut (203) 269-0100
Florida
Ft. Lauderdale (305) 971-9280
Orlando (305) 855-4020
Tampa Bay (813) 530-4543
Georgia
Atlanta (404) 447-8000






Illinois
Chicago (312) 860-3800
Indiana
Indianapolis (317) 872-8875
Kansas
Kansas City (913) 888-4747
Maryland
Baltimore (301) 988-9800
Massachusetts
Boston (617) 935-9777

Minnesota
Minneapolis (612) 944-2600
Missouri
St. Louis (314) 291-5350
New Jersey
Fairfield (201) 575-4415
New York
Long Island (516) 737-0600
North Carolina
Raleigh (919) 872-0712

Ohio
Cleveland (216) 349-4632
Southern Ohio (614) 888-3333
Oklahoma
Tulsa (800) 231-0253
Pennsylvania
Philadelphia (215) 355-7300

Texas
Austin (512) 258-8848
Dallas (214) 553-4300
Houston (713) 781-6000
Utah
Salt Lake City (801) 972-1008
Wisconsin
Milwaukee (414) 797-7844

Blue.



high-speed data processing to 90 cps high density to 30 cps near letter quality, it has the print modes for all your applications.

Need the highest performance levels available? The Pinwriter P5 is the fastest, quietest 24-wire dot matrix on the market today. It has nine built-in character fonts with eight more plug-in fonts available. Speeds range

from 100 cps near letter quality to 290 cps data processing. The Pinwriter P5 is a printer that can grow with you.

Hall-Mark has all these NEC printers and their accessories in stock right now, ready for delivery. So call today. Hall-Mark has the products you need and the service you require because we care about your success.

HALL-MARK
25 YEARS

A COMMITMENT TO EXCELLENCE

CIRCLE NO. 57 ON INQUIRY CARD



Don't miss the SCSI bus.

Fujitsu's line of compatible SCSI data storage products will help you drive your system to its full performance potential.

If you want cartridge tape drives, 5¼-inch, 8-inch, and 10½-inch Winchester drives — or any combination thereof — on your SCSI bus, you'll never miss with Fujitsu America.

Our SCSI storage systems and products can keep up with the most sophisticated multi-host, multi-tasking SCSI-based system you can design. You can take full advantage of the extended performance features of SCSI — with products that set performance standards of their own.

Our MI053 Series Intelligent Disk Controller (IDC) can be configured with up to four drives on a single node, for a storage capacity that can exceed 2.7 Gigabytes. Choose our 8-inch, 337 MB drives or our 10½-inch Eagle XP, 689 MB drives. The MI053 offers either single-ended or differential drivers and common command set support for easy integration into any SCSI environment.

For 5¼-inch drives, there's the MI054 IDC. With up to four Fujitsu 172 MB, 5¼-inch drives on this controller, you can get large capacity and high performance in a compact package.

And Fujitsu's SCSI family even meets your need for cost-effective back-up devices. Our 125 MB, ½-inch cartridge tape drive provides a unique solution to your SCSI tape requirements.

If you'd like to put your SCSI system into high gear — stop! And find out more about Fujitsu's compatible data storage products. Call (408) 946-8777. Or write Fujitsu America, Inc., Storage Products Division, 3055 Orchard Drive, San Jose, CA 95134-2017.

Put Fujitsu drives on your SCSI bus. And give superior system performance the green light.

WE'RE DEVELOPING TECHNOLOGY FOR YOU.

FUJITSU

FUJITSU AMERICA

CIRCLE NO. 58 ON INQUIRY CARD

©Fujitsu America, Inc., 1986. All rights reserved.

FEPs EASE MIGRATION TO NEW LAN PROTOCOLS

An established technology, front-end processors help users preserve investments in local area networks while offering a direct path for incorporating standard, and future, network protocols

Steve Spanier, Excelan Inc.

The ability to connect diverse computer equipment is rapidly supplanting performance, features and even cost as the single most important criterion in selecting local area network equipment. In addition, multivendor networks require standard protocols that will enable them to work with incompatible terminals, bus structures, character sets, storage capacities, processing rates and physical media.

Many LAN protocol standards have emerged to address the problem of how to connect multivendor LANs. But LAN users and system integrators need not fear that the proliferation of these protocols—or of new protocols that emerge in the future—will make current installations obsolete. Accepted technologies, such as front-end processors, allow users to preserve their capital investments in LAN equipment. Front-end processors permit easy migration from present to future protocol standards.

Protocols include the International Standards Organization's Open Systems Interconnection (ISO/OSI) reference model, the Manufacturing Automation Protocol (MAP) and the Technical and Office Protocol (TOP).

Standards lay the foundation

The most popular current protocols upon which to build a network are Ethernet, the File Transfer Protocol (FTP), Telnet, the Simple Mail Transport Protocol (SMTP) and the Transmission Control Protocol/Internet Protocol (TCP/IP). These protocols, designed for heterogeneous environments, command a relatively large share of the LAN market.





Fig. 1. The front-end-processor approach offloads the Transport and Network layers of the OSI model to an intelligent front-end processor. The front-end processor performs all network-oriented tasks, thereby freeing the host for local processing.

Ethernet, a de facto standard, defines layers 1 and 2, the Physical and Data Link layers, of the OSI model. More than 150 companies support Ethernet, which was jointly developed six years ago by Digital Equipment Corp., Intel Corp. and Xerox Corp. The Ethernet specification avoids optional features, thus simplifying the development of compatible variants. Because of its low cost, high bandwidth and flexibility, Ethernet is the most likely media-access technology upon which to build a future network.

At layers 3 and 4, the Network and Transport layers of the OSI model, the question of which protocol is a standard is less clear. Still, TCP/IP

Fig. 2. The front-end-processor approach (red) outperformed the kernel-based solution (blue) in this experiment. The experiment compared the effect of large file-transfer throughput on a CPU-intensive, internally originated task (solid lines) and on an externally originated task that directs heavy network activity at a target node (dashed lines).



stands out as a de facto standard candidate. TCP/IP is a member of the Internet protocol family, developed by the Department of Defense Advanced Research Projects Agency (DARPA).

With a large pool of funds and a distinct need for networking, DARPA began work on the TCP/IP protocols in 1973. Since then, TCP/IP has evolved into the Transport Layer protocol of choice for the federal government. Computer-aided design and manufacturing were the first commercial applications to use TCP/IP. In recent years, with the delayed entry into the market of many recently developed Transport Layer protocols, TCP/IP has strengthened its commercial foothold.

Little standardization has occurred at the Application Layer where most users are demanding three applications: file transfer, virtual-terminal emulation and electronic mail. Because of their longevity, specification completeness and association with the Defense Department, the Internet versions of these applications—FTP, Telnet and SMTP, respectively—have gained popularity over the last seven years.

FEPs provide modularity

To achieve the flexibility that allows easy migration to new protocols, a technology must be modular. Modular design allows users to

employ smaller entities, which can be more easily understood, used and changed than can larger, unwieldy entities. Dividing a problem into smaller pieces, with each piece representing one task, makes the solution more comprehensible. It also makes solutions more malleable because, if a problem changes slightly, a new solution may be found by changing a few isolated parts rather than by having to alter an unwieldy whole. The OSI model applies modular design principles to networking.

Front-end processors embody the principle of modular design in LAN technology. A front-end processor, a self-contained subsystem, acts as a communications buffer between external data-sending devices, such as other network nodes or satellites, and a main processing unit. Front-end processors in LANs typically comprise a board that plugs into the backplane of a host, allowing that host to communicate on a network with similarly equipped computers.


A front-end processor contains a CPU that runs a streamlined operating system to control the front-end processor's resources. These typically include a network interface, a host interface and enough memory not only to buffer incoming and outgoing network information but also to run software implementing layers 3 and 4 of the OSI model.

The intelligence to run Transport and Network layer software without excessive host intervention is the main difference between the front-end-processor approach and the "kernel-based" approach. The Transport and Network layers run on the FEP without excessive host communication because they are, by definition, concerned with network-oriented rather than host-oriented tasks (Fig. 1).

Putting the network-oriented functions of a computer system onto a front-end processor decouples those functions from the main processing unit. The front-end processor presents a consistent interface to the host, without depending on the host operating system. This reduces the time needed to add new protocols and to adapt the network subsystem to new computer systems. It also helps to relieve the problem of outdated equipment and protocols. Front-end processors also offer high data throughput, efficient use of host memory and easy maintenance.

A front-end processor dedicates its resources, such a processor and memory, to network tasks, thus optimizing network throughput. While the host CPU performs database, spreadsheet and other tasks, the front-end processor uses its own resources to handle all network tasks. This results in increased net-

“KEY TRONIC SHOULD BUILD YOUR KEYBOARDS”



Key Tronic Resources:


With worldwide manufacturing capabilities including plants in the United States, Europe and the Far East; Key Tronic can deliver a high quality, high volume product at a competitive price.

Key Tronic is a vertically integrated manufacturer which ensures high quality and on-time delivery.

Key Tronic Capabilities:

In the last 17 years Key Tronic has produced over 7 million keyboards featuring 3,000 custom designs.

Key Tronic uses automated component manufacturing systems and has one of the largest tooling facilities on the West Coast. Over 80% of manufacturing is automated, utilizing



“ I can build your keyboard better, faster and cheaper than anybody in the world. I can customize it to your specification and I can meet your delivery requirements.

If you don't believe me, call me.

If you believe me, call the sales department.”

— Brian Ladyman, Senior V.P., Operations
Key Tronic Corporation

“Feel the Key Tronic Touch”

key tronic®

The Responsive Input Company™

P. O. Box 14687 • Spokane, WA 99214 • USA
(509) 928-8000 TWX 510 773-1885

highly sophisticated equipment developed and built by Key Tronic.

Key Tronic Commitment:

Key Tronic strives for long-term, successful relationships with our customers.

That means commitment. To the product and to you, the customer. Let Key Tronic be your partner in building *your* keyboards.


Contact your Key Tronic Sales Representative today . . . or call OEM Sales at (509) 928-8000 for more information.

Key Tronic . . . the world's largest independent manufacturer of full travel keyboards.

OUR RESOURCES, CAPABILITIES AND COMMITMENT GIVE YOU THE COMPETITIVE EDGE

CIRCLE NO. 59 ON INQUIRY CARD

The World of Pertec® Peripherals



Pertec Peripherals Corporation... the leader in computer peripherals, has served OEMs worldwide since 1967. More than a quarter-million Pertec peripherals are currently in use, backed by PPC's dedicated customer support team.

PPC provides applications consultation, training, product support and a worldwide spares network.

We are providing disk and tape data storage solutions for system builders and integrators ... worldwide, and we are continuing to set new standards for our commitment to excellence.

The new DX548 Winchester disk drives provide storage capacities of 548 megabytes, using the popular SMD interface at the faster data transfer rate of 14.52 MHz. Optional dual-port models are available. Future enhancements will include the SMD-E, SCSI, and IPI-2 interfaces.

With all its capability and capacity, the DX548 still fits an 8" floppy drive footprint.

The newly-announced DX368 provides systems integrators with 368 megabytes of unformatted data and 18 msec access time. This model also provides data transfer at 14.52 MHz.

PPC's new Data Package comprises either one or two DX332 or DX548 drives and power to supply up to **1.1 gigabytes** of data storage in a compact desk-top or rack-mount package. Data access is 18, 20, or 22 msec with a data transfer rate of 9.67 or 14.52 MHz.

The new FS2000 **quad-density** 1/2" autoloader streaming tape drive is ideally suited for Winchester backup, data interchange and mass storage.

The multiple-density feature (800/1600/3200/6250 cpi) provides capacities of 23 to 270 megabytes (unformatted), in ANSI and IBM format. All of these capabilities are housed in the same size package as the FS1000. It's the smallest GCR package available today, in 19" rack mount or a new desk-top enclosure. PPC is the recognized standard for 1/2" tape storage, and the FS2000's reliability is backed by the expertise that has placed tens of thousands of GCR tape drives in the field, worldwide.

Phone, write or TWX for complete technical data and fast, firm delivery dates.



**PERTEC
PERIPHERALS
CORPORATION**

9600 Irondale Ave., Chatsworth, CA 91311
818-882-0030, Toll Free: 800-821-4126 (CA)
800-443-9577, TWX 910-494-2093

CIRCLE NO. 60 ON INQUIRY CARD

VENDORS SUPPORT VARIOUS PROTOCOLS

	Ethernet	TCP/IP	FTP/Telnet	SMTp	UPD	XNS	FTAM	TP-4	LU6.2	NETBIOS	Token-Ring	Token-Bus	MAP	TOP	NFS	Starlan	X.25	SNA	DECnet
AT&T Co.	✓	✓				✓			*	✓						✓	✓	✓	
Bridge Communications Inc.	✓	✓	✓			✓					✓						✓	✓	✓
Communication Machinery Corp.	✓	✓	✓	✓	✓	✓		*		✓							*		✓
Digital Equipment Corp.	✓	✓	✓				✓										✓	✓	✓
Excelan Inc.	✓	✓	✓	✓	✓		*	✓		✓	*	*	*	*		✓	*		✓
IBM Corp.	✓	✓	✓						✓	✓	✓		✓				✓	✓	
Micom-Interlan Corp.	✓	✓	✓		✓	✓										*		✓	✓
Sytek Inc.	*	*					✓	*	✓	✓	*	✓	✓	✓			*		✓
3Com Corp.	✓					✓				*	*					✓			✓
Ungermann-Bass Inc.	✓	✓	✓			✓				✓	✓	✓	✓				✓	✓	✓
The Wollongong Group	✓	✓	✓	✓	✓		*	*					*	*	✓	✓	✓	✓	✓

✓ = already have
* = under development

Source: Mini-Micro Systems

work throughput and decreased host work load during heavy processing periods.

FEP outperforms kernel

Excelan Inc. performed an experiment comparing the kernel-based approach with the front-end-processor approach. In the experiment, the company tested the effect of a CPU-intensive (internally originated) task and a network processing (externally originated) task on large file-transfer throughput.

The experiment was run on two host systems: a Sun Microsystems Inc. 2/120 system to demonstrate the kernel-based approach and an NCR Corp. Tower for the front-end-processor approach. The 2/120 system ran Sun's version of the Berkeley UNIX Version 4.2 operating system with TCP/IP networking in the kernel. The Tower system ran the UNIX System V operating system with TCP/IP on an Excelan EXOS 201 front-end processor. Both hosts used the Motorola Inc. MC68010 processor running at 10 MHz, and the Excelan board provided 512K bytes of RAM and an 8-MHz Intel 80186 CPU. Average disk-access times and total disk space for both machines were similar.

In both the internally originated and the externally originated tasks, the front-end processor solution outperformed the kernel-based solution. Predictably, differences became more noticeable as the CPU or network activity increased.

The front-end processor approach also frees valuable host memory for application programs. As application programs become more

sophisticated, their need for host memory increases. Because of complex acknowledgement schemes, transport software can consume more than 60K bytes of memory. Running the transport software on a front-end processor allows users to run more host applications than if the transport software were running on the host.

Only operating system experts can overcome the difficulties of integrating Transport Layer network processing into the kernel of machines with different file systems, user interfaces and I/O subsystems. This is because such integration typically reaches deeply into the operating system internals. The task is made even more difficult because it involves tying network processing to operating system characteristics. New versions of the operating system often make the machine unable to perform certain network tasks. Therefore, front-end processor systems, which isolate network processing from the host operating system, are easier to maintain than kernel-based systems.

The main difference between a front-end processor and a link-layer board is that the front-end processor has onboard intelligence. With a front-end processor, a user must absorb the extra cost of a CPU and memory that intelligence entails. However, these are inexpensive to add because CPU and memory chips are widely available and low-cost. In addition, if the network software runs on the host, the host's price generally includes this software. If the network software runs on a front-end processor, its price typically depends on the price of the computer it supports. Generally, the cost of adding front-end processor technology to a

VENDORS RIDE VARIOUS BUSES

	Multibus	Multibus II	VMEbus	Q-bus	UNibus	PC-bus	Custom
AT&T Co.						✓	
Bridge Communications Inc.	✓						
Communication Machinery Corp.	✓		✓	✓	✓	✓	
Digital Equipment Corp.				✓	✓		
Excelan Inc.	✓		✓	✓	✓	✓	✓
IBM Corp.						✓	
Micom-Interlan Corp.	✓			✓	✓	✓	
Sytek Inc.						✓	
3Com Corp.						✓	
Ungermann-Bass Inc.	✓	✓	✓			✓	
The Wollongong Group	✓		✓	✓	✓	✓	✓

Source: Mini-Micro Systems

computer system is less than 10 percent of the cost of the computer itself.

FEPs allow migration

The Token-Ring and Token-Bus standards, along with the ISO, MAP and TOP protocols, are all likely to become popular in the next five years. ISO, MAP and TOP, as currently defined, specify all seven OSI layers. Token-Ring and Token-Bus resemble Ethernet in that they specify only the Physical and Data Link layer protocols, but they provide different topology and signaling methods than those of Ethernet. Despite this, migration to these new protocols is reasonably simple.

To do so, users and system integrators can replace Ethernet chips with Token-Ring and

Token-Bus chips. The newly created front-end processors would be largely compatible with the onboard operating systems used by intelligent front-end processors and fully compatible with the Transport Layer protocol software. Using two front-end processors would enable hosts to coexist on an Ethernet and either a Token-Ring or a Token-Bus network. During the transition between the old and new protocols, computers could actually coexist on both networks.

In addition, ISO has adopted the IEEE 802.3, 802.4 and 802.5 media-access protocols as standards, making migration to ISO easier. Because Ethernet and 802.3 are similar, most front-end processors that support one also support the other. Therefore, users need not change Ethernet/IEEE 802.3 front-end-processor hardware to implement ISO's Physical and Data Link specifications.

If the market decides to migrate from TCP/IP to ISO, front-end-processor vendors will most likely offer both the ISO transport protocol (TP-4) and TCP/IP on their boards. This combination is possible with front-end processors because the protocol software interfaces with the board's operating system rather than with its hardware. Many front-end processor vendors offer wide ranges of available memory space on their boards, and users who want to run more than one transport protocol should make sure that the front-end processors they purchase have sufficient memory for this task.

Current ISO applications, primarily File Transfer, Access and Management (FTAM), are more complex than most other popular applications and, therefore, require more host memory. In this light, the ability to run the Trans-

Companies mentioned in this article

AT&T Co.
1 Speedwell Ave.
Morristown, N.J. 07960
(201) 898-2000
Circle 368

Bridge Communications Inc.
2081 Stierlin Road
Mountain View, Calif. 94043
(415) 969-4400
Circle 369

Communication Machinery Corp.
1421 State St.
Santa Barbara, Calif. 93101
(805) 963-9471
Circle 370

Digital Equipment Corp.
146 Main St.
Maynard, Mass. 01754
(617) 897-5111
Circle 371

Excelan Inc.
2180 Fortune Drive
San Jose, Calif. 95131
(408) 434-2300
Circle 372

IBM Corp.
1133 Westchester Ave.
White Plains, N.Y. 10604
(914) 765-1900
Circle 373

Micom-Interlan Corp.
155 Swanson Road
Boxboro, Mass. 01719
(617) 263-9929
Circle 374

Sytek Inc.
6029 Bristol Parkway #210
Culver City, Calif. 90230
(213) 417-8859
Circle 376

3Com Corp.
1365 Shorebird Way
P.O. Box 7390
Mountain View, Calif. 94039
(415) 961-9602
Circle 375

Ungermann-Bass Inc.
2560 Mission College Blvd.
Santa Clara, Calif. 95050
(408) 496-0111
Circle 377

The Wollongong Group
1129 San Antonio Road
Palo Alto, Calif. 94303
(617) 459-5000
Circle 378

Without the right channel connections, you won't break any system speed records.

Your networks or devices are only as fast — and reliable — as their access to the mainframe. Settle for serial connections, and they move at a snail's pace. Buy an unreliable channel product, and they can stop cold.

KMW's Auscom division gives you the best of both worlds: Interfaces to the IBM channel that move data at up to 2 megabytes per second, and a 10-year record of rock-solid reliability no one else can match.

KMW's Auscom channel products let you connect your non-IBM devices and networks directly to any IBM® or plug-compatible mainframe. We offer both system-level channel products for end users and board-level products (such as Q-bus™, Multibus® and VMEbus) for OEM's. And no changes to your host operating system or access methods are required, since our interfaces function as standard control units on your mainframe.

Our channel interfaces emulate multiple controllers and support different devices and protocols simultaneously. For instance, a single Auscom interface can link your host to both local and wide area networks. And they can be programmed by Auscom or your staff to support most any connection you want to make.

Our interfaces connect IBM mainframes to *Ethernet*, *ProNet*, *X.25*, *T1*, *IEEE-488*, high resolution graphic devices, high speed printers, non-IBM computers, custom devices, custom networks and more.

We've got your mainframe connections. Call us at 1-800/531-5167 (in Texas, 512/288-1453) or write KMW Systems Corporation, 8307 Highway 71 West, Austin, Texas 78735.



For the right connections

Auscom is now a division of KMW Systems Corp.

IBM® is a registered trademark of International Business Machines Corporation. Multibus® is a registered trademark of Intel Corporation. Q-bus™ is a trademark of Digital Equipment Corporation.





Profit by Sharing— With EZQueue

Are you losing time and money while people wait to use the printer? Are your PC users frustrated by hassles over who gets the printer next? Are you faced with the prospect of buying more printers?

Try the EZQueue Profit-By-Sharing Plan and watch things improve—morale, productivity, and profits.

How It Works

The Giltronix EZQueue™ connects several PCs (from one to 24) to one, two, or more printers. And it provides buffer capacity of up to 2 megabytes—enough to store simultaneous inputs from all the PCs. Every PC can output to the EZQueue without delay and get on to its next job. The EZQueue stores all inputs as files and automatically outputs the next one to the printer as soon as the printer becomes available.

If you have more than one printer of the same type, EZQueue sends the next job to the first printer available. If you have two or more types of printers, such as a laser printer and a dot matrix, users can choose the desired printer for each job or default to a standard printer.

How It Saves You Money

- Reduces capital spending—you need fewer peripherals
- Eliminates “downtime” while PC users wait for a printer
- Improves efficiency and throughput

You also save because you don't have to buy special cards or cables to adapt EZQueue to your equipment. You can easily program each input port for baud rate, parity, word length, stop bits, and flow control. And EZQueue automatically adjusts to DTE/DCE requirements at each port, so you can use standard cables.

EZQueue is transparent to the users. But they'll know it's there, because their jobs will be easier, with fewer hassles. You'll know it's there, too, when you measure productivity—and profits.

There's a model that's just right for your office, whether it's a small law office or a large department in a Fortune 100 company. Don't get more printers. Get EZQueue.

Don't wait to get a letter through the printer.

Call today for full information on the Giltronix EZQueue 3000 series.

Information Hot Line: 1-800-531-1300 (Outside California)



CIRCLE NO. 62 ON INQUIRY CARD

Headquarters
3780 Fabian Way
Palo Alto, CA 94303
(415) 493-1300
Telex 345542

port and Network layer protocols on a front-end processor is even more important. The front-end processor and the host-resident driver that communicates with it provide application-transparent network access. Applications that become important standards can therefore survive transitions to many different types of front-end processors.

TOP and MAP use ISO layers 2 through 5, the Data Link through Session layers. TOP uses the IEEE 802.3 specification for the media-access layers, MAP uses the IEEE 802.4 (token bus) specification. MAP defines more Application Layer (level 7) specifications than does TOP, although they both use the OSI FTAM protocol. Because of this similarity between TOP, MAP and ISO, once ISO and token bus are implemented on intelligent front-end processors, MAP and TOP will also be essentially complete.

How to choose a LAN vendor

End users and system integrators would be well-advised to look for four main attributes in LAN vendors: support of popular protocols (Fig. 3), support of major bus structures (Fig. 4), technology flexibility and future plans.

Some LAN vendors provide tools that allow the easy adaptation of products to support new protocols. These elements are essential because they reduce users' dependence on the vendor and allow users to employ the tools to add protocols the vendor lacks. Three such tools are application programming libraries, operating system interfaces and tunable transport-protocol modules (Fig. 5).

Vendor-supplied application programming libraries enable users to write their own network applications and isolate the details of the host operating system, thus making applications more portable. These libraries are important to users who need additional functionality beyond the standard file-transfer, terminal-emulation and mail capabilities offered by most LAN vendors.

Many front-end-processor vendors "open" the architecture of their products by providing documented calls, such as "create process," "send message" or "read memory," to the onboard operating system. These calls allow users and integrators to create protocol packages to replace or supplement those provided by the vendor.

A few vendors allow users to modify some parameters of their Transport and Network layer protocol packages. For example, TCP/IP uses a "window" to help the transmitting node determine whether it should send more data to




Fig. 5. In a typical front-end-processor architecture, application programming libraries, onboard operating system calls and tunable protocol modules make it easier for users and system integrators to adapt a vendor's offerings to support specific environments.

the receiving node. The ability to modify the window size allows the user to adjust performance for special circumstances.

Finally, end users and system integrators should have reasonably complete information about LAN vendors' future plans. Most LAN companies are not large enough to offer all the new protocols that will appear over the next few years. Each will therefore focus on specific markets and should be prepared to answer detailed questions on market strategies and products. □

Interest Quotient (Circle One)
High 489 Medium 490 Low 491

Steve Spanier is a technical marketing engineer with Excelan Inc., San Jose, Calif. He holds a master's degree in computer science from West Coast University, Los Angeles.



**IN GERMANY, WE'D RATHER
CREATE A LASTING IMPRESSION THAN
RUSH PRODUCTION TO BE FIRST.**



it through to a superior conclusion.

The result is not just an idle entry into the burgeoning class of 24-needle machines. But a printing plant that some have even suggested is overbuilt.

In contrast to hurriedly stamped frames of sheet metal, the superstructure of the MT330 is solid cast. All of which creates a more substantial, shock-absorbing work platform.

Likewise, the power train is a product of serious deliberation; a push-fed tractor driven by surge resistant DC motors.

Then our engineers went to work on the print head.

For increased speed and resolution, they staggered the 24-needle matrix into two perfect vertical-plane columns.

In addition, they developed a magnetic head assembly that actually requires less

power during printing. So long after our counterparts have overheated, or beaten themselves into obsolescence, the MT330 continues to spew out mountains of data.

Up to 10,000 pages per month at 300 characters per second.

Characters that remain crisp and dense from a ribbon rated at more than 15 million impressions.


So if it seems we were exceedingly patient in our introduction of the MT330, the results of German perfectionism are a justifiable reward.


To make your own evaluation, call us at 1-800-843-1347 for a demonstration.

We think you'll be suitably impressed. Particularly in the long run.

MANNESMANN
TALLY

Call it a manifestation of German pride, but we took our time to introduce the MT330 for good reason: We wanted to think



 SOFTWARE AG

When you're ready to show your users what a DBMS can really do.

When it comes to database management and information processing for VAX superminicomputers, only Software AG can give you a winning performance in a large-scale production environment. ADABAS(VMS), our high-performance database management system, and NATURAL(VMS), our fourth-generation information processing system, put you in

touch with your information quickly. You also get the restart and recovery features you need to maintain data integrity. And, with our NET-WORK(VMS) remote database facility, you can distribute database processing in any DECnet-VAX environment. Call us today at 1-800-336-3761. (In Virginia and Canada, 1-703-860-5050.)

Please see us at DEXPO West '86 Booth #1925

 SOFTWARE AG

© 1986 Software AG of North America, Inc.
ADABAS and NATURAL are trademarks of Software AG of North America, Inc.
VAX, VMS, and DECnet are trademarks of Digital Equipment Corporation.

CIRCLE NO. 64 ON INQUIRY CARD

IBM'S TOKEN-RING: WHAT ARE THE ALTERNATIVES?

IBM's 'serious' LAN has finally arrived, but other LANs should be able to coexist with the Token-Ring

David S. McMaster
Gateway Communications Inc.


While watchers of IBM Corp. have been anticipating the industry leader's Token-Ring Network for several years now, 1986 marks the year that Token-Ring has finally arrived. Throughout the first half of this year, IBM has been shipping and installing its Token-Ring at an increasing rate. Meanwhile, the industry's response has ranged from wholehearted support to skepticism.

In keeping with tradition, IBM's delivery of Token-Ring hardware and software has in effect "blessed" the technology, making LANs the acceptable approach to connecting and sharing personal computer resources. More specifically, many LAN hardware and software vendors have announced products that either support or are compatible with the Token-Ring, and others have developed gateways that will interface to the Token-Ring.

The Token-Ring is not IBM's first PC LAN product. IBM has been shipping the PC Network, which Sytek Inc. produced for IBM, for several years. However, most industry observers point to the Token-Ring as IBM's first "serious" LAN offering. IBM provides a software interface (bridge) that links the Token-Ring and the PC Network.


It's time for action

Before IBM's Token-Ring announcement, many system integrators and in-house PC departments faced with choosing a LAN were playing a "wait-and-see" game, until IBM should play its hand. But they can't wait any



LANs use one of three topologies: bus, star or ring. A bus topology connects all stations to one cable running the length of the network. A star topology connects all workstations to a central station, which routes data to the appropriate place. A ring connects all workstations in a closed loop.

The ring in IBM's Token-Ring resides inside the Multistation Access Unit. Each PC connects to a MAU by individual cable, and each MAU interconnects as many as eight PCs. Users can link MAUs to form a larger network.



longer. Those who must purchase networking solutions for PC users or customers must now undertake serious evaluations.

The logical question is now: "Is the Token-Ring the way to go?" The question is not a black-and-white "Token-Ring vs. the competition" situation. Instead, the answer depends on the application. Several LAN vendors have announced hybrid solutions, gateways from their networks to Token-Ring and software options that allow applications developed for the Token-Ring to run on competitive LAN hardware. These companies include AST Research Inc., Bridge Communications Inc., Corvus Systems Inc., Excelan Inc., Gateway Communications Inc., Nestar Systems Inc., Novell Inc. and 3Com Corp.

As a result, some companies may be able to combine compatible LANs or even competing LANs such as the Token-Ring and Ethernet, the formerly reigning near-standard LAN. Companies that offer Ethernet products include 3Com, Torus Systems Inc. and Xerox Corp.

The first step in evaluating LANs is to examine their basic LAN parameters: topology, access method, transmission method, transmission speed, cabling, software and hardware.

As the name "Token Ring" implies, the IBM product incorporates ring topology and the token-passing access method. This approach differs from most installed LAN systems: About 80 percent use bus topology and the Carrier Sense Multiple Access (CSMA) method, as popularized by Ethernet.

Regarding the remaining parameters, the Token-Ring LAN is a baseband system operating at 4M bits per second (bps) over twisted-pair wiring. It uses the PC LAN Program version 1.1 software running under IBM's NETBIOS (network basic input/output system). PC LAN Program 1.1, announced in April, is an enhanced version of IBM's original PC Network

Program, which IBM provided for its PC Network LAN.

Topology determines the LANscape

Topology refers to the network architecture configuration, or the way in which PCs physically interconnect. The topology of a LAN determines how information will flow across the network. LANs use one of three major topologies: ring, bus or star.

IBM chose ring—the least-used topology—for its LAN. So far, the most visible ring LAN other than the Token-Ring is Proteon Inc.'s ProNet. However, IBM's Token-Ring may change this topology's last-place status.

Ring topology employs a single, relatively short, looped cable interconnecting each of the PCs in the network.

The star topology interconnects each PC to a shared controller via the PCs' individual cables. Any defective node on a star LAN can be fixed from the central hub. However, employing a single controller limits the number of PCs that can be attached to the LAN. If the controller fails, the entire network fails.

About 15 percent of all PC-based LANs employ star topology, making it the second most popular topology. Novell's S-Net, Sytek's System 6000 and TeleVideo Systems Inc.'s Personal Mini employ the star topology.

The bus topology, the most common LAN architecture, interconnects PCs over a shared cable, but the cable ends are not connected. Each station on a bus network connects to the bus and "listens" to the data stream. When the station wants to communicate, it merges its data into the data stream. Bus LANs allow for the easy addition of nodes, and a defective node won't affect any others on the system. LANs that use the bus topology include AST's PCnet II, Gateway's G/Net, IBM's PC Network, Concord Data Systems Inc.'s Token/Net,

27mW and you're ready to roll.


27 milliwatts. That's all it takes for standby mode on our FD-35 Series 3.5 inch floppy disk drives with the Power Saver option. And, in operation, they consume a mere 1.72 watts average at read/write, and 2.90 watts average at seek. These just happen to be the lowest numbers for any 3.5 inch drive.

This remarkable feat is made possible by the use of new custom LSI chips with CMOS technology for more efficient control over all the drive functions.

For added reliability and accuracy we shortened the gap between the band actuator and the head and included a more precise head position mechanism. This means stable reading and writing, even at high track densities.

And, as if all that weren't enough, we've thrown in special aluminum RF shielding to keep out noise pollution.

With the growing need for more portable systems, 27 milliwatts is a load anybody can carry.



Built To Fanatical Standards. **TEAC**

INSTRUMENTATION AND COMPUTER PRODUCTS DIVISION, 7733 TELEGRAPH ROAD, MONTEBELLO, CA 90640

East (617) 475-7311 South/Midwest (312) 351-9124 Rocky Mountain (602) 242-4025 (303) 337-6329 (801) 532-2111

Northwest (408) 727-1427 Southern California (213) 726-0303

© 1985

CIRCLE NO. 65 ON INQUIRY CARD

You can't build tomorrow's systems with yesterday's drives.

You've seen one small disk drive, you've seen them all, right? Not exactly. One disk drive stands above all the rest.

It comes from Maxtor.

The company that refuses to produce disk drives merely as good as everybody else. Instead, we set new standards by producing the only 5¼" disk drives worthy of the next generation of supermicros. Winchester's with 85 to 380 megabytes of storage. And average access times of less than 30 msec.

And we don't mean prototypes. We mean full production. So, you can build the systems of tomorrow, today. And that can be a big advantage.

For you. Or your competition.

Maxtor Corporation, 150 River Oaks Parkway,
San Jose, California 95134,
(408) 942-1700, TELEX: 171074.

Sales Offices:

Austin: (512) 345-2742

Boston: (617) 872-8556

Orange County: (714) 859-3100

San Jose: (408) 435-7884.

Maxtor

CIRCLE NO. 66 ON INQUIRY CARD



Fox Research Inc.'s 10-Net, IDEAssociate Inc.'s IDEAnet, 3Com's EtherSeries, 3M's PC/LAN and Ungermann-Bass Inc.'s Net/One.

When installed, IBM's Token-Ring looks like a star rather than a ring. The heart of the network is a ring, but the ring is inside the Multistation Access Unit (MAU), an expensive "connector box." Each PC connects to the MAU by individual cable, which gives each MAU the star-like appearance. Each MAU interconnects as many as eight PCs, and users can link MAUs to form a larger network. By bringing all the links to a central node, which facilitates troubleshooting, this configuration takes advantage of the star topology. Another LAN using a star/ring topology is Quadram Corp.'s Quadnet IX. It features a star-shaped ring with infrared fiber-optic cable.

The media compared

LANs use one of three general types of media, or wiring: coaxial, twisted pair or fiber optic, and any of these works on any topology. Many baseband LANs and all broadband LANs use coaxial cable; it is the most popular medium. Coaxial consists of a central insulated conductor wrapped with a braid or foil that shares the same axis as the conductor. Coaxial can carry high-frequency signals; the foil or braid protects the signal from outside interference. Installation, including labor, typically

costs \$4 per foot and \$40 per termination.

With coaxial cabling, each personal computer on a LAN connects to the cable through a twist-lock BNC (baby "N" connector), and a BNC terminator connector terminates the coaxial cable.

The second most popular LAN medium, twisted pair, consists of two wires wrapped around each other. The twining reduces the cable's tendency to pick up electrical noise, which can cause data errors. However, its immunity to noise interference is not as good as that of coaxial, and this can degrade performance. Furthermore, twisted-pair wiring cannot carry data rates as high as can coaxial, and signal levels for twisted-pair wiring normally degrade over much shorter distances than do the signal levels on coaxial cable. On the plus side, at pennies per foot, it offers the lowest cost, and users can install it easily.

For short distances, the Token-Ring can connect via standard telephone-line twisted-pair wiring, which IBM calls Type 3 cable. For longer cable runs, however, IBM recommends shielded twisted-pair cabling, which is more expensive than standard telephone twisted-pair wire or coaxial cable. It adds greater noise resistance, however, and higher data rates.

Fiber-optic cable is still rare, but it is immune to interference from electrical or electronic devices, a factor that can be important in

The practical realities of today's PC-based LAN implementations point to the superiority and cost-effectiveness of baseband.

LANs COME IN MANY VARIETIES

Company	Product	Topology	Access method	Bandwidth	Wiring type
AST	PCnet II	bus	CSMA/CA	baseband	twisted pair
Corvus	Omninet	bus	CSMA/CA	baseband	twisted pair
Fox Research	10-Net	bus	CSMA/CA	baseband	twisted pair
Gateway	G/Net	bus	CSMA/CA/CD	baseband	coaxial
IBM	PC Network	bus	CSMA/CD	broadband	coaxial
IBM	Token-Ring	ring	token passing	baseband	twisted pair
IDEAssociates	IDEAnet	bus	CSMA/CD	baseband	coaxial
Novell	S/Net	star	proprietary	baseband	dual twisted pair
Orchid	PCnet	bus	CSMA/CD	baseband	coaxial
Proteon	ProNet	ring	token passing	baseband	coaxial twisted pair
Quadram	Quadnet VI	bus	CSMA/CA/CD	baseband	coaxial
Quadram	Quadnet IX	star/ring	token passing	baseband	dual twisted pair
Standard Microsystems	ARCnet	star/bus	token passing	baseband	coaxial
Sytek	System 6000	star	CSMA/CD	broadband	coaxial
TeleVideo	Personal Mini	star	proprietary	baseband	twisted pair
3Com	EtherSeries	bus	CSMA/CD	baseband	coaxial
Ungermann-Bass	Net/One	bus	CSMA/CD	baseband/broadband	coaxial
Xerox	XC22	bus	CSMA/CD	baseband	twisted pair
Xerox	XC24	bus	CSMA/CD	baseband	coaxial

CSMA: Carrier Sense Multiple Access
 CD: Collision Detection
 CA: Collision Avoidance

Source: Gateway Communications Inc.

Token-Ring is not likely to cause the demise of competitive LAN products that have been using CSMA/CD for some time.

harsh environments involving machinery. But fiber-optic cable can cost \$10 per foot and \$50 per termination. Furthermore, there is a lack of workers who know how to install and maintain it.

There has been debate over the past few years over the virtues of baseband vs. broadband transmission. Broadband systems broadcast a wide number of frequencies over the cable, and, in theory, network nodes "tune in" to different channels. These channels can simultaneously carry voice, video and other signals, unlike baseband, which carries only digital data. However, in most broadband LAN implementations, personal computers attach to the same frequency channel because they do not require voice or video transmissions. Broadband cable also requires more electronics—and, hence, is more expensive—than baseband.

Baseband systems, such as the Token-Ring, send pulses over the wire, and nodes receive those pulses. Baseband systems allow the transmission of only one signal over the cable at a time, and each attached personal computer communicates over that channel.

Baseband seems favored

Thus, the practical realities of today's personal computer-based LAN implementations point to the superiority and cost-effectiveness of baseband. Broadband can extend over greater distances than baseband, however, making it more appropriate as a "backbone" network connecting various widely scattered LANs.

IBM's PC Network, a broadband implementation, supports PCs only on a single channel and does not support voice or video without additional equipment. With such implementations, the added cost and complication of broadband may not be justifiable, which could

be a reason for the PC Network's lack of market acceptance.

Access methods: the 'rules of the road'

Access methods ensure that each station has equal access to the network and determine which station has the "right of way." Before IBM introduced the Token-Ring, the most popular access method for baseband and broadband LANs was CSMA/CD (carrier-sense multiple access with collision detection). Both CSMA/CD and the Token-Ring's token-passing access method are IEEE 802 standards.

Debate continues about which method is better. The IEEE 802 committee struggled with this question for years before deciding to adopt both standards. And, because the Token-Ring is not likely to cause the demise of competitive LAN products that have been using CSMA/CD for some time, the two methods will most likely have to coexist.

CSMA allows many users to share the media's single channel for seemingly "concurrent" communications. Each personal computer on the network can send information when the cable is "free." Each in turn constantly "listens" to the cable for messages addressed to them and pulls them off when they appear.

With carrier sense, each personal computer monitors the media to determine whether the carrier is busy. Multiple access means that every personal computer attached to the media has an equal opportunity to communicate. As a result, it is likely that two or more users will attempt to communicate concurrently, or "collide." Collision detection detects these "collisions" and imposes a "backoff" procedure until the personal computer again tries to communicate.

Some CSMA networks use collision avoidance (CA), which imposes algorithms that enable the personal computers to avoid collisions. The algorithms check to see whether a cable is in use before allowing a personal computer to communicate. If a collision does occur, CA ensures that it will not occur again when the personal computer tries to retransmit.


Some vendors have adopted a third technology, error detection and correction (EDC), which guarantees delivery of a message. EDC acknowledges and verifies the data as it returns from the receiving personal computer to the sending personal computer. EDC, a link-level operation, is transparent to the applications and thus differs from error-correction methods that are incorporated into the application program.

IBM's announcement of Token-Ring boosted

Spec summary

- **Product:** Token-Ring Network
- **Manufacturer:** IBM Corp.
- **Topology:** ring
- **Access method:** token passing
- **Speed:** 4M bits per second
- **Media:** twisted-pair wiring
- **Bandwidth:** baseband
- **File-server software:** IBM PC LAN Program
- **Utility software:** file locking, record locking, file security, electronic mail, remote access, print spooling
- **Maximum cable length:** 990 feet

New From Irwin!



40 Megabyte Capacity

Now . . . the new 40 megabyte, Model 145 Tape BACKUP™ System, plus five other new Irwin models, provide PC designers and system integrators unparalleled flexibility with the widest selection of tape backup peripherals available today.

Irwin offers these unique advantages.

- RELIABILITY — More than 150,000 sold.
- INTERCHANGEABILITY — The new Irwin Model 145 can read data cartridges

created on any of Irwin's seven other Models.

- FLEXIBILITY — Both 5¼" and 3½" form factors, at 500 and 250 Kbps with capacities from 10 to 40 megabytes.
- MARKET ACCEPTANCE — The most frequently integrated tape backup peripheral available today.

When you choose a tape system manufacturer as your partner, consider Irwin Magnetics and the features that have made Irwin BACKUP™ Tape Systems the best sellers of the microcomputer industry.

Call us! We want to work with you.
1-800-BACKUP 1

Irwin BACKUP™ Systems

5¼" FORM FACTOR	3½" FORM FACTOR	CAPACITY	DATA TRANSFER RATE	DATA CARTRIDGE
Model 145 NEW	Model 245 NEW	40 mB	500 Kbps	DC2000
Model 125 ALREADY BEST SELLER	Model 225 NEW	20 mB	500 Kbps	DC1000
Model 120 NEW	Model 220 NEW	20 mB	250 Kbps	DC2000
Model 110 ALREADY BEST SELLER	Model 210 NEW	10 mB	250 Kbps	DC1000

All Irwin models are available NOW!


IRWIN
MAGNETICS

Irwin Magnetics
Box 7639
Mt. Prospect, IL 60068
1-800-BACKUP 1

©1986 Irwin Magnetic Systems, Inc.

CIRCLE NO. 67 ON INQUIRY CARD

Are your modems smart enough to talk to dumb terminals?



Sure, any Hayes®-compatible modem can quickly link up your PC's, but what about your "dumb" terminals?


Your Hayes-compatible "smart" modem may be costing you time and aggravation as you laboriously type in long command sequences to access a mainframe.

But now NEC offers 1200 and 2400 bps modems that handle two auto-dialing protocols—Hayes and NEC. The NEC protocol can store up to 12 telephone numbers and logon sequences, and provides a friendly Help menu to assist you in making the connection.

Best of all, you can get both NEC and Hayes capability in our N1220/30HN and N2420/30HN modems, with the quality and superb design that have become NEC hallmarks. That's why we can offer a generous 5 year limited warranty on both parts and labor.

So give us a call and find out how easy it is to use our NEC auto-dialer with your dumb terminals. Find out about the NEC N1220/30HN and N2420/30HN modems.

They outsmart the smart modems.



800-222-4NEC

Or 800-632-0666.

Call or write for a free brochure on the N1220/30 and N2420/30 modems.

NEC America, Inc., Data Communications Products Division,
110 Rio Robles, San Jose, CA 95134.

**Data Communications
Products**

NEC

CIRCLE NO. 68 ON INQUIRY CARD

its place in the industry, thus likely guaranteeing it as an industry standard. Token passing involves the passing of a token, or "envelope," on the LAN from personal computer to personal computer. A personal computer cannot communicate until it has the envelope in which to place the information. The envelope, or "packet," contains data of some predetermined maximum amount. Typical amounts are 128, 256, 512, 1,024 or 2,048 characters.

When a token-passing LAN is started up, the workstations arbitrate among themselves to determine which is the "master" that will generate the token. The personal computers then pass the token around the ring. With token passing, each personal computer on the net-

work has equal access, but each has to wait until the token reaches it before it can communicate. This means that the network is "deterministic," or predictable. However, the more workstations that are added to the network, the longer each has to wait to get on the network.

Deterministic performance is useful in applications such as process control in which predictable service is necessary. However, most personal computer-based LAN environments involve business communications, which may be better served by CSMA/CD.

A potential drawback of token passing is that when a personal computer powers off, the ring is broken, much like with old-fashioned "serial" Christmas tree lights. When the ring is

**Don't assume
that a
10M-bps LAN
performs
faster than a
1M-bps LAN.**

Companies mentioned in this article

AST Research Inc.
2121 Alton Ave.
Irvine, Calif. 92714
(714) 863-1333
Circle 340

Bridge Communications Inc.
2081 Stierlin Road
Mountain View, Calif. 94043
(415) 969-4400
Circle 341

**Concord Data
Systems Inc.**
397 Williams St.
Marlborough, Mass. 01752
(617) 460-0808
Circle 342

Corvus Systems Inc.
4930 Research Drive
Huntsville, Ala. 35805
(205) 830-4310
Circle 343

Excelan Inc.
2180 Fortune Drive
San Jose, Calif. 95131
(408) 434-2237
Circle 344

Fox Research Inc.
7005 Corporate Way
Dayton, Ohio 45459-4223
(513) 433-2238
Circle 345

**Gateway
Communications Inc.**
2941 Alton Ave.
Irvine, Calif. 92714
(714) 553-1555
Circle 346

IBM Corp.
Entry Systems Division
P.O. Box 1328
Boca Raton, Fla. 33432
Circle 347

IDEAssociates Inc.
35 Dunham Road
Billerica, Mass. 01821
(617) 663-6878
Circle 348

Nestar Systems Inc.
1345 Shorebird Way
Mountain View, Calif. 94043
(415) 969-1777
Circle 349

Novell Inc.
1170 N. Industrial Park Drive
Orem, Utah 84057
(801) 226-8202
Circle 350

Proteon Inc.
4 Tech Circle
Natick, Mass. 01760
(617) 655-3340
Circle 351

Quadram Corp.
4355 International Blvd.
Norcross, Ga. 30093
(404) 923-6666
Circle 352

**Standard
Microsystems Corp.**
35 Marcus Blvd.
Hauppauge, N.Y. 11788
(516) 273-3100
Circle 353

Sytek Inc.
1225 Charleston Road
Mountain View, Calif. 94043
(415) 966-7400
Circle 354

TeleVideo Systems Inc.
550 E. Brokaw Road
San Jose, Calif. 95112
(408) 971-0255
Circle 355

3Com Corp.
1365 Shorebird Way
Mountain View, Calif. 94043
(415) 961-9602
Circle 356

3M
3920 Varsity Drive
Ann Arbor, Mich. 48104
(313) 973-1500
Circle 357

Torus Systems Inc.
485 Seaport Court
Suite 105
Redwood City, Calif. 94063
(415) 363-2418
Circle 358

Ungermann-Bass Inc.
2560 Mission College Blvd.
Santa Clara, Calif. 95050
(408) 496-0111
Circle 359

Xerox Corp.
Business Systems Group
Xerox Square
Rochester, N.Y. 14644
(716) 423-9200
Circle 360

The term 'LAN operating system' is a popular misnomer because the personal computers on any LAN run under the PC-DOS operating system.

broken, the entire token-passing process must begin again. The personal computers must again arbitrate to select a master and regenerate the token, which can take as long as 10 seconds. With CSMA/CD, the powering-off of a PC does not necessitate regeneration. If one "light" goes out, the whole row will not follow suit.

From an application standpoint, token passing might prove superior on a network that is doing file transfers only of a specific, consistent nature. CSMA/CD, on the other hand, better suits networks with a mix of file-transfer and interactive inquiry traffic.

Transmission speed can be deceptive

LAN transmission speed—the speed at which data travels along the cable—is usually measured in megabits per second. The Token-Ring runs at 4M bps, and IBM promises that future versions will be faster. One might assume that a 10M-bps LAN performs faster than a 1M-bps LAN, but this is not usually so. This is because transmission speed does not account for the time it takes for information to move from the media to and through the LAN interface board, the LAN interface software, the PC-DOS operating system, the PC's memory, the application interface and the PC's monitor.

The transmission speed, the software and the access method all measure LAN performance. Users should also consider the incidence of lost tokens, collision, retransmission and backoff. Therefore, benchmark tests provide the only true measurement of relative speed and performance. One approach is to run the application on different LANs being considered. However, if hands-on tests are impractical, users can obtain independent benchmark evaluations that pit the major LANs systems against each other in real-life applications.

The 'LAN OS' myth thrives

Two types of LAN software are available: file-server control software and LAN application software. The term "LAN operating system" is a misnomer because the personal computers on any LAN run under the PC-DOS operating system. What people usually refer to as a LAN operating system is really a file-server operating system, typically a rigid disk-based system, such as an IBM PC/AT. Workstations can use the file-server system for shared access to programs, data, printers and so on.

For example, Novell's NetWare and IBM's PC LAN Program are file managers for the disk-based file servers. Such products provide a LAN with multiuser file access. File-server software provides security, access rights, utilities,

disk optimization, file locking, record locking and printer spooling.

A few LAN vendors provide proprietary file-server operating software. Most, however, support one of two industry "standards," one of which is Novell's NetWare. NetWare runs on some 25 LAN hardware systems, including Corvus' Omninet, Gateway's G/Net, IBM's Token-Ring and PC Network and Standard Microsystems Corp.'s ARCnet. In addition, more than 3,000 multiuser application programs run NetWare.

The second "standard" is based on software from IBM and Microsoft Corp. For the PC Network LAN, IBM provides the PC Network Program (PCNP). IBM announced an upgraded version of this software, called PC LAN Program version 1.1, for the Token-Ring. Microsoft offers a similar file-server operating system, called MS-Net.

PCNP, PC LAN Program and MS-Net all use NETBIOS, an extension of the IBM PC's BIOS, which comprises a group of programs in ROM. There are four alternative configurations for each PC workstation networked on the IBM PC LAN Program: redirector, receiver, messenger and file/print server.

The redirector configuration allows a PC to share resources and send messages to other computers. The remote resources appear as if they were attached locally.

The receiver configuration adds the capabilities to receive messages from other users and display, print or store them in a file. The software that enables a PC to receive messages runs as a background task on the PC.

The messenger configuration additionally allows a PC workstation user to switch between a local application and the IBM PC LAN Program. This configuration includes a full-screen editor plus the ability to forward received messages to multiple users.

The file/print configuration establishes the shared file/print server, which can consist of any PC with a rigid disk. An IBM PC/XT or AT usually can act in this configuration, although a dedicated disk subsystem also works. Users can attach as many as three printers to this type of configuration.

This configuration controls access to the shared file/print server down to the subdirectory level. It assigns each network user various levels of access rights: read only, write only, read/write, write to a specific disk or directory, or read/write to a specific disk or directory. The PC-DOS command ATTRIB controls file access. Using network flags and other PC-DOS calls controls access down to the record or field

Victory is the bottom line.



When it comes down to it, there's only one trophy worth taking in the computer industry. Success.

The computer event of the year, COMDEX/Fall '86 gives you access to over 1,000 of the industry's top manufacturers and suppliers. Introduces the COMDEX Support Services and Products Expo that links you to the suppliers of products and services for managing and expanding your business. And offers the esteemed Conference Program, this year featuring special one-day seminars on how to make the industry's hot profit opportunities—Desktop Publishing and CAD/CAM—pay off for you.

But most important, COMDEX offers something to take home with you: Your business success.

Because the finish line is the bottom line.

For full registration information, write to The Interface Group, Inc., 300 First Avenue, Needham, MA 02194.

COMDEX®/Fall '86

Join The Winner's Circle

November 10-14 • Las Vegas, Nevada

Please send me a registration kit including hotel, travel and conference information.

I am interested in attending COMDEX.

I am interested in exhibiting at COMDEX.

Name _____

Title _____

Company _____ Phone _____

Address _____

City _____ State _____ Zip _____

Mail to: The Interface Group, Inc.

Registration Department

300 First Avenue, Needham, MA 02194

©1986 The Interface Group, Inc.

CIRCLE NO. 20 ON INQUIRY CARD

NetWare has the edge because of the vast amount of multiuser software available, but IBM will probably give Novell a run for its money.

level.

NetWare's adaptability to most LANs gives it the edge because of the vast amount of multiuser software available, but IBM will probably give Novell a run for its money. The result will probably be that both systems will thrive and spawn ever-increasing libraries of application programs.

In addition to the personal computer workstations and the optional file server, the basic hardware to evaluate when selecting a LAN system is the personal computer interface controller. This is a circuit board controller that manages the physical interface between the personal computer and the LAN. The controller resides in the personal computer for ring networks such as the Token-Ring and bus networks such as G/Net or in the common cluster controller on the network for star networks such as S-Net.

The typical interface controller is a standardized personal computer adapter board that plugs into a personal computer expansion slot and connects to the LAN media. For example, on a coaxial-cable-based system, the board usu-

ally contains a standard twist-lock BNC.

Most LAN systems use a personal computer's native CPU to control network management and access. This is not always the most efficient arrangement, however, in that the CPU in the personal computer supports PC-DOS and a single-user application. Any additional software such as network management can seriously degrade the performance of a personal computer.

Only a few LANs, including Token-Ring, PC Network and G/Net, use a separate microprocessor on the network interface board to control network management and access. Such a configuration allows the network interface board to offload the personal computer's native CPU of network-management chores.

Pick one—or more

No one system can solve everyone's application. While one LAN may suit a small installation of 10 personal computers on a single floor of a building, another may provide a better solution for interconnecting 100 PCs scattered across a complex of buildings.

At the risk of oversimplification, however, it's a safe bet that the current implementation of the Token-Ring will perform adequately at the lower end of this scale: small clusters of workstations in predictable, controlled applications, such as process control or file transfers with some interactive inquiries.

So, although the Token-Ring should become a major market success, it will surely not bury the competition. Alternative solutions will continue to offer better price-performance advantages in certain applications.

David S. McMaster is president and co-founder of Gateway Communications Inc., a LAN supplier in Irvine, Calif. Previously, he accumulated more than 20 years' experience in the data-communications field, including 11 years at Control Data Corp.

Interest Quotient (Circle One)
High 492 Medium 493 Low 494

Reprints of Mini-Micro Systems' articles are available on a custom printing basis in quantities of 500 or more. For specific quotations, contact Katie Pyziak, (312) 635-8800.

Light Pens Ahead of the Competition



Yes, there can be a bar code reader in your customer's future, with Caere's new EASY-SCANNER™ 400 Series. Introducing the incredibly versatile lightweight scanner that's designed to fit your product's requirements as well as your budget.

This keyboard wedge with a light pen fits easily between your keyboard and terminal and inputs data 20 times faster than the quickest human hands. Plus it can autodiscriminate between several of the most popular bar codes.

Whether your application is manufacturing, healthcare or retail, the low-cost Caere EASY-SCANNER™ 400 Series is the one. It can be used with your IBM PC's and PC compatibles, ASCII and IBM terminals and point-of-sale systems.

Call Caere at 408-395-7000 and see how the Caere EASY-SCANNER™ 400 Series can put you light pens ahead of your competition.


Volume discounts available to resellers

Caere® Corporation
100 Cooper Court
Los Gatos, CA 95030
408-395-7000
TWX# 910-597-5391




Believe It Again!

FANTASTIC! TEK 4115 DISCOVERED INSIDE PC



A PC HAS BEEN DISCOVERED LEADING A DOUBLE LIFE AS A TEKTRONIX 4115. TO ALL OUTWARD APPEARANCES, THE PC SEEMED STANDARD AND NORMAL. BUT DEEP INSIDE -- DUE TO A UNIQUE AND MYSTERIOUS NEW GRAPHICS EMULATION PACKAGE CALLED TORAF-15™ -- THE PC WAS ABLE TO LEAD AN INCREDIBLY COLORFUL LIFE NEVER BEFORE CONSIDERED POSSIBLE.

KNOWLEDGEABLE EXPERTS CLAIM IT'S POSSIBLE OTHER APPARENTLY UNASSUMING PCs MAY ALSO HAVE TEK 4115s HIDING INSIDE. SUCH PCs WOULD HAVE EXTENDED ACCURACY COORDINATE MODES, AND SHOULD HANDLE 07/11/15 PIXEL FORMATS EXPECT TO FIND THESE PCs SOCIALIZING WITH ANVIL-4000™, PATRAN-G™, ANSYS™, DI-3000™, DISPLA™, PICTURE™, AND REACCS™.



For more information, call or write:

GRAFFPOINT

4340 Stevens Creek Blvd.
Suite 280 San Jose, CA 95129
(408) 249-7951

IBM ASCII terminals:

The case in black and white.

Introducing a somewhat more colorful member of the family.

Meet the IBM 3164 ASCII Color Display Station.

It gives you eight foreground and eight background colors. On a 14" screen.

And because of its 8 x 16 character matrix, the 3164 gives you clear, crisp characters in color.

But is color any reason to buy IBM's 3164? It is, according to studies that indicate the use of color increases productivity, decreases errors and promotes user satisfaction.

Color, of course, is far from the sole reason for choosing the 3164. To appreciate the others, you should get to know the rest of our ASCII family.

Emulation.

Another side of the family.

Our ASCII terminals are designed to fit into existing systems. Even if the systems aren't ours.

Emulation Capability	
3161	IBM 3101 Model 881 ADDS Viewpoint* Hazeltine 1500* Lear Siegler ADM-3A* Lear Siegler ADM-5* TeleVideo 910*
3163	IBM 3101 Model 881 DEC VT 52* DEC VT 100* TeleVideo 950*
3164	IBM 3101 Model 881

For example, our basic ASCII Display Station, the IBM 3161, emulates up to six

Features	3161	3163	3164
Screen size	12"	12"	14"
Lines x characters	25x80	25x80	25x80
Character matrix	8x16	8x16	8x16
Double-sized characters	No	Yes	Yes
Line drawing characters	24	24	24
Vertical scroll	Jump	Jump/ Smooth	Jump/ Smooth
Definable function keys	24	24	24
Windowing	No	Yes	Yes
Partitioning	Horiz.	Vert./ Horiz.	Vert./ Horiz.
Characters in buffer	1920	7680	7680

terminals. And the advanced-function 3163 emulates a number of higher level ASCII data streams.

What's more, every one of our ASCII terminals can operate in its own function-rich native mode.

Our family is flexible.

Our unique plug-in cartridges allow for considerable flexibility in your operation. For example, simply by switching cartridges you can shift a terminal from one data stream to another.

And, in many countries cartridges are also available that go beyond emulation to let you operate your ASCII terminals in several foreign languages. Appropriate foreign language keyboards are also offered.

Enhanced ergonomics. Another family trait.

All our ASCII terminal keyboards have 102 keys. But that's not all they have in common. Every keyboard also has a low profile, gentle contour and typewriter touch.

And our keyboards have

programmable function and editing keys so they can be custom-tailored to fit your application needs. The 3163 and 3164 models also have redefinable and recappable keys.

Superior ergonomic design isn't confined to the key-

board, however. All three displays tilt and swivel for maximum user satisfaction. And, of course, by making the display easy to read, we made it easier on the eyes. In addition to the 8 x 16 character matrix, we gave it an advanced non-glare etched screen, cursors, and character and field attributes like blink, reverse video, under-scoring and dual intensity.

High standards.

Competitive prices.

Quantity discounts are offered, too. And financing is available through the IBM Credit Corporation. Best of all, each terminal comes with the quality, service and support you'd expect from IBM.

Contact your IBM marketing representative, or call 1 800 IBM-2468, Ext. KC/96, for the IBM Authorized Distributor nearest you. And we'll present more evidence in the case for IBM's ASCII terminals.

It may be all you need to color your view.

*ADDS Viewpoint is a trademark of Applied Digital Data Systems, Inc.; Hazeltine 1500 is a trademark of Hazeltine Corp.; Lear Siegler ADM-3A/ADM-5 are trademarks of Lear Siegler, Inc.; TeleVideo 910/950 are trademarks of TeleVideo Systems, Inc.; DEC VT 52/VT 100 are trademarks of Digital Equipment Corporation.

The case in color.



3164 TERMINAL

- Smooth Scrolling
- Double Width & Height Characters
- Definable Function Keys
- Paging
- Most Loadable Characters (up to 94)
- Character and Field Attributes
- 1920 (80 X 24) Character Display
- Attachment to IBM/non-IBM Systems
- CRT Saver
- Emulation
- Line Drawing Characters
- Wide Range of Communication Speeds (50 BPS through 19200 BPS)
- Selectable Interface (EIA RS-232C or RS-422A)
- Longitudinal Redundancy Checking
- Displays up to Eight Colors

3164 DISPLAY

- Tilt/Swivel
- Direct Etched/Anti-Glare
- Adjustable Brightness
- 1920 (80 X 24) Characters
- Reverse Video, Blinking, Underline, Non-Display

3164 KEYBOARD

- Low Profile
- Tactile Feedback
- 12 PF Keys
- Re-Definable Keyboard
- Numeric Keypad
- 3 PA Keys



CIRCLE NO. 72 ON INQUIRY CARD

Introducing the 9-bit word.

Chaparral™ The latest word in complete 32-bit VME systems.

For applications that demand the high performance, reliability and multi-user features that only a VME system can deliver, now the word is out. It's *Chaparral*. Chaparral is Dual's new family of modular VME systems. Based on our proprietary line of VMEbus modules, Chaparral systems offer a range of 32-bit solutions for low- to high-end applications. Each Chaparral system is built around our multi-processor engine, the VMPU-32, using Motorola's advanced MC68020, which runs at a blazing 16 MHz. Optimized for virtual memory UNIX environments, the VMPU-32 offers extensive inter-processor communication capabilities, a full megabyte of dual-ported local memory, and up to 32 Kbytes of EPROM. Chaparral systems also include separate I/O processors and universal system controllers, with their own 10-MHz MC68000s. Packaging options include desktop, pedestal or rack mounting.



For multi-user flexibility, Chaparral is the final word. By adding VMPU-32 modules, for example, you can run up to four different operating systems concurrently. For I/O-intensive applications, each I/O processor can handle up to 32 terminals or other devices.

And when you need large amounts of mass storage, Chaparral's full 32-bit address space lets you access up to 4 Gigabytes of memory. Systems can also be linked to local or wide area networks via communication lines. Chaparral comes complete

with all the software and support you need to get to market fast. Our

implementation of UNIX System V, Release 2.0, Version 2 is available, along with a full

complement of languages: C, Pascal, FORTRAN, COBOL, BASIC and Lisp. Plus application support and a nationwide service network that protects your system. And your investment.

For full details, write Dual Systems Corporation, 2530 San Pablo Avenue, Berkeley, CA 94702. (415) 549-3854. Telex 230199 SWIFT.

**DUAL
CHAPARRAL**

CIRCLE NO. 73 ON INQUIRY CARD

See us at BUSCON Booth 324-326

CHIP SET PAVES THE WAY TO TOKEN-RING ACCESS

A chip set is essential for system integrators who want to build their own custom LAN adapter cards to achieve system-to-system dialogue


James T. Carlo and **Gerald R. Samsen**
Texas Instruments Inc.

After years of operating in their own domains, most computer systems can now communicate with other systems through local area networks. Through the efforts of computer manufacturers, network equipment suppliers, software developers, semiconductor manufacturers and standards organizations, previously self-contained computer hardware now communicates with other systems over LANs that allow them to speak a common language.

Among the protocols making such networks possible are IBM Corp.'s Advanced Program-to-Program Communications (APPC), the industry-sponsored Manufacturing Automation Protocol (MAP) and Technical Office Protocol (TOP). Such protocols enable equipment for offices, factories and other organizations to communicate with their peers.

However, a single communications standard will not dominate in all applications. Although many architectures are based on the International Standards Organization's Open Systems Interconnection (OSI) model, each architecture works best in its target application. For example, the General Motors Corp. MAP, based on the IEEE 802.4 token-bus connection protocol, suits factory applications, while the IBM Corp. Token-Ring Network is likely to emerge as an industry standard for interdepartmental and companywide office network applications.

IBM offers third-party developers access to the Token-Ring's protocol and software interface specifications by maintaining an "open" architecture. Toward that end, IBM incorpo-




rated the bottom two layers of the seven-layer OSI model into the Token-Ring LAN. These two layers, defined by the IEEE 802.5 committee, are the Physical and Data Link layers. In addition, in 1982 IBM began a joint-development program with Texas Instruments Inc. to develop a chip set that would provide compatible connection to the Token-Ring LAN.

The outcome, the Texas Instruments TMS380 chip set, provides rigorously verified and validated compatible protocols through the Medium Access Control sublayer of OSI's Data Link Layer. The chip set allows system integrators to build their own adapter cards for products, such as personal computers and printers, that can benefit from LAN attachment. System integrators who want to take advantage of this chip set face a twofold decision. First, they must decide which higher layer communications protocols to implement. Second, they

The TI TMS380 adapter chip set provides IEEE 802.5-compatible services to the IBM token-ring LAN. These services extend through the Medium Access Control sublayer of the OSI Data Link Layer.

IMPLEMENTING OSI: WHO SUPPLIES WHAT?



SOURCE: TEXAS INSTRUMENTS INC.

Because the TMS380 chip set functions at the two lower layers of the OSI model, it does not affect existing communications or application software at higher layers. System integrators can port most higher layers over a TMS380-based adapter card.


must choose an overall architecture for their network adapter card and select other hardware features that will add value in a particular market.

For example, a network integrator may offer a system based on the Token-Ring LAN and the Xerox Network System (XNS) protocol, originally developed for an Ethernet LAN. The XNS-based system might include Xerox Corp. hardware, such as laser printers and workstations, and application software. System integrators must protect their own and their customers' investments while providing a smooth migration path to the IBM Token-Ring LAN. They must also continue to offer IBM compatibility as the Token-Ring LAN begins to reach the huge installed base of IBM equipment.

Network integrators can accomplish the hardware aspect of this task by using an adapter card that incorporates the TMS380 chip set, thereby implementing the Physical and Medium Access Control layers. Integrators can also preserve the higher layers of the XNS protocols by incorporating a software interface routine between the lower layers of XNS and the Medium Access Control level of the adapter card. Thus, XNS-based applications will be run on the Token-Ring LAN. This approach could leverage the vendor into a specific market whose software base has adopted the Token-Ring Network.

The TMS380 architecture integrates the functions of a LAN adapter into a five-chip set—the TMS38030 system interface, the TMS38010 communications processor, the TMS38020 protocol handler and the TMS38051 and TMS38052 ring-interface pair. The chip set is the heart of a printed circuit card that allows many products to attach to the Token-Ring LAN. Implementing the chip set

ADAPTER CARD SPEEDS DATA TRANSFER



SOURCE: TEXAS INSTRUMENTS INC.

DMA-based data transfers from a TMS380 adapter card to a host system are consistently faster than those performed under host-CPU control.

on an adapter card allows various communications protocols to be ported on top of the Medium Access Control and Physical layers. This leaves the choice of higher layer protocols up to system integrators, who base their selections on such factors as time to market, communications compatibility and installed base.

Choose the protocols

In most cases, system integrators implementing the TMS380 chip set must offer interface-emulator routines, called adapter handlers, which provide an interface between the lower layers of the selected protocol stack and the adapter. The adapter handler makes the token-ring adapter appear to the higher level protocol as the Data Link Layer of Ethernet or some other protocol. This routine provides compatible connection to the Token-Ring and preserves customers' previous investments in off-the-shelf communications and application software. This software uses such protocols as XNS, the Department of Defense's Transmission Control Protocol/Internet Protocol (TCP/IP) and many proprietary protocols implemented in such networks as Datapoint Corp.'s ARCnet and Corvus Systems Inc.'s Omninet.

For personal computer environments, IBM promotes its Network Basic Input/Output System (NETBIOS) and APPC, the application interface for communications within IBM's Systems Network Architecture (SNA). NETBIOS and APPC use the IEEE 802.2 Logical Link Control (LLC) sublayer of the OSI model.

INTRODUCING THE ITT XTRA™ XL. THE POWERFUL NEW BUSINESS SYSTEM.

ITT has taken a giant step in the evolution of system technology.

The new Multi-User ITT XTRA™ XL provides performance, storage and memory unlike any of its competitors.

Ultimate performance.

The ITT XTRA XL is a high performance super micro-computer that runs both DOS and Xenix and expands to meet virtually every business need.

ITT has combined superior components that break the boundaries for processing speed. The ITT XTRA XL line of multi-user systems not only offer users of standalone workstations a powerful server engine for local area networking, but also provides a cost effective solution to a sophisticated shared logic environment.

CPU speeds unsurpassed by industry standards.

The ITT XTRA XL's unsurpassed capabilities are assured by a design that includes the 80286 microprocessor operating at 8Mhz, with zero-wait state memory, dynamic I/O disk caching, and hard disk with an average access time of 28 milliseconds.

ITT's MS DOS 3.1 includes support for disk drives larger than 32 MB without the requirement to partition, unlike other implementations.

Ideal LAN servers.


The ITT XTRA XL Model I (Formatted 40 MB) and Model II (Formatted 72 MB) feature:

- Mass storage capacity up to 144 MB to dramatically extend the typical 80286 LAN server platform.
- Nine industry compatible expansion slots (six 16-bit and three 8-bit).
- 225-watt international power supply with variable speed fan.
- Two serial ports and one parallel port built-in.

Better multi-user performance

ITT's new XTRA XL Models III (40 MB) and IV (72 MB) systems feature:

- XENIX Operating System V.2.



- Unique 8Mhz 80186-based communications coprocessor for dramatic throughput speed.
- Support for up to 32 communication ports.
- License for up to 16 users.
- 60 MB tape backup.

LAN Engines Models I* and II**

640 KB RAM
1.2 MB FD
Keyboard
40 MB HD* or
72 MB HD**

Multi-User Systems Models III* and IV**

1.6 MB RAM
1.2 MB FD
Keyboard
60 MB Tape
Communications
Co-Processor
(8 ports)
XENIX System V.2
40 MB HD* or
72 MB HD**

Entire product line solution.

In addition, ITT addresses entry-level as well as single power-user requirements with the ITT XTRA™ and XTRA™ XP.

The entry-level ITT XTRA is an aggressively-priced standalone system, engineered for ongoing reliability.

While the ITT XTRA XP uses the IBM PC AT as a foundation to provide an even better solution. The result is a system as fast as the IBM PC AT at prices comparable to the IBM PC XT.

Combined with the new ITT XTRA XL it's an entire family of tireless business performers ready for any application, big or small.

Superior support and proven strength.

Over 65 years of telecommunications and technologies credentials back up every ITT product. Which is why we're able to offer computers that deliver unparalleled performance for such competitive prices.

Call ITT today. (800) 321-7661.
In California, (800) 368-7300.

ITT
BUSINESS COMPUTERS

BECAUSE TIME IS THE ULTIMATE BOTTOM LINE.

© 1986, ITT Information Systems
IBM, PC and PC XT are registered trademarks of International Business Machines, Inc. Intel 80286 and 80186 are registered trademarks of Intel Corporation. XENIX and MS DOS are registered trademarks of Microsoft Corp.

CIRCLE NO. 74 ON INQUIRY CARD

We've done 25 years of hard labor.

And it's still not the end of the line.



The Genicom 4000 line printer series has paid its dues. As a matter of fact, in a reliability test, its shuttle mechanism worked 24 hours a day, for over three years without failure. That's the equivalent of 25 years of normal use.

What's our secret? A totally new, patented resonance shuttle mechanism. It's perfectly balanced, so vibration is eliminated. And because the Genicom 4000s are free from those moving parts that normally fail in other printers, this could be the most reliable series of line printers ever built.

Printing At Line Speed.

The Genicom 4000 series was designed to tackle your most punishing printing applications in the blink of an eye.

Blaze through data processing at up to 800 lpm. Or shift into letter quality printing at 165 lpm. The Genicom 4000s even print difficult line and block graphics and bar codes at blistering speeds.

Solitary Confinement.

You can see a Genicom 4000 series printer at work. But at 60 dBA (55 dBA optional), you'll barely ever hear it. Because Genicom uses an innovative,

self-contained sound reduction system that eliminates the need for expensive and bulky external enclosures.

And to ensure that this printer remains a productive member of society, each Genicom 4000 is equipped with a standard serial interface, a 20 inch/second paper slew, multiple character sets and a long-life, self-inking ribbon cartridge.

So, if you're looking for a rugged line printer that works with conviction, call Genicom today at 1-800-437-7468. In Virginia, call 1-703-949-1170. And set a 4000 free.

GENICOM

The Printers That Mean Business.

One Genicom Drive, Waynesboro, VA 22980

CIRCLE NO. 75 ON INQUIRY CARD

Thus, integrators wanting to implement NET-BIOS and APPC must embed 802.2 link-station functions to LLC in their interface-emulator software.

The 802.2 LLC draft standard and its addenda define several classes of service, each of which incorporates a mix of LLC types. For example, APPC uses both Type 1 and Type 2 LLC, corresponding to unacknowledged connectionless, or datagram, services and acknowledged connection-oriented, or virtual-circuit, services. In addition to Type 1 service, MAP incorporates Type 3 service, which corresponds to acknowledged connectionless service, or datagram with acknowledge.


Make the buy-or-build decision

System integrators who build their own cards can distinguish their offerings from those of their competitors by providing cards that can accept special communications software and other value-added functions. But integrators who decide to build their own cards must face the drawbacks of time and cost that this approach entails. However, the TMS380 chip set facilitates LAN adapter-card design. In the most basic case, the integrator must provide only the "glue" necessary to interface the chip set to the backplane of a product.

Of the TMS380's five key components, the primary interface to the system integrators'

backplanes is the TMS38030 system interface. This device provides a 40M-bit-per-second direct-memory-access (DMA) channel to the attaching product. Two chips, collectively called the ring interface, are bipolar—the TMS38051 ring-interface transceiver and the TMS38052 ring-interface controller. These chips contain the digital and analog circuitry to connect the adapter chip set to a LAN through separate receive and transmit channels. The TMS38010 communications processor executes the adapter software within the TMS38020 protocol handler, which provides compatible logical connection to the Token-Ring Network through the IEEE 802.5 Medium Access Control protocol. The embedded communications processor includes diagnostics, which increase the reliability of the network adapters.


However, system integrators have other methods of adding value to hardware. If they select these options, they must first make several architectural decisions. For example, if they want to connect their products to a restricted backplane, they must choose which data-transfer technique to use instead of DMA. The IBM PC and most compatibles restrict expansion cards to bus-slave operation. Thus, the interface between the adapter chip set and the PC's backplane must accommodate this restriction. In this approach, the PC's processor handshakes with glue logic on the adapter card to



The TMS380 chip set comprises five integrated circuits: a communications processor for overall control, a handler for the IEEE 802.5 protocols, two interfaces to

connect to the IBM token-passing ring's twisted-pair wiring and an interface to provide a DMA channel to the attached system.

Let Telxon help you get the lead out of your integrated systems.



The better your integrated system, the greater the need for timely input.

Pencil and paper won't make it.

Telxon gives you the way to start data into your systems electronically.

Telxon Portable Tele-Transaction Computers (PTCs) mean accuracy as well as speed. They prompt. They edit. They transmit and receive machine-readable data — to and from micro, mini, or mainframe.

Consider the advantages. You can collect, process, store, transmit real-time data on the spot — where it originates — no matter how remote the location.

You'll like the way Telxon's Cobol-like

TCAL language handles your most challenging applications. Our documentation is complete, accurate, available.

Telxon's world leadership in handheld computers gives you the support and service you want — with 56 offices and a 24-hour hotline to back you up.

Do you know us?
Call 800-321-2424 (in Ohio 800-222-3330) or write Telxon, 3330 W. Market St., Akron, Ohio 44313-3352.




Call or write for free video tape, "Telxon Portable Tele-Transaction Computers... The Systems Solution." Specify 3/4", 1/2" VHS or Beta.

TELXON®

Think what we can help you do.

CIRCLE NO. 76 ON INQUIRY CARD

ADAPTER CARDS PROVIDE THREE ARCHITECTURAL OPTIONS



Architectural options for implementing Token-Ring adapter cards employ a basic adapter with the full TMS380 chip set (top), incorporate a satellite processor and migrate higher level protocols on-card (center), or expand the set's software with additional protocol software (bottom).

move data under program control. However, this is not usually a consideration with high-performance backplanes such as Multibus or VMEbus. With these backplanes, the TMS380 chip set uses a high-speed DMA interface to move data to and from the ring.

Three basic architectures

System integrators can best take advantage of the flexibility and efficiency of the TMS380's capabilities by providing the adapter card with bus-master capability to the backplane, which increases data-transfer speed. In many applications, such as with the PC, obtaining such high performance is not necessary to the end-to-end response time of the applications. However, some performance-critical applications necessitate the full TMS380 DMA capability.

System integrators must also decide whether to migrate some communications protocols to the adapter card. If they decide to do so, they must then decide where to draw the boundary between on-card and host system functions and whether to add a satellite processor to execute these added protocols, or to let the TMS38010 communications processor execute these functions. These decisions again involve time- and cost-to-market considerations, performance requirements and other trade-offs.

There are two basic architectural configurations for an adapter card. In the most basic

approach, the integrator can use a TMS380 chip set to construct a Medium Access Control level adapter card providing the complete IEEE 802.5 Medium Access Control protocols. The integrator need add no other software or specialized hardware to the adapter card. In this situation, the host system processor executes all higher level communications protocols.


Another option involves expanding the software functions of the TMS380 chip set itself to perform high-level protocols. One approach to this option would be to migrate the IEEE 802.2 LLC to the TMS380. In this case, the communications processor would provide compatible Medium Access Control and LLC functions.

The decision to include a satellite processor, rather than to expand the TMS380's software, is based primarily on risks involved in modifying the TMS380's validated Medium Access Control protocol software. Because IBM and TI tested and ratified the software to assure compatibility, integrators must revalidate the software to maintain compatibility whenever they change the software. However, cost/performance gains may outweigh any potential risks inherent in this approach. □

James T. Carlo is local area network system manager, and **Gerald R. Samsen** is LAN application manager at Texas Instruments Inc., Houston.

Interest Quotient (Circle One)
High 495 Medium 496 Low 497

Cash in on CAD/CAM at COMDEX/Fall.



This year, COMDEX/Fall features CAD/CAM to help CAD/CAM vendors and resellers turn this dynamic technology into a powerful profit tool.

For CAD/CAM vendors, CAD/CAM at COMDEX draws the tens of thousands of resellers you need to reach a global market. And for resellers, COMDEX connects you to the companies with the hardware, software, peripherals and service opportunities that can help you wring cash from CAD/CAM.

A special one-day CAD/CAM seminar on November 13 shows resellers how to wield the power of CAD/CAM to build new profit opportunities. Explore the technology, who uses it, how to sell it, and what it can return to you in this exclusive session.

Put CAD/CAM to work for you November 10-14, 1986. And set aside November 13 for the special CAD/CAM seminar. For more details, send in the coupon now!

I want to cash in on CAD/CAM!

- Send me complete exhibiting information.
- Send me complete registration information.
- I plan to attend the CAD/CAM seminar.

Name _____

Title _____

Company _____

Address _____

City _____ State _____ Zip _____

Telephone _____

Return to: David Thurman, COMDEX/Fall '86
300 First Avenue, Needham, MA 02194

COMDEX®/Fall '86

Join The Winner's Circle
November 10-14, 1986, Las Vegas, Nevada

MicroPDP-11/53

The Entry-Level 16-bit Q-bus Supermicrosystem

digital



The MicroPDP-11/53 is the entry-level, 16-bit supermicrosystem with an attractive price and performance combination that will meet the best of your computing requirements. The MicroPDP-11/53, with approximately twice the system performance of the MicroPDP-11/23, offers just the extra boost of power you may need to solve your realtime or multitasking problems.

At the center of the MicroPDP-11/53 is a 15-megahertz, J-11 single-board computer that contains 0.5 Mbytes of onboard memory. This computing engine can easily devote itself to your dedicated process control program or become a shared resource for your department's multiuser workload. Whatever the job, the MicroPDP-11/53 demonstrates superlative performance.

As is the standard with all PDP-11 systems, the MicroPDP-11/53 is fully compatible with the proven 16-bit PDP-11 architecture and the thousands of PDP-11 software tools and applications in existence today. Along with this compatibility is support for a wide variety of Q22-bus mass-storage devices and communications interfaces, including two new half-height disk drives. Its trim size is small enough to fit comfortably and quietly into your personal work area. And with DECnet and Ethernet networking capability, the MicroPDP-11/53 can send, share, and store files from other systems in your department or organization.

With improved performance at an appealing price, the MicroPDP-11/53 enhances 16-bit computing to help you meet your business goals. And better yet, Digital has it now.

*Literature
Distribution*

*For additional copies of this
information, shut write:
PDP-11 ED-28903-41,
200 Baker Avenue, Concord,
Massachusetts 01742.*

*Current PDP-11 users: If you
would like to be added to
our PDP-11 mailing list
please indicate the CPUs
you are currently using
on the back of your business
card and send it to the
above address.*



Highlights

- Features a high-performance, single-board computer with 0.5 Mbytes of onboard memory.
- Allows for memory expansion for up to 4 Mbytes with parity MOS memory in increments of 0.5, 1, or 2 Mbytes.
- Has complete MicroPDP-11/73 instruction set, including the Extended Instruction Set (EIS) for compatibility with the full line of MicroPDP-11 processors.
- Includes floating-point instructions for increased instruction execution.
- Supports a comprehensive set of communications interfaces and mass-storage devices, including two new half-height disk drives.
- Supported by an extensive number of operating systems, high-level languages, development tools, and application packages.
- Easily integrates into networking environments or into local area networks with DECnet and Ethernet.

The Single-board Computer – A First for MicroPDP-11 Systems

The MicroPDP-11/53 is based on the high-speed, 15-megahertz J-11 chip set. Accompanying this micro-processor on the same quad-height module is 0.5 Mbyte of dynamic RAM, parity MOS memory. This economical combination of CPU and onboard memory saves on module space and input power and, more importantly, increases the basic system performance to approximately twice that of the MicroPDP-11/23. The MicroPDP-11/53 single-board computer comprises:

- A J-11 chipset, including 16-bit I/O, addressing capability up to 4 Mbytes, maximum clock rate of 15 megahertz, and onboard memory management.
- Complete MicroPDP-11/73 instruction set, including floating-point instructions and the Extended Instruction Set (EIS).
- Q22-bus interface that supports block-mode DMA and up to 4 Mbytes of physical memory.
- One console serial-line unit and one printer serial-line unit.
- 32-Kbyte, erasable read-only memory (ROM) for bootstraps and diagnostics.

Half-height Storage Can Increase Your Storage Capacity

The Q-bus links the MicroPDP-11/53 with a compatible set of mass-storage devices. Two new half-height disk drives, the RD31 and the RX33, are available for the first time on a super-microsystem. At half the height of their predecessors, their size allows more storage devices to be housed directly in the system chassis. There is now room for three integrated mass-

storage devices, as opposed to two full-height devices.

Offered as integrated storage devices, the RD31 is a 20-Mbyte Winchester fixed-disk subsystem, and the RX33 is a 1.2-Mbyte single-diskette subsystem. And the following full-height storage devices can be added externally to your MicroPDP-11/53:

- 71-Mbyte RD53 Winchester fixed-disk subsystem.
- 31-Mbyte RD52 Winchester fixed-disk subsystem.
- 95-Mbyte TK50 cartridge-tape subsystem.

The Q-bus also has a wealth of peripherals developed for it by Digital. You can select from a wide range of communications interfaces, videodisplay terminals, hardcopy terminals, and system printers.

Flexible Packaging for Your Style of Working

The MicroPDP-11/53 is packaged in a trim, versatile enclosure that can fit underneath, beside, or on top of your desk. It is also available in a rack-mount model for cabinet integration. This package features an eight-slot backplane and space for three half-height storage devices or for two full-height storage devices. Ample space exists for memory and communications options and room for connecting as many as 26 I/O devices.

Software That Is Proven and Available

The MicroPDP-11/53 runs Digital's leadership 16-bit operating systems.


These are proven operating systems that efficiently and effectively meet a variety of demands—from small, dedicated laboratory and industrial control systems to larger, multiuser information management systems.

Micro/RXS and Micro/RSTS are tailored specifically for the MicroPDP-11 family. Micro/RXS is a low-cost version of Digital's larger RSX-11M-PLUS. It combines the multiuser, realtime capability of RSX with refined commercial capabilities. And Micro/RSTS is a subset of the RSTS/E system that is a multiuser, timesharing system environment.

Also available is RT-11, a single-user, realtime system; RSX-11M-PLUS, RSX-11M, and RSX-11S, three multiuser, realtime systems; RSTS/E, a multiuser, timesharing system; CTS-300, for small business timesharing; ULTRIX-11, Digital's enhanced native-mode UNIX* software; MicroPower/Pascal, an advanced development tool kit; and DSM-11, a multiuser operating system with high-performance, data management capability.

Digital's own layered software includes a wide variety of high-level languages and data management tools. Supported high-level languages include BASIC, C, COBOL, DIBOL-83, FORTRAN-77, FORTRAN IV, MUMPS,* and Pascal. Data management tools include DATATRIEVE-11, a query report-writing and data-maintenance system; RMS-11, a record management system; and FMS-11, a forms management system.

And thousands of application software products already exist for the MicroPDP-11/53 in virtually every



area of science, education, government, business, and industry. These products have been developed both by Digital and third-party software developers. Ask your sales representative for a copy of the *PDP-11 Software Source Book*, a guide to the more than 2,000 applications packages that are available today.

Tie Together Your System, Department, and Organization

A wide variety of communications hardware and software is available to make the MicroPDP-11/53 supermicrosystem interface with the widest possible range of communications and networking applications. Digital's powerful DECnet software supports communications between Digital systems, and between Digital systems and other manufacturers' systems. The MicroPDP-11/53 is also supported

by Ethernet local area networking. Ethernet allows large amounts of data to be exchanged at high rates among various departments of an organization, within one building or within a complex of buildings.

Digital's Commitment To Service

Like all of Digital's products, the MicroPDP-11/53 and its system software have been designed for reliability. And Digital's customer services organization is ready to provide quality support. Digital is the complete service vendor and has the products and tools to back its commitment to customer satisfaction.

If You Would Like To Know More

Find out just what the MicroPDP-11/53 can do for you. Call your local Digital sales office, Digital OEM, or Authorized Digital Distributor for an in-depth discussion of the MicroPDP-11/53 solution.



Specifications

Power Requirements

Line voltage	120 Vac	240 Vac
System power	4.4 amperes	2.2 amperes
Power source phasing	Single	Single
Voltage tolerance	90-128 VRMS	176-256 VRMS
Line frequency tolerance	47-63 Hz	47-63 Hz
Input power	345 watts	345 watts

Operating Environment

Temperature range	15-32°C (59-90°F)
Relative humidity	20-80% noncondensing
Maximum operating altitude	2.4 km (8,000 ft)

Physical Characteristics

Pedestal Model	
Height	62.2 cm (24.5 in)
Width	25.4 cm (10.0 in)
Depth	72.4 cm (28.5 in)
Weight	32 kg (70 lb)
Tabletop Model	
Height	15.2 cm (6.0 in)
Width	56.5 cm (22.25 in)
Depth	72.4 cm (28.5 in)
Weight	32 kg (70 lb)
Rackmount Model	
Height	13.3 cm (5.25 in)
Width	48.3 cm (19.0 in)
Depth	64.8 cm (25.5 in)
Weight	25 kg (55 lb)

Digital believes the information in this publication is accurate as of its publication date; such information is subject to change without notice. Digital is not responsible for any inadvertent errors.

The following are trademarks of Digital Equipment Corporation: CTS-300, DATATRIEVE-11, DEC, DECnet, DIBOL-83, the Digital logo, FMS-11, J-11, MicroPDP-11, MicroPower/Pascal, Q-bus, PDP-11, RMS-11, RSTS/E, RSX, RSX-11M, RSX-11M-PLUS, RSX-11S, RT-11, and ULTRIX-11.

*Third-party trademarks: UNIX is a registered trademark of AT&T Bell Laboratories; MUMPS is a registered trademark of Massachusetts General Hospital.



DATA FLEX®

***A Breakthrough
in
DBMS/4GL
Price and
Performance
for
VAX/VMS***



DATA FLEX

DataFlex is a high performance applications development database system with a rich 4th generation command language and automatic code generators. DataFlex's on-line multi-user transaction processing and powerful multi-file Query give

you the information you need when you need it. Plus, applications can be transported to and from VAX, UNIX V, XENIX and PC systems without change. Pricing for VAX systems starts at \$1,800. Call today for complete details.

DATA ACCESS CORPORATION
8525 S.W. 129th Terrace, Miami, FL 33156-6565 (305) 238-0012 Telex 469021 DATA ACCESS CI

VAX and VMS are trademarks of Digital Equipment Corporation. UNIX V is a trademark of AT&T.
XENIX is a trademark of Microsoft. DataFlex is a Registered Trademark of Data Access Corporation.
CIRCLE NO. 78 ON INQUIRY CARD

DISCOVER THE DIGITIZING POWER OF TRUE GRID™



Discover the ultimate combination of high performance and exceptional value with Houston Instrument's TRUE GRID Digitizers.

A versatile collection of powerful, productive graphics input tools, these intelligent digitizers are specially designed to meet the needs of system designers. Whatever the size or complexity of your graphics system, Houston Instrument has a TRUE GRID Digitizer that is the perfect fit.

If you want a compact digitizer for menu picking or cursor control, we offer our TRUE GRID 1000 Series tablets with active areas ranging in size from 5 × 5 inches to 11 × 17 inches. These tablets feature a resolution of .005 inches, a

built-in RS-232-C compatible interface, and a choice of a stylus, one-button cursor, or four-button cursor.

For mechanical, electrical, mapping, architectural, and surveying applications, we've designed the TRUE GRID 8000 Series digitizers with active areas ranging in size from 11 × 11 inches to 24 × 36 inches. Featuring a high resolution of .001 inches and built-in RS-232-C compatible interface, these precision digitizers can be used with either of our new three-button or 16-button cursors.

Each TRUE GRID Digitizer is easily configured, durable, and backed by a one-year warranty plan.

Discover the digitizing power, versatility, and affordability of TRUE

GRID. Call Houston Instrument at 1-800-531-5205 (512-835-0900 if in Texas), or write Houston Instrument, 8500 Cameron Road, Austin, Texas 78753. In Europe, contact Houston Instrument, Belgium NV., Rochesterlaan 6, 8240 Gistel, Belgium. Tel.: 32-(0)59-277445. Tlx.: 846-81399.

TRUE GRID is a trademark of Houston Instrument.

houston instrument

A Division of AMETEK

CIRCLE NO. 79 ON INQUIRY CARD


NEW PRODUCTS

SYSTEMS

Computer furnishes 640K-byte memory

- IBM compatible
- 10M-byte disk drive
- Eight slots

Offering IBM PC/XT compatibility, the Long Island PC/XT employs 640K bytes of main memory and a 360K-byte



flexible disk drive. The system includes eight expansion slots and a 10M-byte rigid disk drive expandable to 120M bytes. Serial and parallel ports are standard. The computer operates with all IBM-compatible software. \$1,495. **Bi-Tech Enterprises Inc.**, 10 Carlough Road, Bohemia, N.Y. 11716-2996, (516) 567-8155.

Circle 379

Personal computer runs faster than IBM PC

- 360K-byte disk drive
- 8086-1 processor
- Video controller

Running four times faster than the IBM PC and 1.6 times faster than the IBM PC/AT, the Series 30 personal computer utilizes an 8086-1 microprocessor. The unit contains a 360K-

byte flexible disk drive and a monochrome video controller. It is geared toward OEMs and VARs. RAM is 512K bytes, expandable to 640K bytes. \$1,456, quantity 50. **Datavue Technical Systems**, 4355 International Blvd., P.O. Box 2687, Norcross, Ga. 30093, (404) 564-5780.

Circle 380

Multiuser system targets businesses

- 68000 processor
- 256K bytes of memory
- Six I/O ports

Targeting small businesses, the Zebra 1350 multiuser computer employs an MC68000-based CPU with zero wait states. The system supplies 256K bytes of memory, 20M bytes of disk storage, six serial I/O ports and one parallel printer port. It runs under the Pick operating system. Options include a proprietary LAN controller and synchronous communications. The unit can be configured with 512K bytes of memory. \$9,300. **General Automation**, 1045 South St., P.O. Box 4883, Anaheim, Calif. 92803, (714) 778-4800.


Circle 381

System aims at OEMs

- 80286 processor
- 1M-byte RAM
- 128K-byte ROM

Targeting OEMs, the TCS-7000 is an IBM PC/AT-compatible computer. The system utilizes an 80286 processor and operates under MS-DOS 3.0 and higher. It provides 640K bytes of RAM expandable to 1M byte and 64K bytes of ROM expandable to 128K bytes. Features include a 24-bit and a 16-bit address bus. The unit supports a 2M-byte RAM card, a serial/parallel card and color graphics cards. \$2,595. **Tatung Company of America Inc.**, Computer Products Division, 2850 El Presidio St., Long Beach, Calif. 90810, (213) 637-2105.

Circle 382



Portable displays 80 by 25 characters

- 3½-inch drive
- 640K-byte RAM
- 10M-byte disk drive

A portable personal computer, the T3100 weighs 15 pounds. The IBM-compatible unit uses an 80286 processor running at 8 MHz. It offers 640K bytes of RAM, a 720K-byte, 3½-inch flexible disk drive and a 10M-byte rigid disk drive. The screen displays 80 by 25 characters with a 640-by-400 pixel resolution. Interfaces are supplied for an RGB color monitor, a parallel printer and an external disk drive. \$4,499. **Toshiba America Inc.**, Information Systems Division, 2441 Michelle Drive, Tustin, Calif. 92680, (714) 730-5000.

Circle 383

Computer suits IBM PC/AT

- 80286 processor
- 512K bytes of RAM
- Three configurations

The A*Star PC/AT is an IBM PC/AT-compatible microcomputer available in three configurations. Model 100 includes 512K bytes of RAM, a 1.2M-byte flexible disk drive, eight expansion slots and an 80286 microprocessor. Model 200 offers a 20M-byte rigid disk

NEW PRODUCTS SYSTEMS

drive and a serial/parallel adapter; model 300 supplies a 30M-byte rigid disk drive. \$1,495 to \$2,495. **Wells American Corp.**, 3243 Sunset Blvd., West Columbia, S.C. 29169, (803) 796-7800.

Circle 384



Computer achieves IBM PC compatibility

- 8088-2 processor
- 640K bytes of memory
- Two RS232C ports


An IBM PC-compatible computer, the XT/MARK 2 features a dual-speed 8088-2 microprocessor that runs at 4.77 MHz or 8 MHz. The system includes 640K bytes of memory, two half-height flexible disk drives, two RS232C ports and a parallel printer port. An MS-DOS operating system and utility software are standard. Features include five expansion slots and a built-in tape backup controller. \$1,495. **Magnum Computer Inc.**, 12090 S.W. Garden Place, Portland, Ore. 97223, (503) 684-8000.

Circle 385

Scanning system provides OCR

- 300-dpi resolution
- IBM PC interface
- Proprietary software

JetReader is a scanning system that provides optical character recognition and image processing capabilities. Scan times are 43 seconds at 300 dpi and 289 seconds at 200 dpi. The unit provides



automatic paper feed, an IBM PC interface and proprietary software. Full-page conversions take less than a minute for translation and scanning. \$2,950. **Datacopy**, 1215 Terra Bella Ave., Mountain View, Calif. 94043, (415) 965-7900.

Circle 386



Minicomputer supports up to 40 workstations

- 4M bytes of memory
- 16 ports
- 360K-byte disk drive


The VS65T minicomputer supports up to 40 workstations with as much as 4M bytes of main memory, a 360K-byte flexible disk drive, 16 ports and a 16K-byte cache memory. A 32-bit microprocessor achieves a 200-nsec instruction time. The unit accommodates six intelligent I/O processors and a variety of emulation products and interface options. \$25,000 and higher. **Wang Laboratories Inc.**, 1 Industrial Ave., Lowell, Mass. 01851, (617) 459-5000.

Circle 387

Computers aim at business use

- Three models
- 32 users
- 15M bytes of RAM

Geared toward business applications, the 3235, 3255 and 3280 are additions to the System 3200 series. All computers utilize a 68000 or 68020 micro-



processor. Model 3235 supports up to 32 users. It supplies 20 RS232C ports, 500M bytes of rigid disk storage and 256K bytes of memory expandable to 10M bytes. Model 3255 supplies 15M bytes of RAM and a built-in magnetic tape drive and supports up to 64 workstations as does the model 3280, which offers eight 330M-byte Winchester disk drives. \$24,000 and higher. **Pertec Computer Co.**, 17032 Armstrong Ave., Irvine, Calif. 92714, (714) 863-7580.


Circle 388

Computer suits IBM PC/XT

- 8088-2 processor
- 256K bytes of RAM
- Eight expansion slots

Operating at 4.77 MHz or 8 MHz, the PC-88 Turbo High-Speed Personal Computer is compatible with the IBM PC/XT. The unit supplies an 8088-2 microprocessor and an MS-DOS 2.11 operating system. Standard RAM is 256K bytes, expandable to 640K bytes. Features include a 5¼-inch, half-height, flexible disk drive; eight expansion slots; a serial printer port; and a parallel printer port. The computer runs GW BASIC, COBOL, FORTRAN, Pascal and all IBM software. \$1,275. **Intelligent Data Systems Inc.**, 14932 Gwenchris Court, Paramount, Calif. 90723, (213) 633-5504.

Circle 389



Tape drive runs at 72 ips


- 10,000 bpi
- 125M-byte capacity
- 90K bytes per second

A half-height, quarter-inch cartridge tape drive, the model 5125E operates at 72 ips with a data-transfer rate of 90K bytes per second. The device is compatible with the QIC-120 format. It records data on 15 tracks at a density of 10,000 bpi for a formatted capacity of 125M bytes. A QIC-36 interface is included. The unit aims at OEMs. \$555. **Wangtek**, 41 W. Moreland Road, Simi Valley, Calif. 93065, (805) 583-5255.

Circle 390

and QIC-24 data formats. Features include 15-track recording, single-axis head positioning and write precompensation. \$775, QIC-02; \$995, SCSI. **North Atlantic Industries Inc.**, 60 Plant Ave., Hauppauge, N.Y. 11788, (516) 582-6060.

Circle 392



Disk drive stores 20M bytes

- 5M bps transfers
- 80-msec access time
- 3½ inches

Offering a 20M-byte capacity, the

FileCard20 is an internal rigid disk slot card. The 3½-inch device furnishes a 5M-bps transfer rate and an 80-msec access time. Features include plated media, head-lock and IBM PC/XT compatibility. The unit can be operated as a bootable drive C or as a second rigid disk using MS-DOS 2.0 or higher. MTBF is 10,000 hours. \$895. **Western Digital Corp.**, Enhanced Peripherals Division, 2445 McCabe Way, Irvine, Calif. 92714, (714) 863-0102.

Circle 393

Optical disk suits IBM PC and compatibles

- 230M-byte capacity
- 2.5M-bps transfer rate
- 1-msec access time

A WORM optical disk system, N/Hance 525 suits the IBM PC and compatibles. The system supplies 230M bytes of formatted storage capacity, an optical disk, a 5¼-inch removable disk cartridge, an IBM PC short-board con-

Disk drive mounts on card

- 75-msec access time
- 5M bytes per second
- 21M bytes

A rigid disk drive mounted on a card, the 21M-byte SlotMachine fits into a single slot on the IBM PC, PC/XT, PC/AT and compatibles. It provides a 5M-byte-per-second transfer rate, a 75-msec access time and a built-in disk-testing microprocessor. The subsystem supports a second rigid disk drive. \$499. **Kammerman Labs**, 7861 S.W. Cirrus Drive, Beaverton, Ore. 97005, (800) 522-2237.

Circle 391


Tape drive stores 125M bytes

- Two interfaces
- 15-track recording
- 5¼-inch unit


The RoadRunner II is a 5¼-inch, half-height streaming tape drive. Available with a QIC-02 or a SCSI interface, the unit achieves a 125M-byte storage capacity. It reads and writes QIC-120


The Right Look

Aren't you worried about giving a presentation with a portable computer?



Not anymore. This is Datavue. Its screen display is sharp and bright enough to read from the other end of the conference table





DATAVUE™

The powerful, affordable portable.

For more information on the portable with the bright display, call your computer dealer or 404-564-5668.

CIRCLE NO. 81 ON INQUIRY CARD


troller and device-driver software. It generates a data-transfer rate of 2.5M bps and an average track-to-track access time of 1 msec. The unit can be used internally or externally. \$3,495. **N/Hance Systems**, 908R Providence Highway, Dedham, Mass. 02026, (617) 461-1970.

Circle 394

Tape controller links SCSI to QIC-120

- 1.8M-byte data rate
- GCR techniques
- Selectable formats

The T100 streaming tape controller links SCSI to QIC-36 and QIC-120. It features a 1.8M-byte asynchronous data rate, SCSI disconnect/reconnect and QIC-11 or QIC-24 selectable media formats. A SCSI copy command allows the device to read or write from other SCSI devices without host intervention. Data integrity is maintained through use of




GRC techniques. Full parity is standard. \$395. **Adaptive Data Systems Inc.**, 2627 Pomona Blvd., Pomona, Calif. 91768, (714) 594-5858.

Circle 395

Disk drives achieve 382M-byte capacity

- 5¼ inches
- 18-msec access time
- SCSI controller

Offering unformatted capacities of 382M bytes and an average access time




of 18 msec, models 1558 and 1578 are 5¼-inch Winchester disk drives. The 1558 provides ESDI, hard or soft sectoring and a 10M-bps transfer rate. Model 1578 supplies an on-board SCSI controller and a 1.25M-byte-per-second transfer rate. MTBF is 30,000 hours. \$1,900. **Micropolis Corp.**, 21123 Nordhoff St., Chatsworth, Calif. 91311, (818) 709-3300.

Circle 396

This is all it takes to get IBM, Apple, Tandy, Macintosh and Compaq talking to each other.

And it's simple and inexpensive.



Now a powerful **GridNet™** Local Computer Communications Network is as close as your nearest electrical outlet.

Thanks to GridComm's Communicators, virtually any

office can create its own high speed, error-free **GridNet™**... instantly! There's no need to purchase special system software. And there's none of the expense and inconvenience of installing additional wiring. Because a **GridNet™** utilizes your existing electrical grid as a highly-effective data transmission medium.

And a **GridNet™** will support IBM PC, XT, AT, and all IBM compatibles, Apple and Macintosh, Hewlett-Packard, Tandy, AT&T, Epson, NEC...all the most popular

micros and peripherals, in the same network. Freely sharing data, with complete connectivity and effective compatibility.

The cost? As much as 60% below that of specially-wired systems.


Find out just how easy it is to increase your office's productivity. See your local dealer, or contact "The Great Communicator" for more information.



For information call 203-790-9077. P.O. Box 2779, Danbury, Connecticut 06813-2779

Trademarks: IBM, PC, XT, AT/International Business Machines Corp.—Apple/Apple Computer Inc.—Macintosh/McIntosh Laboratory Inc.—Tandy/Tandy Corp.—Compaq/Compaq Computer Corp. Hewlett-Packard/Hewlett-Packard Co.—Epson/Epson America Inc.—AT&T/American Telephone and Telegraph Co.—NEC/NEC Home Electronics (U.S.A.) Inc.

CIRCLE NO. 95 ON INQUIRY CARD



Laser printer runs at 8 ppm

- 384K bytes of memory
- Epson FX-80 emulation
- 10 bit-mapped fonts

The LaserPro EXPRESS laser printer produces 8 ppm. It offers Epson FX-80, HP LaserJet, Diablo 630 and Qume Sprint 11 emulation and provides 384K bytes of memory and 10 bit-mapped fonts. Software compatibility includes Wordstar, Lotus 1-2-3 and Symphony. Features include a 250-sheet paper cassette and a 100-sheet output tray. \$1,895. **Office Automation Systems Inc.**, 8352 Clairemont Mesa Blvd., San Diego, Calif. 92111, (619) 576-9862.

Circle 397

Dot-matrix printer performs at 200 cps

- Four or seven colors
- 136 columns
- RS232C interface


A letter-quality, dot-matrix printer, the Printstation 260 performs at 200 cps with four or seven-color capability. The 136-column device generates charts and graphics in landscape or portrait mode. Features include IBM PC color graphics, Epson FX-80 emulation and eight international character sets. A Centronics parallel and an RS232C interface are standard. \$1,495. **Centronics Data Computer Corp.**, 1 Wall St., Hudson, N.H. 03051, (603) 883-0111.

Circle 398

Printers execute 30 and 45 ppm


- Ion deposition
- 300 by 300 dpi
- DEC compatible

Using ion-deposition technology, the



CIE 3000 series printers execute 30 and 45 ppm. The units are geared toward DEC computers. They supply a 300-by-300-dpi resolution. Features include a 500-sheet feeder, self-test and landscape and portrait modes. \$12,995, 30 ppm; \$15,540, 45 ppm. **CIE Systems Inc.**, 2515 McCabe Way, Irvine, Calif. 92713, (714) 660-1800.

Circle 399



Dot matrix printer runs at 300 cps

- 8K-byte buffer
- 80 columns
- IBM emulation


An 80-column dot matrix printer, the EX-800 runs at 300 cps, draft, and 54 cps, NLQ. Features include an 8K-byte buffer, a bidirectional tractor, automatic sheet-loading and a color option. Parallel and serial interfaces are standard. The device emulates IBM printers. \$749. **Epson America**, Computer Products Division, 2780 Lomita Blvd., Torrance, Calif. 90505, (800) 421-5426.

Circle 400

The Right Choices

I've got four different departments with different needs, but I can't risk buying four different brands of portable computers.


Don't worry. You only need one: Datavue. It gives you a choice of 5 1/4" or 3 1/2" drives and even an internal 20 MB hard drive so you can't go wrong.



DATAVUE™

The powerful, affordable portable.

For more information on the portable with the choices you need, call your computer dealer or 404-564-5668




CIRCLE NO. 82 ON INQUIRY CARD

PRINTERS

Printer generates 8 ppm

- 300 by 300 dpi
- 512 bytes of RAM
- Six fonts


Generating 8 ppm, the LP-3000 laser printer provides 512K bytes of RAM expandable to 2M bytes. Resolution for bit-mapped graphics is 300 by 300 dpi.



The printer emulates the HP LaserJet and LaserJet Plus, Diablo 630 and Epson FX-80. It supports the full IBM graphics character set. Serial and parallel interfaces are supported. Features

include six fonts, a 250-sheet paper tray and automatic page eject. \$3,980, 512K bytes; \$4,995, 2M bytes. **HanZon Data Inc.**, 18732 142nd Ave. N.E., Woodinville, Wash. 98072, (206) 487-1717.

Circle 401



Ink-jet printer executes 192 cps

- 192 by 192 dpi
- 48 dB(a)
- Two interfaces

The HP QuietJet Plus ink-jet printer runs at 40 cps, NLQ, and 160 and 192 cps, draft quality. It executes resolu-

tions of 96 by 96 dpi, 192 by 96 dpi and 192 by 192 dpi. Noise level is 48 dB(a). Serial and parallel interfaces are standard. The model handles tractor-feed and cut-sheet paper from 4 to 15 inches across. It supports IBM character sets and is compatible with many software packages including Lotus 1-2-3, Wordstar and Framework. \$799. **Hewlett-Packard Co.**, 18110 S.E. 34th St., Camas, Wash. 98607, phone locally.


Circle 402

Daisywheel printer runs at 30 cps

- IBM compatible
- 12 cpi
- Minus 59 dB(a)

A daisywheel printer, the D2000 is geared toward the IBM PC and compatibles. The unit produces 30 cps at 12 cpi. Character pitch is 10, 12 and 15 cpi. It prints in unidirectional or bidirectional mode. Noise level is less than 59 dB(a). Features include a 2,500-hour MTBF, a soft parameter setup and automatic paper feed. \$695. **Facit Inc.**, 9 Executive Drive, Merrimack, N.H. 03054, (603) 424-8000.

Circle 403



Printer generates 400 cps

- 144 by 144 dpi
- IBM emulation
- Multiple fonts

The model 1400 dot matrix printer generates 400 cps, draft, 200 cps, correspondence quality and 80 cps, NLQ. It supplies 72-by-72-dpi and 144-by-144-dpi resolutions. Multiple fonts may be resident, and two fonts can be downloaded from the host computer. The unit provides Diablo 630, Epson, and IBM interface emulations. It employs standard tractor paper handling. \$1,845. **Infoscrite Inc.**, 1808 Michael Faraday Court, Reston, Va. 22090, (703) 689-2805.

Circle 404

TERMINALS FROM TRANSNET

SALES SERVICE LEASING

TERMINALS

PERSONAL COMPUTERS

3 Com

Apple
AT&T
DEC
NCR
Panasonic
Wyse

Novell

PRINTERS

TERMINALS

DEC
Wyse
Northern Telecom
Televideo
CIE
TI

NEC
Epson
Okidata
Brother
DEC
CIE

PRINTERS

Paper
Ribbons
Modems
Furniture

MS-DOS / UNIX Software

SOFTWARE & SUPPLIES

12-24-36 MONTH LEASE/RENTAL PROGRAMS - IMMEDIATE DELIVERY
QUANTITY DISCOUNTS - REFURBISHED EQUIPMENT AVAILABLE

TRANSNET CORPORATION

1945 ROUTE 22 • UNION, NJ 07083 • 201-688-7800
OUTSIDE NJ - 800-526-4965
Offices in Philadelphia - 215-592-4247
New York City - 212-714-0233

Terminals are DEC compatible

- 14-inch screen
- 720 by 336 pixels
- Tektronix Plot 10

The models 955 and 9220 graphics terminals supply Tektronix 4010/4014 compatibility while running Tektronix Plot 10 programs. They display resolutions of 720 by 336 pixels and 640 by 240 pixels, respectively, on a 14-inch screen. The 9220 is compatible with DEC's VT52, VT100 and VT220 terminals. Features include circle and arc generation, bar and polygon fill and eight line-types. Display RAM is 32K bytes. \$1,129. **TeleVideo Systems Inc.**, 550 East Brokaw Road, P.O. Box 6602, San Jose, Calif. 95150-6602, (408) 745-7760.

Circle 405

Terminal provides 26 or 44 lines

- 14-inch screen
- 16 function keys
- IBM keyboard


The WY-60 ASCII terminal furnishes a resolution of 7 by 12 characters in a 10-inch by 16-inch matrix. It supplies 26 or 44 lines of text in an 80- or 132-column format. Screen size is 14 inches. The unit supports IBM PC/AT, IBM 3161 and WY-50 keyboards. Up to seven pages of display memory are supplied. Features include 16 dedicated function keys and 66 programmable functions. The terminal emulates Data General, Lear Siegler, TeleVideo, ADDS and Hazeltine devices. \$699. **Wyse Technology**, 3571 N. First St., San Jose, Calif. 95134, (408) 433-1000.

Circle 406

Terminal offers 249 fill patterns

- 16 colors
- 38.4K-baud throughput
- Tektronix compatible

The ColorTrend 4100 model 100 is a graphics terminal for data representation and analytical applications. It supplies 16 colors and 249 fill patterns, 100 of which are programmable. Throughput is 38.4K baud. The Tektronix-compatible unit contains programmable function keys, a detachable keyboard



and commands such as paint, circle and zoom. \$1,995. **Intecolor Corp.**, Intecolor Drive, 225 Technology Park, Norcross, Ga. 30092, (404) 449-5961.

Circle 407

Terminal emulates DEC units

- 1,024 by 780 pixels
- 80, 132 columns
- 60-Hz display

A composite terminal, the GO-235 emulates DEC's VT100 and VT220

units. The terminal offers a resolution of 1,024 by 780 pixels and a 60-Hz non-interlaced display. It writes up to 52 lines of text in 80 or 132 columns. \$1,695. **GraphOn Corp.**, Tower One, Fifth Floor, 1901 S. Bascom Ave., Campbell, Calif. 95008, (408) 371-8500.

Circle 408

Monitors perform CAD/CAM applications

- 16-, 20-inch unit
- 1,024 by 1,280 pixels
- 60-MHz raster scanning

Suiting CAD/CAM and graphics applications, the CD-S1611 and CD-S2011 are color monitors with a 1,024-by-1,280-pixel resolution. The 16- and 20-inch units offer a standard dot pitch of 0.26 mm and 0.31 mm, respectively. They use a 60-MHz non-interlaced scanning system. \$2,500, CD-S1611; \$3,000, CD-S2011. **C. Itoh Electronics Inc.**, 5301 Beethoven St., Los Angeles, Calif. 90066, (213) 306-6700.

Circle 409

The Right Decision

Datavue offers you more than any other portable computer. And more than many desktops. Plus, Datavue is fully IBM compatible.


More screen choices: LCD, Fluorescent, and Gas Light.

More drive choices: 5¼", 3½", and 20Mb internal hard drive.

More standard features: RGB and composite ports, up to 1.25MB system memory, detachable keyboard, tilt screen, serial port, printer port, modem port, RAM drive software.

More options: Expansion chassis, internal modem, external 5¼" floppy drive.

Find out more about this powerful, affordable portable computer today. See your computer dealer or contact us at One Meca Way, Norcross, Georgia, 30093, 404-564-5668.



DATAVUE™

The powerful, affordable portable.

CIRCLE NO. 83 ON INQUIRY CARD



PRESENTS

SCSI FORUM / BOSTON '86

A comprehensive 3-day technical conference for system integrators and suppliers to discuss SCSI (Small Computer System Interface) issues, learn about the latest SCSI developments, and promote industry standardization.

WHERE The Hilton at Colonial, Route 128, Wakefield, Massachusetts

WHEN October 7 - 9, 1986

TECHNICAL PROGRAM The new Fall Technical Program, presented by the world's leading SCSI experts, consists of nine one and one-half hour Technical Sessions:

- What is SCSI and What Can It Do For Your System?
- SCSI Command Set Overview
- SCSI Common Command Set (CCS) Status
- High Performance SCSI Features
- Backup and the Copy Command
- SCSI Overhead Trade-offs
- Host Adapters
- SCSI Applications: PC's to Supermini's
- SCSI Test Issues

EXHIBITORS PROGRAM

- **WORKSHOPS**
The optional half-hour SCSI Exhibitors Workshops conducted by participating SCSI Suppliers provide an opportunity to interactively learn more about a particular SCSI product or supplier.
- **RECEPTION**
The Tuesday evening Exhibitors Reception provides an opportunity to see the latest SCSI products and talk to technical representatives from participating SCSI suppliers. A light buffet and cocktails will be served.

SPONSORS

- | | | |
|-------------------------------|----------------------------------|-------------------------------------|
| • Adaptec, Inc. | • Micropolis | • Siemens Information Systems, Inc. |
| • Adaptive Data Systems, Inc. | • Mini-Micro Systems | • System Surety Group |
| • Control Data Corporation | • NCR E & M | • Technology Forums |
| • Emulex Corporation | • NCR Microelectronics | • Western Digital |
| • ENDL Consulting | • NSA/Hitachi | • Xebec Systems, Inc. |
| • Fujitsu America, Inc. | • Pertec Peripherals Corporation | |
| | • Scientific Micro Systems, Inc. | |

REGISTRATION FEE The Registration Fee of \$995 includes attendance at all scheduled functions, copies of the SCSI and CCS Specifications, Speaker Presentations, Continental Breakfast and Luncheon each day, a Welcome Reception, and the Exhibitors Reception.

REGISTRATION FORM

Please register me for the SCSI Forum. I have printed the following information as I want it to appear on my name tag and on the list of attendees:

Name _____

Title _____ **Phone** (____) _____

Company _____

Address _____

- Please send information on exhibiting at the SCSI Forum.
- Please send information on the SCSI Source Guide, A Comprehensive Handbook on SCSI Hardware and Software Products.

SCSI Forum registrations cannot be accepted unless accompanied by full payment of \$995. Please make checks payable to "SCSI Forum" and mail with this registration form to:

TECHNOLOGY FORUMS
3425 Pomona Blvd., Suite F • Pomona, CA 91768 • (714) 861-7300

CIRCLE NO. 19 ON INQUIRY CARD

“and we meet at the Invitational Computer Conferences throughout the world”



For 16 years, the “OEM Only” ICCs have brought OEM manufacturers to where the volume buyers live and work. And only the ICCs cover 17 major OEM territories throughout the U.S. and Europe — time and cost efficiently.

In one day, regional design engineers/system integrators can attend a full day of high-tech seminars and meet with major OEM suppliers of mini/micro computers, disk/tape drives, printers, terminals, controllers, etc. And the ICCs unique business hospitality format, unlike big national shows, make it easy for manufacturers to meet their invited guests one-on-one. So don't miss out! If you are a computer and peripheral OEM manufacturer, call us today to reserve space. If you are a volume buyer, call your local OEM supplier, or our offices, for an ICC invitation.

In the U.S., contact B.J. Johnson & Associates, Inc., 3151 Airway Avenue #C-2, Costa Mesa, CA 92626, Phone (714) 957-0171, Telex 5101002189 BJ JOHN.

In Europe, contact C. J. Nicholl & Associates, Ltd., 37 Brompton Road, London SW3 1DE, England, Phone 01-581 2326/9, Telex 888068 CJNAD G.



1986/87 U.S. SERIES:

Newton, MA—9/4/86
Dallas, TX—9/16/86
Minneapolis, MN—9/30/86
Gaithersburg, MD—10/16/86
Westlake Village, CA—10/28/86

Irvine, CA—1/8/87
Ft. Lauderdale, FL—1/29/87
Raleigh, NC—2/19/87
Austin, TX—3/3/87
San Jose, CA—3/17/87
Nashua, NH—4/2/87

1986/87 EUROPE SERIES:

Munich, W. Germany—9/10/86
Stockholm, Sweden—9/16/86
London, England—9/22/86

Frankfurt, W. Germany—1/22/87
Paris, France—1/27/87
Milano, Italy—2/3/87

CIRCLE NO. 93 ON INQUIRY CARD

THE GREAT ESCAPE!

FROM IVORY TOWERS AND
COLD COMPUTER ROOMS TO
THE WARMTH OF YOUR OFFICE.

Artificial intelligence for business
has arrived in a revolutionary new
product . . . Guru.

At last, artificial intelligence designed especially for business! Guru brings together expert system capabilities of artificial intelligence, the productivity of familiar business computing tools and the ease of communicating with your computer using menus, commands or plain English. All available in a single, integrated program.

Guru works like human experts, considering uncertainties, reasoning through forward and backward chaining, asking for more information when needed, and explaining its recommendations.

Guru's expert system works hand-in-hand with all the familiar business computing tools like spreadsheets, statistical analysis, business graphics and a programming language, always available for both expert consultation and your everyday business computing needs.

Best of all, you won't need to learn LISP or PROLOG or buy fancy computers . . . Guru runs on your PC and communicates in plain English! Guru is artificial intelligence that means business.

For more information, call or write Micro Data Base Systems, Inc./Marketing & Sales, P.O. Box 248, Lafayette, IN, 47902, 317/463-2581, Telex 209147 ISE UR.


GURU™

ARTIFICIAL INTELLIGENCE THAT MEANS BUSINESS.

mdb is a registered trademark and Guru is a trademark of Micro Data Base Systems, Inc., P.O. Box 248, Lafayette, IN, 47902



CIRCLE NO. 80 ON INQUIRY CARD




Communications board supplies eight ports

- 50 to 19.2K baud rate
- Stop bits
- Odd or even parity

The DIGICOM/8 communications board contains four or eight asynchronous serial ports. Selectable baud rates for each port range from 50 to 19.2K. The unit provides 5-, 6-, 7- or 8-bit characters, odd or even parity and 1, 1½ or 2 stop bits. As many as four boards can be linked to supply 32 serial communications ports. \$649. **DigiBoard Inc.**, 6751 Oxford St., Louis Park, Minn. 55426, (612) 922-8055.

Circle 410




Multiplexer uses up to 16 channels

- RS232C compatible
- Four configurations
- 56K and 64K bps

A time division multiplexer for 56K-bps and 64K-bps applications, the KILOMUX 1281 interleaves up to 16 channels and supports data rates of up to 19.2K bps. The unit allows selection of RS232C, RS422, RS423 or CCITT V.35-compatible interfaces. It accommodates synchronous and asynchronous channels and comes in four configurations. \$2,000 and higher. **General DataComm Industries Inc.**, 1475 Straits Turnpike, Route 63, Middlebury, Conn. 06762-1299, (201) 574-1118.

Circle 412




Communications board targets OEMs

- 800K bps
- 80186 processor
- 512K bytes of memory

Targeting OEMs and system integrators, the WNIM-186 communications board is based on the 80186 microprocessor. The device generates speeds of up to 800K bps. It supports X.25, SNA/SDLC, asynchronous and bisynchronous data transmission. Up to 512K bytes of dual-ported memory with parity is supplied. \$795. **Gateway Communications Inc.**, 16782 Red Hill Ave., Irvine, Calif. 92714, (714) 261-0762.

Circle 413



Multiplexers suit DEC users

- Asynchronous units
- 64K bps
- Self-test

Asynchronous multipoint multiplexers, the TC-1000 UNIBus Concentrator and the TS-1000 Switching Multiplexer work with DEC products. The TC-1000 supports 64 simultaneous sessions with terminals at remote sites. It emulates the asynchronous portion of eight DEC DMF-32 Communications Controllers. The TS-1000 connects terminals from four remote sites to a central-site CPU. Up to 32 computer ports and terminal connections are supported at each site. Both units offer speeds up to 64K bps. Features include self-test. \$7,500, TS-1000; \$2,100, TC-1000. **ComDesign Inc.**, 751 S. Kellogg Ave., Goleta, Calif. 93117-3880, (805) 964-9852.


Circle 411

Bus Specific Networks
NEW SOLUTION

Complete network solutions for the price of a single card.
 Entry level costs to networking are reduced by ICM's unique integration of the most common components of both file servers and network workstations.

ICM's WS-286 contains all the common local area network components on one board—including ARCnet, SCSI, 1 MByte RAM, and 5 expansion slots. This greatly reduces system complexity, repair costs, and stock of multiple costly components. The on-board SCSI controller provides easy interface to ICM's single-board disk and tape workstation, supporting Novell and TurboDOS. It fits into standard IBM-XT enclosures without software or hardware modification. The 80286-based workstation operates at 10 MHz with no wait states when accessing on-board peripherals and RAM, while the expansion slots operate at 4.77 MHz to allow full XT expansion card compatibility. Call ICM for more information and Reseller pricing.

PC, ARCNET, AND S-100 APPLICATIONS.



ICM


TOMORROW'S BREAKTHROUGHS TODAY
InterContinental Microsystems
 4015 Leaverton Ct., Anaheim, CA 92807
 Phone: (714) 630-0964
 Telex: 821375 SUPPORT UD
 Easylink 62562040 BBS (714) 632-8750

CIRCLE NO. 87 ON INQUIRY CARD


ALL THINGS ARE NOT CREATED VMEqual.



V/SMD 3200
SMD Disk Controller



V/ESDI 3201
ESDI Disk Controller



V/Tape 3209
1/2 Inch Tape Controller

All VMEbus products are not created equal. In fact, we don't know of ANY that are equal to the Interphase® line of high-performance VMEbus controllers.

Interphase takes a family approach to VMEbus product development. Our system architecture and software features are compatible across the product line. This allows quicker development cycles and offers logical growth paths.

V/SMD 3200 SMD Disk Controller—is the industry's preeminent 32-bit SMD controller with more V/SMD 3200's installed today in VMEbus systems than any other similar product. It interfaces to any SMD or SMD-E drive with data rates up to 24 Mb/s, and adapts to your system environment through programmable system parameters.

Interphase's multitasking Virtual Buffer ArchitectureSM permits the V/SMD 3200 to move data with extraordinary speed and is the key to zero-latency operation. The on-board 68000 processor manages a pool of buffers and state machines, which allow it to immediately start moving data no matter where the head lands on the

track. It can transfer an entire track of data in one disk rotation and by pre-fetch caching, will continue to read and cache data even after it has finished transferring those requested. These cached sectors can then be transferred without an additional disk access.

V/ESDI 3201 ESDI Disk Controller—using the powerful Interphase Virtual Buffer Architecture, handles the latest high-speed 5 1/4" ESDI disk drives with hundreds of Megabyte capacities. A sister product to the V/SMD 3200 SMD disk controller, the V/ESDI 3201 is the logical migration path from SMD storage devices to a 5 1/4" form factor. Totally software compatible with the V/SMD 3200, the V/ESDI 3201 will "PLUG AND PLAY" with existing drivers to protect software investments for the future.

A 24 Mb/s disk drive front-end ensures complete compatibility with future higher speed drives.

V/Tape 3209 1/2 Inch Tape Controller—represents the Interphase commitment to design compatibility and ease of integration through its close-coupling with both V/SMD 3200

and V/ESDI 3201 disk controllers. It supports 8, PERTEC interface, 1/2" 9-track tape drives at speeds of 200 ips and above and is the perfect controller for start/stop or streaming applications.

An Interphase exclusive CacheFlowSM feature allows expensive drive performance with an inexpensive drive by eliminating the need for costly intelligence and large buffers. An on-board processor and 8K or optional 128K buffer create intelligent FIFOs that start moving data even before the tape is up to speed and keeps tape streaming. The V/Tape 3209 can run at up to 320 ips, at 6250 bpi, meaning that it will handle future tape drive advances.

FIND OUT MORE

Our family approach to these and other VMEbus products makes your task much easier. From peripheral controllers to system foundations, from our Design Assistance Group to our First Time User Program, no one is VMEqual to Interphase. To learn more about our products, our support or anything else, just call:

(214) 350-9000



INTERPHASE®
corporation

2925 Merrell Road • Dallas, Texas 75229 • Telex: 9109976245 NASDAQ-NMS:INPH
Interphase International
93a New Street, Aylesbury, Bucks. HP20 2NY, England (0296)35661 Telex: 826715 AERO G

Interphase is a registered trademark of Interphase Corporation
Virtual Buffer Architecture and CacheFlow are Service Marks of Interphase Corporation

CIRCLE NO. 8 ON INQUIRY CARD

Software targets system integrators

Targeting system integrators, Intelligent Query is a tool for application software developers. The product is based on a data dictionary and artificial-intelligence concepts. It combines an intelligent query language, a custom report writer and a graphics utility. Database files can be transferred directly to Lotus worksheets without reformatting. \$300. **Programmed Intelligence Corp.**, Suite 5, 3069 Amwiller Road, Atlanta, Ga. 30360, (404) 446-8880.

Circle 414

Network file manager runs under OS-9

The Network File Manager runs under OS-9, a real-time, multitasking operating system. The software-based product combines the file and I/O systems of all connected computers into one file system. Existing utility application software can be used. The package is compatible with a variety of LAN or long-haul data communications hardware. \$60 per copy. **Microware Systems Corp.**, 1866 N.W. 114th St., Des Moines, Iowa 50322, (515) 224-1929.

Circle 415

Software supports IBM token-ring

A software key for IBM's Token-Ring Network, NETBIOS works in conjunction with DOS 3.1 to handle the operating system requirements of networks. The product is available in versions for MultiLink Advanced multi-user software and LANLink, a software-driven network. \$495. **The Software Link**, Suite 632, 8601 Dunwoody Place, Atlanta, Ga. 30338, (404) 998-0700.

Circle 416

Graphics software addresses business

A business graphics software package for the IBM PC and compatibles, SYON offers a choice of 11 graphs. It integrates text and graphs. The package loads and edits files from any IBM-compatible word-processing software

package and integrates software such as Lotus 1-2-3 or MultiPlan. Resolution is 640 by 200 monochrome pixels and 320 by 200 color pixels. \$199. **Stella Systems**, Suite 185, 10430 S. De Anza Blvd., Cupertino, Calif. 95014, (408) 257-6644.

Circle 417

Worksheet supplies four functions

Logistix is an integrated software package that combines time-management, database, spreadsheet and graphics functions. The worksheet measures 2,048 rows by 1,024 columns. It supplies intelligent memory management, color-support formatting options and more than 150 screens of context-sensitive help. The database stores 2,027 records by 64 fields. \$450. **Lattice Inc.**, P.O. Box 3072, Glen Ellyn, Ill. 60138, (312) 858-7950.

Circle 418

Software accesses DEC files

Dataware enables users to access Digital Equipment Corp. disk files and output peripherals from IBM PCs. The software is supplied with a proprietary VT-220 emulator. PC users can transfer information to and from DEC files. \$195. **Logicraft Inc.**, 410 Amherst St., Nashua, N.H. 03063, (603) 880-0300.

Circle 419

C compiler runs with MS-DOS 2.0

A C compiler, LET's C provides a complete C language, full UNIX compatibility and a standard C library. The product runs on the IBM PC and compatibles under MS-DOS 2.0 or higher. It requires 128K bytes of RAM and disk drives. \$495. **Mark William Co.**, 1430 Wrightwood Ave., Chicago, Ill. 60614, (312) 472-6659.

Circle 420


Bus Specific Networks

NEW FUTURE

Finally PC-DOS capabilities on S-100 systems—a major breakthrough the noncompatibility barrier.

For the first time, you can run monochrome PC-DOS and MS-DOS—including Lotus 123, Wordstar, and Sidekick—on your existing S-100 system. All with the brand new CPS-16F, a powerful single board network processor, only from ICM. It fits existing installations without a LAN hookup and has low entry requirements for TurboDOS Systems. The CPS/MS-1000 package (with 1000 opportunities) consists of the CPS-16F processor; and ICM's exclusive MS-1000 software. ICM brings PC-DOS to the S-100 industry. Call ICM for Reseller pricing on the CPS/MS-1000 package and info about our upcoming products.

PC, ARCNET, AND S-100 APPLICATIONS.



ICM
TOMORROW'S BREAKTHROUGHS TODAY
InterContinental Microsystems
4015 Leaverton Ct., Anaheim, CA 92807
Phone: (714) 630-0964
Telex: 821375 SUPPORT UD
Easylink 62562040 BBS (714) 632-8750

THERE'S A REASON WHY THEY DON'T PARK PLANES ON THE RUNWAY.



Parking violations.

Most Winchester manufacturers "park" the read/write heads on the media. That's where the trouble starts. Like stiction between the heads and media causing drive failure on start-up. Or shock and vibration causing the heads and media to slap together, which can mean errors, lost data, head crashes.

Heads-up technology.

That's why all Titan™ 3.5-inch 20 Mbyte Winchesters have LaPine's patented head lifters. To hold the heads off the media during power-down. So there are no take-offs and landings. Not only do the heads never "park on the runway," they never touch the media at all.

Top flight performance.

Because the heads don't rest on the media, LaPine's Titan drives are virtually shockproof, built to withstand 60 G's shock and 2.5 G's vibration. And at 5°C to 55°C, the operating thermal range is the widest around. To speed system throughput, track-to-track access time is just 15 MS, with an average access time of 65 MS.

***Shockproof 3.5-inch
20-Mbyte Winchesters that
eliminate head-disk wear
and stiction — completely.***

LaPine means reliability.

Only LaPine eliminates the three main causes of Winchester failure:

- ***Eliminates stiction.***
Heads don't touch or park on media, so they can't adhere.
- ***Prevents head/media wear.***
Heads never contact disks, even during power down.
- ***Ends head-slap.***
Shock and vibration can't damage the heads or media.

For your customers, this means reliability, durability and data dependability. In even the most demanding applications. And now they're backed by the only two year warranty in the industry.

Available now.

To compete in today's systems markets, you need the most reliable Winchester storage there is. You need LaPine. Affordable quality you and your customers can't afford to be without.

Whether you want a single drive for evaluation or 5,000 drives for your next production run, we're delivering. Now.

Call us at (408) 262-7077. Ask for "Titan Information, please." We'll show you how to take the worry out of Winchesters.

LAPINE
TECHNOLOGY

182 Topaz Street
Milpitas, CA 95035
408-262-7077
FAX 408-945-9949
Telex 171693


™Titan is a trademark of LaPine Technology Corporation.
*Patent pending.

CIRCLE NO. 92 ON INQUIRY CARD

Software accesses color graphics

- IBM compatible
- Coaxial adapter
- Four host sessions

The Attachmate 3270 Host Graphics Program allows personal computers to access host-generated color graphics. The software uses a proprietary coaxial adapter and a 3270-PC emulation program to manage up to four concurrent



host sessions. Combinations of 3270 text and graphics can run simultaneously. Host graphics screens can be saved and edited locally. The IBM Color Graphics Adapter and Enhanced Graphics Adapter are supported. \$595. Attachmate Corp., 3241 118th S.E., Bellevue, Wash. 98005, (206) 644-4010. Circle 421

Software handles multiple projects

- 18 menus
- Six windows
- 25 Help-screens

Running on an IBM PC with 256K bytes of RAM, Project Major is a project-management software program that uses Lotus 1-2-3. The package supplies 18 menus, 25 Help screens, six windows and a sample tutorial. Data entry is done with menus or single keystrokes. Setup codes are provided for 80 printers. A print menu selects fonts and line spacing. \$69.95. Hunter Consultants, 15 Chipping Green Drive, Arden, N.C. 28704, (704) 684-0947.

Circle 422

Operating system addresses 16M bytes

- 16-bit OS
- Multitasking
- 32 users

A multiuser, multitasking operating

system, THEOS 286-Virtual addresses up to 16M bytes of RAM. As many as 32 users can run applications simultaneously. The 16-bit operating system provides built-in security and memory management. \$695. THEOS Software Corp., Suite 100, 201 Lafayette Circle, Lafayette, Calif. 94549-4370, (415) 283-4290.

Circle 423

DBMS emulates dBASE III Plus

- MS-DOS support
- 10 files
- Help system

Compatible with Ashton-Tate's dBASE III Plus, dBXL supplies extended language features, MS-DOS and PC-DOS support, a Help system and networking capabilities. The software utilizes the same data and index files as dBASE III Plus. As many as 10 files can be open simultaneously, each with up to seven open index files. No copy protec-

tion. \$695. WordTech Systems Inc., P.O. Box 1747, Orinda, Calif. 94563, (415) 254-0900.

Circle 424

Software suits math applications

- For IBM PCs
- 384K bytes of RAM
- Numerical analysis

MathCAD aims at computer aided mathematics applications. The software runs under MS-DOS 2.0 and higher on the IBM PC, PC/XT, PC/AT and compatibles. It requires 384K bytes of RAM. The package supports 8087 and 80287 coprocessors, the IBM graphics printer and the Hewlett-Packard laser jet printer. Applications include numerical analysis and document results. \$189. MathSoft Inc., 1 Kendall Square, Cambridge, Mass. 02139, (617) 577-1017.

Circle 425

Bus Specific Networks

NEW SIZE

4-in-1 processor board.
 More compact, our new CPS-Q6A opens a myriad of new opportunities. Only from ICM. Combining four 8-bit network processors on a single board shrinks the bus space, uses 35% less power and costs less per processor. Designed to operate at 10 MHz, it offers S-100 users the highest degree of performance and system integration available in the market today!

ICM's CPS-216 is also available — with two 16-bit network processors operating at 8 MHz with 256K RAM each, all on a single board.

ICM provides the system integrator with the best price performance products possible. Call ICM for Reseller pricing on the CPS-Q6A and CPS-216 package and info about our upcoming products.

PC, ARCNET, AND S-100 APPLICATIONS.

ICM
 TOMORROW'S BREAKTHROUGHS TODAY
 InterContinental Microsystems
 4015 Leaverton Ct., Anaheim, CA 92807
 Phone: (714) 630-0964
 Telex: 821375 SUPPORT UD
 Easylink 62562040 BBS (714) 632-8750


NEW PRODUCTS

SUBASSEMBLIES

Controller suits IBM PC, PC/XT and PC/AT

- 16 colors
- 640-by-350 resolution
- 1,024 characters

A controller card for color or monochrome graphics, the EGA Master is compatible with IBM's Enhanced Graphics Adapter. The device runs on the IBM PC, PC/XT and PC/AT. It



provides 256K bytes of memory and 640-by-350 resolution for text and graphics in 16 colors from a 64-color palette. The card supplies smooth scrolling, smooth panning and the production of 1,024 programmable characters. \$395. **Tecmar Inc.**, 6225 Cochran Road, Solon, Ohio 44139-3377, (216) 349-0600.

Circle 426

Single-board PC runs faster than IBM PC/AT

- 8086-1 processor
- 512K bytes of RAM
- 16-bit words


The 8612 single-board personal computer runs 1.6 times faster than the IBM PC/AT and over four times faster than the IBM PC/XT. The device is mounted on a full-size personal computer expansion card. It utilizes an 8086-1 microprocessor and 512K bytes of RAM to handle data in 16-bit-wide words. The unit is geared toward OEMs and VARs. \$626. **Datavue Technical Systems**, 4355 International Blvd., P.O. Box 2687, Norcross, Ga. 30093, (404) 564-5780.

Circle 427

Boards run at 19.2K bytes


- IBM PC compatible
- Interrupts
- Switch-selectable

The DS-101 and DS-102 boards pro-



vide dual, independent RS232C interfaces for asynchronous communication. For use with the IBM PC, PC/XT, PC/AT and compatibles, the 19.2K-byte boards may be used as two serial ports or disable units. Switch-selectable addressing allow the devices to be re-assigned as additional serial ports or anywhere else in the available I/O space. Interrupts are supplied. Optional software supports baud rates up to 19.2K. \$295. **Qua Tech Inc.**, 478 E. Exchange St., Akron, Ohio 44304, (216) 434-3154.

Circle 428



SBC aids VMEbus

- Four configurations
- 200-nsec access time
- 16, 32 bits


A 16/32-bit single board computer for the VMEbus, the VMP68KB offers a choice of four microprocessors. The ruggedized unit performs real-time applications at 8, 10 and 12 MHz. It features 128K bytes of dynamic RAM, a 200-nsec access time and a seven-level interrupt handler. The device supplies eight programmable control lines for parallel I/O and two independent serial I/O ports. \$1,095. **PEP Modular Computers Inc.**, 600 N. Bell Ave., Pittsburgh, Pa. 15106, (412) 279-6661.

Circle 429

Board suits IBM RT PC


- 8M bytes of memory
- Two 40-bit arrays
- 150-nsec access time

Add-in memory boards for the IBM RT PC, the RTRAM/4 and RTRAM/8 offer 4M and 8M bytes of memory, respectively. Up to 16M bytes are configurable for the full address space of the RT PC. The boards are organized as



two 40-bit arrays to allow interleaved operation. Data access time is 150 nsec. \$1,895, RTRAM/4; \$4,395, RTRAM/8. **Clearpoint Inc.**, 99 South St., Hopkinton, Mass. 01748, (617) 435-5395.

Circle 430



Board incorporates IBM EGA

- 2M bytes of memory
- Rigid disk controller
- Two ports

A multifunction board for the IBM PC/XT, All Aboard combines IBM EGA or IBM monochrome and color graphics support, up to 2M bytes of expanded memory, a rigid disk controller and serial and parallel ports. The device occupies one slot. \$545, monochrome and color graphics; \$795, EGA support. **IDEAssociates Inc.**, 35 Dunham Road, Billerica, Mass. 01821, (617) 663-6878.

Circle 431

SUBASSEMBLIES

Package furnishes voice recognition

The PC Executive Secretary offers voice-recognition and telephone-management capabilities to the IBM PC and compatibles. The hardware/software package reproduces speech at rates of 4,000 bps. Functions include automatic answering, message recording and playback and automatic call logging. \$1,695 **VOTAN**, 4487 Technology Drive, Fremont, Calif. 94538, (415) 490-7600.

Circle 432

Graphics controller targets OEMs

The Ω 3610 graphics display controller achieves a 1,280-by-1,024 pixel and 60-Hz color resolution. Targeting OEMs, the unit includes 32 bit-planes and a custom bit-slice processor. It can define 16 million colors. Vector drawing mode is 6 million pixels per second, and rectangle-fill is 160 million pixels per second. Features include a 16-bit, double-buffered interface or an IEEE-488 interface. The unit operates in full-raster mode and performs pan and zoom. \$16,950. **Metheus Corp.**, 5510 N.E. Elam Young Parkway, Hillsboro, Ore. 97123, (503) 640-8000.

Circle 433

Emulation adapter fits in IBM PC

The Advanced 3278/79 Emulation Adapter fits in either a full or half slot of an IBM PC, /XT or /AT, allowing the PC to emulate an IBM 3278 monochrome terminal or an IBM 3279 color terminal. Files are transferred to and from host systems in 3270 environments. Multiple concurrent 3270 sessions may be implemented. \$595. **IBM Corp.**, 900 King St., Rye Brook, N.Y. 10573, (914) 934-4000.

Circle 434

Board furnishes up to 2M bytes of RAM

- 8086-1 processor
- Standard ports
- Single-slot unit

The Dream Board is an IBM PC- and PC/XT-compatible multifunction

"I need a LAN that works with our existing hardware."



"I need 10-NET."

Requiring no dedicated server, 10-NET allows systems sharing disk drives and printers to continue functioning as work stations. Think of the flexibility this 10-NET capability offers. Consider what this can mean in savings.

Once you add up 10-NET advantages, you'll see why over 50,000 installations are already in place worldwide.

A phone call gets you the facts. Call:

1-800-358-1010.

In Ohio call 1-800-782-1010 • 513-433-2238 • Telex 650-2079125



Fox Research, Inc. • 7016 Corporate Way • Dayton, Ohio 45459
10-NET is designed for use with IBM PCs, ATs and compatibles.



More than just talk.

CIRCLE NO. 93 ON INQUIRY CARD

REGIONAL SALES OFFICES

Robert K. Singer
National Sales Manager
275 Washington St.
Newton, MA 02158
(617) 964-3030

NEW ENGLAND

John J. Fahey
Regional Manager
Susan Rapaport
Regional Manager
275 Washington St.
Newton, MA 02158
(617) 964-3030

NEW YORK/MID-ATLANTIC

Stephen B. Donohue
Regional Manager
1873 Route 70, Suite 302
Cherry Hill, NJ 08003
(609) 751-0170
in N.Y.: (212) 972-0058

SOUTHEAST

Larry Pullman
Regional Manager
6540 Powers Ferry Rd.,
Suite 170
Atlanta, GA 30339
(404) 955-6500

MIDWEST

Robert D. Wentz
Regional Manager
Marianne Majerus
Sales Coordinator
Cahners Plaza
1350 E. Touhy Ave.
P.O. Box 5080
Des Plaines, IL 60018
(312) 635-8800

SOUTHWEST

Don Ward, Regional Manager
13740 Midway, Suite 515
Dallas, TX 75234
(214) 980-0318

MOUNTAIN STATES

John Huff
Regional Manager
270 St. Paul St.
Denver, CO 80206
(303) 388-4511

SOUTHERN CALIFORNIA/ NEVADA

Len Ganz
Regional Manager
18818 Teller Ave.
Irvine, CA 92715
(714) 851-9422

NORTHERN CALIFORNIA/ NORTHWEST

Frank Barbagallo
Northwestern Regional Sales
Manager
Rick Jamison
Regional Manager
Sherman Building, Suite 100
3031 Tisch Way
San Jose, CA 95128
(408) 243-8838

UK/BENELUX/SCANDINAVIA

Jan Dawson
Regional Manager
39 A Bowling Green Lane
London, EC1R/0BJ UK
1-278-2152
Telex: 28339

ISRAEL

Elan Marketing Group
13 Haifa St., P.O. Box 33439
Tel Aviv
Tel: 972-3-252967
Telex: 341667

JAPAN

Kaoru Hara
General Manager
Dynaco International Inc.
7-2-8 Minamiaoyama
Minato-ku, Tokyo 107
Tel: 011-81-3-409-4569
Fax: 011-81-3-499-4554

TAIWAN

Donald H. Shapiro
Trade Winds, 2nd Floor
132 Hsin Yi Road, Sec. 2
Taipei
Tel: 3932718
Telex: 24177 FC Trade

EUROPE, EXCEPT UK/ BENELUX/SCANDINAVIA

Elan Marketing Group
Neutor g. 2
P.O. Box 84
1013 Vienna, Austria
Tel. 43-222-663012

Mini-Micro Marketplace

Carol Flanagan
275 Washington St.
Newton, MA 02158
(617) 964-3030

Direct-Response Postcards

Carol Flanagan
275 Washington St.
Newton, MA 02158
(617) 964-3030

Career Opportunities

Carol Flanagan
Recruitment Advertising Manager
275 Washington St.
Newton, MA 02158
(617) 964-3030

Cahners Magazine Division

William Platt, President
T.M. McDermott, Vice President
Electronics/Computer Group
Tom Dellamaria, VP/Production
Ira Siegel, VP/Research

Promotion Staff

Susan Rapaport
Marketing Communications
Director
Mary Gregory
Promotion Manager
Elizabeth Phillips
Marketing Assistant

Circulation

Denver, CO:
(303) 388-4511
Sherri Gronli
Group Manager

SAME DAY DASH.[®] DELTA TAKES IT THERE.[®]

For same-day delivery of small packages, Delta DASH takes it there. Any package, under 70 lbs., shipped during the normal business hours will arrive that same day.

For packages over 70 lbs., Delta Air Express takes it there on the flight specified. Guaranteed.

Delta ships airport to airport or door to door. And we can deliver your shipment to

over 100 cities, over 10,000 U.S. communities.

With Delta DASH, time is on your side.

Call 800-638-7333; in Baltimore call 269-6393.



NEW PRODUCTS SUBASSEMBLIES

board that offers 512K bytes of RAM expandable to 2M bytes of EMS-compatible RAM. Occupying a single slot in the PC, the device utilizes an 8086-1 microprocessor. Serial and parallel ports are standard. \$795. **Univation Inc.**, 1231 California Circle, Milpitas, Calif. 95035, (408) 263-1200.

Circle 435

Memory board suits 200 PC applications

- 8M bytes of memory
- Windowing software
- PC-DOS compatible

A memory and multifunction board for the IBM PC, PC/XT and compatibles, SixPacPremium increases the PC's memory by 2M bytes. The PC-DOS-compatible device supplies two serial ports, one parallel port and proprietary windowing software. Memory is expandable to 8M bytes. The board is compatible with over 200 PC application programs. \$595 to \$1,395. **AST Research Inc.**, 2121 Alton Ave., Irvine, Calif. 92714, (714) 863-1333.

Circle 436




Graphics adapter converts color to gray

- 8-by-14-dot characters
- 1,024 by 348 pixels
- IBM PC compatible

A monochrome and color graphics adapter, the Chauffeur HT is compatible with the IBM PC, PC/XT and PC/AT. It converts color to 16 shades of gray for monochrome monitors. Text is displayed as 8-by-14-dot characters with a 1,024-by-348-pixel display. The device runs all IBM Color Graphics Adapter and Monochrome/Printer Adapter software on standard RGB color monitors. Up to 16 colors are supported. The unit also drives 256-kHz color monitors. Features include a parallel printer port and PC Accelerator software. \$349. **STB Systems Inc.**, Suite 125, 601 N. Glenville, Richardson, Texas 75081, (214) 234-8750.

Circle 437

“I need a LAN
that lets us
communicate
with other
buildings—
or other
continents.”



“I need 10-NET.”

With 10-NET RS232 you can tie entire networks, or individual PCs to networks, via phone lines. 10-NET is your key to economical, easily installed PC communications, unsurpassed in speed and transparency.

Once you add up 10-NET advantages, you'll see why over 50,000 installations are already in place worldwide.

A phone call gets you the facts. Call:

1-800-358-1010.

In Ohio call 1-800-782-1010. Telex 650-2079125



Fox Research, Inc. • 7016 Corporate Way • Dayton, Ohio 45459

10-NET is designed for use with IBM PCs, ATs and compatibles.



More than just talk.

CIRCLE NO. 94 ON INQUIRY CARD

ADVERTISERS INDEX

COMPANY	PAGE NO.
Agfa	E1
Algo	156
Allen Bradley	89
Analog & Digital Peripherals	155
Augat Broadband	82
Augat Fiberoptics	Cov. 3
BASF	E2-E4
Bizcomp	36
Caere Corp.	116
Carroll Touch Technology	29
Chinon America	45
Clearpoint	37, 39, 41, 43
Communications Research Group	156
Computone	44
Control Data Corp./OEM	74-75
Convergent Technologies	66-67
Craig Data Cable	156
CXI	76
Data Access Corp.	133
Data Track	156
Delta Airlines	152
Digital Equipment Corp.	58-59, 129-132
Dual Systems	120
Electronic Processors Inc. (EPI)	64
Equinox Systems	17
Facit	54-55
Falco Data Products	63
Fox Research	151, 153
Fujitsu America Inc. Storage Division	92
Genicom	124
Giltronix	100
Grafpont	117
Gridcomm, Inc.	138
Hall-Mark/Motorola	56
Hall-Mark/NEC	90-91
Hayes Microcomputer Products	52
Hewlett-Packard Co./ISG	88
Hitachi America Ltd.	80-81
Houston Instrument Div. of Bausch & Lomb	134
IBC/Integrated Business Computers	60
Ibex Computers Corp.	78
IBM/Information Systems	118-119
ICC	143
Illbruck/USA	44
Imagen Corp.	10-11
Inmac	6
Intercontinental Micro	145, 147, 149
Interface Group	115, 128
Interphase Corp.	146
Ioline Corp.	155
Irwin Magnetics	111
Iskra VME	33
ITT Information Systems	123
K-Systems	156
Keytronics	95
KMW Systems Corp.	99
Language Processors, Inc.	6
LaPine Technology	148
Leading Edge Products	8
Liberty Electronics USA	Cov. 2
Macs	156
Mannesmann Tally	102-103
Maxtor Corp.	108
Melard	156
Micro Data Base Systems, Inc.	144
Microware Systems Corp.	13
Modgraph	18
Multi-Tech	40
National Electric Cable	48
NEC America	112
NEC Information Systems Inc.	34-35

INQUIRY

NO.
253
213
56
201
53
96
254,255
21
70
16
31
22-25
210
30
48
45
208
49
78
209, 212
—
41
73
44
11
252
43
93, 94
58
75
62
71
95
40
57
36
55
52
79
42
50
72
93
29
7
4
87-89
20, 77
8
205
67
18
74
211
59
61
3
92
6
1
207
63
66
214, 215
80
9
12
27
34
68
98

COMPANY	PAGE NO.
Newbury Data	51
Persyst	7
Pertec Peripherals Corp.	96
Plexus Computers	69
Pyramid Technology	22-23
Quadram Corp.	137, 139, 141
Qualstar	155
Radio Shack (Tandy Corp.)	21
Scientific Micro Systems	42
Seagate Technology	30-31
Seiko Instruments USA	87
Servo	155
Siemens Corp.	49
Softronics	155
Software AG	104
Software Link	79
SRD Corp.	47
Systech	1
TEAC Corp.	107
Technology Forums	142
Tektronix Inc.	14
Telebyte Technology	12
Televideo/Terminals	73
Telxon	126
Texas Instruments	2-3
Texas Instruments Inc./Speech Div.	70
TransNet Corp.	140
Universal Data Systems Inc.	Cov. 4
Verbex	24
Versatec Inc. (a Xerox Co.)	38
Viking Acoustical	12
Wave Mate	155
Wyse Technology	46

INQUIRY

NO.
35
5
60
46
14
81-83
206
13
28
17
54
202
251
203
64
51
33
2
65
19
10
90
47
76
—
98
97
15
26
91
204
32

DEC DIRECTIONS ADVERTISERS

Be sure to send for more information about these DEC-compatible products, too:

The following advertisers in DEC DIRECTIONS invite you to send for more information about their DEC-compatible products. (DEC DIRECTIONS is a special MINI-MICRO SYSTEMS supplement appearing only in magazine copies sent to subscribers who have indicated involvement with DEC computers.)

Able Computer (terminal network)	D3	151
Computer Products/Grant Technology Div. (DMA interface)	D16	161
DEXCOMP (DEXCOMP '86)	D12	158
Logicraft (PC processor for Q-Bus, UNIBUS systems)	D7	153
Oregon Software (Pascal compiler)	D9	155
RDM (application developer)	D11	157
S & H Computer (PDP-11 multi-user operating system)	D15	159
Sequent Computer Systems (parallel computer)	D4-D5	152
TD Systems (SCSI to Q-Bus host adapter)	D8	154
Walker, Richer, & Quinn (VT 220 terminal emulator)	D10	156
White Pine Software (VT 240 emulation for Mac)	D16	160

DEC USED EQUIPMENT ADVERTISERS

Adcomp	D13	191
Industrial Computer Products	D13	189
Newman Computer Exchange	D13	190
Texas Computer Exchange	D14	192

DEC is a trademark of Equipment Corp.

MINI-MICRO MARKETPLACE

A special section for advertisers of hardware, software and services.


READERS: Please circle reader service numbers on Reader Inquiry Card for additional information.

IBM PC COMPATIBLE RS232 EASI-DISK 5 1/4" FLOPPY DATA STORAGE & TRANSFER SYSTEM



- Reads & Writes IBM PC DOS 5 1/4" Disks
- RS-232C I/O
- Rugged Portable Package
- Host and/or Manual Controls
- ASCII or Full Binary Operation
- Baud Rates 110 to 19.2 K Baud
- Automatic Data Verification
- Price \$1,095 in Singles - OEM Qtys. Less

28 other systems with storage from 100K to 35 megabytes
ANALOG & DIGITAL PERIPHERALS INC




815 Diana Drive
Troy, Ohio 45373
513/339-2241

TWX 810/450-2685

Branch Off Oklahoma City, OK - Factory Yucca Valley, CA

CIRCLE NO. 201 ON INQUIRY CARD

PROCESS CONTROL AND DATA ACQUISITION FOR LABORATORY AND INDUSTRY



General Purpose Analog and Digital Input/Output Controller

\$495

- 24 Analog Inputs 0.1% Accuracy
- 8 Analog Outputs 0.1% Accuracy
- 16 Digital Inputs & 64 Digital Outputs
- 14 Bit Resolution ■ Compact: 5 3/4" x 8 1/2"

Up to 65,535 optional (\$389) serial interfaces, each controlling 8 Servo Control Boards, can be connected to one serial port. Any computer, IBM* or other, can gather data and send control signals using simple English commands. Custom engineering assistance available.



360-B N. Ellensburg St.
Box 566
Gold Beach, OR. 97444
(503) 247-2021

* IBM is a Registered Trademark of International Business Machines

CIRCLE NO. 202 ON INQUIRY CARD

Background Communications

Softerm PC lets you transfer files and print in the background while you work. Memory resident, ready to use at any time from your Spreadsheet or Word Processing program. Supports 3 printer and 4 communication ports simultaneously. Includes 32 exact terminal emulations.


For IBM PC/XT/AT, DG, NEC, HP, Wang, TI, Gridcase, Tandy, Zenith

\$195 - Visa, MC, COD
Call **800-225-8590** orders/info.

SOFTRONICS

7899 Lexington Dr., Ste 210
Colorado Springs, CO 80918
(303) 593-9540 Telex #450236

CIRCLE NO. 203 ON INQUIRY CARD



10 Mhz 80286 IBM PC/XT MOTHERBOARD

- 11.5 Times Faster Than PC; Twice as fast as the AT
- 1MB Ram On-Board Zero Wait States
- Optional 80287 Math Co-Processor
- PC/XT Hardware & Software Compatible
- Supports PC-DOS, Unix, Pick, CP/M-86, SMC OS



WAVE MATE, Inc.
14009 S. Crenshaw Blvd., Hawthorne, CA 90250
(213) 978-8600 TLX 194369
In Europe: Brussels 649-1070 TLX 61828


CIRCLE NO. 204 ON INQUIRY CARD

CREATE A BETTER IMAGE

Ioline Corporation introduces the **LP3700** large format line plotter: the high performance, professional quality instrument that maximizes value...with a price that draws conclusions:
\$4,995.

The LP3700 offers:

- **Versatility**
- Lets you plot on any media at any size up through E (37 1/2" x 81")
- **Precision**
- .0025" Resolution & Repeatability
- **Buffering**
- 14K to 512K
- **Speed**
- Up to 10 ips (axial)
- **Reliability**
- Rugged all metal frame
- Endurance tested at over 60 million cycles



LP3700 Plotter


- **Value**
- At \$4,995, the LP3700 is in a class all by itself.

19417 36th AVENUE WEST, SUITE D1
LYNNWOOD, WA 98036
(206) 775-7861



CIRCLE NO. 205 ON INQUIRY CARD

9-Track Tape Drives



Qualstar's low-cost streaming 1/2" tape drives provide full 1600/3200 BPI capability in a package that is perfect for today's desk-top and desk-side market. Both 7" and 10 1/2" units are available. Interfaces include Cipher/Pertec, SCSI, and IBM-PC. For more information, call us today.




9015 Eton Ave., Canoga Park, CA 91304
Telephone: (818) 882-5822

CIRCLE NO. 206 ON INQUIRY CARD

Responsive **Interactive** Menu-guided Ready-to-go
 Accurate Purchasing **Multi-user** Inventory
 COBOL Bills of Materials Materials Requirements
Production Secure Order Processing **Distribution**
 Sales Analysis Sales Support Accurate
 Receivables **Financial** Payables Source Code
 General Ledger Payroll **Software**

\$595 each

for VAX and MicroVAX computers



CIRCLE NO. 207 ON INQUIRY CARD

600+
 INTERFACE CABLES
 IBM, DEC, HP, PC's
 Overnight Shipping!!
**EXTENDED
 DISTANCE**

PLENUM CABLE


Lowest Prices
 In The Industry
 TEDC12 Assemblies
 \$15 plus .90 per ft
NEW!! NEW!!
 1200 BPS MODEMS \$159
 2400 BPS MODEMS \$349
 Breakout Boxes, Modem
 Eliminators, Short Haul
 Modems, and more!!
 Call for Super
 Low Introductory
 Prices!!



USA 800-243-5760 in CT 203-356-9315 Canada 800-233-9542
 FAX 203-323-9044 TWX 510 10 10 669
 Craig Data Products Co., Inc.
 652 Glenbrook Rd Stamford, CT 06906

CIRCLE NO. 208 ON INQUIRY CARD

NEW



**IBM-AT COMPATIBLE POWER FAIL
 PROTECTED 1.2 or 2.4 MBYTE RS-232-C
 FLOPPY DATA COLLECTION
 AND TRANSFER SYSTEM**

Writes/Reads IBM-AT High Density DOS
 3 Discs
 Power Fail Protected with No Data Loss
 Remotely pollable
 Up to 223 files per disc
 Manual or remote operation


For all of your RS-232-C Data Storage Needs
 Contact:

**Data Track
 USA**

Data Track USA
 9451 Sohaph Lane
 Columbia, MD 21045
 301-992-9143

CIRCLE NO. 209 ON INQUIRY CARD

BLAST



**PC-MINI-MAINFRAME
 COMMUNICATIONS SOFTWARE**

ANY COMPUTER WITH BLAST CAN TALK TO ANY OTHER
 COMPUTER WITH BLAST, the universal file transfer utility
 linking many different computers, operating systems,
 and networks, via RS 232 serial ports

NO ADD-ON BOARDS TO BUY! BLAST software uses any
 asynchronous modems or direct connect for fast, error-free
 data transfer through noisy lines and PBXs, across LANs,
 and over satellites or packet switched networks.


THE PERFECT LOW-COST LINK FOR PC's, MINIS, MAINFRAMES
 Transfer binary or text files, or executable commands. Use
 BLAST standalone, or build it into your application

\$250 / Micros \$495-895 / Minis \$2495 / up Mainframes

COMMUNICATIONS RESEARCH GROUP

(800)-24-BLAST

CIRCLE NO. 210 ON INQUIRY CARD



**WORLD'S SMALLEST
 VT100 EMULATION**

The STD-100 offers complete VT100
 emulation with Advanced Video Option,
 NVRAM Set-up, RS-232 or TTL serial I/O;
 RS-170 or separate sync video. Use as
 stand-alone unit or plug into STD-BUS.
\$300 ea. qty. 100. Versions for Q-bus and
 VMEbus also available. **K-Systems, Inc.,**
 3902 Lilac, Las Cruces, NM 88005,
 505-526-3209, Telex WUI 6502763972/
 Ansbk. MCI.

CIRCLE NO. 211 ON INQUIRY CARD

NEW



**Tracker 1700 Intelligent Stand Alone 15 to 20 Mbyte
 ASCII or Binary RS-232-C Cartridge Tape System**

- Standard Power Fail with No Data Loss
- 24K CMOS Buffered Stop-Start system
- Dual RS-232-C ports with Independent Baud rate select 110 to 19.2K Baud and Auto Answer
- Ideal Hard & Software replacement for Tektronics, Tandburg & Columbia low capacity RS-232-C Drives
- Quantity Priced under \$2000



Data Track USA
 9451 Sohaph Lane
 Columbia, MD 21045
 301-992-9143
 Telex 6971182 COLRESH

CIRCLE NO. 212 ON INQUIRY CARD

**Cartridge Tape
 Systems**



**Intelligent Stand Alone RS-232 or
 IEEE-488 Cartridge Tape System**

Replacement for Tandberg,
 Columbia 300 B, C, & D and
 European MFG Tape Drives

- Stores 5.3 Mbytes or 20 Mbytes of Binary or ASC II Data
- Power Fail Standard-Power Fail "NO DATA LOSS" Optional
- Auto Answer Standard
- Intelligent Search & Retrieval
- IEEE-488 and/or RS-232-C with data rates up to 2,500 characters/sec
- Large input buffer allows unit to accept data non-stop

APPLICATIONS: Data Logging, Control System, Archiving,
 Program Loading & Storage, Back-up, and Telephone
 Switch Monitoring. Auto-pollled Remote Data Storage.

1200
 5.3 Mbyte

1600
 20 Mbyte

WE SERVICE COLUMBIA TAPE DRIVES
 300B - 300C - 300D

Return Authorization Number Required



9198-C Red Branch Rd, Columbia,
 MD 21045 TX333405 ALGO COL
 1-800-252-ALGO in MD:
 (301) 730-7442

CIRCLE NO. 213 ON INQUIRY CARD



ACCESS.
 The perfect portable
 for dozens of
 applications...
 including
 yours!

Displays
 eight full
 40 character
 lines.
 320 K
 capacity.
 So portable,
 it fits in
 your pocket!
 Engineered to
 your specifications.

MELARD TECHNOLOGIES, INC.
 Five Westchester Plaza
 Elmford, NY 10523

(914) 592-3044


CIRCLE NO. 214 ON INQUIRY CARD

CONVENIENT FEATURES!

- 320K memory, RAM and ROM, is allocated between interchangeable cartridges and onboard memory.
- Direct-connect onboard modem, 1200 baud, auto dial/ auto answer, voice and data.
- Acoustic modem cups, 300 baud.
- RS232 serial ports.
- Flexible, interchangeable battery system to satisfy any requirement.
- Compact, portable printers.
- Bar code reader.
- Weighs from 24 oz!

CIRCLE NO. 215 ON INQUIRY CARD

See the light.




The **hole** story about fiberoptic connectors

The more concentric the hole in a fiberoptic connector, the more precise the alignment... the lower the signal loss... the greater the efficiency of the system.

Augat Fiberoptic Connectors are produced with a hole tolerance held to an incredible $+4, -0$ microns. Concentricity is maintained within 2 microns of geometric center. (Ferrules are machined in Augat's Swiss facility by the world masters of precision components.)

Augat Rhode Island further ensures optimal alignment by



subjecting its connectors to profile magnification and laser optical power measurements on uniquely revealing instruments. No other manufacturer dares take such a close and potentially unflattering look at itself.

Best of all, you pay no more for the superior excellence of the finest fiberoptic connectors.

Our complete line of SMA style multimode connectors are available in Arcap and Nickel Plated Brass. We also
CIRCLE NO. 96 ON INQUIRY CARD


offer a field installable single mode connector with less than .5dB insertion loss.

You'll find Augat Fiberoptics refreshing to do business with... the substantial resources of a large corporation combined with the responsiveness and service you require.

See the light with AUGAT FIBEROPTICS, 710 Narragansett Park Drive, Pawtucket, RI, 02861. Telephone (401) 724-4400. Telex-511450.

AUGAT[®] FIBEROPTICS

Quality and Innovation



Dial Now, Dedicate Later at 9600 bps

Take your datacomm system to 9600 bps *now*. You can do it with UDS 9600A/B modems! Buy them today and instantly speed up your system *on the dial-up network*. Later, when traffic growth demands an upgrade, three simple strap changes will adapt your modems to dedicated lines.

The UDS 9600A/B provides optional data rates of 7200 and 4800 bps. Communication may be half-duplex (two-wire) or full-duplex (four-wire, V.29). A wide range of integral test capabilities simplifies system diagnostics.

Don't wait to accelerate your datacomm system throughput. Dial-up or dedicated, you can move

to 9600 bps now. For complete details, contact Universal Data Systems, 5000 Bradford Drive, Huntsville, AL 35805. Phone 205/721-8000 Telex 752602 UDS HTV.

QUANTITY ONE PRICE \$1,995



Universal Data Systems

MOTOROLA INC.
Information Systems Group

UDS modems are offered nationally by leading distributors. Call the nearest UDS office for distributor listings in your area.
DISTRICT OFFICES: Apple Valley, MN, 612/432-2344 • Atlanta, GA, 404/998-2715 • Aurora, CO, 303/368-9000 • Blue Bell, PA, 215/643-2336 • Boston, MA, 617/875-8868 • Columbus, OH, 614/895-3025 • East Brunswick, NJ, 201/238-1515 • Glenview, IL, 312/998-8180 • Houston, TX, 713/988-5506 • Huntsville, AL, 205/721-8000 • Issaquah, WA, 206/392-9600 • Livonia, MI, 313/522-4750 • Mesa, AZ, 602/820-8611 • Milwaukee, WI, 414/273-8743 • Mission Viejo, CA, 714/770-4555 • Mountain View, CA, 415/969-3323 • Richardson, TX, 214/680-0002 • St. Louis, MO, 314/434-4919 • Silver Spring, MD, 301/942-8558 • Tampa, FL, 813/684-0615 • Uniondale, NY, 516/222-0918 • Van Nuys, CA, 818/891-3282 • Willowdale, Ont, Can, 416/495-0008

CIRCLE NO. 97 ON INQUIRY CARD

Created by Dayner/Hall, Inc., Winter Park, Florida