

# PowerBook Duo 250

## **Features**

### Power and speed

33-MHz 68030 microprocessor

4MB of RAM, expandable to 24MB

- Bright, backlit, active-matrix display (640 by 400 pixels) Full-page-width, 9-in. diagonal; 16-level
- gray scale
- Adjustable brightness and contrast

· 2.5 to 6 hours on a single charge

### Expansion

- Built-in high-speed serial port for peri-pheral devices, including LocalTalk network and printers
- Slots for internal modem and RAM
- Docking connector Optional PowerBook Express Modem

## Features Built Into Every PowerBook

- Usability
  Runs thousands of Macintosh applications
- Easy to set up, learn, use, and expand

## System software

System software version 7, with multitasking, file sharing, Balloon Help, TrueType fonts, and more

- Networking
   Built-in LocalTalk networking
- File sharing without a dedicated server

## Compatibility

Reads and writes Macintosh, Windows, MS-DOS, OS/2, and ProDOS floppy disk formats with appropriate software

For users looking for light weight and small size in a powerful notebook computer, the Apple PowerBook Duo System is an excellent choice. The PowerBook Duo offers high-speed processors, active matrix screens, large RAM expansion, and desktop expansion—features normally found only on much larger, heavier systems—all in a package that weighs less than 5 pounds.

The PowerBook Duo 250 is part of Apple's acclaimed PowerBook family of lightweight, compact, and flexible notebook computers. Featuring a 68030 microprocessor that runs at 33 megahertz, the PowerBook Duo 250 is more powerful than many desktop computers. It supports up to 24 megabytes of RAM, so you can work with multiple applications simultaneously.


The PowerBook Duo 250 is ready for computing wherever you go. It weighs just 4.2 pounds, so it's light enough to take anywhere. Its 9-inch (229-millimeter) backlit, activematrix display has 16 levels of gray and provides the best screen image, performance, and contrast available in a gray-scale notebook computer without adding bulk or weight.

With the PowerBook Duo 250, you'll also find all the connections you need to work anywhere on the road, in a conference room, or at your desk. AppleTalk networking is built in, so you can connect to all the resources in an AppleTalk network, such as electronic mail, printers, and file servers.

Add a modem and AppleTalk Remote Access software to gain full access to AppleTalk networks practically anywhere in the world.

When you're back at the office, simply insert your PowerBook Duo notebook into a PowerBook Duo Dock, and you're instantly working with a complete Macintosh desktop system. There's nothing to reconfigure, no switches to flip, and no cables to connect.

The PowerBook Duo system lets you decide which capabilities you want, letting you invest in exactly the setup that suits your needs.





# PowerBook Duo 250

## **Ordering Information**

PowerBook Duo 250 4/200

Order No. M1933LL/A PowerBook Duo 250 computer with 4MB of RAM and internal 200MB hard

Battery and AC adapter

System software version 7.1

Complete setup, learning, and reference documentation

Training software

Limited warranty

Optional PowerBook Duo 250

onfiguration
Order No. M4189LL/A
• PowerBook Duo 250 computer with
12MB of RAM and internal PowerBook Express Modem with Express Fax software

PowerBook Duo 4MB Memory Expansion Kit<sup>4</sup> Order No. M4184LL/A

PowerBook Duo 8MB Memory Expansion Kit\* Order No. M4185LL/A

PowerBook Duo Fax/Data Modem (U.S., Canada, Japan) Order No. M0970LL/A

Express Modem for PowerBook Duo\* (U.S., Canada, Japan) Order No. M4186LL/A

PowerBook Duo Rechargeable Battery Order No. M1835LL/A

PowerBook Duo AC Adapter Order No. M4174LL/A

PowerBook Duo Battery Recharger Order No. M4176LL/A

Apple HDI-30 SCSI Disk Adapter Order No. M2539LL/A

Apple HDI-30 SCSI System Cable Order No. M2538LL/A

\*Dealer installation recommended

## **Technical Specifications**

Microprocessor

Motorola 68030, running at 33 MHz

Comes with 4MB of RAM

Can be expanded to up to 24MB of RAM with PowerBook Duo 4MB or 8MB Memory Expansion Kits, or third-party memory expansion cards Disk drive

One internal 200MB hard disk

Display

• 9-in. (229-mm) diagonal

• Backlit, active-matrix display, 640 by 400 pixels

Battery

Nickel-metal-hydride High Capacity Type II battery provides 2.5 to 6 hours of computer use before recharging is necessary

EverWatch Battery Saver technology

Built-in, 2.5-mm travel, 18-mm pitch

Two-level tilt adjustment LED light when caps lock is engaged

Trackball

19-mm diameter, dual-button trackball

Clock/calendar

CMOS custom-integrated circuit with long-life lithium battery

Microphone

Built-in omnidirectional electret; output voltage of 4 mV, peak-to-peak, at normal volume

Power adapter port

152-pin PDS connector for connecting PowerBook Duo Dock, PowerBook Duo MiniDock, PowerBook Floppy Adapter, or other expansion devices

RS-422 serial port for LocalTalk networking, printers, modems, and other devices

Port for optional internal modem

File-transfer options

LocalTalk cables and System 7 file sharing Serial cable and System 7 file sharing Fax/data modem and AppleTalk Remote Access software

Duo MiniDock with external Apple SuperDrive, SCSI Disk Adapter, and HDI-30 SCSI system cable Duo Dock internal Apple SuperDrive, optional internal hard drive, and HDI-30 SCSI system cable

Docking options

PowerBook Duo Dock

PowerBook Duo MiniDock

PowerBook Duo Floppy Adapter Docking solutions from third-party vendors

· Optional internal PowerBook Express Modem: sends and receives data at 14,400 bps and sends and receives faxes at 9,600 bps. Includes Express Fax software.

Subframe

Magnesium subframe structural rigidity and heat

Sound generator

Built-in speaker

 Apple Sound Chip provides monophonic 8-bit sound and is capable of driving stereo headphones or other stereo equipment with the same signal supplied to both channels through optional PowerBook Duo Dock or PowerBook Duo MiniDock

4-voice sound with 8-bit analog-to-digital conversion recording at 11 or 22 kHz sampling rate

 CloseView, Easy Access, and visible-beep included with system software. These built-in solutions and third-party options provide alternative input and output devices for people with disabilities.

Electrical requirements

· Line voltage: 85 to 270 VAC, RMS single phase, automatically configured Frequency: 47 to 63 Hz, single phase Power: 25 W maximum

ADB power requirements

 Maximum current draw for all ADB devices is 200 mA (a maximum of three ADB devices is recommended)

Size and weight

Thickness: 1.4 in. (3.6 cm) Width: 10.9 in. (27.7 cm) Depth: 8.5 in. (21.6 cm) Weight: 4.2 lb. (1.9 kg)

Operating environment Operating temperature: 50° to 104° F

(10° C to 40° C)

Storage temperature: -40° to 116° F (-40° C to 47° C)

Relative humidity: 20% to 80% noncondensing

Operating altitude: 0 to 10,000 ft. (0 to 3,048 m) Maximum storage altitude: 15,000 ft. (4,722 m)

Apple Computer, Inc. 20525 Mariani Avenue Cupertino, CA 95014 (408) 996-1010 TLX 171-576

© 1993 Apple Computer, Inc. All rights reserved. Apple, the Apple logo, AppleTalk, LocalTalk, Macintosh, and ProDOS are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. Apple Desktop Bus, Apple SuperDrive, Balloon Help, PowerBook, PowerBook Duo, and TrueType are trademarks of Apple Computer, Inc. MS-DOS is a registered trademark and Windows is a trademark of Microsoft Corporation. OS/2 is a trademark of International Business Machines Corporation. Mention of non-Apple products is for informational purposes and constitutes neither an endorsement nor a recommendation. Apple assumes no responsibility with regard to the selection, performance, or use of these products. All understandings, agreements, or warranties, if any, take place directly between the vendors and the prospective users. September 1993. Product specifications are subject to change without notice. Printed in U.S.A.